APPENDIX H1

DRAINGE REPORT

ALLARD ENGINEERING
civil engineering land surveying land planning

Conco Commercial
13052 Dahlia Street
Fontana, CA 92337


Preliminary Drainage Report

June 20, 2023

Prepared For:
The Conco Companies
5141 Commercial Circle
Concord, CA 94520
Tel.: (925) 685-6799

Prepared By:
Allard Engineering
16866 Seville Avenue
Fontana, CA 92335
(909) 356-1815

Prepared under the supervision of:



Robert Allard

Robert K Allard, P.E. RCE 85349 Exp. 06-30-24

Discussion

Introduction

This report is for the proposed re-development of an existing commercial site located in the City of Fontana at 13052 Dahlia Street which is approximately 7.8 acres. This site is currently used as developed with existing building, parking area and concrete pads covering 1/3 of the site area, 2/3 of the site area is compacted gravel paved in existing condition.

The current runoff, which occurs during storm events drains southwest on the existing surface and discharges into the street gutter in Dahlia Street which is tributary to the San Sevaine Channel. In developed condition the site will drain to the proposed Infiltration Chamber System and existing drywell system for low flow (WQMP water volume) infiltration and the Detention Chamber will be used for high flow detention and mitigation of the peak runoff from 100-yr, 25-yr, 10-yr & 5-yr storm event. The mitigated runoff flows will drain to the proposed bubbler catch basin in the driveway at the southwest corner of the site and will overflow and drain to the street through an under sidewalk drain.

Purpose

The purpose of this Preliminary Drainage Report is to assess the existing and future flows that affect the site and provide necessary onsite drainage facilities to safely convey the mitigated peak flow generated from the proposed development into the Dahlia Street via surface flow which will ultimately conveys to the City storm drain system (Existing catch basin and 30"/52" RCP) in Etiwanda Avenue, west of the proposed site.

The purpose of this Drainage Report is to quantify the developed condition runoff and show that the proposed drainage system is adequate to detain the water volume and drain the mitigated runoff flow into the Dahlia Street which ultimately drains to the San Sevaine Channel.

Criteria

The criteria utilized for hydrologic analysis is the San Bernardino County Hydrology Manual and Detention Basin Policy. Rational Method Hydrology was used to quantify flow rates (Developed and Existing condition), CivilDesign software to quantify detention volume (Unit Hydrograph Method) and Flood Routing of the Detention Chamber to mitigate outflow rate. Also, WSPG was utilize to run water surface pressure-gradient analysis of the proposed 18" outflow line from detention chamber system. AES software was used to size the proposed storm drain and swales/valley gutters to carry the flow onsite.

Findings

The proposed development will consist of building structures, trucking docks, parking lot, driveways, sidewalks, paved area and landscape/planters. The overall existing site condition is considered 60% pervious with pre-existing commercial buildings and paved gravel area.

In developed condition we have estimated the proposed development (Commercial/Industrial land use) will create impervious areas which is about 90% overall of the site.

The primary drainage solution for the site will be an underground chamber detention system. This detention chamber system (CMP-2) has an 18" outlet pipe that will discharge into the proposed bubbler catch basin in driveway at the southwest corner of the site. The detention chamber system (CMP-2) will mitigate the developed runoff to less than 90% of the existing runoff flow rate. This onsite detention system (CMP-2) will consist of 5ft diameter perforated CMP system (with 4-barrels) located upstream in the west driveway/parking area.

We calculated the runoff flowrate and runoff volume for 100-yr, 25-yr, 10-yr, & 5-yr storm events. Largest Increase in runoff volume and runoff flow rate generated in 100-yr storm event due to the proposed development from its existing condition.

Please see below table for the output of the hydrology analysis for 100-yr, 25-yr, 10-yr, 5-yr storm events in existing and developed condition.

SUMMARY OF RUNOFF FLOW CALCULATION: CALABASH INDUSTRIAL


Storm Event	Site (Area: 7.8 ac)	Peak Runoff Rate (CFS)	Reqd Mitg. Runoff Rate (CFS)	Mitg. Runoff Rate via Detention System Routing
100-yr, 1-hr	Developed Condition	23.0		8.3 CFS < 10.3 CFS
100-yr, 1-hr	Existing Condition	11.5	10.3 (90% of 11.5)	
25-yr, 1-hr	Developed Condition	17.7		5.8 CFS < 7.7 CFS
25-yr, 1-hr	Existing Condition	8.5	7.7 (90% of 8.5)	
10-yr, 1-hr	Developed Condition	14.4		4.1 CFS < 5.8 CFS
10-yr, 1-hr	Existing Condition	6.4	5.8 (90% of 6.4)	
5-yr, 1-hr	Developed Condition	11.9		3.3 CFS < 3.4 CFS
5-yr, 1-hr	Existing Condition	3.8	3.4 (90% of 3.8)	

Higher up in the proposed sites watershed are WQMP infiltration basin to treat the water and the overflow will be the drive isles that will convey larger runoff to the said detention system. Ultimately the mitigated runoff will drain down Dahlia Street which will drain to City Storm Drain System in Etiwanda Avenue and then drain to San Sevaine Channel.

There are no offsite tributary areas that drain through the property in existing/developed condition. The proposed developed site is consistent with drainage pattern in the area.


Calculations and exhibits are attached to support these findings.


Reference Materials





VICINITY MAP

NTS




CONCO
SANTA ANA AVE., FONTANA
Santa Ana Ave
Santa Ana Ave
Santa Ana Ave
Lynam Industries
Fulfillment - Etiwanda
34.054199, -117.520694
SITE IN EXISTING CONDITION
The Conco Companies
Statco-DSI
Dahlia St
Dahlia St
Dahlia St
Google Earth
400 ft
N


ement Plans
Sewer
Storm Drain
SITE
EX. CB
CITY SD
30" RCP
CITY SD
54" RCP
CITY SD
SAN
SAVAINE
CHANNEL
Santa Ana St
Santa Ana Ave
Dahlia St
Jurupa St
Jurupa Ave
Mulberry Ave
Fontana
Gateway
952 ft
948 ft
943 ft
911 ft


ETIWANDA
CALTRANS
100 YEAR
I-10 FREEWAY
25 YEAR
CITY OF ONTARIO
SS-5A
SS-5B
100 YEAR
SLOVER AVE
site
SANTA ANA AVE
SS-6
ETIWANDA AVE
CHANNEL
30" RCP
CITY SD
54" RCP
CITY SD
AREAS IN ADJOINING
DRAINAGE STUDY
JURUPA BASIN
JURUPA AVE
SS-7
LOWER
ETIWANDA
SAN SEVAINE
I-10
SOUTH
MULBERRY AVE
DZ-16
DZ-15
DZ-14
DZ-13
DZ-12
DZ-11
CHERRY AVE
CHANNEL
DECLEZ
MARLAY AVE
SS-8
SS-10
CITY OF FONTANA
34°02'30"

930 CL

930 RT

PROPOSED FINISH SURFACE @ CENTERLINE

TAN= 2.56%

VC 50.00'
VPI=927.01

SEE SHEET 2 FOR CURB RETURN

TOP OF EXISTING 8" CURB @ 22' RT

12+92.25 BOR (928.68'TC) (928.02'FL) JOIN EXIST.

13+42.25 C/L 40' D/W 928.27'FL

13+92.26 EOR (929.18'TC) (928.52'FL) JOIN EXIST.

12+84.21 (928.70')TC

13+22.24 PI 928.17'FL

13+62.26 PI 928.37'FL

11+03.05 EOR 927.45'TC 926.78'FL

11+00.72 (927.43')TC

11+97.23 (928.25')TC

10+93.97 BOR 927.79'TC, 927.12'FL JOIN EXISTING

10+34.50 (927.15')FS JOIN EXISTING

10+00.00 DAHLIA STREET = 69+16.62 ETIWANDA AVENUE

10+14.17 (928.11')FS

10+47.66 (926.70')FS

10+58.00 BVC 926.39'FS

10+83.00 MVC 926.91'FS

11+08.00 EVC (927.22')FS

12+00.00 (938.02')FS

12+00.00 (939.50')FS

12+00.00 (939.00')FS

12+00.00 (939.46')FS

12+00.00 (940.46')FS

12+00.00 (940.95')FS

12+00.00 (941.43')FS

12+00.00 (941.92')FS

12+00.00 (942.41')FS

12+00.00 (943.24')FS

12+00.00 (943.40')FS

22+49.74 END PAVEMENT MATCH EXIST.

22+50.25 (934.56')FS

22+70.25 (934.65')FS

PROPOSED PAVEMENT TO MATCH EXISTING FS @ C/L

150' EXIST. C.F. TRANSITION 8" - 0" C.F.

14+83.14 (925.35')TC

15+82.13 (930.08')TC

16+78.95 (930.97')TC

17+75.53 (931.04')TC

18+67.43 (931.45')TC

19+62.16 (931.89')TC

20+59.17 (932.37')TC

21+55.61 (932.82')TC

21+60.71 BOR (932.28'TC) (932.34'FL) JOIN EXIST.

21+99.74 C/L 40' D/W 932.79'FL

22+49.74 EOR (933.32'TC) (933.24'FL) JOIN EXIST.

22+69.67 (933.33')TC

22+70.17 (933.32')TC

21+60.02 PI 932.59'FL

22+20.04 PI 932.99'FL

TOP OF EXISTING 8" CURB @ 22' RT

EXISTING FL 8" C.F.

PROFILE SCALES
HORIZ: 1" = 40'
VERT: 1" = 4'

11 12 13 14 15 16 17 18 19 20 21 22 23

SCALE: 1"= 40'

SITE

APN: 0238-112-17

APN: 0238-112-16

APN: 0238-112-07

APN: 0238-112-32

FUTURE ST. LT.

LINE OF SIGHT L=300', MPH=40

LIMITED USE AREA (NOTHING HIGHER THAN 30" ALLOWED)

N89°27'25"E

℄ DAHLIA STREET

EXIST. STREET LIGHT

EXIST. SEWER

EXIST. CURB & GUTTER

EXIST. R/W

PROPOSED R/W

GUY WIRE

PP

FH

WV

EXIST. UTILITY EASEMENT

UTILITY EASEMENT

CAUTION! EXISTING WATER

68+46.00 BCR 926.10'TC, 925.43'FL

11+03.05 EOR 927.45'TC, 926.78'FL MEET EXISTING

12+92.25 MEET EXISTING

13+42.25 C/L 40' DRIVEWAY

13+92.26 MEET EXISTING

16+32

19+71

21+49.73 JOIN EXISTING

21+99.74 C/L 40' DRIVEWAY

22+49.74 ANG. PT

22+49.74 MEET EXISTING

933.05'TC 0'CF

933.15'FL

933.22'TC 6'CF

933.45'TC 6'CF

933.32'TC (933.32'TC) (933.24'FL) 1'C.F.

933.34'TC 0'CF

934.48'FL

934.58'FS

5.4'C.F. (932.79'TC) (932.34'FL)

R.R. SIGNAL

ELEC. BOX

ELEC. METER

50'

EXIST. RAILROAD EASEMENT

SEE DETAIL ON SHEET 4.

ETIWANDA AVENUE
SEE SHEET 2

EX. CB

EX. 30" RCP CITY SD

CONSTRUCTION NOTES:

(2) CONSTRUCT 5.5" MIN. ASPHALT CONCRETE PAVEMENT OVER 95% COMPACTED SUBGRADE

(4) ADJUST TO GRADE AS NEEDED PER CITY OF FONTANA STD. PLAN NO. 130.

(6) CONSTRUCT CONC. DRIVEWAY (WIDTH PER PLAN) PER CITY OF FONTANA STD. PLAN NO. 1005A.

(7) CONSTRUCT 6' CONCRETE SIDEWALK PER CITY OF FONTANA STD. PLAN NO. 1015.

(12) SAW CUT EXISTING CONCRETE CURB, GUTTER, AND/OR AC PAVEMENT.

(13) REMOVE EXISTING CONCRETE CURB, GUTTER AND/OR AC PAVEMENT.

(16) PROTECT IN PLACE; ITEM SPECIFIED ON PLAN.

(17) EXISTING POLE TO BE REMOVED AND LINES UNDERGROUNDED AS REQUIRED BY UTILITY.

(18) PROPOSED STREET LIGHT; SEE STREET LIGHT IMPROVEMENT PLANS FOR DETAILS

CURVE DATA

CURVE	RADIUS	DELTA	LENGTH	TANGENT
1	50.00	89°14'00"	77.87	49.34
2	30.00	90°46'00"	47.53	30.40
3	30.00	89°14'00"	46.72	29.60
4	25.00	89°14'00"	38.94	24.67

EXISTING PLAN REFERENCE

PLAN	DRAWING NO.
STREET	CO. STD. ACP-90
STORM DRAIN	CITY STD. 3096
SEWER	CITY STDS. 1545 & 1678
WATER	FONTANA WATER CO. ATLAS
GAS	GAS CO. ATLAS

PAVING LEGEND

(1) OR (2)

(3) NOT USED 1

(13)

DAHLIA STREET

STA10+00 TO STA 23+00

0 20 40 80 120 160

SCALE: 1 INCH = 40 FEET

REGISTERED PROFESSIONAL ENGINEER — TERESITO N. TABIOLO No. 38826 Exp. 3-31-09 CIVIL STATE OF CALIFORNIA

RECORD DRAWING 2

Teresito Tabiolo 2-22-08
TERESITO TABIOLO DATE
RCE 38826, EXP. 3-31-09

NOTE:
RAILROAD APPROVAL REQUIRED PRIOR TO CONSTRUCTION WITHIN THE RAILROAD EASEMENT.

BENCH MARK:
TOP OF 3/4" I.P. WEST 1/4 COR. SECTION 28 T.1S, R.6W. AT THE INTERSECTION OF ETIWANDA AVE. AND SANTA ANA STREET.
ELEVATION 941.95

BASIS OF BEARINGS:
BASIS OF BEARING IS THE CENTERLINE OF DAHLIA STREET AS SHOWN BY TRACT MAP NO. 8554, ON FILE IN BOOK 123 OF MAPS, PAGES 13 THROUGH 17, THEREOF, RECORDS OF SAN BERNARDINO COUNTY, CALIFORNIA, BEING N89°27'25"E.

Underground Service Alert
Call: TOLL FREE
1-800
227-2600
TWO WORKING DAYS BEFORE YOU DIG

REV.	REVISION DESCRIPTION	DATE	ENGR.	CITY	DATE
2	RECORD DRAWING	2-22-08	JJ	PW	2/3/08
1	DELETED OVERLAY; REVISED DRIVEWAY AT 21+99.74	10/25/06	JJ	PW	11-9-06

SHOULD CONSTRUCTION OF THE REQUIRED IMPROVEMENTS NOT COMMENCE WITHIN TWO YEARS OF THE DATE OF APPROVAL SHOWN HEREON AND CARRIED FORTH IN A DILIGENT MANNER, THE CITY ENGINEER MAY REQUIRE REVISIONS TO THE PLANS TO BRING THEM INTO CONFORMANCE WITH CONDITIONS AND STANDARDS IN EFFECT.

REGISTERED PROFESSIONAL ENGINEER — TERESITO N. TABIOLO RCE No. 38826 Exp. 3-31-07 CIVIL STATE OF CALIFORNIA

KCT CONSULTANTS, INC.
Civil Engineers - Surveyors - Planners
P.O. Box 5705 Riverside, CA 92517-5705
4344 Latham St., Suite 200, Riverside, CA 92501
Phone: 951-341-8940 Fax: 951-341-8945
e-mail: kctinc@kctconsultants.com

Prepared Under The Supervision Of : Date 10-25-06

TERESITO N. TABIOLO R.C.E. 38826 EXP. 03-31-07

W.O.: 1335-02

CITY OF FONTANA, CALIFORNIA
STREET IMPROVEMENT PLANS

DAHLIA STREET
FROM ETIWANDA AVENUE TO ±1300' EAST OF ETIWANDA AVENUE

DRAWN BY:	ND	SCALE:	1"=40'
DESIGNED BY:	RC	DATE:	04/12/06
CHECKED BY:	TT	DWG. NO.:	4066
APPROVED BY:	CITY ENGINEER	R.C.E. 51152	DATE 11-9-06	SHEET	3/4

ETIWANDA AVE.

56+25.66 C/L M.H.=
10+00.00 LAT A-12
RIM=925.5

68+24.50 C/L CB
925.88TC
W=21'; V=5.68'

HGL100

WS ELEV.
=924.5

920 LAT

S=0.0100

HYD. DATA
Q100=26.3CFS
V100=5.4FPS

10+02.95
920.05 INV
30" RCP

10+17.68
920.05 INV
30" RCP

INSTALL 14.73 L.F.
OF 30" R.C.P. (D-1500)

LATERAL A-12

920

910

EXISTING FINISHED
SURFACE

EXIST. LAT. A-10- 36" RCP
(307.32INV)

47+32.73 EXISTING
JUNCTION STRUCTURE

47+43.54 C/L M.H.
RIM=915.4

CAUTION!!!
SEWER CROSSING

1

47+60
10" WAT.
911.3 BOT.

18"

HGL100

S=0.0412

47+43.54
906.09INV

47+38.87
906.59INV

EXISTING 54" RCP
PER DWG. NO. 3096

JOIN EXISTING

48+50.00 GRADE BREAK
911.08INV
CONCRETE COLLAR
PER APWA 380-3

1.0'
CLR

S=0.0050

929.88
TOP

PROP. 6" SEWER
LATERAL

HYD. DATA
Q100=43.9CFS
V100=13.2FPS

INSTALL 203.63 L.F. OF 30" R.C.P. (D-1500)

49+50.00 C/L M.H.
RIM=918.1

49+47.17
911.57INV

48+51.83 GB
911.59INV

PROPOSED FINISHED
SURFACE @ C/L OF S.D.

HGL100

S=0.0105

HYD. DATA
Q100=43.9CFS
V100=8.9FPS

EXISTING 24" VCP SEWER
PER DWG. NO. 1678

INSTALL 345.34 L.F. OF 30" R.C.P. (D-1500)

53+00.00 C/L M.H.
RIM=922.0

52+97.17
915.22INV

53+01.83 GB
915.27INV

HGL100

S=0.0110

HYD. DATA
Q100=43.9CFS
V100=8.9FPS

EXISTING 24" VCP SEWER
PER DWG. NO. 1678

INSTALL 305.57 L.F. OF 30" R.C.P. (D-1500)

LAT. A-11- 24" RCP
919.88 INV

LAT. A-12- 30" RCP
920.05 INV

56+10.23 C/L M.H.
RIM=925.3

56+25.68 C/L M.H.
RIM=925.5

56+07.40
916.63INV

56+12.06
916.68INV

56+22.82
916.80INV

930

EXISTING FINISHED
SURFACE

920

HYD. DATA
Q100=26.3CFS
V100=5.4FPS

INSTALL 10.76 L.F.
OF 30" R.C.P. (D-1500)

INSTALL 14.73 L.F.
OF 24" R.C.P. (D-1500)

56+10.23 C/L M.H.=
10+00.00 LAT A-11
RIM=930.0

56+25.68 C/L CB
925.68TC
W=14'; V=5.65'

WS ELEV.
=924.1

HGL100

920 LAT

S=0.0100

HYD. DATA
Q100=17.6CFS
V100=5.6FPS

10+02.95
919.98 INV
24" RCP

10+17.68
919.98 INV
24" RCP

LATERAL A-11

PROFILE SCALES
HORIZ: 1" = 40'
VERT: 1" = 4'

LINE "A" STORM DRAIN

46 47 48 49 50 51 52 53 54 55 56 57

SCALE: 1" = 40'

APN: 0238-101-65

APN: 0238-101-64

APN: 0238-081-51

SECTION LINE

SECTION 29
SECTION 28

CAUTION!!!
GTE MO
PROTECT IN PLACE

CITY OF ONTARIO
CITY OF FONTANA

℄ ETIWANDA AVENUE

LATERAL A-12 30"SD
N45°13'25"E 14.73'
PROFILE THIS SHEET

69+16.62 ETIWANDA AVENUE
=10+00.00 DAHLIA STREET

EXIST LINE 'A' 54" SD
REFER TO STORM DRAIN
DRAWING NO. 3096

EXIST. 14' CB

EXIST. 28' CB

EXIST. 42" INLET
TO BE REMOVED

(47+32.73) EXISTING JUNCTION STRUCTURE
REFER TO STORM DRAIN DRAWING NO. 3096

47+43.54 C/L M.H.
REMOVE 5' CENTRAL BULKHEAD
CONNECT TO EXISTING 54" PIPE

PROPOSED 6" SEWER

CAUTION!!!
SEWER CROSSING

EXIST CURB
& GUTTER

208.80'

N00°13'25"E

350.00'

EXIST SEWER

EXIST GAS

EXIST WATER

310.23'

15.43'

EXIST PP TO BE REMOVED

PROPOSED CURB & GUTTER

PROPOSED STORM DRAIN
SEE ONSITE STORM DRAIN
PLANS FOR CONSTRUCTION

PROPOSED R/W

C/L LINE "A"
STORM DRAIN

LATERAL A-11 24"SD
N45°13'25"E 14.73'
PROFILE THIS SHEET

EXIST PP AND GUY
TO BE REMOVED

EXIST F.H.

APN: 0238-112-49

APN: 0238-111-30

APN: 0238-112-17

EXIST P/L

DAHLIA STREET

SITE

* CONTRACTOR TO VERIFY LOCATION AND ELEVATION PRIOR TO CONSTRUCTION.

STORM DRAIN CONSTRUCTION NOTES:

1. CONSTRUCT 30" RCP D-1500; INSTALLATION & BEDDING PER DETAIL ON SHT. 1.
2. CONSTRUCT 24" RCP D-1500; INSTALLATION & BEDDING PER DETAIL ON SHT. 1.
3. CONSTRUCT CONCRETE CATCH BASIN PER APWA STD. PLAN NO. 300-2; W & V PER PLAN.
4. CONSTRUCT STORM DRAIN MANHOLE PER APWA STANDARD DRAWING NO. 320-1. MODIFIED PER DETAIL ON SHT. 2.
5. CONSTRUCT STORM DRAIN MANHOLE PER APWA STANDARD DRAWING NO. 321-1.

EXIST 54" S.D.

PROP. 30" RCP
STORM DRAIN

36" M.H. SHAFT

47+38.87
906.59INV
JOIN EXIST.

47+43.54
906.09INV

SECTION VIEW

M.H. SHAFT

PROP. 30" RCP
STORM DRAIN

NORTH ELEVATION

LINE "A" STORM DRAIN

STA 47+38.87 TO STA 56+27.83

0 20 40 80 120 160

SCALE: 1 INCH = 40 FEET

1 STA. 47+43.54

MODIFIED APWA M.H. STANDARD DETAIL NO. 320-1
1" = 4'

REGISTERED PROFESSIONAL ENGINEER
TERESITO N. TABIOLO
No. 38826
Exp. 3-31-09
CIVIL
STATE OF CALIFORNIA

RECORD DRAWING 2

Teresito Tabiolo 2-28-08
TERESITO TABIOLO DATE
RCE 38826, EXP. 3-31-09

BENCH MARK:
TOP OF 3/4" I.P. WEST 1/4 COR. SECTION 28 T1S, R.6W. AT THE INTERSECTION OF ETIWANDA AVE. AND SANTA ANA STREET.
ELEVATION 941.95

BASIS OF BEARINGS:
BASIS OF BEARING IS THE CENTERLINE OF DAHLIA STREET AS SHOWN BY TRACT MAP NO. 8554, ON FILE IN BOOK 123 OF MAPS, PAGES 13 THROUGH 17, THEREOF, RECORDS OF SAN BERNARDINO COUNTY, CALIFORNIA, BEING N89°27'25"E.

Underground Service Alert
Call: TOLL FREE
1-800
227-2600
TWO WORKING DAYS BEFORE YOU DIG

REV.	REVISION DESCRIPTION	DATE	ENGR.	CITY	DATE
2	RECORD DRAWING	2-22-08	TT	RG	3/3/08
1	REVISED STORM DRAIN TO GO UNDER FIRE LINE; REVISED MANHOLE DETAIL	10/29/07	TT	RG	11-9-07

SHOULD CONSTRUCTION OF THE REQUIRED IMPROVEMENTS NOT COMMENCE WITHIN TWO YEARS OF THE DATE OF APPROVAL SHOWN HEREON AND CARRIED FORTH IN A DILIGENT MANNER, THE CITY ENGINEER MAY REQUIRE REVISIONS TO THE PLANS TO BRING THEM INTO CONFORMANCE WITH CONDITIONS AND STANDARDS IN EFFECT.

REGISTERED PROFESSIONAL ENGINEER
TERESITO N. TABIOLO
RCE No. 38826
Exp. 3-31-07
CIVIL
STATE OF CALIFORNIA

TERESITO N. TABIOLO R.C.E. 38826 EXP. 03-31-07

KCT CONSULTANTS, INC.
Civil Engineers - Surveyors - Planners
P.O. Box 5705 Riverside, CA 92517-5705
4344 Latham St., Suite 200, Riverside, CA 92501
Phone: 951-341-8940 Fax: 951-341-8945
e-mail: kctinc@kctconsultants.com

Prepared Under The Supervision Of :

Date 10-25-06

W.O.: 1335-02

CITY OF FONTANA, CALIFORNIA

STORM DRAIN IMPROVEMENT PLANS

ETIWANDA AVENUE
LINE A STORM DRAIN
STA 47+38.87 TO STA 56+27.83

DRAWN BY:	NO	SCALE:	1"=40'
DESIGNED BY:	RC	DATE:	04/12/06
CHECKED BY:	RG / TT	APPROVED BY:	CITY ENGINEER R.C.E. 51152 DATE 11-9-07
		DWG. NO.:	4067
			2/3

www.nws.noaa.gov

NOAA's National Weather Service
Hydrometeorological Design Studies Center
Precipitation Frequency Data Server (PFDS)

General Information
Homepage
Progress Reports
FAQ
Glossary

Precipitation Frequency
Data Server
GIS Grids
Maps
Time Series
Temporals
Documents

Probable Maximum Precipitation
Documents

Miscellaneous
Publications
Storm Analysis
Record Precipitation

Contact Us
Inquiries

NOAA ATLAS 14 POINT PRECIPITATION FREQUENCY ESTIMATES: CA

Data description

Data type: Precipitation depth | Units: English | Time series type: Partial duration

Select location


1) Manually:

a) **By location** (decimal degrees, use "-" for S and W): Latitude: 34.05419 Longitude: -117.52069 Submit

b) **By station** (list of CA stations): Select station

c) **By address** Search

2) Use map:



POINT PRECIPITATION FREQUENCY (PF) ESTIMATES

WITH 90% CONFIDENCE INTERVALS AND SUPPLEMENTARY INFORMATION
NOAA Atlas 14, Volume 6, Version 2

PF tabular | PF graphical | Supplementary information | Print page

PDS-based precipitation frequency estimates with 90% confidence intervals (in inches)[1]

Duration	Average recurrence interval (years)									
	1	2	5	10	25	50	100	200	500	1000
5-min	**0.102** (0.085-0.123)	**0.134** (0.112-0.163)	**0.176** (0.147-0.215)	**0.211** (0.174-0.259)	**0.258** (0.205-0.328)	**0.295** (0.229-0.383)	**0.332** (0.252-0.442)	**0.371** (0.274-0.509)	**0.425** (0.300-0.608)	**0.467** (0.318-0.692)
10-min	**0.146** (0.122-0.177)	**0.192** (0.160-0.233)	**0.253** (0.210-0.308)	**0.302** (0.249-0.371)	**0.370** (0.294-0.470)	**0.423** (0.329-0.549)	**0.476** (0.361-0.634)	**0.532** (0.392-0.729)	**0.609** (0.430-0.871)	**0.669** (0.456-0.992)
15-min	**0.177** (0.147-0.214)	**0.232** (0.194-0.282)	**0.306** (0.254-0.372)	**0.366** (0.301-0.449)	**0.448** (0.356-0.569)	**0.511** (0.398-0.663)	**0.576** (0.437-0.767)	**0.644** (0.474-0.882)	**0.736** (0.520-1.05)	**0.809** (0.551-1.20)
30-min	**0.266** (0.222-0.322)	**0.350** (0.292-0.425)	**0.461** (0.383-0.560)	**0.551** (0.454-0.676)	**0.674** (0.536-0.856)	**0.770** (0.599-0.999)	**0.868** (0.658-1.16)	**0.969** (0.714-1.33)	**1.11** (0.783-1.59)	**1.22** (0.830-1.81)
60-min	**0.393** (0.328-0.476)	**0.518** (0.431-0.628)	**0.681** (0.566-0.829)	**0.815** (0.671-0.999)	**0.997** (0.793-1.27)	**1.14** (0.886-1.48)	**1.28** (0.973-1.71)	**1.43** (1.06-1.96)	**1.64** (1.16-2.35)	**1.80** (1.23-2.67)
2-hr	**0.587** (0.489-0.711)	**0.763** (0.635-0.925)	**0.990** (0.822-1.20)	**1.17** (0.966-1.44)	**1.42** (1.13-1.80)	**1.61** (1.25-2.09)	**1.80** (1.37-2.40)	**2.00** (1.47-2.74)	**2.27** (1.60-3.24)	**2.47** (1.68-3.67)
3-hr	**0.742**	**0.960**	**1.24**	**1.46**	**1.76**	**1.99**	**2.22**	**2.46**	**2.77**	**3.02**

	(0.619-0.899)	(0.800-1.16)	(1.03-1.51)	(1.21-1.80)	(1.40-2.24)	(1.55-2.59)	(1.69-2.96)	(1.81-3.37)	(1.96-3.97)	(2.05-4.47)
6-hr	**1.05** (0.878-1.28)	**1.36** (1.13-1.65)	**1.75** (1.45-2.13)	**2.06** (1.70-2.53)	**2.47** (1.96-3.14)	**2.77** (2.16-3.60)	**3.08** (2.33-4.10)	**3.38** (2.49-4.64)	**3.79** (2.68-5.42)	**4.10** (2.79-6.08)
12-hr	**1.38** (1.15-1.68)	**1.80** (1.50-2.19)	**2.33** (1.94-2.84)	**2.74** (2.26-3.36)	**3.28** (2.61-4.16)	**3.67** (2.86-4.76)	**4.05** (3.08-5.40)	**4.44** (3.27-6.08)	**4.93** (3.48-7.06)	**5.30** (3.61-7.86)
24-hr	**1.85** (1.64-2.13)	**2.45** (2.16-2.82)	**3.19** (2.82-3.69)	**3.77** (3.30-4.40)	**4.52** (3.83-5.45)	**5.06** (4.20-6.23)	**5.60** (4.53-7.05)	**6.12** (4.82-7.92)	**6.79** (5.14-9.16)	**7.29** (5.33-10.2)
2-day	**2.26** (2.00-2.60)	**3.05** (2.70-3.52)	**4.06** (3.58-4.70)	**4.85** (4.25-5.66)	**5.90** (4.99-7.10)	**6.67** (5.53-8.20)	**7.43** (6.02-9.36)	**8.20** (6.46-10.6)	**9.20** (6.96-12.4)	**9.94** (7.27-13.9)
3-day	**2.47** (2.18-2.85)	**3.39** (3.00-3.92)	**4.58** (4.04-5.30)	**5.53** (4.84-6.45)	**6.79** (5.75-8.19)	**7.75** (6.43-9.53)	**8.70** (7.05-11.0)	**9.67** (7.62-12.5)	**11.0** (8.29-14.8)	**11.9** (8.73-16.7)
4-day	**2.70** (2.39-3.11)	**3.74** (3.31-4.32)	**5.10** (4.50-5.90)	**6.19** (5.42-7.22)	**7.66** (6.49-9.23)	**8.78** (7.28-10.8)	**9.91** (8.03-12.5)	**11.1** (8.72-14.3)	**12.6** (9.54-17.0)	**13.8** (10.1-19.3)
7-day	**3.16** (2.80-3.64)	**4.42** (3.91-5.10)	**6.08** (5.36-7.04)	**7.44** (6.51-8.68)	**9.29** (7.86-11.2)	**10.7** (8.89-13.2)	**12.2** (9.86-15.3)	**13.7** (10.8-17.7)	**15.7** (11.9-21.2)	**17.3** (12.7-24.2)
10-day	**3.41** (3.02-3.93)	**4.80** (4.24-5.54)	**6.64** (5.86-7.68)	**8.16** (7.14-9.52)	**10.2** (8.68-12.4)	**11.9** (9.85-14.6)	**13.5** (11.0-17.1)	**15.3** (12.0-19.8)	**17.7** (13.4-23.8)	**19.5** (14.3-27.3)
20-day	**3.98** (3.52-4.58)	**5.67** (5.01-6.54)	**7.96** (7.02-9.21)	**9.88** (8.64-11.5)	**12.6** (10.6-15.2)	**14.7** (12.2-18.1)	**16.9** (13.7-21.3)	**19.3** (15.2-25.0)	**22.6** (17.1-30.5)	**25.2** (18.5-35.2)
30-day	**4.69** (4.15-5.40)	**6.71** (5.93-7.75)	**9.48** (8.36-11.0)	**11.8** (10.3-13.8)	**15.1** (12.8-18.3)	**17.8** (14.8-21.9)	**20.6** (16.7-26.0)	**23.6** (18.6-30.6)	**27.8** (21.0-37.5)	**31.2** (22.8-43.6)
45-day	**5.55** (4.92-6.40)	**7.93** (7.01-9.15)	**11.2** (9.89-13.0)	**14.0** (12.3-16.4)	**18.0** (15.3-21.7)	**21.3** (17.7-26.2)	**24.8** (20.0-31.2)	**28.5** (22.4-36.9)	**33.8** (25.5-45.5)	**38.1** (27.8-53.1)
60-day	**6.46** (5.72-7.45)	**9.16** (8.10-10.6)	**12.9** (11.4-14.9)	**16.1** (14.1-18.8)	**20.8** (17.6-25.0)	**24.6** (20.4-30.2)	**28.6** (23.2-36.0)	**33.0** (26.0-42.7)	**39.2** (29.7-52.9)	**44.4** (32.5-61.9)

[1] Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS).

Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values.

Please refer to NOAA Atlas 14 document for more information.

Estimates from the table in CSV format: Precipitation frequency estimates Submit

Main Link Categories:
Home | OWP

US Department of Commerce
National Oceanic and Atmospheric Administration
National Weather Service
Office of Water Prediction (OWP)
1325 East West Highway
Silver Spring, MD 20910
Page Author: HDSC webmaster
Page last modified: April 21, 2017

Map Disclaimer
Disclaimer
Credits
Glossary

Privacy Polic
About U
Career Opportunitie

Search

Map Unit Legend


San Bernardino County Southwestern Part, California (CA677)

San Bernardino County Southwestern Part, California (CA677)

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
TuB	Tujunga loamy sand, 0 to 5 percent slopes	4.2	53.5%
TvC	Tujunga gravelly loamy sand, 0 to 9 percent slopes	3.6	46.5%
Totals for Area of Interest		**7.8**	**100.0%**

Soil Map

Scale (not to scale)



Warning: Soil Map may not be valid at this scale.

You have zoomed in beyond the scale at which the soil map for this area is intended to be used. Mapping of soils is done at a particular scale. The soil surveys that comprise your AOI were mapped at 1:24,000. The design of map units and the level of detail shown in the resulting soil map are dependent on that map scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

San Bernardino County Southwestern Part, California

TvC—Tujunga gravelly loamy sand, 0 to 9 percent slopes

Map Unit Setting

National map unit symbol: hcl2
Elevation: 10 to 1,500 feet
Mean annual precipitation: 10 to 25 inches
Mean annual air temperature: 59 to 64 degrees F
Frost-free period: 250 to 350 days
Farmland classification: Not prime farmland

Map Unit Composition

Tujunga and similar soils: 85 percent
Minor components: 15 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Tujunga

Setting

Landform: Alluvial fans
Landform position (two-dimensional): Backslope
Landform position (three-dimensional): Tread
Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Alluvium derived from granite

Typical profile

H1 - 0 to 36 inches: gravelly loamy sand
H2 - 36 to 60 inches: gravelly sand

Properties and qualities

Slope: 0 to 9 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Somewhat excessively drained
Runoff class: Very low
Capacity of the most limiting layer to transmit water (Ksat): High to very high (5.95 to 19.98 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: Rare
Frequency of ponding: None
Available water supply, 0 to 60 inches: Low (about 3.8 inches)

avg. 12.96"/hr

Interpretive groups

Land capability classification (irrigated): 4s
Land capability classification (nonirrigated): 4e
Hydrologic Soil Group: A
Ecological site: R019XG912CA - Sandy Fan
Hydric soil rating: No

Minor Components

Unnamed
Percent of map unit: 5 percent
Landform: Drainageways
Hydric soil rating: Yes

Soboba, gravelly loamy sand
Percent of map unit: 5 percent
Hydric soil rating: No

Delhi, fine sand
Percent of map unit: 5 percent
Hydric soil rating: No

Data Source Information

Soil Survey Area: San Bernardino County Southwestern Part, California
Survey Area Data: Version 14, Sep 6, 2022

San Bernardino County Southwestern Part, California

TuB—Tujunga loamy sand, 0 to 5 percent slopes

Map Unit Setting

National map unit symbol: 2sx6y
Elevation: 650 to 3,110 feet
Mean annual precipitation: 10 to 25 inches
Mean annual air temperature: 62 to 65 degrees F
Frost-free period: 325 to 365 days
Farmland classification: Farmland of statewide importance

Map Unit Composition

Tujunga, loamy sand, and similar soils: 85 percent
Minor components: 15 percent
Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Tujunga, Loamy Sand

Setting

Landform: Alluvial fans
Landform position (three-dimensional): Tread
Down-slope shape: Linear
Across-slope shape: Linear
Parent material: Alluvium derived from granite

Typical profile

A - 0 to 6 inches: loamy sand
C1 - 6 to 18 inches: loamy sand
C2 - 18 to 60 inches: loamy sand

Properties and qualities

Slope: 0 to 5 percent
Depth to restrictive feature: More than 80 inches
Drainage class: Somewhat excessively drained
Runoff class: Very low
Capacity of the most limiting layer to transmit water (Ksat): High to very high (5.95 to 19.98 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: Rare
Frequency of ponding: None
Available water supply, 0 to 60 inches: Low (about 4.2 inches)

Interpretive groups

Land capability classification (irrigated): None specified
Land capability classification (nonirrigated): 4e
Hydrologic Soil Group: A
Ecological site: R019XG912CA - Sandy Fan
Hydric soil rating: No

Minor Components

Tujunga, gravelly loamy sand
Percent of map unit: 10 percent
Landform: Alluvial fans
Landform position (three-dimensional): Tread
Down-slope shape: Linear
Across-slope shape: Linear
Hydric soil rating: No

Hanford, sandy loam
Percent of map unit: 5 percent
Landform: Alluvial fans
Landform position (three-dimensional): Tread
Down-slope shape: Linear
Across-slope shape: Linear
Hydric soil rating: No

Data Source Information

Soil Survey Area: San Bernardino County Southwestern Part, California
Survey Area Data: Version 14, Sep 6, 2022

Worksheet H: Factor of Safety and Design Infiltration Rate and Worksheet

Factor Category		Factor Description	Assigned Weight (w)	Factor Value (v)	Product (p) p = w x v
A	Suitability Assessment	Soil assessment methods	0.25	3	0.75
		Predominant soil texture	0.25	1	0.25
		Site soil variability	0.25	1	0.25
		Depth to groundwater / impervious layer	0.25	1	0.25
		Suitability Assessment Safety Factor, $S_A = \Sigma p$			1.50
B	Design	Tributary area size	0.25	2	0.50
		Level of pretreatment/ expected sediment loads	0.25	2	0.50
		Redundancy	0.25	3	0.75
		Compaction during construction	0.25	1	0.25
		Design Safety Factor, $S_B = \Sigma p$			2.00
Combined Safety Factor, $S_{TOT} = S_A \times S_B$					3.00
Measured Infiltration Rate, inch/hr, K_M (corrected for test-specific bias)					12.96
Design Infiltration Rate, in/hr, $K_{DESIGN} = S_{TOT} / K_M$					4.3

Supporting Data

Briefly describe infiltration test and provide reference to test forms:

Average Inf. Rate : 12.96 in/hr from USDA WebSoil Report
Design Inf Rate: 12.96/3.0 = 4.3"/hr

Note: The minimum combined adjustment factor shall not be less than 2.0 and the maximum combined adjustment factor shall not exceed 9.0.

Hydrology Calculation
Rational Method Hydrology

Developed Condition (100-yr Storm Event)

```
**************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
         (c) Copyright 1983-2016 Advanced Engineering Software (aes)
             Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:




 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                        *
* DEVELOPED CONDITION                                                   *
* 100-YR STORM EVENT                                                    *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 13:08 06/21/2023
==========================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==========================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =  100.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 1.2800

  *ANTECEDENT MOISTURE CONDITION (AMC) III ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

**************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
--------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==========================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   962.00
  ELEVATION DATA: UPSTREAM(FEET) =    948.80  DOWNSTREAM(FEET) =    936.50

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   11.345
  * 100 YEAR RAINFALL INTENSITY(INCH/HR) =  3.477
  SUBAREA Tc AND LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  COMMERCIAL                 A        5.50      0.74     0.100    52   11.34
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA RUNOFF(CFS) =     16.84
```

```
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =     16.84

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  31
----------------------------------------------------------------------------
  >>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
  >>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =   936.50  DOWNSTREAM(FEET) =   934.80
  FLOW LENGTH(FEET) =   284.00   MANNING'S N =  0.013
  DEPTH OF FLOW IN  27.0 INCH PIPE IS  17.3 INCHES
  PIPE-FLOW VELOCITY(FEET/SEC.) =   6.26
  ESTIMATED PIPE DIAMETER(INCH) =  27.00    NUMBER OF PIPES =   1
  PIPE-FLOW(CFS) =      16.84
  PIPE TRAVEL TIME(MIN.) =   0.76    Tc(MIN.) =   12.10
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1246.00 FEET.

****************************************************************************
  FLOW PROCESS FROM NODE      2.00 TO NODE      2.00 IS CODE =  81
----------------------------------------------------------------------------
  >>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
============================================================================
  MAINLINE Tc(MIN.) =   12.10
  * 100 YEAR RAINFALL INTENSITY(INCH/HR) =  3.345
  SUBAREA LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.74     0.100    52
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA AREA(ACRES) =    2.30      SUBAREA RUNOFF(CFS) =    6.77
  EFFECTIVE AREA(ACRES) =      7.80   AREA-AVERAGED Fm(INCH/HR) =  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap =  0.10
  TOTAL AREA(ACRES) =        7.8       PEAK FLOW RATE(CFS) =      22.96
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     12.10
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap = 0.100
  PEAK FLOW RATE(CFS)   =      22.96
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Existing Condition (100-yr Storm Event)

```
**************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
         (c) Copyright 1983-2016 Advanced Engineering Software (aes)
             Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:



 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                         *
* EXISTING CONDITION                                                     *
* 100-YR STORM EVENT                                                     *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 13:47 06/19/2023
==========================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==========================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =   25.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.9970

  *ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

**************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
--------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==========================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   752.00
  ELEVATION DATA: UPSTREAM(FEET) =    949.00  DOWNSTREAM(FEET) =    937.00

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   15.152
  *  25 YEAR RAINFALL INTENSITY(INCH/HR) =  2.277
  SUBAREA Tc AND LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  RESIDENTIAL
  "1 DWELLING/ACRE"          A        5.50      0.98     0.800    32   15.15
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.97
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.800
```

25-yr, 1-hr intensity

```
  SUBAREA RUNOFF(CFS) =      7.41
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =      7.41

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  51
----------------------------------------------------------------------------
  >>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
  >>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =    937.00  DOWNSTREAM(FEET) =    934.00
  CHANNEL LENGTH THRU SUBAREA(FEET) =   296.00   CHANNEL SLOPE =  0.0078
  CHANNEL BASE(FEET) =    2.00   "Z" FACTOR =   2.000
  MANNING'S FACTOR = 0.015   MAXIMUM DEPTH(FEET) =   0.50

        ==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
            CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
            ALLOWABLE DEPTH).
            AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
            ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.

  *  25 YEAR RAINFALL INTENSITY(INCH/HR) =  2.210
  SUBAREA LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.98     0.100    32
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.98
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) =       9.59
  TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) =   6.39
  AVERAGE FLOW DEPTH(FEET) =   0.50   TRAVEL TIME(MIN.) =   0.77
  Tc(MIN.) =   15.92
  SUBAREA AREA(ACRES) =     2.30       SUBAREA RUNOFF(CFS) =    4.37
  EFFECTIVE AREA(ACRES) =      7.80     AREA-AVERAGED Fm(INCH/HR) =   0.58
  AREA-AVERAGED Fp(INCH/HR) =   0.97  AREA-AVERAGED Ap =   0.59
  TOTAL AREA(ACRES) =        7.8         PEAK FLOW RATE(CFS) =      11.45

        ==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
            CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
            ALLOWABLE DEPTH).
            AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
            ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.


  END OF SUBAREA CHANNEL FLOW HYDRAULICS:
  DEPTH(FEET) =  0.50   FLOW VELOCITY(FEET/SEC.) =   7.63

  ==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1040.00 FEET.
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     15.92
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.58
  AREA-AVERAGED Fp(INCH/HR) =  0.97  AREA-AVERAGED Ap = 0.594
  PEAK FLOW RATE(CFS)   =      11.45
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Developed Condition (25-yr Storm Event)

```
******************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
         (c) Copyright 1983-2016 Advanced Engineering Software (aes)
             Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:




 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                         *
* DEVELOPED CONDITION                                                    *
* 25-YR STORM EVENT                                                      *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 11:55 07/01/2023
==============================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==============================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =   25.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.9970

  *ANTECEDENT MOISTURE CONDITION (AMC) III ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

******************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
------------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==============================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   962.00
  ELEVATION DATA: UPSTREAM(FEET) =    948.80  DOWNSTREAM(FEET) =    936.50

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   11.345
  *  25 YEAR RAINFALL INTENSITY(INCH/HR) =  2.708
  SUBAREA Tc AND LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  COMMERCIAL                 A        5.50      0.74     0.100    52   11.34
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA RUNOFF(CFS) =     13.04
```

```
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =     13.04

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  31
----------------------------------------------------------------------------
  >>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
  >>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =   936.50  DOWNSTREAM(FEET) =   934.80
  FLOW LENGTH(FEET) =   284.00   MANNING'S N =  0.013
  DEPTH OF FLOW IN  24.0 INCH PIPE IS  16.0 INCHES
  PIPE-FLOW VELOCITY(FEET/SEC.) =   5.85
  ESTIMATED PIPE DIAMETER(INCH) =  24.00    NUMBER OF PIPES =   1
  PIPE-FLOW(CFS) =      13.04
  PIPE TRAVEL TIME(MIN.) =   0.81    Tc(MIN.) =   12.15
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1246.00 FEET.

****************************************************************************
  FLOW PROCESS FROM NODE      2.00 TO NODE      2.00 IS CODE =  81
----------------------------------------------------------------------------
  >>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
============================================================================
  MAINLINE Tc(MIN.) =   12.15
  *  25 YEAR RAINFALL INTENSITY(INCH/HR) =  2.599
  SUBAREA LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.74     0.100    52
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA AREA(ACRES) =    2.30      SUBAREA RUNOFF(CFS) =    5.23
  EFFECTIVE AREA(ACRES) =      7.80   AREA-AVERAGED Fm(INCH/HR) =  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap =  0.10
  TOTAL AREA(ACRES) =        7.8       PEAK FLOW RATE(CFS) =      17.72
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     12.15
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap = 0.100
  PEAK FLOW RATE(CFS)   =      17.72
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Existing Condition (25-yr Storm Event)

```
**************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
         (c) Copyright 1983-2016 Advanced Engineering Software (aes)
             Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:




 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                         *
* EXISTING CONDITION                                                     *
* 28-YR STORM EVENT                                                      *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 12:06 07/01/2023
==========================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==========================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =   10.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.8150

  *ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

**************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
--------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==========================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   744.00
  ELEVATION DATA: UPSTREAM(FEET) =    946.00  DOWNSTREAM(FEET) =    934.30

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   15.152
  *  10 YEAR RAINFALL INTENSITY(INCH/HR) =  1.861
  SUBAREA Tc AND LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  RESIDENTIAL
  "1 DWELLING/ACRE"          A        5.50      0.98     0.800    32   15.15
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.97
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.800
```

```
  SUBAREA RUNOFF(CFS) =      5.35
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =      5.35

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  51
----------------------------------------------------------------------------
  >>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
  >>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =    934.30  DOWNSTREAM(FEET) =    932.00
  CHANNEL LENGTH THRU SUBAREA(FEET) =   296.00   CHANNEL SLOPE =  0.0078
  CHANNEL BASE(FEET) =    2.00   "Z" FACTOR =   2.000
  MANNING'S FACTOR = 0.015   MAXIMUM DEPTH(FEET) =   0.50
  *  10 YEAR RAINFALL INTENSITY(INCH/HR) =  1.788
  SUBAREA LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE           GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                A        2.30      0.98     0.100    32
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.98
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) =       7.09
  TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) =   4.73
  AVERAGE FLOW DEPTH(FEET) =   0.50   TRAVEL TIME(MIN.) =   1.04
  Tc(MIN.) =   16.20
  SUBAREA AREA(ACRES) =     2.30       SUBAREA RUNOFF(CFS) =    3.50
  EFFECTIVE AREA(ACRES) =      7.80     AREA-AVERAGED Fm(INCH/HR) =   0.58
  AREA-AVERAGED Fp(INCH/HR) =   0.97  AREA-AVERAGED Ap =   0.59
  TOTAL AREA(ACRES) =        7.8         PEAK FLOW RATE(CFS) =       8.49

         ==>>WARNING: FLOW IN CHANNEL EXCEEDS CHANNEL
             CAPACITY( NORMAL DEPTH EQUAL TO SPECIFIED MAXIMUM
             ALLOWABLE DEPTH).
             AS AN APPROXIMATION, FLOWDEPTH IS SET AT MAXIMUM
             ALLOWABLE DEPTH AND IS USED FOR TRAVELTIME CALCULATIONS.


  END OF SUBAREA CHANNEL FLOW HYDRAULICS:
  DEPTH(FEET) =  0.50   FLOW VELOCITY(FEET/SEC.) =   5.66

  ==>FLOWDEPTH EXCEEDS MAXIMUM ALLOWABLE DEPTH

  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1040.00 FEET.
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     16.20
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.58
  AREA-AVERAGED Fp(INCH/HR) =  0.97  AREA-AVERAGED Ap = 0.594
  PEAK FLOW RATE(CFS)   =       8.49
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Developed Condition (10-yr Storm Event)

```
**************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
        (c) Copyright 1983-2016 Advanced Engineering Software (aes)
            Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:




 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                         *
* DEVELOPED CONDITION                                                    *
* 10-YR STOR EVENT                                                       *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 11:59 07/01/2023
==========================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==========================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =   10.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.8150

  *ANTECEDENT MOISTURE CONDITION (AMC) III ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

**************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
--------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==========================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   962.00
  ELEVATION DATA: UPSTREAM(FEET) =    948.80  DOWNSTREAM(FEET) =    936.50

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   11.345
  *  10 YEAR RAINFALL INTENSITY(INCH/HR) =  2.214
  SUBAREA Tc AND LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
        LAND USE           GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  COMMERCIAL                 A        5.50      0.74     0.100    52   11.34
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA RUNOFF(CFS) =     10.59
```

```
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =     10.59

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  31
----------------------------------------------------------------------------
  >>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
  >>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =   936.50  DOWNSTREAM(FEET) =   934.80
  FLOW LENGTH(FEET) =   284.00   MANNING'S N =  0.013
  DEPTH OF FLOW IN  21.0 INCH PIPE IS  15.7 INCHES
  PIPE-FLOW VELOCITY(FEET/SEC.) =   5.48
  ESTIMATED PIPE DIAMETER(INCH) =  21.00    NUMBER OF PIPES =   1
  PIPE-FLOW(CFS) =      10.59
  PIPE TRAVEL TIME(MIN.) =   0.86    Tc(MIN.) =   12.21
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1246.00 FEET.

****************************************************************************
  FLOW PROCESS FROM NODE      2.00 TO NODE      2.00 IS CODE =  81
----------------------------------------------------------------------------
  >>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
============================================================================
  MAINLINE Tc(MIN.) =   12.21
  *  10 YEAR RAINFALL INTENSITY(INCH/HR) =  2.119
  SUBAREA LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.74     0.100    52
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA AREA(ACRES) =    2.30      SUBAREA RUNOFF(CFS) =    4.23
  EFFECTIVE AREA(ACRES) =      7.80   AREA-AVERAGED Fm(INCH/HR) =  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap =  0.10
  TOTAL AREA(ACRES) =        7.8       PEAK FLOW RATE(CFS) =      14.35
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     12.21
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap = 0.100
  PEAK FLOW RATE(CFS)   =      14.35
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Existing Condition (10-yr Storm Event)

```
****************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
        (c) Copyright 1983-2016 Advanced Engineering Software (aes)
            Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:



 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                        *
* EXISTING CONDITION                                                    *
* 10YR STORM EVENT                                                      *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 12:13 07/01/2023
============================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
============================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =    5.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.6810

  *ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

****************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
----------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
============================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   744.00
  ELEVATION DATA: UPSTREAM(FEET) =    946.00  DOWNSTREAM(FEET) =    934.30

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   15.152
  *   5 YEAR RAINFALL INTENSITY(INCH/HR) =  1.555
  SUBAREA Tc AND LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  RESIDENTIAL
  "1 DWELLING/ACRE"          A        5.50      0.98     0.800    32   15.15
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.97
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.800
```

```
  SUBAREA RUNOFF(CFS) =      3.84
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =      3.84

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  51
----------------------------------------------------------------------------
  >>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
  >>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =    934.30  DOWNSTREAM(FEET) =    932.00
  CHANNEL LENGTH THRU SUBAREA(FEET) =   296.00   CHANNEL SLOPE =  0.0078
  CHANNEL BASE(FEET) =    2.00   "Z" FACTOR =   2.000
  MANNING'S FACTOR = 0.015   MAXIMUM DEPTH(FEET) =   0.50
  *   5 YEAR RAINFALL INTENSITY(INCH/HR) =  1.485
  SUBAREA LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.98     0.100    32
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.98
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) =       5.27
  TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) =   4.09
  AVERAGE FLOW DEPTH(FEET) =   0.45   TRAVEL TIME(MIN.) =   1.21
  Tc(MIN.) =   16.36
  SUBAREA AREA(ACRES) =     2.30       SUBAREA RUNOFF(CFS) =    2.87
  EFFECTIVE AREA(ACRES) =      7.80     AREA-AVERAGED Fm(INCH/HR) =   0.58
  AREA-AVERAGED Fp(INCH/HR) =   0.97  AREA-AVERAGED Ap =   0.59
  TOTAL AREA(ACRES) =        7.8         PEAK FLOW RATE(CFS) =       6.36

  END OF SUBAREA CHANNEL FLOW HYDRAULICS:
  DEPTH(FEET) =  0.49   FLOW VELOCITY(FEET/SEC.) =   4.32
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1040.00 FEET.
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     16.36
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.58
  AREA-AVERAGED Fp(INCH/HR) =  0.97  AREA-AVERAGED Ap = 0.594
  PEAK FLOW RATE(CFS)   =       6.36
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Developed Condition (5-yr Storm Event)

```
****************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
        (c) Copyright 1983-2016 Advanced Engineering Software (aes)
            Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:




 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                        *
* DEVELOPED CONDITION                                                   *
* 5-YR STORM EVENT                                                      *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 12:02 07/01/2023
============================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
============================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =    5.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.6810

  *ANTECEDENT MOISTURE CONDITION (AMC) III ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

****************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
----------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
============================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   962.00
  ELEVATION DATA: UPSTREAM(FEET) =    948.80  DOWNSTREAM(FEET) =    936.50

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   11.345
  *   5 YEAR RAINFALL INTENSITY(INCH/HR) =  1.850
  SUBAREA Tc AND LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
        LAND USE           GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  COMMERCIAL                 A        5.50      0.74     0.100    52   11.34
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA RUNOFF(CFS) =      8.79
```

```
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =      8.79

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  31
----------------------------------------------------------------------------
  >>>>>COMPUTE PIPE-FLOW TRAVEL TIME THRU SUBAREA<<<<<
  >>>>>USING COMPUTER-ESTIMATED PIPESIZE (NON-PRESSURE FLOW)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =   936.50  DOWNSTREAM(FEET) =   934.80
  FLOW LENGTH(FEET) =   284.00   MANNING'S N =  0.013
  DEPTH OF FLOW IN  21.0 INCH PIPE IS  13.6 INCHES
  PIPE-FLOW VELOCITY(FEET/SEC.) =   5.31
  ESTIMATED PIPE DIAMETER(INCH) =  21.00    NUMBER OF PIPES =   1
  PIPE-FLOW(CFS) =       8.79
  PIPE TRAVEL TIME(MIN.) =   0.89    Tc(MIN.) =   12.24
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1246.00 FEET.

****************************************************************************
  FLOW PROCESS FROM NODE      2.00 TO NODE      2.00 IS CODE =  81
----------------------------------------------------------------------------
  >>>>>ADDITION OF SUBAREA TO MAINLINE PEAK FLOW<<<<<
============================================================================
  MAINLINE Tc(MIN.) =   12.24
  *   5 YEAR RAINFALL INTENSITY(INCH/HR) =  1.768
  SUBAREA LOSS RATE DATA(AMC III):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.74     0.100    52
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.74
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  SUBAREA AREA(ACRES) =    2.30      SUBAREA RUNOFF(CFS) =    3.51
  EFFECTIVE AREA(ACRES) =      7.80   AREA-AVERAGED Fm(INCH/HR) =  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap =  0.10
  TOTAL AREA(ACRES) =        7.8       PEAK FLOW RATE(CFS) =      11.89
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     12.24
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.07
  AREA-AVERAGED Fp(INCH/HR) =  0.74  AREA-AVERAGED Ap = 0.100
  PEAK FLOW RATE(CFS)   =      11.89
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Existing Condition (5-yr Storm Event)

```
**************************************************************************
            RATIONAL METHOD HYDROLOGY COMPUTER PROGRAM PACKAGE
          (Reference: 1986 SAN BERNARDINO CO. HYDROLOGY CRITERION)
         (c) Copyright 1983-2016 Advanced Engineering Software (aes)
             Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:



 ************************* DESCRIPTION OF STUDY *************************
* CONCO, FONTANA                                                         *
* EXISTING CONDITION                                                     *
* 5-STORM EVENT                                                          *
 ************************************************************************

  FILE NAME: CONC.DAT
  TIME/DATE OF STUDY: 12:19 07/01/2023
==========================================================================
  USER SPECIFIED HYDROLOGY AND HYDRAULIC MODEL INFORMATION:
==========================================================================
                    --*TIME-OF-CONCENTRATION MODEL*--

  USER SPECIFIED STORM EVENT(YEAR) =    2.00
  SPECIFIED MINIMUM PIPE SIZE(INCH) =  12.00
  SPECIFIED PERCENT OF GRADIENTS(DECIMAL) TO USE FOR FRICTION SLOPE = 0.90
  *USER-DEFINED LOGARITHMIC INTERPOLATION USED FOR RAINFALL*

  SLOPE OF INTENSITY DURATION CURVE(LOG(I;IN/HR) vs. LOG(Tc;MIN)) = 0.6000
  USER SPECIFIED 1-HOUR INTENSITY(INCH/HOUR) = 0.5180

  *ANTECEDENT MOISTURE CONDITION (AMC) II ASSUMED FOR RATIONAL METHOD*

  *USER-DEFINED STREET-SECTIONS FOR COUPLED PIPEFLOW AND STREETFLOW MODEL*
     HALF-  CROWN TO   STREET-CROSSFALL:   CURB  GUTTER-GEOMETRIES:  MANNING
     WIDTH  CROSSFALL  IN-  / OUT-/PARK-  HEIGHT  WIDTH  LIP   HIKE  FACTOR
NO.   (FT)     (FT)    SIDE / SIDE/ WAY    (FT)    (FT)  (FT)  (FT)    (n)
===  =====  =========  =================  ======  ===== ====== ===== =======
  1   30.0     20.0    0.018/0.018/0.020   0.67    2.00 0.0313 0.167 0.0150

  GLOBAL STREET FLOW-DEPTH CONSTRAINTS:
    1. Relative Flow-Depth =  0.00 FEET
       as (Maximum Allowable Street Flow Depth) - (Top-of-Curb)
    2. (Depth)*(Velocity) Constraint =  6.0 (FT*FT/S)
  *SIZE PIPE WITH A FLOW CAPACITY GREATER THAN
   OR EQUAL TO THE UPSTREAM TRIBUTARY PIPE.*
  *USER-SPECIFIED MINIMUM TOPOGRAPHIC SLOPE ADJUSTMENT NOT SELECTED

**************************************************************************
  FLOW PROCESS FROM NODE      0.00 TO NODE      1.00 IS CODE =  21
--------------------------------------------------------------------------
  >>>>>RATIONAL METHOD INITIAL SUBAREA ANALYSIS<<<<<
  >>USE TIME-OF-CONCENTRATION NOMOGRAPH FOR INITIAL SUBAREA<<
==========================================================================
  INITIAL SUBAREA FLOW-LENGTH(FEET) =   744.00
  ELEVATION DATA: UPSTREAM(FEET) =    946.00  DOWNSTREAM(FEET) =    934.30

  Tc = K*[(LENGTH** 3.00)/(ELEVATION CHANGE)]**0.20
  SUBAREA ANALYSIS USED MINIMUM Tc(MIN.) =   15.152
  *   2 YEAR RAINFALL INTENSITY(INCH/HR) =  1.183
  SUBAREA Tc AND LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS   Tc
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN  (MIN.)
  RESIDENTIAL
  "1 DWELLING/ACRE"          A        5.50      0.98     0.800    32   15.15
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.97
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.800
```

```
  SUBAREA RUNOFF(CFS) =      1.99
  TOTAL AREA(ACRES) =      5.50   PEAK FLOW RATE(CFS) =      1.99

****************************************************************************
  FLOW PROCESS FROM NODE      1.00 TO NODE      2.00 IS CODE =  51
----------------------------------------------------------------------------
  >>>>>COMPUTE TRAPEZOIDAL CHANNEL FLOW<<<<<
  >>>>>TRAVELTIME THRU SUBAREA (EXISTING ELEMENT)<<<<<
============================================================================
  ELEVATION DATA: UPSTREAM(FEET) =    934.30  DOWNSTREAM(FEET) =    932.00
  CHANNEL LENGTH THRU SUBAREA(FEET) =   296.00   CHANNEL SLOPE =  0.0078
  CHANNEL BASE(FEET) =    2.00   "Z" FACTOR =   2.000
  MANNING'S FACTOR = 0.015   MAXIMUM DEPTH(FEET) =   0.50
  *   2 YEAR RAINFALL INTENSITY(INCH/HR) =  1.121
  SUBAREA LOSS RATE DATA(AMC  II):
   DEVELOPMENT TYPE/      SCS SOIL   AREA      Fp         Ap     SCS
       LAND USE            GROUP   (ACRES)  (INCH/HR)  (DECIMAL)  CN
  COMMERCIAL                 A        2.30      0.98     0.100    32
  SUBAREA AVERAGE PERVIOUS LOSS RATE, Fp(INCH/HR) =  0.98
  SUBAREA AVERAGE PERVIOUS AREA FRACTION, Ap =  0.100
  TRAVEL TIME COMPUTED USING ESTIMATED FLOW(CFS) =       3.05
  TRAVEL TIME THRU SUBAREA BASED ON VELOCITY(FEET/SEC.) =   3.46
  AVERAGE FLOW DEPTH(FEET) =   0.33   TRAVEL TIME(MIN.) =   1.42
  Tc(MIN.) =   16.58
  SUBAREA AREA(ACRES) =     2.30       SUBAREA RUNOFF(CFS) =    2.12
  EFFECTIVE AREA(ACRES) =      7.80     AREA-AVERAGED Fm(INCH/HR) =   0.58
  AREA-AVERAGED Fp(INCH/HR) =   0.97  AREA-AVERAGED Ap =   0.59
  TOTAL AREA(ACRES) =        7.8         PEAK FLOW RATE(CFS) =       3.80

  END OF SUBAREA CHANNEL FLOW HYDRAULICS:
  DEPTH(FEET) =  0.37   FLOW VELOCITY(FEET/SEC.) =   3.74
  LONGEST FLOWPATH FROM NODE      0.00 TO NODE      2.00 =    1040.00 FEET.
============================================================================
  END OF STUDY SUMMARY:
  TOTAL AREA(ACRES)     =        7.8  TC(MIN.) =     16.58
  EFFECTIVE AREA(ACRES) =      7.80  AREA-AVERAGED Fm(INCH/HR)=  0.58
  AREA-AVERAGED Fp(INCH/HR) =  0.97  AREA-AVERAGED Ap = 0.594
  PEAK FLOW RATE(CFS)   =       3.80
============================================================================
============================================================================
  END OF RATIONAL METHOD ANALYSIS
```

Hydrology Calculation
Unit Hydrograph Analysis

Unit Hydrograph Analysis: Developed Condition (100 yr, 24 hr Storm Event)

```
        U n i t   H y d r o g r a p h   A n a l y s i s

        Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018, Version 9.0

                Study date  06/04/23

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
------------------------------------------------------------------------------

San Bernardino County Synthetic Unit Hydrology Method
                Manual date - August 1986


Program License Serial Number 6484

------------------------------------------------------------------------
UH ANALYSIS
DEVELOPED CONDITION
100-YR STORM EVENT

------------------------------------------------------------------------

        Storm Event Year = 100

        Antecedent Moisture Condition = 3

 English (in-lb) Input Units Used

 English Rainfall Data (Inches) Input Values Used

 English Units used in output format



Area averaged rainfall intensity isohyetal data:
        Sub-Area        Duration        Isohyetal
        (Ac.)            (hours)         (In)
Rainfall data for year 100
             7.80            1           1.28
------------------------------------------------------------------------
Rainfall data for year 100
             7.80            6           3.08
------------------------------------------------------------------------
Rainfall data for year 100
             7.80           24           5.60
------------------------------------------------------------------------
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

******** Area-averaged max loss rate, Fm ********


SCS curve  SCS curve     Area     Area     Fp(Fig C6)    Ap      Fm
No.(AMCII) NO.(AMC 3)    (Ac.)    Fraction     (In/Hr)  (dec.)   (In/Hr)
 32.0      52.0          7.80      1.000     0.785    0.100    0.079

Area-averaged adjusted loss rate Fm (In/Hr) =  0.079

********* Area-Averaged low loss rate fraction, Yb **********

Area       Area          SCS CN    SCS CN      S     Pervious
 (Ac.)      Fract         (AMC2)    (AMC3)           Yield Fr
     0.78   0.100         32.0      52.0       9.23     0.194
     7.02   0.900         98.0      98.0       0.20     0.958

Area-averaged catchment yield fraction, Y =  0.881
Area-averaged low loss fraction, Yb =  0.119
Direct entry of lag time by user
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
```

Watershed area = 7.80(Ac.)
Catchment Lag time = 0.164 hours
Unit interval = 5.000 minutes
Unit interval percentage of lag time = 50.8130
Hydrograph baseflow = 0.00(CFS)
Average maximum watershed loss rate(Fm) = 0.079(In/Hr)
Average low loss rate fraction (Yb) = 0.119 (decimal)
VALLEY DEVELOPED S-Graph Selected
Computed peak 5-minute rainfall = 0.474(In)
Computed peak 30-minute rainfall = 0.970(In)
Specified peak 1-hour rainfall = 1.280(In)
Computed peak 3-hour rainfall = 2.193(In)
Specified peak 6-hour rainfall = 3.080(In)
Specified peak 24-hour rainfall = 5.600(In)

Rainfall depth area reduction factors:
Using a total area of 7.80(Ac.) (Ref: fig. E-4)

5-minute factor = 1.000 Adjusted rainfall = 0.474(In)
30-minute factor = 1.000 Adjusted rainfall = 0.970(In)
1-hour factor = 1.000 Adjusted rainfall = 1.280(In)
3-hour factor = 1.000 Adjusted rainfall = 2.193(In)
6-hour factor = 1.000 Adjusted rainfall = 3.080(In)
24-hour factor = 1.000 Adjusted rainfall = 5.600(In)

U n i t H y d r o g r a p h

Interval Number	'S' Graph Mean values	Unit Hydrograph ((CFS))
	(K = 94.33 (CFS))	
1	4.721	4.453
2	30.727	24.532
3	70.062	37.105
4	90.587	19.362
5	97.250	6.286
6	98.831	1.491
7	100.000	1.103

Peak Unit Number	Adjusted mass rainfall (In)	Unit rainfall (In)
1	0.4736	0.4736
2	0.6249	0.1513
3	0.7349	0.1100
4	0.8245	0.0896
5	0.9015	0.0770
6	0.9697	0.0682
7	1.0314	0.0617
8	1.0880	0.0566
9	1.1404	0.0525
10	1.1895	0.0491
11	1.2358	0.0462
12	1.2795	0.0438
13	1.3308	0.0512
14	1.3800	0.0492
15	1.4275	0.0475
16	1.4734	0.0459
17	1.5178	0.0445
18	1.5610	0.0431
19	1.6029	0.0419
20	1.6437	0.0408
21	1.6835	0.0398
22	1.7224	0.0388
23	1.7603	0.0380
24	1.7975	0.0371
25	1.8338	0.0363
26	1.8694	0.0356
27	1.9043	0.0349

28	1.9386	0.0343
29	1.9722	0.0336
30	2.0053	0.0331
31	2.0378	0.0325
32	2.0698	0.0320
33	2.1013	0.0315
34	2.1322	0.0310
35	2.1628	0.0305
36	2.1928	0.0301
37	2.2225	0.0296
38	2.2517	0.0292
39	2.2806	0.0288
40	2.3090	0.0285
41	2.3372	0.0281
42	2.3649	0.0278
43	2.3924	0.0274
44	2.4195	0.0271
45	2.4463	0.0268
46	2.4728	0.0265
47	2.4990	0.0262
48	2.5249	0.0259
49	2.5505	0.0256
50	2.5759	0.0254
51	2.6010	0.0251
52	2.6259	0.0249
53	2.6505	0.0246
54	2.6749	0.0244
55	2.6991	0.0242
56	2.7230	0.0239
57	2.7467	0.0237
58	2.7702	0.0235
59	2.7936	0.0233
60	2.8167	0.0231
61	2.8396	0.0229
62	2.8623	0.0227
63	2.8848	0.0225
64	2.9072	0.0224
65	2.9293	0.0222
66	2.9513	0.0220
67	2.9732	0.0218
68	2.9948	0.0217
69	3.0163	0.0215
70	3.0377	0.0213
71	3.0589	0.0212
72	3.0799	0.0210
73	3.0983	0.0184
74	3.1165	0.0182
75	3.1346	0.0181
76	3.1526	0.0180
77	3.1704	0.0178
78	3.1881	0.0177
79	3.2057	0.0176
80	3.2231	0.0174
81	3.2404	0.0173
82	3.2576	0.0172
83	3.2747	0.0171
84	3.2916	0.0170
85	3.3085	0.0168
86	3.3252	0.0167
87	3.3418	0.0166
88	3.3583	0.0165
89	3.3747	0.0164
90	3.3910	0.0163
91	3.4072	0.0162
92	3.4233	0.0161
93	3.4393	0.0160
94	3.4552	0.0159
95	3.4710	0.0158
96	3.4868	0.0157
97	3.5024	0.0156
98	3.5179	0.0155

99	3.5333	0.0154
100	3.5487	0.0153
101	3.5639	0.0153
102	3.5791	0.0152
103	3.5942	0.0151
104	3.6092	0.0150
105	3.6241	0.0149
106	3.6390	0.0148
107	3.6537	0.0148
108	3.6684	0.0147
109	3.6830	0.0146
110	3.6976	0.0145
111	3.7120	0.0145
112	3.7264	0.0144
113	3.7407	0.0143
114	3.7550	0.0142
115	3.7691	0.0142
116	3.7832	0.0141
117	3.7973	0.0140
118	3.8112	0.0140
119	3.8251	0.0139
120	3.8390	0.0138
121	3.8527	0.0138
122	3.8664	0.0137
123	3.8801	0.0136
124	3.8936	0.0136
125	3.9071	0.0135
126	3.9206	0.0134
127	3.9340	0.0134
128	3.9473	0.0133
129	3.9606	0.0133
130	3.9738	0.0132
131	3.9870	0.0132
132	4.0000	0.0131
133	4.0131	0.0130
134	4.0261	0.0130
135	4.0390	0.0129
136	4.0519	0.0129
137	4.0647	0.0128
138	4.0775	0.0128
139	4.0902	0.0127
140	4.1029	0.0127
141	4.1155	0.0126
142	4.1280	0.0126
143	4.1405	0.0125
144	4.1530	0.0125
145	4.1654	0.0124
146	4.1778	0.0124
147	4.1901	0.0123
148	4.2024	0.0123
149	4.2146	0.0122
150	4.2268	0.0122
151	4.2389	0.0121
152	4.2510	0.0121
153	4.2630	0.0120
154	4.2750	0.0120
155	4.2870	0.0119
156	4.2989	0.0119
157	4.3107	0.0119
158	4.3225	0.0118
159	4.3343	0.0118
160	4.3461	0.0117
161	4.3577	0.0117
162	4.3694	0.0117
163	4.3810	0.0116
164	4.3926	0.0116
165	4.4041	0.0115
166	4.4156	0.0115
167	4.4271	0.0115
168	4.4385	0.0114
169	4.4498	0.0114

170	4.4612	0.0113
171	4.4725	0.0113
172	4.4837	0.0113
173	4.4950	0.0112
174	4.5062	0.0112
175	4.5173	0.0112
176	4.5284	0.0111
177	4.5395	0.0111
178	4.5505	0.0110
179	4.5615	0.0110
180	4.5725	0.0110
181	4.5835	0.0109
182	4.5944	0.0109
183	4.6052	0.0109
184	4.6161	0.0108
185	4.6269	0.0108
186	4.6376	0.0108
187	4.6484	0.0107
188	4.6591	0.0107
189	4.6697	0.0107
190	4.6804	0.0106
191	4.6910	0.0106
192	4.7016	0.0106
193	4.7121	0.0105
194	4.7226	0.0105
195	4.7331	0.0105
196	4.7436	0.0105
197	4.7540	0.0104
198	4.7644	0.0104
199	4.7747	0.0104
200	4.7851	0.0103
201	4.7954	0.0103
202	4.8057	0.0103
203	4.8159	0.0102
204	4.8261	0.0102
205	4.8363	0.0102
206	4.8465	0.0102
207	4.8566	0.0101
208	4.8667	0.0101
209	4.8768	0.0101
210	4.8868	0.0100
211	4.8968	0.0100
212	4.9068	0.0100
213	4.9168	0.0100
214	4.9268	0.0099
215	4.9367	0.0099
216	4.9466	0.0099
217	4.9564	0.0099
218	4.9663	0.0098
219	4.9761	0.0098
220	4.9859	0.0098
221	4.9956	0.0098
222	5.0054	0.0097
223	5.0151	0.0097
224	5.0247	0.0097
225	5.0344	0.0097
226	5.0440	0.0096
227	5.0537	0.0096
228	5.0632	0.0096
229	5.0728	0.0096
230	5.0824	0.0095
231	5.0919	0.0095
232	5.1014	0.0095
233	5.1108	0.0095
234	5.1203	0.0094
235	5.1297	0.0094
236	5.1391	0.0094
237	5.1485	0.0094
238	5.1579	0.0094
239	5.1672	0.0093
240	5.1765	0.0093

241	5.1858	0.0093
242	5.1951	0.0093
243	5.2043	0.0092
244	5.2135	0.0092
245	5.2227	0.0092
246	5.2319	0.0092
247	5.2411	0.0092
248	5.2502	0.0091
249	5.2593	0.0091
250	5.2684	0.0091
251	5.2775	0.0091
252	5.2866	0.0091
253	5.2956	0.0090
254	5.3046	0.0090
255	5.3136	0.0090
256	5.3226	0.0090
257	5.3316	0.0090
258	5.3405	0.0089
259	5.3494	0.0089
260	5.3583	0.0089
261	5.3672	0.0089
262	5.3760	0.0089
263	5.3849	0.0088
264	5.3937	0.0088
265	5.4025	0.0088
266	5.4113	0.0088
267	5.4201	0.0088
268	5.4288	0.0087
269	5.4375	0.0087
270	5.4462	0.0087
271	5.4549	0.0087
272	5.4636	0.0087
273	5.4722	0.0087
274	5.4809	0.0086
275	5.4895	0.0086
276	5.4981	0.0086
277	5.5067	0.0086
278	5.5152	0.0086
279	5.5238	0.0085
280	5.5323	0.0085
281	5.5408	0.0085
282	5.5493	0.0085
283	5.5578	0.0085
284	5.5663	0.0085
285	5.5747	0.0084
286	5.5831	0.0084
287	5.5916	0.0084
288	5.5999	0.0084

Unit Period (number)	Unit Rainfall (In)	Unit Soil-Loss (In)	Effective Rainfall (In)
1	0.0084	0.0010	0.0074
2	0.0084	0.0010	0.0074
3	0.0084	0.0010	0.0074
4	0.0085	0.0010	0.0075
5	0.0085	0.0010	0.0075
6	0.0085	0.0010	0.0075
7	0.0085	0.0010	0.0075
8	0.0086	0.0010	0.0075
9	0.0086	0.0010	0.0076
10	0.0086	0.0010	0.0076
11	0.0087	0.0010	0.0076
12	0.0087	0.0010	0.0076
13	0.0087	0.0010	0.0077
14	0.0087	0.0010	0.0077
15	0.0088	0.0010	0.0077
16	0.0088	0.0010	0.0077
17	0.0088	0.0010	0.0078
18	0.0088	0.0011	0.0078

19	0.0089	0.0011	0.0078
20	0.0089	0.0011	0.0078
21	0.0089	0.0011	0.0079
22	0.0090	0.0011	0.0079
23	0.0090	0.0011	0.0079
24	0.0090	0.0011	0.0079
25	0.0091	0.0011	0.0080
26	0.0091	0.0011	0.0080
27	0.0091	0.0011	0.0080
28	0.0091	0.0011	0.0081
29	0.0092	0.0011	0.0081
30	0.0092	0.0011	0.0081
31	0.0092	0.0011	0.0081
32	0.0093	0.0011	0.0082
33	0.0093	0.0011	0.0082
34	0.0093	0.0011	0.0082
35	0.0094	0.0011	0.0083
36	0.0094	0.0011	0.0083
37	0.0094	0.0011	0.0083
38	0.0095	0.0011	0.0083
39	0.0095	0.0011	0.0084
40	0.0095	0.0011	0.0084
41	0.0096	0.0011	0.0084
42	0.0096	0.0011	0.0085
43	0.0097	0.0011	0.0085
44	0.0097	0.0012	0.0085
45	0.0097	0.0012	0.0086
46	0.0098	0.0012	0.0086
47	0.0098	0.0012	0.0086
48	0.0098	0.0012	0.0087
49	0.0099	0.0012	0.0087
50	0.0099	0.0012	0.0087
51	0.0100	0.0012	0.0088
52	0.0100	0.0012	0.0088
53	0.0100	0.0012	0.0089
54	0.0101	0.0012	0.0089
55	0.0101	0.0012	0.0089
56	0.0102	0.0012	0.0090
57	0.0102	0.0012	0.0090
58	0.0102	0.0012	0.0090
59	0.0103	0.0012	0.0091
60	0.0103	0.0012	0.0091
61	0.0104	0.0012	0.0092
62	0.0104	0.0012	0.0092
63	0.0105	0.0012	0.0092
64	0.0105	0.0012	0.0093
65	0.0106	0.0013	0.0093
66	0.0106	0.0013	0.0093
67	0.0107	0.0013	0.0094
68	0.0107	0.0013	0.0094
69	0.0108	0.0013	0.0095
70	0.0108	0.0013	0.0095
71	0.0109	0.0013	0.0096
72	0.0109	0.0013	0.0096
73	0.0110	0.0013	0.0097
74	0.0110	0.0013	0.0097
75	0.0111	0.0013	0.0098
76	0.0111	0.0013	0.0098
77	0.0112	0.0013	0.0099
78	0.0112	0.0013	0.0099
79	0.0113	0.0013	0.0100
80	0.0113	0.0013	0.0100
81	0.0114	0.0014	0.0101
82	0.0115	0.0014	0.0101
83	0.0115	0.0014	0.0102
84	0.0116	0.0014	0.0102
85	0.0117	0.0014	0.0103
86	0.0117	0.0014	0.0103
87	0.0118	0.0014	0.0104
88	0.0118	0.0014	0.0104
89	0.0119	0.0014	0.0105

90	0.0119	0.0014	0.0105
91	0.0120	0.0014	0.0106
92	0.0121	0.0014	0.0106
93	0.0122	0.0014	0.0107
94	0.0122	0.0015	0.0108
95	0.0123	0.0015	0.0109
96	0.0124	0.0015	0.0109
97	0.0125	0.0015	0.0110
98	0.0125	0.0015	0.0110
99	0.0126	0.0015	0.0111
100	0.0127	0.0015	0.0112
101	0.0128	0.0015	0.0113
102	0.0128	0.0015	0.0113
103	0.0129	0.0015	0.0114
104	0.0130	0.0015	0.0114
105	0.0131	0.0016	0.0115
106	0.0132	0.0016	0.0116
107	0.0133	0.0016	0.0117
108	0.0133	0.0016	0.0117
109	0.0134	0.0016	0.0119
110	0.0135	0.0016	0.0119
111	0.0136	0.0016	0.0120
112	0.0137	0.0016	0.0121
113	0.0138	0.0016	0.0122
114	0.0139	0.0017	0.0122
115	0.0140	0.0017	0.0124
116	0.0141	0.0017	0.0124
117	0.0142	0.0017	0.0125
118	0.0143	0.0017	0.0126
119	0.0145	0.0017	0.0127
120	0.0145	0.0017	0.0128
121	0.0147	0.0017	0.0129
122	0.0148	0.0018	0.0130
123	0.0149	0.0018	0.0132
124	0.0150	0.0018	0.0132
125	0.0152	0.0018	0.0134
126	0.0153	0.0018	0.0134
127	0.0154	0.0018	0.0136
128	0.0155	0.0018	0.0137
129	0.0157	0.0019	0.0138
130	0.0158	0.0019	0.0139
131	0.0160	0.0019	0.0141
132	0.0161	0.0019	0.0142
133	0.0163	0.0019	0.0144
134	0.0164	0.0019	0.0145
135	0.0166	0.0020	0.0146
136	0.0167	0.0020	0.0147
137	0.0170	0.0020	0.0149
138	0.0171	0.0020	0.0150
139	0.0173	0.0021	0.0153
140	0.0174	0.0021	0.0154
141	0.0177	0.0021	0.0156
142	0.0178	0.0021	0.0157
143	0.0181	0.0021	0.0159
144	0.0182	0.0022	0.0161
145	0.0210	0.0025	0.0185
146	0.0212	0.0025	0.0187
147	0.0215	0.0026	0.0189
148	0.0217	0.0026	0.0191
149	0.0220	0.0026	0.0194
150	0.0222	0.0026	0.0195
151	0.0225	0.0027	0.0199
152	0.0227	0.0027	0.0200
153	0.0231	0.0027	0.0204
154	0.0233	0.0028	0.0205
155	0.0237	0.0028	0.0209
156	0.0239	0.0028	0.0211
157	0.0244	0.0029	0.0215
158	0.0246	0.0029	0.0217
159	0.0251	0.0030	0.0221
160	0.0254	0.0030	0.0224

161	0.0259	0.0031	0.0228
162	0.0262	0.0031	0.0231
163	0.0268	0.0032	0.0236
164	0.0271	0.0032	0.0239
165	0.0278	0.0033	0.0245
166	0.0281	0.0033	0.0248
167	0.0288	0.0034	0.0254
168	0.0292	0.0035	0.0258
169	0.0301	0.0036	0.0265
170	0.0305	0.0036	0.0269
171	0.0315	0.0037	0.0277
172	0.0320	0.0038	0.0282
173	0.0331	0.0039	0.0291
174	0.0336	0.0040	0.0296
175	0.0349	0.0041	0.0308
176	0.0356	0.0042	0.0314
177	0.0371	0.0044	0.0327
178	0.0380	0.0045	0.0334
179	0.0398	0.0047	0.0351
180	0.0408	0.0049	0.0360
181	0.0431	0.0051	0.0380
182	0.0445	0.0053	0.0392
183	0.0475	0.0056	0.0418
184	0.0492	0.0059	0.0434
185	0.0438	0.0052	0.0386
186	0.0462	0.0055	0.0407
187	0.0525	0.0062	0.0462
188	0.0566	0.0065	0.0500
189	0.0682	0.0065	0.0617
190	0.0770	0.0065	0.0704
191	0.1100	0.0065	0.1035
192	0.1513	0.0065	0.1448
193	0.4736	0.0065	0.4670
194	0.0896	0.0065	0.0831
195	0.0617	0.0065	0.0551
196	0.0491	0.0058	0.0433
197	0.0512	0.0061	0.0451
198	0.0459	0.0055	0.0404
199	0.0419	0.0050	0.0370
200	0.0388	0.0046	0.0342
201	0.0363	0.0043	0.0320
202	0.0343	0.0041	0.0302
203	0.0325	0.0039	0.0286
204	0.0310	0.0037	0.0273
205	0.0296	0.0035	0.0261
206	0.0285	0.0034	0.0251
207	0.0274	0.0033	0.0242
208	0.0265	0.0031	0.0233
209	0.0256	0.0030	0.0226
210	0.0249	0.0030	0.0219
211	0.0242	0.0029	0.0213
212	0.0235	0.0028	0.0207
213	0.0229	0.0027	0.0202
214	0.0224	0.0027	0.0197
215	0.0218	0.0026	0.0192
216	0.0213	0.0025	0.0188
217	0.0184	0.0022	0.0162
218	0.0180	0.0021	0.0158
219	0.0176	0.0021	0.0155
220	0.0172	0.0020	0.0151
221	0.0168	0.0020	0.0148
222	0.0165	0.0020	0.0145
223	0.0162	0.0019	0.0143
224	0.0159	0.0019	0.0140
225	0.0156	0.0019	0.0138
226	0.0153	0.0018	0.0135
227	0.0151	0.0018	0.0133
228	0.0148	0.0018	0.0131
229	0.0146	0.0017	0.0129
230	0.0144	0.0017	0.0127
231	0.0142	0.0017	0.0125

232	0.0140	0.0017	0.0123
233	0.0138	0.0016	0.0121
234	0.0136	0.0016	0.0120
235	0.0134	0.0016	0.0118
236	0.0132	0.0016	0.0116
237	0.0130	0.0015	0.0115
238	0.0129	0.0015	0.0113
239	0.0127	0.0015	0.0112
240	0.0126	0.0015	0.0111
241	0.0124	0.0015	0.0109
242	0.0123	0.0015	0.0108
243	0.0121	0.0014	0.0107
244	0.0120	0.0014	0.0106
245	0.0119	0.0014	0.0105
246	0.0117	0.0014	0.0103
247	0.0116	0.0014	0.0102
248	0.0115	0.0014	0.0101
249	0.0114	0.0014	0.0100
250	0.0113	0.0013	0.0099
251	0.0112	0.0013	0.0098
252	0.0110	0.0013	0.0097
253	0.0109	0.0013	0.0096
254	0.0108	0.0013	0.0095
255	0.0107	0.0013	0.0095
256	0.0106	0.0013	0.0094
257	0.0105	0.0013	0.0093
258	0.0105	0.0012	0.0092
259	0.0104	0.0012	0.0091
260	0.0103	0.0012	0.0091
261	0.0102	0.0012	0.0090
262	0.0101	0.0012	0.0089
263	0.0100	0.0012	0.0088
264	0.0099	0.0012	0.0088
265	0.0099	0.0012	0.0087
266	0.0098	0.0012	0.0086
267	0.0097	0.0012	0.0086
268	0.0096	0.0011	0.0085
269	0.0096	0.0011	0.0084
270	0.0095	0.0011	0.0084
271	0.0094	0.0011	0.0083
272	0.0094	0.0011	0.0082
273	0.0093	0.0011	0.0082
274	0.0092	0.0011	0.0081
275	0.0092	0.0011	0.0081
276	0.0091	0.0011	0.0080
277	0.0090	0.0011	0.0080
278	0.0090	0.0011	0.0079
279	0.0089	0.0011	0.0079
280	0.0089	0.0011	0.0078
281	0.0088	0.0010	0.0078
282	0.0087	0.0010	0.0077
283	0.0087	0.0010	0.0077
284	0.0086	0.0010	0.0076
285	0.0086	0.0010	0.0076
286	0.0085	0.0010	0.0075
287	0.0085	0.0010	0.0075
288	0.0084	0.0010	0.0074

Total soil rain loss = 0.59(In)
Total effective rainfall = 5.01(In)
Peak flow rate in flood hydrograph = 23.24(CFS)

++


24 - H O U R S T O R M
R u n o f f H y d r o g r a p h

Hydrograph in 5 Minute intervals ((CFS))

Time(h+m) Volume Ac.Ft Q(CFS) 0 7.5 15.0 22.5 30.0

0+ 5	0.0002	0.03	Q				
0+10	0.0017	0.21	Q				
0+15	0.0051	0.49	Q				
0+20	0.0094	0.63	Q				
0+25	0.0141	0.68	Q				
0+30	0.0189	0.70	Q				
0+35	0.0238	0.71	Q				
0+40	0.0287	0.71	Q				
0+45	0.0336	0.71	Q				
0+50	0.0385	0.71	Q				
0+55	0.0434	0.71	Q				
1+ 0	0.0483	0.72	Q				
1+ 5	0.0533	0.72	Q				
1+10	0.0582	0.72	Q				
1+15	0.0632	0.72	Q				
1+20	0.0682	0.73	Q				
1+25	0.0732	0.73	Q				
1+30	0.0782	0.73	Q				
1+35	0.0833	0.73	QV				
1+40	0.0884	0.73	QV				
1+45	0.0934	0.74	QV				
1+50	0.0985	0.74	QV				
1+55	0.1036	0.74	QV				
2+ 0	0.1088	0.74	QV				
2+ 5	0.1139	0.75	QV				
2+10	0.1191	0.75	QV				
2+15	0.1243	0.75	|Q				
2+20	0.1295	0.75	|Q				
2+25	0.1347	0.76	|Q				
2+30	0.1399	0.76	|Q				
2+35	0.1452	0.76	|Q				
2+40	0.1504	0.77	|Q				
2+45	0.1557	0.77	|Q				
2+50	0.1610	0.77	|Q				
2+55	0.1664	0.77	|QV				
3+ 0	0.1717	0.78	|QV				
3+ 5	0.1771	0.78	|QV				
3+10	0.1825	0.78	|QV				
3+15	0.1879	0.78	|QV				
3+20	0.1933	0.79	|QV				
3+25	0.1987	0.79	|QV				
3+30	0.2042	0.79	|QV				
3+35	0.2097	0.80	|QV				
3+40	0.2152	0.80	|QV				
3+45	0.2207	0.80	|QV				
3+50	0.2263	0.81	|QV				
3+55	0.2318	0.81	|QV				
4+ 0	0.2374	0.81	|QV				
4+ 5	0.2430	0.81	|QV				
4+10	0.2487	0.82	|Q V				
4+15	0.2543	0.82	|Q V				
4+20	0.2600	0.82	|Q V				
4+25	0.2657	0.83	|Q V				
4+30	0.2714	0.83	|Q V				
4+35	0.2772	0.83	|Q V				
4+40	0.2829	0.84	|Q V				
4+45	0.2887	0.84	|Q V				
4+50	0.2945	0.84	|Q V				
4+55	0.3004	0.85	|Q V				
5+ 0	0.3063	0.85	|Q V				
5+ 5	0.3121	0.86	|Q V				
5+10	0.3181	0.86	|Q V				
5+15	0.3240	0.86	|Q V				
5+20	0.3300	0.87	|Q V				
5+25	0.3360	0.87	|Q V				
5+30	0.3420	0.87	|Q V				
5+35	0.3480	0.88	|Q V				
5+40	0.3541	0.88	|Q V				
5+45	0.3602	0.89	|Q V				
5+50	0.3664	0.89	|Q V				

```
 5+55       0.3725      0.89  |Q  V     |         |         |         |
 6+ 0       0.3787      0.90  |Q  V     |         |         |         |
 6+ 5       0.3849      0.90  |Q  V     |         |         |         |
 6+10       0.3912      0.91  |Q  V     |         |         |         |
 6+15       0.3974      0.91  |Q  V     |         |         |         |
 6+20       0.4037      0.92  |Q  V     |         |         |         |
 6+25       0.4101      0.92  |Q   V    |         |         |         |
 6+30       0.4164      0.92  |Q   V    |         |         |         |
 6+35       0.4228      0.93  |Q   V    |         |         |         |
 6+40       0.4293      0.93  |Q   V    |         |         |         |
 6+45       0.4357      0.94  |Q   V    |         |         |         |
 6+50       0.4422      0.94  |Q   V    |         |         |         |
 6+55       0.4487      0.95  |Q   V    |         |         |         |
 7+ 0       0.4553      0.95  |Q   V    |         |         |         |
 7+ 5       0.4619      0.96  |Q   V    |         |         |         |
 7+10       0.4685      0.96  |Q   V    |         |         |         |
 7+15       0.4752      0.97  |Q   V    |         |         |         |
 7+20       0.4819      0.97  |Q   V    |         |         |         |
 7+25       0.4886      0.98  |Q    V   |         |         |         |
 7+30       0.4954      0.98  |Q    V   |         |         |         |
 7+35       0.5022      0.99  |Q    V   |         |         |         |
 7+40       0.5090      0.99  |Q    V   |         |         |         |
 7+45       0.5159      1.00  |Q    V   |         |         |         |
 7+50       0.5228      1.00  |Q    V   |         |         |         |
 7+55       0.5298      1.01  |Q    V   |         |         |         |
 8+ 0       0.5368      1.02  |Q    V   |         |         |         |
 8+ 5       0.5438      1.02  |Q    V   |         |         |         |
 8+10       0.5509      1.03  |Q    V   |         |         |         |
 8+15       0.5580      1.03  |Q    V   |         |         |         |
 8+20       0.5652      1.04  |Q    V   |         |         |         |
 8+25       0.5724      1.05  |Q     V  |         |         |         |
 8+30       0.5797      1.05  |Q     V  |         |         |         |
 8+35       0.5870      1.06  |Q     V  |         |         |         |
 8+40       0.5943      1.07  |Q     V  |         |         |         |
 8+45       0.6017      1.07  |Q     V  |         |         |         |
 8+50       0.6092      1.08  |Q     V  |         |         |         |
 8+55       0.6166      1.09  |Q     V  |         |         |         |
 9+ 0       0.6242      1.09  |Q     V  |         |         |         |
 9+ 5       0.6318      1.10  |Q     V  |         |         |         |
 9+10       0.6394      1.11  |Q     V  |         |         |         |
 9+15       0.6471      1.12  |Q     V  |         |         |         |
 9+20       0.6548      1.12  |Q      V |         |         |         |
 9+25       0.6626      1.13  |Q      V |         |         |         |
 9+30       0.6705      1.14  |Q      V |         |         |         |
 9+35       0.6784      1.15  |Q      V |         |         |         |
 9+40       0.6863      1.16  |Q      V |         |         |         |
 9+45       0.6943      1.16  |Q      V |         |         |         |
 9+50       0.7024      1.17  |Q      V |         |         |         |
 9+55       0.7106      1.18  |Q      V |         |         |         |
10+ 0       0.7188      1.19  |Q      V |         |         |         |
10+ 5       0.7270      1.20  |Q      V |         |         |         |
10+10       0.7354      1.21  |Q       V|         |         |         |
10+15       0.7437      1.22  |Q       V|         |         |         |
10+20       0.7522      1.23  |Q       V|         |         |         |
10+25       0.7607      1.24  |Q       V|         |         |         |
10+30       0.7693      1.25  |Q       V|         |         |         |
10+35       0.7780      1.26  |Q       V|         |         |         |
10+40       0.7867      1.27  |Q       V|         |         |         |
10+45       0.7956      1.28  |Q       V|         |         |         |
10+50       0.8045      1.29  |Q       V|         |         |         |
10+55       0.8134      1.30  |Q       V|         |         |         |
11+ 0       0.8225      1.31  |Q        V         |         |         |
11+ 5       0.8316      1.33  |Q        V         |         |         |
11+10       0.8409      1.34  |Q        V         |         |         |
11+15       0.8502      1.35  |Q        V         |         |         |
11+20       0.8596      1.36  |Q        V         |         |         |
11+25       0.8691      1.38  |Q        V         |         |         |
11+30       0.8786      1.39  |Q        V         |         |         |
11+35       0.8883      1.41  |Q        V         |         |         |
11+40       0.8981      1.42  |Q        |V        |         |         |
11+45       0.9080      1.44  |Q        |V        |         |         |
```



17+45	2.7076	2.02	Q			V	
17+50	2.7211	1.96	Q			V	
17+55	2.7343	1.91	Q			V	
18+ 0	2.7471	1.86	Q			V	
18+ 5	2.7596	1.81	Q			V	
18+10	2.7714	1.71	Q			V	
18+15	2.7823	1.59	Q			V	
18+20	2.7928	1.52	Q			V	
18+25	2.8029	1.47	Q			V	
18+30	2.8128	1.43	Q			V	
18+35	2.8225	1.40	Q			V	
18+40	2.8319	1.38	Q			V	
18+45	2.8412	1.35	Q			V	
18+50	2.8503	1.32	Q			V	
18+55	2.8593	1.30	Q			V	
19+ 0	2.8681	1.28	Q			V	
19+ 5	2.8768	1.26	Q			V	
19+10	2.8853	1.24	Q			V	
19+15	2.8936	1.22	Q			V	
19+20	2.9019	1.20	Q			V	
19+25	2.9100	1.18	Q			V	
19+30	2.9180	1.16	Q			V	
19+35	2.9259	1.15	Q			V	
19+40	2.9337	1.13	Q			V	
19+45	2.9414	1.11	Q			V	
19+50	2.9489	1.10	Q			V	
19+55	2.9564	1.09	Q			V	
20+ 0	2.9638	1.07	Q			V	
20+ 5	2.9711	1.06	Q			V	
20+10	2.9783	1.05	Q			V	
20+15	2.9854	1.03	Q			V	
20+20	2.9924	1.02	Q			V	
20+25	2.9994	1.01	Q			V	
20+30	3.0063	1.00	Q			V	
20+35	3.0131	0.99	Q			V	
20+40	3.0198	0.98	Q			V	
20+45	3.0264	0.97	Q			V	
20+50	3.0330	0.96	Q			V	
20+55	3.0395	0.95	Q			V	
21+ 0	3.0460	0.94	Q			V	
21+ 5	3.0524	0.93	Q			V	
21+10	3.0587	0.92	Q			V	
21+15	3.0650	0.91	Q			V	
21+20	3.0712	0.90	Q			V	
21+25	3.0773	0.89	Q			V	
21+30	3.0834	0.89	Q			V	
21+35	3.0895	0.88	Q			V	
21+40	3.0955	0.87	Q			V	
21+45	3.1014	0.86	Q			V	
21+50	3.1073	0.85	Q			V	
21+55	3.1131	0.85	Q			V	
22+ 0	3.1189	0.84	Q			V	
22+ 5	3.1247	0.83	Q			V	
22+10	3.1304	0.83	Q			V	
22+15	3.1360	0.82	Q			V	
22+20	3.1416	0.81	Q			V	
22+25	3.1472	0.81	Q			V	
22+30	3.1527	0.80	Q			V	
22+35	3.1582	0.80	Q			V	
22+40	3.1636	0.79	Q			V	
22+45	3.1690	0.78	Q			V	
22+50	3.1744	0.78	Q			V	
22+55	3.1797	0.77	Q			V	
23+ 0	3.1850	0.77	Q			V	
23+ 5	3.1902	0.76	Q			V	
23+10	3.1954	0.76	Q			V	
23+15	3.2006	0.75	Q			V	
23+20	3.2058	0.75	Q			V	
23+25	3.2109	0.74	Q			V	
23+30	3.2159	0.74	Q			V	
23+35	3.2210	0.73	Q			V	

```
   23+40       3.2260      0.73  Q         |         |         |        V|
   23+45       3.2310      0.72  Q         |         |         |        V|
   23+50       3.2359      0.72  Q         |         |         |        V|
   23+55       3.2408      0.71  Q         |         |         |        V|
   24+ 0       3.2457      0.71  Q         |         |         |        V|
   24+ 5       3.2503      0.67  Q         |         |         |        V|
   24+10       3.2537      0.49  Q         |         |         |        V|
   24+15       3.2551      0.21  Q         |         |         |        V|
   24+20       3.2556      0.07  Q         |         |         |        V|
   24+25       3.2557      0.02  Q         |         |         |        V|
   24+30       3.2558      0.01  Q         |         |         |         V
-------------------------------------------------------------------------
```

Unit Hydrograph Analysis: Existing Condition (100 yr, 24 hr Storm Event)

```
       U n i t   H y d r o g r a p h   A n a l y s i s

       Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018, Version 9.0

              Study date  06/19/23

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
------------------------------------------------------------------------------

San Bernardino County Synthetic Unit Hydrology Method
              Manual date - August 1986


Program License Serial Number 6484

------------------------------------------------------------------------
UH ANALYSIS
EXISTING CONDITION
100-YR STORM EVENT

------------------------------------------------------------------------

       Storm Event Year = 100

       Antecedent Moisture Condition = 2

 English (in-lb) Input Units Used

 English Rainfall Data (Inches) Input Values Used

 English Units used in output format



Area averaged rainfall intensity isohyetal data:
       Sub-Area        Duration        Isohyetal
       (Ac.)            (hours)         (In)
Rainfall data for year 100
            7.80            1           1.00
------------------------------------------------------------------------
Rainfall data for year 100
            7.80            6           2.47
------------------------------------------------------------------------
Rainfall data for year 100
            7.80           24           4.52
------------------------------------------------------------------------
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

******** Area-averaged max loss rate, Fm ********


SCS curve  SCS curve     Area     Area     Fp(Fig C6)    Ap      Fm
No.(AMCII) NO.(AMC 2)    (Ac.)    Fraction     (In/Hr)  (dec.)   (In/Hr)
 32.0      32.0          7.80      1.000     0.978    0.594    0.581

Area-averaged adjusted loss rate Fm (In/Hr) =  0.581

********* Area-Averaged low loss rate fraction, Yb **********

Area       Area          SCS CN    SCS CN      S     Pervious
 (Ac.)      Fract         (AMC2)    (AMC2)           Yield Fr
     4.63   0.594         32.0      32.0      21.25     0.001
     3.17   0.406         98.0      98.0       0.20     0.948

Area-averaged catchment yield fraction, Y =  0.385
Area-averaged low loss fraction, Yb =  0.615
Direct entry of lag time by user
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
```

Watershed area = 7.80(Ac.)
Catchment Lag time = 0.212 hours
Unit interval = 5.000 minutes
Unit interval percentage of lag time = 39.2711
Hydrograph baseflow = 0.00(CFS)
Average maximum watershed loss rate(Fm) = 0.581(In/Hr)
Average low loss rate fraction (Yb) = 0.615 (decimal)
VALLEY DEVELOPED S-Graph proportion = 0.300
VALLEY UNDEVELOPED S-Graph proportion = 0.700
FOOTHILL S-Graph proportion = 0.000
MOUNTAIN S-Graph proportion = 0.000
DESERT S-Graph proportion = 0.000

Computed peak 5-minute rainfall = 0.369(In)
Computed peak 30-minute rainfall = 0.756(In)
Specified peak 1-hour rainfall = 0.997(In)
Computed peak 3-hour rainfall = 1.739(In)
Specified peak 6-hour rainfall = 2.470(In)
Specified peak 24-hour rainfall = 4.520(In)

Rainfall depth area reduction factors:
Using a total area of 7.80(Ac.) (Ref: fig. E-4)

5-minute factor = 1.000 Adjusted rainfall = 0.369(In)
30-minute factor = 1.000 Adjusted rainfall = 0.755(In)
1-hour factor = 1.000 Adjusted rainfall = 0.997(In)
3-hour factor = 1.000 Adjusted rainfall = 1.739(In)
6-hour factor = 1.000 Adjusted rainfall = 2.470(In)
24-hour factor = 1.000 Adjusted rainfall = 4.520(In)

U n i t H y d r o g r a p h

Interval Number	'S' Graph Mean values	Unit Hydrograph ((CFS))
	(K = 94.33 (CFS))	
1	3.850	3.632
2	20.757	15.948
3	47.935	25.638
4	68.988	19.860
5	79.273	9.702
6	84.829	5.241
7	88.269	3.245
8	90.683	2.278
9	92.668	1.872
10	94.061	1.314
11	95.161	1.038
12	96.038	0.828
13	96.861	0.776
14	97.524	0.626
15	98.075	0.519
16	98.541	0.440
17	98.919	0.357
18	99.211	0.275
19	99.486	0.259
20	99.761	0.259
21	100.000	0.226

Peak Unit Number	Adjusted mass rainfall (In)	Unit rainfall (In)
1	0.3689	0.3689
2	0.4867	0.1179
3	0.5724	0.0857
4	0.6422	0.0698
5	0.7022	0.0600
6	0.7553	0.0531
7	0.8033	0.0480
8	0.8474	0.0441

9	0.8883	0.0409
10	0.9265	0.0382
11	0.9625	0.0360
12	0.9966	0.0341
13	1.0379	0.0412
14	1.0776	0.0397
15	1.1159	0.0383
16	1.1530	0.0371
17	1.1890	0.0360
18	1.2239	0.0349
19	1.2579	0.0340
20	1.2910	0.0331
21	1.3233	0.0323
22	1.3549	0.0316
23	1.3857	0.0309
24	1.4159	0.0302
25	1.4455	0.0296
26	1.4745	0.0290
27	1.5030	0.0285
28	1.5310	0.0279
29	1.5584	0.0275
30	1.5854	0.0270
31	1.6120	0.0266
32	1.6381	0.0261
33	1.6638	0.0257
34	1.6892	0.0254
35	1.7142	0.0250
36	1.7388	0.0246
37	1.7631	0.0243
38	1.7871	0.0240
39	1.8107	0.0237
40	1.8341	0.0234
41	1.8572	0.0231
42	1.8800	0.0228
43	1.9025	0.0225
44	1.9248	0.0223
45	1.9468	0.0220
46	1.9686	0.0218
47	1.9902	0.0216
48	2.0115	0.0213
49	2.0326	0.0211
50	2.0535	0.0209
51	2.0742	0.0207
52	2.0947	0.0205
53	2.1150	0.0203
54	2.1351	0.0201
55	2.1550	0.0199
56	2.1748	0.0198
57	2.1944	0.0196
58	2.2138	0.0194
59	2.2330	0.0192
60	2.2521	0.0191
61	2.2711	0.0189
62	2.2898	0.0188
63	2.3085	0.0186
64	2.3269	0.0185
65	2.3453	0.0183
66	2.3635	0.0182
67	2.3815	0.0181
68	2.3995	0.0179
69	2.4173	0.0178
70	2.4350	0.0177
71	2.4525	0.0176
72	2.4699	0.0174
73	2.4848	0.0149
74	2.4996	0.0148
75	2.5143	0.0147
76	2.5288	0.0146
77	2.5433	0.0145
78	2.5576	0.0143
79	2.5719	0.0142

80	2.5860	0.0141
81	2.6001	0.0140
82	2.6140	0.0139
83	2.6279	0.0138
84	2.6416	0.0138
85	2.6553	0.0137
86	2.6689	0.0136
87	2.6823	0.0135
88	2.6957	0.0134
89	2.7090	0.0133
90	2.7223	0.0132
91	2.7354	0.0131
92	2.7485	0.0131
93	2.7615	0.0130
94	2.7744	0.0129
95	2.7872	0.0128
96	2.7999	0.0128
97	2.8126	0.0127
98	2.8252	0.0126
99	2.8378	0.0125
100	2.8502	0.0125
101	2.8626	0.0124
102	2.8749	0.0123
103	2.8872	0.0123
104	2.8994	0.0122
105	2.9115	0.0121
106	2.9235	0.0121
107	2.9355	0.0120
108	2.9475	0.0119
109	2.9593	0.0119
110	2.9711	0.0118
111	2.9829	0.0117
112	2.9946	0.0117
113	3.0062	0.0116
114	3.0177	0.0116
115	3.0293	0.0115
116	3.0407	0.0115
117	3.0521	0.0114
118	3.0635	0.0113
119	3.0747	0.0113
120	3.0860	0.0112
121	3.0972	0.0112
122	3.1083	0.0111
123	3.1194	0.0111
124	3.1304	0.0110
125	3.1414	0.0110
126	3.1523	0.0109
127	3.1632	0.0109
128	3.1740	0.0108
129	3.1848	0.0108
130	3.1956	0.0107
131	3.2063	0.0107
132	3.2169	0.0106
133	3.2275	0.0106
134	3.2381	0.0106
135	3.2486	0.0105
136	3.2590	0.0105
137	3.2695	0.0104
138	3.2798	0.0104
139	3.2902	0.0103
140	3.3005	0.0103
141	3.3107	0.0103
142	3.3210	0.0102
143	3.3311	0.0102
144	3.3413	0.0101
145	3.3514	0.0101
146	3.3614	0.0101
147	3.3714	0.0100
148	3.3814	0.0100
149	3.3913	0.0099
150	3.4012	0.0099

151	3.4111	0.0099
152	3.4209	0.0098
153	3.4307	0.0098
154	3.4405	0.0098
155	3.4502	0.0097
156	3.4599	0.0097
157	3.4696	0.0097
158	3.4792	0.0096
159	3.4887	0.0096
160	3.4983	0.0095
161	3.5078	0.0095
162	3.5173	0.0095
163	3.5267	0.0094
164	3.5362	0.0094
165	3.5455	0.0094
166	3.5549	0.0094
167	3.5642	0.0093
168	3.5735	0.0093
169	3.5828	0.0093
170	3.5920	0.0092
171	3.6012	0.0092
172	3.6103	0.0092
173	3.6195	0.0091
174	3.6286	0.0091
175	3.6377	0.0091
176	3.6467	0.0090
177	3.6557	0.0090
178	3.6647	0.0090
179	3.6737	0.0090
180	3.6826	0.0089
181	3.6915	0.0089
182	3.7004	0.0089
183	3.7092	0.0088
184	3.7181	0.0088
185	3.7269	0.0088
186	3.7356	0.0088
187	3.7444	0.0087
188	3.7531	0.0087
189	3.7618	0.0087
190	3.7704	0.0087
191	3.7791	0.0086
192	3.7877	0.0086
193	3.7963	0.0086
194	3.8048	0.0086
195	3.8134	0.0085
196	3.8219	0.0085
197	3.8304	0.0085
198	3.8388	0.0085
199	3.8473	0.0084
200	3.8557	0.0084
201	3.8641	0.0084
202	3.8724	0.0084
203	3.8808	0.0083
204	3.8891	0.0083
205	3.8974	0.0083
206	3.9057	0.0083
207	3.9139	0.0083
208	3.9222	0.0082
209	3.9304	0.0082
210	3.9386	0.0082
211	3.9467	0.0082
212	3.9549	0.0081
213	3.9630	0.0081
214	3.9711	0.0081
215	3.9792	0.0081
216	3.9872	0.0081
217	3.9953	0.0080
218	4.0033	0.0080
219	4.0113	0.0080
220	4.0193	0.0080
221	4.0272	0.0080

222	4.0351	0.0079	
223	4.0431	0.0079	
224	4.0509	0.0079	
225	4.0588	0.0079	
226	4.0667	0.0079	
227	4.0745	0.0078	
228	4.0823	0.0078	
229	4.0901	0.0078	
230	4.0979	0.0078	
231	4.1056	0.0078	
232	4.1134	0.0077	
233	4.1211	0.0077	
234	4.1288	0.0077	
235	4.1365	0.0077	
236	4.1442	0.0077	
237	4.1518	0.0076	
238	4.1594	0.0076	
239	4.1670	0.0076	
240	4.1746	0.0076	
241	4.1822	0.0076	
242	4.1898	0.0076	
243	4.1973	0.0075	
244	4.2048	0.0075	
245	4.2123	0.0075	
246	4.2198	0.0075	
247	4.2273	0.0075	
248	4.2347	0.0075	
249	4.2422	0.0074	
250	4.2496	0.0074	
251	4.2570	0.0074	
252	4.2644	0.0074	
253	4.2717	0.0074	
254	4.2791	0.0074	
255	4.2864	0.0073	
256	4.2937	0.0073	
257	4.3010	0.0073	
258	4.3083	0.0073	
259	4.3156	0.0073	
260	4.3229	0.0073	
261	4.3301	0.0072	
262	4.3373	0.0072	
263	4.3445	0.0072	
264	4.3517	0.0072	
265	4.3589	0.0072	
266	4.3661	0.0072	
267	4.3732	0.0071	
268	4.3803	0.0071	
269	4.3875	0.0071	
270	4.3946	0.0071	
271	4.4017	0.0071	
272	4.4087	0.0071	
273	4.4158	0.0071	
274	4.4228	0.0070	
275	4.4299	0.0070	
276	4.4369	0.0070	
277	4.4439	0.0070	
278	4.4509	0.0070	
279	4.4578	0.0070	
280	4.4648	0.0070	
281	4.4717	0.0069	
282	4.4787	0.0069	
283	4.4856	0.0069	
284	4.4925	0.0069	
285	4.4994	0.0069	
286	4.5062	0.0069	
287	4.5131	0.0069	
288	4.5200	0.0068	

Unit Period (number)	Unit Rainfall (In)	Unit Soil-Loss (In)	Effective Rainfall (In)

1	0.0068	0.0042	0.0026
2	0.0069	0.0042	0.0026
3	0.0069	0.0042	0.0027
4	0.0069	0.0042	0.0027
5	0.0069	0.0043	0.0027
6	0.0069	0.0043	0.0027
7	0.0070	0.0043	0.0027
8	0.0070	0.0043	0.0027
9	0.0070	0.0043	0.0027
10	0.0070	0.0043	0.0027
11	0.0071	0.0043	0.0027
12	0.0071	0.0043	0.0027
13	0.0071	0.0044	0.0027
14	0.0071	0.0044	0.0027
15	0.0071	0.0044	0.0028
16	0.0072	0.0044	0.0028
17	0.0072	0.0044	0.0028
18	0.0072	0.0044	0.0028
19	0.0072	0.0045	0.0028
20	0.0073	0.0045	0.0028
21	0.0073	0.0045	0.0028
22	0.0073	0.0045	0.0028
23	0.0073	0.0045	0.0028
24	0.0074	0.0045	0.0028
25	0.0074	0.0045	0.0028
26	0.0074	0.0046	0.0029
27	0.0074	0.0046	0.0029
28	0.0075	0.0046	0.0029
29	0.0075	0.0046	0.0029
30	0.0075	0.0046	0.0029
31	0.0075	0.0046	0.0029
32	0.0076	0.0046	0.0029
33	0.0076	0.0047	0.0029
34	0.0076	0.0047	0.0029
35	0.0076	0.0047	0.0029
36	0.0077	0.0047	0.0030
37	0.0077	0.0047	0.0030
38	0.0077	0.0047	0.0030
39	0.0078	0.0048	0.0030
40	0.0078	0.0048	0.0030
41	0.0078	0.0048	0.0030
42	0.0078	0.0048	0.0030
43	0.0079	0.0048	0.0030
44	0.0079	0.0049	0.0030
45	0.0079	0.0049	0.0031
46	0.0080	0.0049	0.0031
47	0.0080	0.0049	0.0031
48	0.0080	0.0049	0.0031
49	0.0081	0.0050	0.0031
50	0.0081	0.0050	0.0031
51	0.0081	0.0050	0.0031
52	0.0081	0.0050	0.0031
53	0.0082	0.0050	0.0032
54	0.0082	0.0050	0.0032
55	0.0083	0.0051	0.0032
56	0.0083	0.0051	0.0032
57	0.0083	0.0051	0.0032
58	0.0083	0.0051	0.0032
59	0.0084	0.0052	0.0032
60	0.0084	0.0052	0.0032
61	0.0085	0.0052	0.0033
62	0.0085	0.0052	0.0033
63	0.0085	0.0052	0.0033
64	0.0086	0.0053	0.0033
65	0.0086	0.0053	0.0033
66	0.0086	0.0053	0.0033
67	0.0087	0.0053	0.0033
68	0.0087	0.0054	0.0034
69	0.0088	0.0054	0.0034
70	0.0088	0.0054	0.0034

71	0.0088	0.0054	0.0034
72	0.0089	0.0055	0.0034
73	0.0089	0.0055	0.0034
74	0.0090	0.0055	0.0035
75	0.0090	0.0055	0.0035
76	0.0090	0.0056	0.0035
77	0.0091	0.0056	0.0035
78	0.0091	0.0056	0.0035
79	0.0092	0.0057	0.0035
80	0.0092	0.0057	0.0036
81	0.0093	0.0057	0.0036
82	0.0093	0.0057	0.0036
83	0.0094	0.0058	0.0036
84	0.0094	0.0058	0.0036
85	0.0095	0.0058	0.0037
86	0.0095	0.0058	0.0037
87	0.0096	0.0059	0.0037
88	0.0096	0.0059	0.0037
89	0.0097	0.0060	0.0037
90	0.0097	0.0060	0.0037
91	0.0098	0.0060	0.0038
92	0.0098	0.0060	0.0038
93	0.0099	0.0061	0.0038
94	0.0099	0.0061	0.0038
95	0.0100	0.0062	0.0039
96	0.0101	0.0062	0.0039
97	0.0101	0.0062	0.0039
98	0.0102	0.0063	0.0039
99	0.0103	0.0063	0.0040
100	0.0103	0.0063	0.0040
101	0.0104	0.0064	0.0040
102	0.0104	0.0064	0.0040
103	0.0105	0.0065	0.0040
104	0.0106	0.0065	0.0041
105	0.0106	0.0065	0.0041
106	0.0107	0.0066	0.0041
107	0.0108	0.0066	0.0042
108	0.0108	0.0067	0.0042
109	0.0109	0.0067	0.0042
110	0.0110	0.0067	0.0042
111	0.0111	0.0068	0.0043
112	0.0111	0.0068	0.0043
113	0.0112	0.0069	0.0043
114	0.0113	0.0069	0.0043
115	0.0114	0.0070	0.0044
116	0.0115	0.0070	0.0044
117	0.0116	0.0071	0.0045
118	0.0116	0.0071	0.0045
119	0.0117	0.0072	0.0045
120	0.0118	0.0073	0.0045
121	0.0119	0.0073	0.0046
122	0.0120	0.0074	0.0046
123	0.0121	0.0075	0.0047
124	0.0122	0.0075	0.0047
125	0.0123	0.0076	0.0047
126	0.0124	0.0076	0.0048
127	0.0125	0.0077	0.0048
128	0.0126	0.0077	0.0049
129	0.0128	0.0078	0.0049
130	0.0128	0.0079	0.0049
131	0.0130	0.0080	0.0050
132	0.0131	0.0080	0.0050
133	0.0132	0.0081	0.0051
134	0.0133	0.0082	0.0051
135	0.0135	0.0083	0.0052
136	0.0136	0.0083	0.0052
137	0.0138	0.0085	0.0053
138	0.0138	0.0085	0.0053
139	0.0140	0.0086	0.0054
140	0.0141	0.0087	0.0054
141	0.0143	0.0088	0.0055

142	0.0145	0.0089	0.0056
143	0.0147	0.0090	0.0057
144	0.0148	0.0091	0.0057
145	0.0174	0.0107	0.0067
146	0.0176	0.0108	0.0068
147	0.0178	0.0109	0.0069
148	0.0179	0.0110	0.0069
149	0.0182	0.0112	0.0070
150	0.0183	0.0113	0.0071
151	0.0186	0.0115	0.0072
152	0.0188	0.0115	0.0072
153	0.0191	0.0117	0.0074
154	0.0192	0.0118	0.0074
155	0.0196	0.0120	0.0075
156	0.0198	0.0121	0.0076
157	0.0201	0.0124	0.0077
158	0.0203	0.0125	0.0078
159	0.0207	0.0127	0.0080
160	0.0209	0.0128	0.0081
161	0.0213	0.0131	0.0082
162	0.0216	0.0133	0.0083
163	0.0220	0.0135	0.0085
164	0.0223	0.0137	0.0086
165	0.0228	0.0140	0.0088
166	0.0231	0.0142	0.0089
167	0.0237	0.0145	0.0091
168	0.0240	0.0147	0.0092
169	0.0246	0.0151	0.0095
170	0.0250	0.0154	0.0096
171	0.0257	0.0158	0.0099
172	0.0261	0.0161	0.0101
173	0.0270	0.0166	0.0104
174	0.0275	0.0169	0.0106
175	0.0285	0.0175	0.0110
176	0.0290	0.0178	0.0112
177	0.0302	0.0186	0.0116
178	0.0309	0.0190	0.0119
179	0.0323	0.0199	0.0124
180	0.0331	0.0204	0.0128
181	0.0349	0.0215	0.0135
182	0.0360	0.0221	0.0139
183	0.0383	0.0236	0.0148
184	0.0397	0.0244	0.0153
185	0.0341	0.0210	0.0131
186	0.0360	0.0221	0.0139
187	0.0409	0.0251	0.0157
188	0.0441	0.0271	0.0170
189	0.0531	0.0327	0.0205
190	0.0600	0.0369	0.0231
191	0.0857	0.0484	0.0373
192	0.1179	0.0484	0.0695
193	0.3689	0.0484	0.3205
194	0.0698	0.0429	0.0269
195	0.0480	0.0295	0.0185
196	0.0382	0.0235	0.0147
197	0.0412	0.0254	0.0159
198	0.0371	0.0228	0.0143
199	0.0340	0.0209	0.0131
200	0.0316	0.0194	0.0122
201	0.0296	0.0182	0.0114
202	0.0279	0.0172	0.0108
203	0.0266	0.0163	0.0102
204	0.0254	0.0156	0.0098
205	0.0243	0.0149	0.0094
206	0.0234	0.0144	0.0090
207	0.0225	0.0139	0.0087
208	0.0218	0.0134	0.0084
209	0.0211	0.0130	0.0081
210	0.0205	0.0126	0.0079
211	0.0199	0.0123	0.0077
212	0.0194	0.0119	0.0075

213	0.0189	0.0116	0.0073
214	0.0185	0.0114	0.0071
215	0.0181	0.0111	0.0070
216	0.0177	0.0109	0.0068
217	0.0149	0.0092	0.0057
218	0.0146	0.0090	0.0056
219	0.0142	0.0088	0.0055
220	0.0139	0.0086	0.0054
221	0.0137	0.0084	0.0053
222	0.0134	0.0082	0.0052
223	0.0131	0.0081	0.0051
224	0.0129	0.0079	0.0050
225	0.0127	0.0078	0.0049
226	0.0125	0.0077	0.0048
227	0.0123	0.0075	0.0047
228	0.0121	0.0074	0.0046
229	0.0119	0.0073	0.0046
230	0.0117	0.0072	0.0045
231	0.0115	0.0071	0.0044
232	0.0113	0.0070	0.0044
233	0.0112	0.0069	0.0043
234	0.0110	0.0068	0.0042
235	0.0109	0.0067	0.0042
236	0.0107	0.0066	0.0041
237	0.0106	0.0065	0.0041
238	0.0105	0.0064	0.0040
239	0.0103	0.0064	0.0040
240	0.0102	0.0063	0.0039
241	0.0101	0.0062	0.0039
242	0.0100	0.0061	0.0038
243	0.0099	0.0061	0.0038
244	0.0098	0.0060	0.0038
245	0.0097	0.0059	0.0037
246	0.0095	0.0059	0.0037
247	0.0094	0.0058	0.0036
248	0.0094	0.0057	0.0036
249	0.0093	0.0057	0.0036
250	0.0092	0.0056	0.0035
251	0.0091	0.0056	0.0035
252	0.0090	0.0055	0.0035
253	0.0089	0.0055	0.0034
254	0.0088	0.0054	0.0034
255	0.0087	0.0054	0.0034
256	0.0087	0.0053	0.0033
257	0.0086	0.0053	0.0033
258	0.0085	0.0052	0.0033
259	0.0084	0.0052	0.0033
260	0.0084	0.0051	0.0032
261	0.0083	0.0051	0.0032
262	0.0082	0.0051	0.0032
263	0.0082	0.0050	0.0031
264	0.0081	0.0050	0.0031
265	0.0080	0.0049	0.0031
266	0.0080	0.0049	0.0031
267	0.0079	0.0049	0.0030
268	0.0079	0.0048	0.0030
269	0.0078	0.0048	0.0030
270	0.0077	0.0048	0.0030
271	0.0077	0.0047	0.0030
272	0.0076	0.0047	0.0029
273	0.0076	0.0047	0.0029
274	0.0075	0.0046	0.0029
275	0.0075	0.0046	0.0029
276	0.0074	0.0046	0.0029
277	0.0074	0.0045	0.0028
278	0.0073	0.0045	0.0028
279	0.0073	0.0045	0.0028
280	0.0072	0.0044	0.0028
281	0.0072	0.0044	0.0028
282	0.0071	0.0044	0.0027
283	0.0071	0.0044	0.0027

284	0.0070	0.0043	0.0027
285	0.0070	0.0043	0.0027
286	0.0070	0.0043	0.0027
287	0.0069	0.0043	0.0027
288	0.0069	0.0042	0.0026

Total soil rain loss = 2.57(In)
Total effective rainfall = 1.95(In)
Peak flow rate in flood hydrograph = 10.80(CFS)


++


24 - H O U R S T O R M
R u n o f f H y d r o g r a p h

Hydrograph in 5 Minute intervals ((CFS))

Time(h+m)	Volume Ac.Ft	Q(CFS)	0	5.0	10.0	15.0	20.0
0+ 5	0.0001	0.01	Q				
0+10	0.0004	0.05	Q				
0+15	0.0012	0.12	Q				
0+20	0.0024	0.17	Q				
0+25	0.0038	0.20	Q				
0+30	0.0053	0.21	Q				
0+35	0.0068	0.22	Q				
0+40	0.0084	0.23	Q				
0+45	0.0100	0.23	Q				
0+50	0.0116	0.24	Q				
0+55	0.0133	0.24	Q				
1+ 0	0.0150	0.24	Q				
1+ 5	0.0167	0.25	Q				
1+10	0.0184	0.25	Q				
1+15	0.0201	0.25	Q				
1+20	0.0219	0.25	Q				
1+25	0.0236	0.26	Q				
1+30	0.0254	0.26	Q				
1+35	0.0272	0.26	Q				
1+40	0.0290	0.26	Q				
1+45	0.0308	0.26	Q				
1+50	0.0326	0.26	QV				
1+55	0.0344	0.26	QV				
2+ 0	0.0362	0.26	QV				
2+ 5	0.0381	0.27	QV				
2+10	0.0399	0.27	QV				
2+15	0.0417	0.27	QV				
2+20	0.0436	0.27	QV				
2+25	0.0454	0.27	QV				
2+30	0.0473	0.27	QV				
2+35	0.0491	0.27	QV				
2+40	0.0510	0.27	QV				
2+45	0.0529	0.27	QV				
2+50	0.0548	0.27	QV				
2+55	0.0567	0.27	QV				
3+ 0	0.0586	0.28	QV				
3+ 5	0.0605	0.28	QV				
3+10	0.0624	0.28	QV				
3+15	0.0643	0.28	Q V				
3+20	0.0662	0.28	Q V				
3+25	0.0681	0.28	Q V				
3+30	0.0701	0.28	Q V				
3+35	0.0720	0.28	Q V				
3+40	0.0740	0.28	Q V				
3+45	0.0759	0.28	Q V				
3+50	0.0779	0.29	Q V				
3+55	0.0799	0.29	Q V				
4+ 0	0.0819	0.29	Q V				
4+ 5	0.0838	0.29	Q V				
4+10	0.0858	0.29	Q V				
4+15	0.0878	0.29	Q V				

4+20	0.0899	0.29	Q V	|	|	|	|
4+25	0.0919	0.29	Q V	|	|	|	|
4+30	0.0939	0.29	Q V	|	|	|	|
4+35	0.0959	0.30	Q V	|	|	|	|
4+40	0.0980	0.30	Q V	|	|	|	|
4+45	0.1000	0.30	Q V	|	|	|	|
4+50	0.1021	0.30	Q V	|	|	|	|
4+55	0.1042	0.30	Q V	|	|	|	|
5+ 0	0.1062	0.30	Q V	|	|	|	|
5+ 5	0.1083	0.30	Q V	|	|	|	|
5+10	0.1104	0.30	Q V	|	|	|	|
5+15	0.1125	0.31	Q V	|	|	|	|
5+20	0.1146	0.31	Q V	|	|	|	|
5+25	0.1168	0.31	Q V	|	|	|	|
5+30	0.1189	0.31	Q V	|	|	|	|
5+35	0.1210	0.31	Q V	|	|	|	|
5+40	0.1232	0.31	Q V	|	|	|	|
5+45	0.1253	0.31	Q V	|	|	|	|
5+50	0.1275	0.31	Q V	|	|	|	|
5+55	0.1297	0.32	Q V	|	|	|	|
6+ 0	0.1319	0.32	Q V	|	|	|	|
6+ 5	0.1341	0.32	Q V	|	|	|	|
6+10	0.1363	0.32	Q V	|	|	|	|
6+15	0.1385	0.32	Q V	|	|	|	|
6+20	0.1407	0.32	Q V	|	|	|	|
6+25	0.1430	0.33	Q V	|	|	|	|
6+30	0.1452	0.33	Q V	|	|	|	|
6+35	0.1475	0.33	Q V	|	|	|	|
6+40	0.1498	0.33	Q V	|	|	|	|
6+45	0.1520	0.33	Q V	|	|	|	|
6+50	0.1543	0.33	Q V	|	|	|	|
6+55	0.1566	0.33	Q V	|	|	|	|
7+ 0	0.1590	0.34	Q V	|	|	|	|
7+ 5	0.1613	0.34	Q V	|	|	|	|
7+10	0.1636	0.34	Q V	|	|	|	|
7+15	0.1660	0.34	Q V	|	|	|	|
7+20	0.1683	0.34	Q V	|	|	|	|
7+25	0.1707	0.35	Q V	|	|	|	|
7+30	0.1731	0.35	Q V	|	|	|	|
7+35	0.1755	0.35	Q V	|	|	|	|
7+40	0.1779	0.35	Q V	|	|	|	|
7+45	0.1804	0.35	Q V	|	|	|	|
7+50	0.1828	0.35	Q V	|	|	|	|
7+55	0.1853	0.36	Q V	|	|	|	|
8+ 0	0.1877	0.36	Q V	|	|	|	|
8+ 5	0.1902	0.36	Q V	|	|	|	|
8+10	0.1927	0.36	Q V	|	|	|	|
8+15	0.1952	0.36	Q V	|	|	|	|
8+20	0.1978	0.37	Q V	|	|	|	|
8+25	0.2003	0.37	Q V	|	|	|	|
8+30	0.2029	0.37	Q V	|	|	|	|
8+35	0.2054	0.37	Q V	|	|	|	|
8+40	0.2080	0.38	Q V	|	|	|	|
8+45	0.2106	0.38	Q V	|	|	|	|
8+50	0.2132	0.38	Q V	|	|	|	|
8+55	0.2159	0.38	Q V	|	|	|	|
9+ 0	0.2185	0.39	Q V	|	|	|	|
9+ 5	0.2212	0.39	Q V	|	|	|	|
9+10	0.2239	0.39	Q V	|	|	|	|
9+15	0.2266	0.39	Q V	|	|	|	|
9+20	0.2293	0.40	Q V	|	|	|	|
9+25	0.2321	0.40	Q V	|	|	|	|
9+30	0.2348	0.40	Q V	|	|	|	|
9+35	0.2376	0.40	Q V	|	|	|	|
9+40	0.2404	0.41	Q V	|	|	|	|
9+45	0.2432	0.41	Q V	|	|	|	|
9+50	0.2461	0.41	Q V	|	|	|	|
9+55	0.2489	0.42	Q V	|	|	|	|
10+ 0	0.2518	0.42	Q V	|	|	|	|
10+ 5	0.2547	0.42	Q V	|	|	|	|
10+10	0.2577	0.42	Q V	|	|	|	|





22+ 5	1.2158	0.30	Q	|	|	|	V |
22+10	1.2179	0.30	Q	|	|	|	V |
22+15	1.2199	0.30	Q	|	|	|	V |
22+20	1.2219	0.29	Q	|	|	|	V |
22+25	1.2239	0.29	Q	|	|	|	V |
22+30	1.2259	0.29	Q	|	|	|	V |
22+35	1.2279	0.29	Q	|	|	|	V |
22+40	1.2299	0.28	Q	|	|	|	V |
22+45	1.2318	0.28	Q	|	|	|	V |
22+50	1.2337	0.28	Q	|	|	|	V |
22+55	1.2357	0.28	Q	|	|	|	V|
23+ 0	1.2376	0.28	Q	|	|	|	V|
23+ 5	1.2395	0.27	Q	|	|	|	V|
23+10	1.2413	0.27	Q	|	|	|	V|
23+15	1.2432	0.27	Q	|	|	|	V|
23+20	1.2450	0.27	Q	|	|	|	V|
23+25	1.2469	0.27	Q	|	|	|	V|
23+30	1.2487	0.27	Q	|	|	|	V|
23+35	1.2505	0.26	Q	|	|	|	V|
23+40	1.2523	0.26	Q	|	|	|	V|
23+45	1.2541	0.26	Q	|	|	|	V|
23+50	1.2559	0.26	Q	|	|	|	V|
23+55	1.2577	0.26	Q	|	|	|	V|
24+ 0	1.2594	0.26	Q	|	|	|	V|
24+ 5	1.2611	0.24	Q	|	|	|	V|
24+10	1.2625	0.20	Q	|	|	|	V|
24+15	1.2634	0.13	Q	|	|	|	V|
24+20	1.2639	0.08	Q	|	|	|	V|
24+25	1.2643	0.05	Q	|	|	|	V|
24+30	1.2646	0.04	Q	|	|	|	V|
24+35	1.2648	0.03	Q	|	|	|	V|
24+40	1.2649	0.02	Q	|	|	|	V|
24+45	1.2651	0.02	Q	|	|	|	V|
24+50	1.2652	0.02	Q	|	|	|	V|
24+55	1.2653	0.01	Q	|	|	|	V|
25+ 0	1.2653	0.01	Q	|	|	|	V|
25+ 5	1.2654	0.01	Q	|	|	|	V|
25+10	1.2654	0.01	Q	|	|	|	V|
25+15	1.2655	0.00	Q	|	|	|	V|
25+20	1.2655	0.00	Q	|	|	|	V|
25+25	1.2655	0.00	Q	|	|	|	V|
25+30	1.2655	0.00	Q	|	|	|	V|
25+35	1.2655	0.00	Q	|	|	|	V|
25+40	1.2655	0.00	Q	|	|	|	V|

Unit Hydrograph Analysis: Developed Condition (25 yr, 24 hr Storm Event)

```
        U n i t   H y d r o g r a p h   A n a l y s i s

        Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018, Version 9.0

                Study date  07/01/23

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
------------------------------------------------------------------------------

San Bernardino County Synthetic Unit Hydrology Method
                Manual date - August 1986


Program License Serial Number 6484

------------------------------------------------------------------------
UH ANALYSIS
DEVELOPED CONDITION
25-YR STORM EVENT

------------------------------------------------------------------------

        Storm Event Year = 25

        Antecedent Moisture Condition = 3

 English (in-lb) Input Units Used

 English Rainfall Data (Inches) Input Values Used

 English Units used in output format



Area averaged rainfall intensity isohyetal data:
        Sub-Area        Duration        Isohyetal
        (Ac.)            (hours)         (In)
Rainfall data for year 25
             7.80            1           1.00
------------------------------------------------------------------------
Rainfall data for year 25
             7.80            6           2.47
------------------------------------------------------------------------
Rainfall data for year 25
             7.80           24           4.52
------------------------------------------------------------------------
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

******** Area-averaged max loss rate, Fm ********


SCS curve  SCS curve     Area     Area     Fp(Fig C6)    Ap      Fm
No.(AMCII) NO.(AMC 3)    (Ac.)    Fraction     (In/Hr)  (dec.)   (In/Hr)
 32.0      52.0          7.80      1.000     0.785    0.100    0.079

Area-averaged adjusted loss rate Fm (In/Hr) =  0.079

********* Area-Averaged low loss rate fraction, Yb **********

Area       Area          SCS CN    SCS CN      S     Pervious
 (Ac.)      Fract         (AMC2)    (AMC3)           Yield Fr
     0.78   0.100         32.0      52.0       9.23     0.133
     7.02   0.900         98.0      98.0       0.20     0.948

Area-averaged catchment yield fraction, Y =  0.866
Area-averaged low loss fraction, Yb =  0.134
Direct entry of lag time by user
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
```

Watershed area = 7.80(Ac.)
Catchment Lag time = 0.162 hours
Unit interval = 5.000 minutes
Unit interval percentage of lag time = 51.4403
Hydrograph baseflow = 0.00(CFS)
Average maximum watershed loss rate(Fm) = 0.079(In/Hr)
Average low loss rate fraction (Yb) = 0.134 (decimal)
VALLEY DEVELOPED S-Graph Selected
Computed peak 5-minute rainfall = 0.369(In)
Computed peak 30-minute rainfall = 0.756(In)
Specified peak 1-hour rainfall = 0.997(In)
Computed peak 3-hour rainfall = 1.739(In)
Specified peak 6-hour rainfall = 2.470(In)
Specified peak 24-hour rainfall = 4.520(In)

Rainfall depth area reduction factors:
Using a total area of 7.80(Ac.) (Ref: fig. E-4)

5-minute factor = 1.000 Adjusted rainfall = 0.369(In)
30-minute factor = 1.000 Adjusted rainfall = 0.755(In)
1-hour factor = 1.000 Adjusted rainfall = 0.997(In)
3-hour factor = 1.000 Adjusted rainfall = 1.739(In)
6-hour factor = 1.000 Adjusted rainfall = 2.470(In)
24-hour factor = 1.000 Adjusted rainfall = 4.520(In)

U n i t H y d r o g r a p h

Interval Number	'S' Graph Mean values	Unit Hydrograph ((CFS))
	(K = 94.33 (CFS))	
1	4.833	4.559
2	31.441	25.099
3	71.022	37.337
4	91.060	18.902
5	97.413	5.993
6	98.893	1.396
7	100.000	1.045

Peak Unit Number	Adjusted mass rainfall (In)	Unit rainfall (In)
1	0.3689	0.3689
2	0.4867	0.1179
3	0.5724	0.0857
4	0.6422	0.0698
5	0.7022	0.0600
6	0.7553	0.0531
7	0.8033	0.0480
8	0.8474	0.0441
9	0.8883	0.0409
10	0.9265	0.0382
11	0.9625	0.0360
12	0.9966	0.0341
13	1.0379	0.0412
14	1.0776	0.0397
15	1.1159	0.0383
16	1.1530	0.0371
17	1.1890	0.0360
18	1.2239	0.0349
19	1.2579	0.0340
20	1.2910	0.0331
21	1.3233	0.0323
22	1.3549	0.0316
23	1.3857	0.0309
24	1.4159	0.0302
25	1.4455	0.0296
26	1.4745	0.0290
27	1.5030	0.0285

28	1.5310	0.0279
29	1.5584	0.0275
30	1.5854	0.0270
31	1.6120	0.0266
32	1.6381	0.0261
33	1.6638	0.0257
34	1.6892	0.0254
35	1.7142	0.0250
36	1.7388	0.0246
37	1.7631	0.0243
38	1.7871	0.0240
39	1.8107	0.0237
40	1.8341	0.0234
41	1.8572	0.0231
42	1.8800	0.0228
43	1.9025	0.0225
44	1.9248	0.0223
45	1.9468	0.0220
46	1.9686	0.0218
47	1.9902	0.0216
48	2.0115	0.0213
49	2.0326	0.0211
50	2.0535	0.0209
51	2.0742	0.0207
52	2.0947	0.0205
53	2.1150	0.0203
54	2.1351	0.0201
55	2.1550	0.0199
56	2.1748	0.0198
57	2.1944	0.0196
58	2.2138	0.0194
59	2.2330	0.0192
60	2.2521	0.0191
61	2.2711	0.0189
62	2.2898	0.0188
63	2.3085	0.0186
64	2.3269	0.0185
65	2.3453	0.0183
66	2.3635	0.0182
67	2.3815	0.0181
68	2.3995	0.0179
69	2.4173	0.0178
70	2.4350	0.0177
71	2.4525	0.0176
72	2.4699	0.0174
73	2.4848	0.0149
74	2.4996	0.0148
75	2.5143	0.0147
76	2.5288	0.0146
77	2.5433	0.0145
78	2.5576	0.0143
79	2.5719	0.0142
80	2.5860	0.0141
81	2.6001	0.0140
82	2.6140	0.0139
83	2.6279	0.0138
84	2.6416	0.0138
85	2.6553	0.0137
86	2.6689	0.0136
87	2.6823	0.0135
88	2.6957	0.0134
89	2.7090	0.0133
90	2.7223	0.0132
91	2.7354	0.0131
92	2.7485	0.0131
93	2.7615	0.0130
94	2.7744	0.0129
95	2.7872	0.0128
96	2.7999	0.0128
97	2.8126	0.0127
98	2.8252	0.0126

99	2.8378	0.0125
100	2.8502	0.0125
101	2.8626	0.0124
102	2.8749	0.0123
103	2.8872	0.0123
104	2.8994	0.0122
105	2.9115	0.0121
106	2.9235	0.0121
107	2.9355	0.0120
108	2.9475	0.0119
109	2.9593	0.0119
110	2.9711	0.0118
111	2.9829	0.0117
112	2.9946	0.0117
113	3.0062	0.0116
114	3.0177	0.0116
115	3.0293	0.0115
116	3.0407	0.0115
117	3.0521	0.0114
118	3.0635	0.0113
119	3.0747	0.0113
120	3.0860	0.0112
121	3.0972	0.0112
122	3.1083	0.0111
123	3.1194	0.0111
124	3.1304	0.0110
125	3.1414	0.0110
126	3.1523	0.0109
127	3.1632	0.0109
128	3.1740	0.0108
129	3.1848	0.0108
130	3.1956	0.0107
131	3.2063	0.0107
132	3.2169	0.0106
133	3.2275	0.0106
134	3.2381	0.0106
135	3.2486	0.0105
136	3.2590	0.0105
137	3.2695	0.0104
138	3.2798	0.0104
139	3.2902	0.0103
140	3.3005	0.0103
141	3.3107	0.0103
142	3.3210	0.0102
143	3.3311	0.0102
144	3.3413	0.0101
145	3.3514	0.0101
146	3.3614	0.0101
147	3.3714	0.0100
148	3.3814	0.0100
149	3.3913	0.0099
150	3.4012	0.0099
151	3.4111	0.0099
152	3.4209	0.0098
153	3.4307	0.0098
154	3.4405	0.0098
155	3.4502	0.0097
156	3.4599	0.0097
157	3.4696	0.0097
158	3.4792	0.0096
159	3.4887	0.0096
160	3.4983	0.0095
161	3.5078	0.0095
162	3.5173	0.0095
163	3.5267	0.0094
164	3.5362	0.0094
165	3.5455	0.0094
166	3.5549	0.0094
167	3.5642	0.0093
168	3.5735	0.0093
169	3.5828	0.0093

170	3.5920	0.0092
171	3.6012	0.0092
172	3.6103	0.0092
173	3.6195	0.0091
174	3.6286	0.0091
175	3.6377	0.0091
176	3.6467	0.0090
177	3.6557	0.0090
178	3.6647	0.0090
179	3.6737	0.0090
180	3.6826	0.0089
181	3.6915	0.0089
182	3.7004	0.0089
183	3.7092	0.0088
184	3.7181	0.0088
185	3.7269	0.0088
186	3.7356	0.0088
187	3.7444	0.0087
188	3.7531	0.0087
189	3.7618	0.0087
190	3.7704	0.0087
191	3.7791	0.0086
192	3.7877	0.0086
193	3.7963	0.0086
194	3.8048	0.0086
195	3.8134	0.0085
196	3.8219	0.0085
197	3.8304	0.0085
198	3.8388	0.0085
199	3.8473	0.0084
200	3.8557	0.0084
201	3.8641	0.0084
202	3.8724	0.0084
203	3.8808	0.0083
204	3.8891	0.0083
205	3.8974	0.0083
206	3.9057	0.0083
207	3.9139	0.0083
208	3.9222	0.0082
209	3.9304	0.0082
210	3.9386	0.0082
211	3.9467	0.0082
212	3.9549	0.0081
213	3.9630	0.0081
214	3.9711	0.0081
215	3.9792	0.0081
216	3.9872	0.0081
217	3.9953	0.0080
218	4.0033	0.0080
219	4.0113	0.0080
220	4.0193	0.0080
221	4.0272	0.0080
222	4.0351	0.0079
223	4.0431	0.0079
224	4.0509	0.0079
225	4.0588	0.0079
226	4.0667	0.0079
227	4.0745	0.0078
228	4.0823	0.0078
229	4.0901	0.0078
230	4.0979	0.0078
231	4.1056	0.0078
232	4.1134	0.0077
233	4.1211	0.0077
234	4.1288	0.0077
235	4.1365	0.0077
236	4.1442	0.0077
237	4.1518	0.0076
238	4.1594	0.0076
239	4.1670	0.0076
240	4.1746	0.0076

241	4.1822	0.0076
242	4.1898	0.0076
243	4.1973	0.0075
244	4.2048	0.0075
245	4.2123	0.0075
246	4.2198	0.0075
247	4.2273	0.0075
248	4.2347	0.0075
249	4.2422	0.0074
250	4.2496	0.0074
251	4.2570	0.0074
252	4.2644	0.0074
253	4.2717	0.0074
254	4.2791	0.0074
255	4.2864	0.0073
256	4.2937	0.0073
257	4.3010	0.0073
258	4.3083	0.0073
259	4.3156	0.0073
260	4.3229	0.0073
261	4.3301	0.0072
262	4.3373	0.0072
263	4.3445	0.0072
264	4.3517	0.0072
265	4.3589	0.0072
266	4.3661	0.0072
267	4.3732	0.0071
268	4.3803	0.0071
269	4.3875	0.0071
270	4.3946	0.0071
271	4.4017	0.0071
272	4.4087	0.0071
273	4.4158	0.0071
274	4.4228	0.0070
275	4.4299	0.0070
276	4.4369	0.0070
277	4.4439	0.0070
278	4.4509	0.0070
279	4.4578	0.0070
280	4.4648	0.0070
281	4.4717	0.0069
282	4.4787	0.0069
283	4.4856	0.0069
284	4.4925	0.0069
285	4.4994	0.0069
286	4.5062	0.0069
287	4.5131	0.0069
288	4.5200	0.0068

Unit Period (number)	Unit Rainfall (In)	Unit Soil-Loss (In)	Effective Rainfall (In)
1	0.0068	0.0009	0.0059
2	0.0069	0.0009	0.0059
3	0.0069	0.0009	0.0060
4	0.0069	0.0009	0.0060
5	0.0069	0.0009	0.0060
6	0.0069	0.0009	0.0060
7	0.0070	0.0009	0.0060
8	0.0070	0.0009	0.0061
9	0.0070	0.0009	0.0061
10	0.0070	0.0009	0.0061
11	0.0071	0.0009	0.0061
12	0.0071	0.0009	0.0061
13	0.0071	0.0009	0.0062
14	0.0071	0.0010	0.0062
15	0.0071	0.0010	0.0062
16	0.0072	0.0010	0.0062
17	0.0072	0.0010	0.0062
18	0.0072	0.0010	0.0062

19	0.0072	0.0010	0.0063
20	0.0073	0.0010	0.0063
21	0.0073	0.0010	0.0063
22	0.0073	0.0010	0.0063
23	0.0073	0.0010	0.0064
24	0.0074	0.0010	0.0064
25	0.0074	0.0010	0.0064
26	0.0074	0.0010	0.0064
27	0.0074	0.0010	0.0064
28	0.0075	0.0010	0.0065
29	0.0075	0.0010	0.0065
30	0.0075	0.0010	0.0065
31	0.0075	0.0010	0.0065
32	0.0076	0.0010	0.0065
33	0.0076	0.0010	0.0066
34	0.0076	0.0010	0.0066
35	0.0076	0.0010	0.0066
36	0.0077	0.0010	0.0066
37	0.0077	0.0010	0.0067
38	0.0077	0.0010	0.0067
39	0.0078	0.0010	0.0067
40	0.0078	0.0010	0.0067
41	0.0078	0.0010	0.0068
42	0.0078	0.0010	0.0068
43	0.0079	0.0011	0.0068
44	0.0079	0.0011	0.0068
45	0.0079	0.0011	0.0069
46	0.0080	0.0011	0.0069
47	0.0080	0.0011	0.0069
48	0.0080	0.0011	0.0069
49	0.0081	0.0011	0.0070
50	0.0081	0.0011	0.0070
51	0.0081	0.0011	0.0070
52	0.0081	0.0011	0.0071
53	0.0082	0.0011	0.0071
54	0.0082	0.0011	0.0071
55	0.0083	0.0011	0.0071
56	0.0083	0.0011	0.0072
57	0.0083	0.0011	0.0072
58	0.0083	0.0011	0.0072
59	0.0084	0.0011	0.0073
60	0.0084	0.0011	0.0073
61	0.0085	0.0011	0.0073
62	0.0085	0.0011	0.0074
63	0.0085	0.0011	0.0074
64	0.0086	0.0011	0.0074
65	0.0086	0.0012	0.0075
66	0.0086	0.0012	0.0075
67	0.0087	0.0012	0.0075
68	0.0087	0.0012	0.0076
69	0.0088	0.0012	0.0076
70	0.0088	0.0012	0.0076
71	0.0088	0.0012	0.0077
72	0.0089	0.0012	0.0077
73	0.0089	0.0012	0.0077
74	0.0090	0.0012	0.0078
75	0.0090	0.0012	0.0078
76	0.0090	0.0012	0.0078
77	0.0091	0.0012	0.0079
78	0.0091	0.0012	0.0079
79	0.0092	0.0012	0.0080
80	0.0092	0.0012	0.0080
81	0.0093	0.0012	0.0080
82	0.0093	0.0012	0.0081
83	0.0094	0.0013	0.0081
84	0.0094	0.0013	0.0082
85	0.0095	0.0013	0.0082
86	0.0095	0.0013	0.0082
87	0.0096	0.0013	0.0083
88	0.0096	0.0013	0.0083
89	0.0097	0.0013	0.0084

90	0.0097	0.0013	0.0084
91	0.0098	0.0013	0.0085
92	0.0098	0.0013	0.0085
93	0.0099	0.0013	0.0086
94	0.0099	0.0013	0.0086
95	0.0100	0.0013	0.0087
96	0.0101	0.0013	0.0087
97	0.0101	0.0014	0.0088
98	0.0102	0.0014	0.0088
99	0.0103	0.0014	0.0089
100	0.0103	0.0014	0.0089
101	0.0104	0.0014	0.0090
102	0.0104	0.0014	0.0090
103	0.0105	0.0014	0.0091
104	0.0106	0.0014	0.0091
105	0.0106	0.0014	0.0092
106	0.0107	0.0014	0.0093
107	0.0108	0.0014	0.0093
108	0.0108	0.0014	0.0094
109	0.0109	0.0015	0.0095
110	0.0110	0.0015	0.0095
111	0.0111	0.0015	0.0096
112	0.0111	0.0015	0.0096
113	0.0112	0.0015	0.0097
114	0.0113	0.0015	0.0098
115	0.0114	0.0015	0.0099
116	0.0115	0.0015	0.0099
117	0.0116	0.0015	0.0100
118	0.0116	0.0016	0.0101
119	0.0117	0.0016	0.0102
120	0.0118	0.0016	0.0102
121	0.0119	0.0016	0.0103
122	0.0120	0.0016	0.0104
123	0.0121	0.0016	0.0105
124	0.0122	0.0016	0.0106
125	0.0123	0.0016	0.0107
126	0.0124	0.0017	0.0107
127	0.0125	0.0017	0.0109
128	0.0126	0.0017	0.0109
129	0.0128	0.0017	0.0110
130	0.0128	0.0017	0.0111
131	0.0130	0.0017	0.0112
132	0.0131	0.0017	0.0113
133	0.0132	0.0018	0.0115
134	0.0133	0.0018	0.0115
135	0.0135	0.0018	0.0117
136	0.0136	0.0018	0.0118
137	0.0138	0.0018	0.0119
138	0.0138	0.0019	0.0120
139	0.0140	0.0019	0.0122
140	0.0141	0.0019	0.0123
141	0.0143	0.0019	0.0124
142	0.0145	0.0019	0.0125
143	0.0147	0.0020	0.0127
144	0.0148	0.0020	0.0128
145	0.0174	0.0023	0.0151
146	0.0176	0.0023	0.0152
147	0.0178	0.0024	0.0154
148	0.0179	0.0024	0.0155
149	0.0182	0.0024	0.0158
150	0.0183	0.0025	0.0159
151	0.0186	0.0025	0.0161
152	0.0188	0.0025	0.0163
153	0.0191	0.0026	0.0165
154	0.0192	0.0026	0.0167
155	0.0196	0.0026	0.0170
156	0.0198	0.0026	0.0171
157	0.0201	0.0027	0.0174
158	0.0203	0.0027	0.0176
159	0.0207	0.0028	0.0179
160	0.0209	0.0028	0.0181

161	0.0213	0.0029	0.0185
162	0.0216	0.0029	0.0187
163	0.0220	0.0029	0.0191
164	0.0223	0.0030	0.0193
165	0.0228	0.0030	0.0198
166	0.0231	0.0031	0.0200
167	0.0237	0.0032	0.0205
168	0.0240	0.0032	0.0208
169	0.0246	0.0033	0.0213
170	0.0250	0.0033	0.0216
171	0.0257	0.0034	0.0223
172	0.0261	0.0035	0.0226
173	0.0270	0.0036	0.0234
174	0.0275	0.0037	0.0238
175	0.0285	0.0038	0.0247
176	0.0290	0.0039	0.0251
177	0.0302	0.0040	0.0262
178	0.0309	0.0041	0.0267
179	0.0323	0.0043	0.0280
180	0.0331	0.0044	0.0287
181	0.0349	0.0047	0.0303
182	0.0360	0.0048	0.0312
183	0.0383	0.0051	0.0332
184	0.0397	0.0053	0.0344
185	0.0341	0.0046	0.0295
186	0.0360	0.0048	0.0312
187	0.0409	0.0055	0.0354
188	0.0441	0.0059	0.0382
189	0.0531	0.0065	0.0466
190	0.0600	0.0065	0.0534
191	0.0857	0.0065	0.0792
192	0.1179	0.0065	0.1113
193	0.3689	0.0065	0.3623
194	0.0698	0.0065	0.0633
195	0.0480	0.0064	0.0416
196	0.0382	0.0051	0.0331
197	0.0412	0.0055	0.0357
198	0.0371	0.0050	0.0321
199	0.0340	0.0045	0.0294
200	0.0316	0.0042	0.0273
201	0.0296	0.0040	0.0256
202	0.0279	0.0037	0.0242
203	0.0266	0.0036	0.0230
204	0.0254	0.0034	0.0220
205	0.0243	0.0032	0.0210
206	0.0234	0.0031	0.0202
207	0.0225	0.0030	0.0195
208	0.0218	0.0029	0.0189
209	0.0211	0.0028	0.0183
210	0.0205	0.0027	0.0178
211	0.0199	0.0027	0.0173
212	0.0194	0.0026	0.0168
213	0.0189	0.0025	0.0164
214	0.0185	0.0025	0.0160
215	0.0181	0.0024	0.0157
216	0.0177	0.0024	0.0153
217	0.0149	0.0020	0.0129
218	0.0146	0.0019	0.0126
219	0.0142	0.0019	0.0123
220	0.0139	0.0019	0.0121
221	0.0137	0.0018	0.0118
222	0.0134	0.0018	0.0116
223	0.0131	0.0018	0.0114
224	0.0129	0.0017	0.0112
225	0.0127	0.0017	0.0110
226	0.0125	0.0017	0.0108
227	0.0123	0.0016	0.0106
228	0.0121	0.0016	0.0104
229	0.0119	0.0016	0.0103
230	0.0117	0.0016	0.0101
231	0.0115	0.0015	0.0100

232	0.0113	0.0015	0.0098
233	0.0112	0.0015	0.0097
234	0.0110	0.0015	0.0096
235	0.0109	0.0015	0.0094
236	0.0107	0.0014	0.0093
237	0.0106	0.0014	0.0092
238	0.0105	0.0014	0.0091
239	0.0103	0.0014	0.0090
240	0.0102	0.0014	0.0088
241	0.0101	0.0013	0.0087
242	0.0100	0.0013	0.0086
243	0.0099	0.0013	0.0085
244	0.0098	0.0013	0.0085
245	0.0097	0.0013	0.0084
246	0.0095	0.0013	0.0083
247	0.0094	0.0013	0.0082
248	0.0094	0.0013	0.0081
249	0.0093	0.0012	0.0080
250	0.0092	0.0012	0.0079
251	0.0091	0.0012	0.0079
252	0.0090	0.0012	0.0078
253	0.0089	0.0012	0.0077
254	0.0088	0.0012	0.0076
255	0.0087	0.0012	0.0076
256	0.0087	0.0012	0.0075
257	0.0086	0.0011	0.0074
258	0.0085	0.0011	0.0074
259	0.0084	0.0011	0.0073
260	0.0084	0.0011	0.0072
261	0.0083	0.0011	0.0072
262	0.0082	0.0011	0.0071
263	0.0082	0.0011	0.0071
264	0.0081	0.0011	0.0070
265	0.0080	0.0011	0.0070
266	0.0080	0.0011	0.0069
267	0.0079	0.0011	0.0069
268	0.0079	0.0011	0.0068
269	0.0078	0.0010	0.0068
270	0.0077	0.0010	0.0067
271	0.0077	0.0010	0.0067
272	0.0076	0.0010	0.0066
273	0.0076	0.0010	0.0066
274	0.0075	0.0010	0.0065
275	0.0075	0.0010	0.0065
276	0.0074	0.0010	0.0064
277	0.0074	0.0010	0.0064
278	0.0073	0.0010	0.0063
279	0.0073	0.0010	0.0063
280	0.0072	0.0010	0.0063
281	0.0072	0.0010	0.0062
282	0.0071	0.0010	0.0062
283	0.0071	0.0009	0.0061
284	0.0070	0.0009	0.0061
285	0.0070	0.0009	0.0061
286	0.0070	0.0009	0.0060
287	0.0069	0.0009	0.0060
288	0.0069	0.0009	0.0060

Total soil rain loss = 0.54(In)
Total effective rainfall = 3.98(In)
Peak flow rate in flood hydrograph = 18.01(CFS)

++


24 - H O U R S T O R M
R u n o f f H y d r o g r a p h

Hydrograph in 5 Minute intervals ((CFS))

Time(h+m) Volume Ac.Ft Q(CFS) 0 5.0 10.0 15.0 20.0

0+ 5	0.0002	0.03	Q				
0+10	0.0014	0.18	Q				
0+15	0.0041	0.40	Q				
0+20	0.0077	0.51	VQ				
0+25	0.0114	0.55	VQ				
0+30	0.0153	0.56	VQ				
0+35	0.0192	0.57	VQ				
0+40	0.0231	0.57	VQ				
0+45	0.0270	0.57	VQ				
0+50	0.0309	0.57	VQ				
0+55	0.0349	0.57	VQ				
1+ 0	0.0388	0.57	VQ				
1+ 5	0.0428	0.58	VQ				
1+10	0.0468	0.58	VQ				
1+15	0.0508	0.58	VQ				
1+20	0.0548	0.58	VQ				
1+25	0.0588	0.58	VQ				
1+30	0.0628	0.59	VQ				
1+35	0.0669	0.59	|Q				
1+40	0.0710	0.59	|Q				
1+45	0.0750	0.59	|Q				
1+50	0.0791	0.59	|Q				
1+55	0.0832	0.60	|Q				
2+ 0	0.0873	0.60	|Q				
2+ 5	0.0914	0.60	|Q				
2+10	0.0956	0.60	|Q				
2+15	0.0997	0.60	|Q				
2+20	0.1039	0.61	|Q				
2+25	0.1081	0.61	|Q				
2+30	0.1123	0.61	|Q				
2+35	0.1165	0.61	|Q				
2+40	0.1207	0.61	|Q				
2+45	0.1250	0.62	|Q				
2+50	0.1292	0.62	|QV				
2+55	0.1335	0.62	|QV				
3+ 0	0.1378	0.62	|QV				
3+ 5	0.1421	0.62	|QV				
3+10	0.1464	0.63	|QV				
3+15	0.1507	0.63	|QV				
3+20	0.1551	0.63	|QV				
3+25	0.1594	0.63	|QV				
3+30	0.1638	0.64	|QV				
3+35	0.1682	0.64	|QV				
3+40	0.1726	0.64	|QV				
3+45	0.1770	0.64	|QV				
3+50	0.1815	0.65	|QV				
3+55	0.1859	0.65	|QV				
4+ 0	0.1904	0.65	|QV				
4+ 5	0.1949	0.65	|Q V				
4+10	0.1994	0.66	|Q V				
4+15	0.2040	0.66	|Q V				
4+20	0.2085	0.66	|Q V				
4+25	0.2131	0.66	|Q V				
4+30	0.2177	0.67	|Q V				
4+35	0.2223	0.67	|Q V				
4+40	0.2269	0.67	|Q V				
4+45	0.2315	0.67	|Q V				
4+50	0.2362	0.68	|Q V				
4+55	0.2409	0.68	|Q V				
5+ 0	0.2456	0.68	|Q V				
5+ 5	0.2503	0.69	|Q V				
5+10	0.2550	0.69	|Q V				
5+15	0.2598	0.69	|Q V				
5+20	0.2646	0.69	|Q V				
5+25	0.2694	0.70	|Q V				
5+30	0.2742	0.70	|Q V				
5+35	0.2790	0.70	|Q V				
5+40	0.2839	0.71	|Q V				
5+45	0.2888	0.71	|Q V				
5+50	0.2937	0.71	|Q V				

5+55	0.2986	0.72	Q V			
6+ 0	0.3036	0.72	Q V			
6+ 5	0.3085	0.72	Q V			
6+10	0.3135	0.73	Q V			
6+15	0.3186	0.73	Q V			
6+20	0.3236	0.73	Q V			
6+25	0.3287	0.74	Q V			
6+30	0.3338	0.74	Q V			
6+35	0.3389	0.74	Q V			
6+40	0.3440	0.75	Q V			
6+45	0.3492	0.75	Q V			
6+50	0.3544	0.75	Q V			
6+55	0.3596	0.76	Q V			
7+ 0	0.3649	0.76	Q V			
7+ 5	0.3701	0.77	Q V			
7+10	0.3754	0.77	Q V			
7+15	0.3808	0.77	Q V			
7+20	0.3861	0.78	Q V			
7+25	0.3915	0.78	Q V			
7+30	0.3969	0.79	Q V			
7+35	0.4024	0.79	Q V			
7+40	0.4079	0.79	Q V			
7+45	0.4134	0.80	Q V			
7+50	0.4189	0.80	Q V			
7+55	0.4245	0.81	Q V			
8+ 0	0.4301	0.81	Q V			
8+ 5	0.4357	0.82	Q V			
8+10	0.4414	0.82	Q V			
8+15	0.4470	0.83	Q V			
8+20	0.4528	0.83	Q V			
8+25	0.4585	0.84	Q V			
8+30	0.4643	0.84	Q V			
8+35	0.4702	0.85	Q V			
8+40	0.4761	0.85	Q V			
8+45	0.4820	0.86	Q V			
8+50	0.4879	0.86	Q V			
8+55	0.4939	0.87	Q V			
9+ 0	0.4999	0.87	Q V			
9+ 5	0.5060	0.88	Q V			
9+10	0.5121	0.89	Q V			
9+15	0.5182	0.89	Q V			
9+20	0.5244	0.90	Q V			
9+25	0.5306	0.90	Q V			
9+30	0.5369	0.91	Q V			
9+35	0.5432	0.92	Q V			
9+40	0.5496	0.92	Q V			
9+45	0.5560	0.93	Q V			
9+50	0.5624	0.94	Q V			
9+55	0.5689	0.94	Q V			
10+ 0	0.5755	0.95	Q V			
10+ 5	0.5821	0.96	Q V			
10+10	0.5887	0.97	Q V			
10+15	0.5954	0.97	Q V			
10+20	0.6022	0.98	Q V			
10+25	0.6090	0.99	Q V			
10+30	0.6159	1.00	Q V			
10+35	0.6228	1.01	Q V			
10+40	0.6298	1.01	Q V			
10+45	0.6368	1.02	Q V			
10+50	0.6439	1.03	Q V			
10+55	0.6511	1.04	Q V			
11+ 0	0.6583	1.05	Q V			
11+ 5	0.6656	1.06	Q V			
11+10	0.6730	1.07	Q V			
11+15	0.6804	1.08	Q V			
11+20	0.6879	1.09	Q V			
11+25	0.6955	1.10	Q V			
11+30	0.7031	1.11	Q V			
11+35	0.7108	1.12	Q V			
11+40	0.7186	1.13	Q V			
11+45	0.7265	1.15	Q V			



17+45	2.1450	1.63	| Q	|	|	| V	|
17+50	2.1559	1.59	| Q	|	|	| V	|
17+55	2.1666	1.55	| Q	|	|	| V	|
18+ 0	2.1770	1.51	| Q	|	|	| V	|
18+ 5	2.1871	1.47	| Q	|	|	| V	|
18+10	2.1967	1.39	| Q	|	|	| V	|
18+15	2.2055	1.28	| Q	|	|	| V	|
18+20	2.2138	1.21	| Q	|	|	| V	|
18+25	2.2219	1.17	| Q	|	|	| V	|
18+30	2.2298	1.14	| Q	|	|	| V	|
18+35	2.2375	1.12	| Q	|	|	| V	|
18+40	2.2450	1.10	| Q	|	|	| V	|
18+45	2.2524	1.08	| Q	|	|	| V	|
18+50	2.2597	1.06	| Q	|	|	| V	|
18+55	2.2668	1.04	| Q	|	|	| V	|
19+ 0	2.2739	1.02	| Q	|	|	| V	|
19+ 5	2.2808	1.00	| Q	|	|	| V	|
19+10	2.2876	0.99	|Q	|	|	| V	|
19+15	2.2942	0.97	|Q	|	|	| V	|
19+20	2.3008	0.96	|Q	|	|	| V	|
19+25	2.3073	0.94	|Q	|	|	| V	|
19+30	2.3137	0.93	|Q	|	|	| V	|
19+35	2.3200	0.91	|Q	|	|	| V	|
19+40	2.3262	0.90	|Q	|	|	| V	|
19+45	2.3324	0.89	|Q	|	|	| V	|
19+50	2.3384	0.88	|Q	|	|	| V	|
19+55	2.3444	0.87	|Q	|	|	| V	|
20+ 0	2.3503	0.86	|Q	|	|	| V	|
20+ 5	2.3561	0.85	|Q	|	|	| V	|
20+10	2.3619	0.84	|Q	|	|	| V	|
20+15	2.3675	0.83	|Q	|	|	| V	|
20+20	2.3732	0.82	|Q	|	|	| V	|
20+25	2.3787	0.81	|Q	|	|	| V	|
20+30	2.3842	0.80	|Q	|	|	| V	|
20+35	2.3896	0.79	|Q	|	|	| V	|
20+40	2.3950	0.78	|Q	|	|	| V	|
20+45	2.4003	0.77	|Q	|	|	| V	|
20+50	2.4056	0.76	|Q	|	|	| V	|
20+55	2.4108	0.76	|Q	|	|	| V	|
21+ 0	2.4160	0.75	|Q	|	|	| V	|
21+ 5	2.4211	0.74	|Q	|	|	| V	|
21+10	2.4262	0.74	|Q	|	|	| V	|
21+15	2.4312	0.73	|Q	|	|	| V	|
21+20	2.4361	0.72	|Q	|	|	| V	|
21+25	2.4411	0.71	|Q	|	|	| V	|
21+30	2.4459	0.71	|Q	|	|	| V	|
21+35	2.4508	0.70	|Q	|	|	| V	|
21+40	2.4556	0.70	|Q	|	|	| V	|
21+45	2.4603	0.69	|Q	|	|	| V	|
21+50	2.4650	0.68	|Q	|	|	| V	|
21+55	2.4697	0.68	|Q	|	|	| V	|
22+ 0	2.4744	0.67	|Q	|	|	| V	|
22+ 5	2.4789	0.67	|Q	|	|	| V	|
22+10	2.4835	0.66	|Q	|	|	| V	|
22+15	2.4880	0.66	|Q	|	|	| V	|
22+20	2.4925	0.65	|Q	|	|	| V	|
22+25	2.4970	0.65	|Q	|	|	| V	|
22+30	2.5014	0.64	|Q	|	|	| V	|
22+35	2.5058	0.64	|Q	|	|	| V	|
22+40	2.5101	0.63	|Q	|	|	| V	|
22+45	2.5145	0.63	|Q	|	|	| V	|
22+50	2.5188	0.62	|Q	|	|	| V	|
22+55	2.5230	0.62	|Q	|	|	| V	|
23+ 0	2.5273	0.61	|Q	|	|	| V	|
23+ 5	2.5315	0.61	|Q	|	|	| V	|
23+10	2.5357	0.61	|Q	|	|	| V	|
23+15	2.5398	0.60	|Q	|	|	| V	|
23+20	2.5439	0.60	|Q	|	|	| V	|
23+25	2.5480	0.59	|Q	|	|	| V	|
23+30	2.5521	0.59	|Q	|	|	| V	|
23+35	2.5561	0.59	|Q	|	|	| V	|

```
   23+40       2.5601      0.58  |Q        |         |         |        V|
   23+45       2.5641      0.58  |Q        |         |         |        V|
   23+50       2.5681      0.58  |Q        |         |         |        V|
   23+55       2.5720      0.57  |Q        |         |         |        V|
   24+ 0       2.5760      0.57  |Q        |         |         |        V|
   24+ 5       2.5797      0.54  |Q        |         |         |        V|
   24+10       2.5823      0.39  Q         |         |         |        V|
   24+15       2.5834      0.16  Q         |         |         |        V|
   24+20       2.5838      0.05  Q         |         |         |        V|
   24+25       2.5839      0.01  Q         |         |         |        V|
   24+30       2.5839      0.01  Q         |         |         |        V|
-------------------------------------------------------------------------
```

Unit Hydrograph Analysis: Developed Condition (10 yr, 24 hr Storm Event)

```
       U n i t   H y d r o g r a p h   A n a l y s i s

       Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018, Version 9.0

              Study date  07/01/23

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
------------------------------------------------------------------------------

San Bernardino County Synthetic Unit Hydrology Method
              Manual date - August 1986


Program License Serial Number 6484

------------------------------------------------------------------------
UH ANALYSIS
DEVELOPED CONDITION
10-YR STORM EVENT

------------------------------------------------------------------------

       Storm Event Year = 10

       Antecedent Moisture Condition = 3

 English (in-lb) Input Units Used

 English Rainfall Data (Inches) Input Values Used

 English Units used in output format



Area averaged rainfall intensity isohyetal data:
       Sub-Area        Duration        Isohyetal
       (Ac.)            (hours)         (In)
Rainfall data for year 10
            7.80            1           0.81
------------------------------------------------------------------------
Rainfall data for year 10
            7.80            6           2.06
------------------------------------------------------------------------
Rainfall data for year 10
            7.80           24           3.77
------------------------------------------------------------------------
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

******** Area-averaged max loss rate, Fm ********


SCS curve  SCS curve     Area     Area     Fp(Fig C6)    Ap      Fm
No.(AMCII) NO.(AMC 3)    (Ac.)    Fraction     (In/Hr)  (dec.)   (In/Hr)
 32.0      52.0          7.80      1.000     0.785    0.100    0.079

Area-averaged adjusted loss rate Fm (In/Hr) =  0.079

********* Area-Averaged low loss rate fraction, Yb **********

Area       Area          SCS CN    SCS CN      S     Pervious
 (Ac.)      Fract         (AMC2)    (AMC3)           Yield Fr
     0.78   0.100         32.0      52.0       9.23     0.088
     7.02   0.900         98.0      98.0       0.20     0.938

Area-averaged catchment yield fraction, Y =  0.853
Area-averaged low loss fraction, Yb =  0.147
Direct entry of lag time by user
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
```

Watershed area = 7.80(Ac.)
Catchment Lag time = 0.163 hours
Unit interval = 5.000 minutes
Unit interval percentage of lag time = 51.1876
Hydrograph baseflow = 0.00(CFS)
Average maximum watershed loss rate(Fm) = 0.079(In/Hr)
Average low loss rate fraction (Yb) = 0.147 (decimal)
VALLEY DEVELOPED S-Graph Selected
Computed peak 5-minute rainfall = 0.302(In)
Computed peak 30-minute rainfall = 0.618(In)
Specified peak 1-hour rainfall = 0.815(In)
Computed peak 3-hour rainfall = 1.439(In)
Specified peak 6-hour rainfall = 2.060(In)
Specified peak 24-hour rainfall = 3.770(In)

Rainfall depth area reduction factors:
Using a total area of 7.80(Ac.) (Ref: fig. E-4)

5-minute factor = 1.000 Adjusted rainfall = 0.302(In)
30-minute factor = 1.000 Adjusted rainfall = 0.617(In)
1-hour factor = 1.000 Adjusted rainfall = 0.815(In)
3-hour factor = 1.000 Adjusted rainfall = 1.439(In)
6-hour factor = 1.000 Adjusted rainfall = 2.060(In)
24-hour factor = 1.000 Adjusted rainfall = 3.770(In)

U n i t H y d r o g r a p h

Interval Number	'S' Graph Mean values	Unit Hydrograph ((CFS))
	(K = 94.33 (CFS))	
1	4.788	4.516
2	31.153	24.871
3	70.637	37.245
4	90.873	19.089
5	97.349	6.109
6	98.868	1.432
7	100.000	1.068

Peak Unit Number	Adjusted mass rainfall (In)	Unit rainfall (In)
1	0.3015	0.3015
2	0.3979	0.0963
3	0.4679	0.0701
4	0.5250	0.0571
5	0.5740	0.0490
6	0.6174	0.0434
7	0.6567	0.0393
8	0.6927	0.0360
9	0.7261	0.0334
10	0.7574	0.0313
11	0.7868	0.0294
12	0.8147	0.0279
13	0.8492	0.0345
14	0.8824	0.0332
15	0.9145	0.0321
16	0.9456	0.0311
17	0.9757	0.0302
18	1.0050	0.0293
19	1.0336	0.0285
20	1.0614	0.0278
21	1.0885	0.0272
22	1.1151	0.0265
23	1.1411	0.0260
24	1.1665	0.0254
25	1.1914	0.0249
26	1.2158	0.0244
27	1.2398	0.0240

28	1.2634	0.0236
29	1.2866	0.0232
30	1.3094	0.0228
31	1.3318	0.0224
32	1.3538	0.0221
33	1.3756	0.0217
34	1.3970	0.0214
35	1.4182	0.0211
36	1.4390	0.0208
37	1.4595	0.0206
38	1.4798	0.0203
39	1.4999	0.0200
40	1.5196	0.0198
41	1.5392	0.0195
42	1.5585	0.0193
43	1.5776	0.0191
44	1.5965	0.0189
45	1.6152	0.0187
46	1.6336	0.0185
47	1.6519	0.0183
48	1.6700	0.0181
49	1.6879	0.0179
50	1.7057	0.0177
51	1.7232	0.0176
52	1.7406	0.0174
53	1.7579	0.0172
54	1.7750	0.0171
55	1.7919	0.0169
56	1.8087	0.0168
57	1.8254	0.0166
58	1.8419	0.0165
59	1.8582	0.0164
60	1.8745	0.0162
61	1.8906	0.0161
62	1.9065	0.0160
63	1.9224	0.0159
64	1.9381	0.0157
65	1.9537	0.0156
66	1.9692	0.0155
67	1.9846	0.0154
68	1.9999	0.0153
69	2.0151	0.0152
70	2.0301	0.0151
71	2.0451	0.0150
72	2.0599	0.0149
73	2.0724	0.0124
74	2.0847	0.0123
75	2.0969	0.0122
76	2.1091	0.0121
77	2.1211	0.0121
78	2.1331	0.0120
79	2.1450	0.0119
80	2.1568	0.0118
81	2.1685	0.0117
82	2.1801	0.0116
83	2.1917	0.0116
84	2.2031	0.0115
85	2.2145	0.0114
86	2.2259	0.0113
87	2.2371	0.0112
88	2.2483	0.0112
89	2.2594	0.0111
90	2.2704	0.0110
91	2.2814	0.0110
92	2.2923	0.0109
93	2.3031	0.0108
94	2.3139	0.0108
95	2.3246	0.0107
96	2.3352	0.0106
97	2.3458	0.0106
98	2.3563	0.0105

99	2.3668	0.0105
100	2.3771	0.0104
101	2.3875	0.0103
102	2.3978	0.0103
103	2.4080	0.0102
104	2.4181	0.0102
105	2.4282	0.0101
106	2.4383	0.0101
107	2.4483	0.0100
108	2.4583	0.0099
109	2.4682	0.0099
110	2.4780	0.0098
111	2.4878	0.0098
112	2.4975	0.0097
113	2.5072	0.0097
114	2.5169	0.0096
115	2.5265	0.0096
116	2.5360	0.0096
117	2.5456	0.0095
118	2.5550	0.0095
119	2.5644	0.0094
120	2.5738	0.0094
121	2.5831	0.0093
122	2.5924	0.0093
123	2.6017	0.0092
124	2.6109	0.0092
125	2.6200	0.0092
126	2.6291	0.0091
127	2.6382	0.0091
128	2.6473	0.0090
129	2.6563	0.0090
130	2.6652	0.0090
131	2.6741	0.0089
132	2.6830	0.0089
133	2.6919	0.0088
134	2.7007	0.0088
135	2.7094	0.0088
136	2.7182	0.0087
137	2.7269	0.0087
138	2.7355	0.0087
139	2.7441	0.0086
140	2.7527	0.0086
141	2.7613	0.0086
142	2.7698	0.0085
143	2.7783	0.0085
144	2.7867	0.0085
145	2.7952	0.0084
146	2.8036	0.0084
147	2.8119	0.0084
148	2.8202	0.0083
149	2.8285	0.0083
150	2.8368	0.0083
151	2.8450	0.0082
152	2.8532	0.0082
153	2.8614	0.0082
154	2.8695	0.0081
155	2.8776	0.0081
156	2.8857	0.0081
157	2.8938	0.0081
158	2.9018	0.0080
159	2.9098	0.0080
160	2.9177	0.0080
161	2.9257	0.0079
162	2.9336	0.0079
163	2.9415	0.0079
164	2.9493	0.0079
165	2.9571	0.0078
166	2.9649	0.0078
167	2.9727	0.0078
168	2.9805	0.0077
169	2.9882	0.0077

170	2.9959	0.0077
171	3.0036	0.0077
172	3.0112	0.0076
173	3.0188	0.0076
174	3.0264	0.0076
175	3.0340	0.0076
176	3.0415	0.0075
177	3.0490	0.0075
178	3.0565	0.0075
179	3.0640	0.0075
180	3.0715	0.0075
181	3.0789	0.0074
182	3.0863	0.0074
183	3.0937	0.0074
184	3.1010	0.0074
185	3.1084	0.0073
186	3.1157	0.0073
187	3.1230	0.0073
188	3.1303	0.0073
189	3.1375	0.0072
190	3.1447	0.0072
191	3.1519	0.0072
192	3.1591	0.0072
193	3.1663	0.0072
194	3.1734	0.0071
195	3.1805	0.0071
196	3.1876	0.0071
197	3.1947	0.0071
198	3.2018	0.0071
199	3.2088	0.0070
200	3.2158	0.0070
201	3.2228	0.0070
202	3.2298	0.0070
203	3.2368	0.0070
204	3.2437	0.0069
205	3.2507	0.0069
206	3.2576	0.0069
207	3.2644	0.0069
208	3.2713	0.0069
209	3.2782	0.0068
210	3.2850	0.0068
211	3.2918	0.0068
212	3.2986	0.0068
213	3.3054	0.0068
214	3.3121	0.0068
215	3.3189	0.0067
216	3.3256	0.0067
217	3.3323	0.0067
218	3.3390	0.0067
219	3.3456	0.0067
220	3.3523	0.0067
221	3.3589	0.0066
222	3.3655	0.0066
223	3.3721	0.0066
224	3.3787	0.0066
225	3.3853	0.0066
226	3.3918	0.0066
227	3.3984	0.0065
228	3.4049	0.0065
229	3.4114	0.0065
230	3.4179	0.0065
231	3.4244	0.0065
232	3.4308	0.0065
233	3.4373	0.0064
234	3.4437	0.0064
235	3.4501	0.0064
236	3.4565	0.0064
237	3.4629	0.0064
238	3.4692	0.0064
239	3.4756	0.0063
240	3.4819	0.0063

241	3.4882	0.0063
242	3.4945	0.0063
243	3.5008	0.0063
244	3.5071	0.0063
245	3.5133	0.0063
246	3.5196	0.0062
247	3.5258	0.0062
248	3.5320	0.0062
249	3.5382	0.0062
250	3.5444	0.0062
251	3.5506	0.0062
252	3.5568	0.0062
253	3.5629	0.0061
254	3.5690	0.0061
255	3.5752	0.0061
256	3.5813	0.0061
257	3.5874	0.0061
258	3.5934	0.0061
259	3.5995	0.0061
260	3.6056	0.0061
261	3.6116	0.0060
262	3.6176	0.0060
263	3.6236	0.0060
264	3.6296	0.0060
265	3.6356	0.0060
266	3.6416	0.0060
267	3.6476	0.0060
268	3.6535	0.0059
269	3.6594	0.0059
270	3.6654	0.0059
271	3.6713	0.0059
272	3.6772	0.0059
273	3.6831	0.0059
274	3.6889	0.0059
275	3.6948	0.0059
276	3.7007	0.0059
277	3.7065	0.0058
278	3.7123	0.0058
279	3.7181	0.0058
280	3.7239	0.0058
281	3.7297	0.0058
282	3.7355	0.0058
283	3.7413	0.0058
284	3.7470	0.0058
285	3.7528	0.0057
286	3.7585	0.0057
287	3.7643	0.0057
288	3.7700	0.0057

Unit Period (number)	Unit Rainfall (In)	Unit Soil-Loss (In)	Effective Rainfall (In)
1	0.0057	0.0008	0.0049
2	0.0057	0.0008	0.0049
3	0.0057	0.0008	0.0049
4	0.0058	0.0008	0.0049
5	0.0058	0.0009	0.0049
6	0.0058	0.0009	0.0049
7	0.0058	0.0009	0.0050
8	0.0058	0.0009	0.0050
9	0.0059	0.0009	0.0050
10	0.0059	0.0009	0.0050
11	0.0059	0.0009	0.0050
12	0.0059	0.0009	0.0050
13	0.0059	0.0009	0.0051
14	0.0059	0.0009	0.0051
15	0.0060	0.0009	0.0051
16	0.0060	0.0009	0.0051
17	0.0060	0.0009	0.0051
18	0.0060	0.0009	0.0051

19	0.0060	0.0009	0.0052
20	0.0061	0.0009	0.0052
21	0.0061	0.0009	0.0052
22	0.0061	0.0009	0.0052
23	0.0061	0.0009	0.0052
24	0.0061	0.0009	0.0052
25	0.0062	0.0009	0.0053
26	0.0062	0.0009	0.0053
27	0.0062	0.0009	0.0053
28	0.0062	0.0009	0.0053
29	0.0062	0.0009	0.0053
30	0.0063	0.0009	0.0053
31	0.0063	0.0009	0.0054
32	0.0063	0.0009	0.0054
33	0.0063	0.0009	0.0054
34	0.0063	0.0009	0.0054
35	0.0064	0.0009	0.0054
36	0.0064	0.0009	0.0055
37	0.0064	0.0009	0.0055
38	0.0064	0.0009	0.0055
39	0.0065	0.0010	0.0055
40	0.0065	0.0010	0.0055
41	0.0065	0.0010	0.0056
42	0.0065	0.0010	0.0056
43	0.0066	0.0010	0.0056
44	0.0066	0.0010	0.0056
45	0.0066	0.0010	0.0056
46	0.0066	0.0010	0.0057
47	0.0067	0.0010	0.0057
48	0.0067	0.0010	0.0057
49	0.0067	0.0010	0.0057
50	0.0067	0.0010	0.0057
51	0.0068	0.0010	0.0058
52	0.0068	0.0010	0.0058
53	0.0068	0.0010	0.0058
54	0.0068	0.0010	0.0058
55	0.0069	0.0010	0.0059
56	0.0069	0.0010	0.0059
57	0.0069	0.0010	0.0059
58	0.0070	0.0010	0.0059
59	0.0070	0.0010	0.0060
60	0.0070	0.0010	0.0060
61	0.0071	0.0010	0.0060
62	0.0071	0.0010	0.0060
63	0.0071	0.0010	0.0061
64	0.0071	0.0011	0.0061
65	0.0072	0.0011	0.0061
66	0.0072	0.0011	0.0061
67	0.0072	0.0011	0.0062
68	0.0073	0.0011	0.0062
69	0.0073	0.0011	0.0062
70	0.0073	0.0011	0.0063
71	0.0074	0.0011	0.0063
72	0.0074	0.0011	0.0063
73	0.0075	0.0011	0.0064
74	0.0075	0.0011	0.0064
75	0.0075	0.0011	0.0064
76	0.0075	0.0011	0.0064
77	0.0076	0.0011	0.0065
78	0.0076	0.0011	0.0065
79	0.0077	0.0011	0.0065
80	0.0077	0.0011	0.0066
81	0.0077	0.0011	0.0066
82	0.0078	0.0011	0.0066
83	0.0078	0.0012	0.0067
84	0.0079	0.0012	0.0067
85	0.0079	0.0012	0.0067
86	0.0079	0.0012	0.0068
87	0.0080	0.0012	0.0068
88	0.0080	0.0012	0.0068
89	0.0081	0.0012	0.0069

90	0.0081	0.0012	0.0069
91	0.0082	0.0012	0.0070
92	0.0082	0.0012	0.0070
93	0.0083	0.0012	0.0070
94	0.0083	0.0012	0.0071
95	0.0084	0.0012	0.0071
96	0.0084	0.0012	0.0072
97	0.0085	0.0012	0.0072
98	0.0085	0.0012	0.0072
99	0.0086	0.0013	0.0073
100	0.0086	0.0013	0.0073
101	0.0087	0.0013	0.0074
102	0.0087	0.0013	0.0074
103	0.0088	0.0013	0.0075
104	0.0088	0.0013	0.0075
105	0.0089	0.0013	0.0076
106	0.0089	0.0013	0.0076
107	0.0090	0.0013	0.0077
108	0.0090	0.0013	0.0077
109	0.0091	0.0013	0.0078
110	0.0092	0.0013	0.0078
111	0.0092	0.0014	0.0079
112	0.0093	0.0014	0.0079
113	0.0094	0.0014	0.0080
114	0.0094	0.0014	0.0080
115	0.0095	0.0014	0.0081
116	0.0096	0.0014	0.0081
117	0.0096	0.0014	0.0082
118	0.0097	0.0014	0.0083
119	0.0098	0.0014	0.0084
120	0.0098	0.0014	0.0084
121	0.0099	0.0015	0.0085
122	0.0100	0.0015	0.0085
123	0.0101	0.0015	0.0086
124	0.0102	0.0015	0.0087
125	0.0103	0.0015	0.0088
126	0.0103	0.0015	0.0088
127	0.0105	0.0015	0.0089
128	0.0105	0.0015	0.0090
129	0.0106	0.0016	0.0091
130	0.0107	0.0016	0.0091
131	0.0108	0.0016	0.0092
132	0.0109	0.0016	0.0093
133	0.0110	0.0016	0.0094
134	0.0111	0.0016	0.0095
135	0.0112	0.0017	0.0096
136	0.0113	0.0017	0.0097
137	0.0115	0.0017	0.0098
138	0.0116	0.0017	0.0099
139	0.0117	0.0017	0.0100
140	0.0118	0.0017	0.0101
141	0.0120	0.0018	0.0102
142	0.0121	0.0018	0.0103
143	0.0122	0.0018	0.0104
144	0.0123	0.0018	0.0105
145	0.0149	0.0022	0.0127
146	0.0150	0.0022	0.0128
147	0.0152	0.0022	0.0129
148	0.0153	0.0022	0.0130
149	0.0155	0.0023	0.0132
150	0.0156	0.0023	0.0133
151	0.0159	0.0023	0.0135
152	0.0160	0.0024	0.0136
153	0.0162	0.0024	0.0138
154	0.0164	0.0024	0.0140
155	0.0166	0.0024	0.0142
156	0.0168	0.0025	0.0143
157	0.0171	0.0025	0.0146
158	0.0172	0.0025	0.0147
159	0.0176	0.0026	0.0150
160	0.0177	0.0026	0.0151

161	0.0181	0.0027	0.0154
162	0.0183	0.0027	0.0156
163	0.0187	0.0027	0.0159
164	0.0189	0.0028	0.0161
165	0.0193	0.0028	0.0165
166	0.0195	0.0029	0.0167
167	0.0200	0.0029	0.0171
168	0.0203	0.0030	0.0173
169	0.0208	0.0031	0.0178
170	0.0211	0.0031	0.0180
171	0.0217	0.0032	0.0185
172	0.0221	0.0032	0.0188
173	0.0228	0.0034	0.0194
174	0.0232	0.0034	0.0198
175	0.0240	0.0035	0.0205
176	0.0244	0.0036	0.0208
177	0.0254	0.0037	0.0217
178	0.0260	0.0038	0.0221
179	0.0272	0.0040	0.0232
180	0.0278	0.0041	0.0237
181	0.0293	0.0043	0.0250
182	0.0302	0.0044	0.0257
183	0.0321	0.0047	0.0274
184	0.0332	0.0049	0.0283
185	0.0279	0.0041	0.0238
186	0.0294	0.0043	0.0251
187	0.0334	0.0049	0.0285
188	0.0360	0.0053	0.0307
189	0.0434	0.0064	0.0370
190	0.0490	0.0065	0.0425
191	0.0701	0.0065	0.0635
192	0.0963	0.0065	0.0898
193	0.3015	0.0065	0.2950
194	0.0571	0.0065	0.0505
195	0.0393	0.0058	0.0335
196	0.0313	0.0046	0.0267
197	0.0345	0.0051	0.0294
198	0.0311	0.0046	0.0265
199	0.0285	0.0042	0.0243
200	0.0265	0.0039	0.0226
201	0.0249	0.0037	0.0213
202	0.0236	0.0035	0.0201
203	0.0224	0.0033	0.0191
204	0.0214	0.0032	0.0183
205	0.0206	0.0030	0.0175
206	0.0198	0.0029	0.0169
207	0.0191	0.0028	0.0163
208	0.0185	0.0027	0.0158
209	0.0179	0.0026	0.0153
210	0.0174	0.0026	0.0148
211	0.0169	0.0025	0.0144
212	0.0165	0.0024	0.0141
213	0.0161	0.0024	0.0137
214	0.0157	0.0023	0.0134
215	0.0154	0.0023	0.0131
216	0.0151	0.0022	0.0128
217	0.0124	0.0018	0.0106
218	0.0121	0.0018	0.0104
219	0.0119	0.0017	0.0101
220	0.0116	0.0017	0.0099
221	0.0114	0.0017	0.0097
222	0.0112	0.0016	0.0095
223	0.0110	0.0016	0.0094
224	0.0108	0.0016	0.0092
225	0.0106	0.0016	0.0090
226	0.0104	0.0015	0.0089
227	0.0102	0.0015	0.0087
228	0.0101	0.0015	0.0086
229	0.0099	0.0015	0.0084
230	0.0097	0.0014	0.0083
231	0.0096	0.0014	0.0082

232	0.0095	0.0014	0.0081
233	0.0093	0.0014	0.0080
234	0.0092	0.0014	0.0078
235	0.0091	0.0013	0.0077
236	0.0090	0.0013	0.0076
237	0.0088	0.0013	0.0075
238	0.0087	0.0013	0.0074
239	0.0086	0.0013	0.0074
240	0.0085	0.0013	0.0073
241	0.0084	0.0012	0.0072
242	0.0083	0.0012	0.0071
243	0.0082	0.0012	0.0070
244	0.0081	0.0012	0.0069
245	0.0081	0.0012	0.0069
246	0.0080	0.0012	0.0068
247	0.0079	0.0012	0.0067
248	0.0078	0.0011	0.0067
249	0.0077	0.0011	0.0066
250	0.0076	0.0011	0.0065
251	0.0076	0.0011	0.0065
252	0.0075	0.0011	0.0064
253	0.0074	0.0011	0.0063
254	0.0074	0.0011	0.0063
255	0.0073	0.0011	0.0062
256	0.0072	0.0011	0.0062
257	0.0072	0.0011	0.0061
258	0.0071	0.0010	0.0061
259	0.0070	0.0010	0.0060
260	0.0070	0.0010	0.0060
261	0.0069	0.0010	0.0059
262	0.0069	0.0010	0.0059
263	0.0068	0.0010	0.0058
264	0.0068	0.0010	0.0058
265	0.0067	0.0010	0.0057
266	0.0067	0.0010	0.0057
267	0.0066	0.0010	0.0056
268	0.0066	0.0010	0.0056
269	0.0065	0.0010	0.0055
270	0.0065	0.0009	0.0055
271	0.0064	0.0009	0.0055
272	0.0064	0.0009	0.0054
273	0.0063	0.0009	0.0054
274	0.0063	0.0009	0.0054
275	0.0062	0.0009	0.0053
276	0.0062	0.0009	0.0053
277	0.0061	0.0009	0.0052
278	0.0061	0.0009	0.0052
279	0.0061	0.0009	0.0052
280	0.0060	0.0009	0.0051
281	0.0060	0.0009	0.0051
282	0.0059	0.0009	0.0051
283	0.0059	0.0009	0.0050
284	0.0059	0.0009	0.0050
285	0.0058	0.0009	0.0050
286	0.0058	0.0009	0.0050
287	0.0058	0.0008	0.0049
288	0.0057	0.0008	0.0049

Total soil rain loss = 0.50(In)
Total effective rainfall = 3.27(In)
Peak flow rate in flood hydrograph = 14.60(CFS)

++


24 - H O U R S T O R M
R u n o f f H y d r o g r a p h

Hydrograph in 5 Minute intervals ((CFS))

Time(h+m) Volume Ac.Ft Q(CFS) 0 5.0 10.0 15.0 20.0

0+ 5	0.0002	0.02	Q				
0+10	0.0011	0.14	Q				
0+15	0.0034	0.33	Q				
0+20	0.0063	0.42	Q				
0+25	0.0094	0.45	Q				
0+30	0.0125	0.46	Q				
0+35	0.0157	0.46	Q				
0+40	0.0189	0.47	Q				
0+45	0.0221	0.47	Q				
0+50	0.0254	0.47	Q				
0+55	0.0286	0.47	Q				
1+ 0	0.0319	0.47	Q				
1+ 5	0.0351	0.47	Q				
1+10	0.0384	0.47	Q				
1+15	0.0417	0.48	Q				
1+20	0.0450	0.48	Q				
1+25	0.0483	0.48	Q				
1+30	0.0516	0.48	Q				
1+35	0.0549	0.48	QV				
1+40	0.0582	0.48	QV				
1+45	0.0616	0.49	QV				
1+50	0.0649	0.49	QV				
1+55	0.0683	0.49	QV				
2+ 0	0.0717	0.49	QV				
2+ 5	0.0751	0.49	QV				
2+10	0.0785	0.49	QV				
2+15	0.0819	0.50	QV				
2+20	0.0853	0.50	QV				
2+25	0.0887	0.50	QV				
2+30	0.0922	0.50	|Q				
2+35	0.0956	0.50	|Q				
2+40	0.0991	0.50	|Q				
2+45	0.1026	0.51	|Q				
2+50	0.1061	0.51	|Q				
2+55	0.1096	0.51	|QV				
3+ 0	0.1131	0.51	|QV				
3+ 5	0.1166	0.51	|QV				
3+10	0.1202	0.51	|QV				
3+15	0.1237	0.52	|QV				
3+20	0.1273	0.52	|QV				
3+25	0.1309	0.52	|QV				
3+30	0.1345	0.52	|QV				
3+35	0.1381	0.52	|QV				
3+40	0.1417	0.53	|QV				
3+45	0.1453	0.53	|QV				
3+50	0.1490	0.53	|QV				
3+55	0.1527	0.53	|QV				
4+ 0	0.1563	0.53	|QV				
4+ 5	0.1600	0.54	|Q V				
4+10	0.1637	0.54	|Q V				
4+15	0.1675	0.54	|Q V				
4+20	0.1712	0.54	|Q V				
4+25	0.1749	0.54	|Q V				
4+30	0.1787	0.55	|Q V				
4+35	0.1825	0.55	|Q V				
4+40	0.1863	0.55	|Q V				
4+45	0.1901	0.55	|Q V				
4+50	0.1939	0.56	|Q V				
4+55	0.1978	0.56	|Q V				
5+ 0	0.2016	0.56	|Q V				
5+ 5	0.2055	0.56	|Q V				
5+10	0.2094	0.57	|Q V				
5+15	0.2133	0.57	|Q V				
5+20	0.2172	0.57	|Q V				
5+25	0.2212	0.57	|Q V				
5+30	0.2251	0.57	|Q V				
5+35	0.2291	0.58	|Q V				
5+40	0.2331	0.58	|Q V				
5+45	0.2371	0.58	|Q V				
5+50	0.2411	0.59	|Q V				

5+55	0.2452	0.59	|Q V |	|	|	|
6+ 0	0.2493	0.59	|Q V |	|	|	|
6+ 5	0.2533	0.59	|Q V |	|	|	|
6+10	0.2574	0.60	|Q V |	|	|	|
6+15	0.2616	0.60	|Q V |	|	|	|
6+20	0.2657	0.60	|Q V |	|	|	|
6+25	0.2699	0.60	|Q V |	|	|	|
6+30	0.2741	0.61	|Q V |	|	|	|
6+35	0.2783	0.61	|Q V |	|	|	|
6+40	0.2825	0.61	|Q V |	|	|	|
6+45	0.2867	0.62	|Q V |	|	|	|
6+50	0.2910	0.62	|Q V |	|	|	|
6+55	0.2953	0.62	|Q V |	|	|	|
7+ 0	0.2996	0.63	|Q V |	|	|	|
7+ 5	0.3039	0.63	|Q V |	|	|	|
7+10	0.3083	0.63	|Q V |	|	|	|
7+15	0.3127	0.64	|Q V |	|	|	|
7+20	0.3171	0.64	|Q V |	|	|	|
7+25	0.3215	0.64	|Q V |	|	|	|
7+30	0.3259	0.65	|Q V |	|	|	|
7+35	0.3304	0.65	|Q V |	|	|	|
7+40	0.3349	0.65	|Q V |	|	|	|
7+45	0.3394	0.66	|Q V |	|	|	|
7+50	0.3440	0.66	|Q V |	|	|	|
7+55	0.3485	0.66	|Q V |	|	|	|
8+ 0	0.3531	0.67	|Q V |	|	|	|
8+ 5	0.3578	0.67	|Q V |	|	|	|
8+10	0.3624	0.68	|Q V |	|	|	|
8+15	0.3671	0.68	|Q V |	|	|	|
8+20	0.3718	0.68	|Q V |	|	|	|
8+25	0.3765	0.69	|Q V |	|	|	|
8+30	0.3813	0.69	|Q V |	|	|	|
8+35	0.3861	0.70	|Q V |	|	|	|
8+40	0.3909	0.70	|Q V |	|	|	|
8+45	0.3957	0.70	|Q V |	|	|	|
8+50	0.4006	0.71	|Q V |	|	|	|
8+55	0.4055	0.71	|Q V |	|	|	|
9+ 0	0.4105	0.72	|Q V |	|	|	|
9+ 5	0.4155	0.72	|Q V |	|	|	|
9+10	0.4205	0.73	|Q V |	|	|	|
9+15	0.4255	0.73	|Q V |	|	|	|
9+20	0.4306	0.74	|Q V |	|	|	|
9+25	0.4357	0.74	|Q V |	|	|	|
9+30	0.4409	0.75	|Q V |	|	|	|
9+35	0.4461	0.75	|Q V |	|	|	|
9+40	0.4513	0.76	|Q V |	|	|	|
9+45	0.4565	0.76	|Q V |	|	|	|
9+50	0.4618	0.77	|Q V |	|	|	|
9+55	0.4672	0.78	|Q V |	|	|	|
10+ 0	0.4725	0.78	|Q V |	|	|	|
10+ 5	0.4780	0.79	|Q V|	|	|	|
10+10	0.4834	0.79	|Q V|	|	|	|
10+15	0.4889	0.80	|Q V|	|	|	|
10+20	0.4945	0.81	|Q V|	|	|	|
10+25	0.5001	0.81	|Q V|	|	|	|
10+30	0.5057	0.82	|Q V|	|	|	|
10+35	0.5114	0.83	|Q V|	|	|	|
10+40	0.5171	0.83	|Q V|	|	|	|
10+45	0.5229	0.84	|Q V|	|	|	|
10+50	0.5287	0.85	|Q V|	|	|	|
10+55	0.5346	0.85	|Q V |	|	|	|
11+ 0	0.5405	0.86	|Q V |	|	|	|
11+ 5	0.5465	0.87	|Q V |	|	|	|
11+10	0.5526	0.88	|Q V |	|	|	|
11+15	0.5587	0.89	|Q V |	|	|	|
11+20	0.5648	0.89	|Q V |	|	|	|
11+25	0.5711	0.90	|Q V |	|	|	|
11+30	0.5773	0.91	|Q V |	|	|	|
11+35	0.5837	0.92	|Q |V |	|	|	|
11+40	0.5901	0.93	|Q |V |	|	|	|
11+45	0.5966	0.94	|Q |V |	|	|	|



17+45	1.7610	1.37	Q				V
17+50	1.7702	1.33	Q				V
17+55	1.7791	1.30	Q				V
18+ 0	1.7878	1.27	Q				V
18+ 5	1.7963	1.23	Q				V
18+10	1.8043	1.16	Q				V
18+15	1.8116	1.06	Q				V
18+20	1.8184	1.00	Q				V
18+25	1.8251	0.96	Q				V
18+30	1.8315	0.94	Q				V
18+35	1.8379	0.92	Q				V
18+40	1.8441	0.90	Q				V
18+45	1.8502	0.88	Q				V
18+50	1.8561	0.87	Q				V
18+55	1.8620	0.85	Q				V
19+ 0	1.8678	0.84	Q				V
19+ 5	1.8734	0.82	Q				V
19+10	1.8790	0.81	Q				V
19+15	1.8845	0.80	Q				V
19+20	1.8899	0.79	Q				V
19+25	1.8952	0.77	Q				V
19+30	1.9005	0.76	Q				V
19+35	1.9057	0.75	Q				V
19+40	1.9108	0.74	Q				V
19+45	1.9158	0.73	Q				V
19+50	1.9208	0.72	Q				V
19+55	1.9257	0.71	Q				V
20+ 0	1.9305	0.70	Q				V
20+ 5	1.9353	0.69	Q				V
20+10	1.9400	0.69	Q				V
20+15	1.9447	0.68	Q				V
20+20	1.9493	0.67	Q				V
20+25	1.9539	0.66	Q				V
20+30	1.9584	0.66	Q				V
20+35	1.9629	0.65	Q				V
20+40	1.9673	0.64	Q				V
20+45	1.9716	0.63	Q				V
20+50	1.9760	0.63	Q				V
20+55	1.9803	0.62	Q				V
21+ 0	1.9845	0.62	Q				V
21+ 5	1.9887	0.61	Q				V
21+10	1.9928	0.60	Q				V
21+15	1.9970	0.60	Q				V
21+20	2.0010	0.59	Q				V
21+25	2.0051	0.59	Q				V
21+30	2.0091	0.58	Q				V
21+35	2.0131	0.58	Q				V
21+40	2.0170	0.57	Q				V
21+45	2.0209	0.57	Q				V
21+50	2.0248	0.56	Q				V
21+55	2.0286	0.56	Q				V
22+ 0	2.0324	0.55	Q				V
22+ 5	2.0362	0.55	Q				V
22+10	2.0399	0.54	Q				V
22+15	2.0437	0.54	Q				V
22+20	2.0474	0.54	Q				V
22+25	2.0510	0.53	Q				V
22+30	2.0546	0.53	Q				V
22+35	2.0582	0.52	Q				V
22+40	2.0618	0.52	Q				V
22+45	2.0654	0.52	Q				V
22+50	2.0689	0.51	Q				V
22+55	2.0724	0.51	Q				V
23+ 0	2.0759	0.50	Q				V
23+ 5	2.0793	0.50	Q				V
23+10	2.0828	0.50	Q				V
23+15	2.0862	0.49	Q				V
23+20	2.0896	0.49	Q				V
23+25	2.0929	0.49	Q				V
23+30	2.0963	0.49	Q				V
23+35	2.0996	0.48	Q				V

```
   23+40       2.1029      0.48  Q         |         |         |        V|
   23+45       2.1062      0.48  Q         |         |         |        V|
   23+50       2.1094      0.47  Q         |         |         |        V|
   23+55       2.1127      0.47  Q         |         |         |        V|
   24+ 0       2.1159      0.47  Q         |         |         |        V|
   24+ 5       2.1189      0.44  Q         |         |         |        V|
   24+10       2.1211      0.32  Q         |         |         |        V|
   24+15       2.1221      0.14  Q         |         |         |        V|
   24+20       2.1223      0.04  Q         |         |         |        V|
   24+25       2.1224      0.01  Q         |         |         |        V|
   24+30       2.1225      0.01  Q         |         |         |         V
-------------------------------------------------------------------------
```

Unit Hydrograph Analysis: Developed Condition (5 yr, 24 hr Storm Event)

```
       U n i t   H y d r o g r a p h   A n a l y s i s

       Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018, Version 9.0

              Study date  07/01/23

++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
------------------------------------------------------------------------------

San Bernardino County Synthetic Unit Hydrology Method
              Manual date - August 1986


Program License Serial Number 6484

------------------------------------------------------------------------
UH ANALYSIS
DEVELOPED CONDITION
5-YR STORM EVENT

------------------------------------------------------------------------

       Storm Event Year = 5

       Antecedent Moisture Condition = 3

 English (in-lb) Input Units Used

 English Rainfall Data (Inches) Input Values Used

 English Units used in output format



Area averaged rainfall intensity isohyetal data:
       Sub-Area        Duration        Isohyetal
       (Ac.)            (hours)         (In)
Rainfall data for year 5
            7.80            1           0.68
------------------------------------------------------------------------
Rainfall data for year 5
            7.80            6           1.75
------------------------------------------------------------------------
Rainfall data for year 5
            7.80           24           3.19
------------------------------------------------------------------------
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++

******** Area-averaged max loss rate, Fm ********


SCS curve  SCS curve     Area     Area     Fp(Fig C6)    Ap      Fm
No.(AMCII) NO.(AMC 3)    (Ac.)    Fraction     (In/Hr)  (dec.)   (In/Hr)
 32.0      52.0          7.80      1.000     0.785    0.100    0.079

Area-averaged adjusted loss rate Fm (In/Hr) =  0.079

********* Area-Averaged low loss rate fraction, Yb **********

Area       Area          SCS CN    SCS CN      S     Pervious
 (Ac.)      Fract         (AMC2)    (AMC3)           Yield Fr
     0.78   0.100         32.0      52.0       9.23     0.054
     7.02   0.900         98.0      98.0       0.20     0.927

Area-averaged catchment yield fraction, Y =  0.840
Area-averaged low loss fraction, Yb =  0.160
Direct entry of lag time by user
++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
```

Watershed area = 7.80(Ac.)
Catchment Lag time = 0.163 hours
Unit interval = 5.000 minutes
Unit interval percentage of lag time = 51.0621
Hydrograph baseflow = 0.00(CFS)
Average maximum watershed loss rate(Fm) = 0.079(In/Hr)
Average low loss rate fraction (Yb) = 0.160 (decimal)
VALLEY DEVELOPED S-Graph Selected
Computed peak 5-minute rainfall = 0.252(In)
Computed peak 30-minute rainfall = 0.516(In)
Specified peak 1-hour rainfall = 0.681(In)
Computed peak 3-hour rainfall = 1.215(In)
Specified peak 6-hour rainfall = 1.750(In)
Specified peak 24-hour rainfall = 3.190(In)

Rainfall depth area reduction factors:
Using a total area of 7.80(Ac.) (Ref: fig. E-4)

5-minute factor = 1.000 Adjusted rainfall = 0.252(In)
30-minute factor = 1.000 Adjusted rainfall = 0.516(In)
1-hour factor = 1.000 Adjusted rainfall = 0.681(In)
3-hour factor = 1.000 Adjusted rainfall = 1.215(In)
6-hour factor = 1.000 Adjusted rainfall = 1.750(In)
24-hour factor = 1.000 Adjusted rainfall = 3.190(In)

U n i t H y d r o g r a p h

Interval Number	'S' Graph Mean values	Unit Hydrograph ((CFS))
	(K = 94.33 (CFS))	
1	4.765	4.495
2	31.011	24.758
3	70.445	37.199
4	90.778	19.181
5	97.317	6.168
6	98.855	1.451
7	100.000	1.080

Peak Unit Number	Adjusted mass rainfall (In)	Unit rainfall (In)
1	0.2520	0.2520
2	0.3325	0.0805
3	0.3910	0.0585
4	0.4387	0.0477
5	0.4796	0.0410
6	0.5159	0.0363
7	0.5487	0.0328
8	0.5788	0.0301
9	0.6068	0.0279
10	0.6329	0.0261
11	0.6575	0.0246
12	0.6808	0.0233
13	0.7101	0.0293
14	0.7384	0.0283
15	0.7657	0.0273
16	0.7922	0.0265
17	0.8179	0.0257
18	0.8429	0.0250
19	0.8673	0.0244
20	0.8911	0.0238
21	0.9143	0.0232
22	0.9370	0.0227
23	0.9592	0.0222
24	0.9809	0.0218
25	1.0023	0.0213
26	1.0232	0.0209
27	1.0438	0.0206

28	1.0640	0.0202
29	1.0838	0.0199
30	1.1034	0.0195
31	1.1226	0.0192
32	1.1415	0.0189
33	1.1602	0.0187
34	1.1786	0.0184
35	1.1967	0.0181
36	1.2146	0.0179
37	1.2323	0.0177
38	1.2497	0.0174
39	1.2670	0.0172
40	1.2840	0.0170
41	1.3008	0.0168
42	1.3174	0.0166
43	1.3338	0.0164
44	1.3501	0.0163
45	1.3662	0.0161
46	1.3821	0.0159
47	1.3978	0.0157
48	1.4134	0.0156
49	1.4288	0.0154
50	1.4441	0.0153
51	1.4593	0.0151
52	1.4743	0.0150
53	1.4891	0.0149
54	1.5039	0.0147
55	1.5185	0.0146
56	1.5330	0.0145
57	1.5473	0.0144
58	1.5616	0.0142
59	1.5757	0.0141
60	1.5897	0.0140
61	1.6036	0.0139
62	1.6174	0.0138
63	1.6311	0.0137
64	1.6447	0.0136
65	1.6582	0.0135
66	1.6716	0.0134
67	1.6849	0.0133
68	1.6981	0.0132
69	1.7112	0.0131
70	1.7242	0.0130
71	1.7371	0.0129
72	1.7500	0.0128
73	1.7604	0.0105
74	1.7708	0.0104
75	1.7812	0.0103
76	1.7914	0.0102
77	1.8016	0.0102
78	1.8117	0.0101
79	1.8217	0.0100
80	1.8317	0.0100
81	1.8415	0.0099
82	1.8514	0.0098
83	1.8611	0.0097
84	1.8708	0.0097
85	1.8804	0.0096
86	1.8899	0.0095
87	1.8994	0.0095
88	1.9089	0.0094
89	1.9182	0.0094
90	1.9275	0.0093
91	1.9368	0.0092
92	1.9460	0.0092
93	1.9551	0.0091
94	1.9642	0.0091
95	1.9732	0.0090
96	1.9822	0.0090
97	1.9911	0.0089
98	1.9999	0.0089

99	2.0088	0.0088
100	2.0175	0.0088
101	2.0262	0.0087
102	2.0349	0.0087
103	2.0435	0.0086
104	2.0521	0.0086
105	2.0606	0.0085
106	2.0691	0.0085
107	2.0775	0.0084
108	2.0859	0.0084
109	2.0942	0.0083
110	2.1025	0.0083
111	2.1108	0.0083
112	2.1190	0.0082
113	2.1272	0.0082
114	2.1353	0.0081
115	2.1434	0.0081
116	2.1515	0.0081
117	2.1595	0.0080
118	2.1675	0.0080
119	2.1754	0.0079
120	2.1833	0.0079
121	2.1912	0.0079
122	2.1990	0.0078
123	2.2068	0.0078
124	2.2145	0.0078
125	2.2222	0.0077
126	2.2299	0.0077
127	2.2376	0.0076
128	2.2452	0.0076
129	2.2528	0.0076
130	2.2603	0.0075
131	2.2678	0.0075
132	2.2753	0.0075
133	2.2828	0.0074
134	2.2902	0.0074
135	2.2976	0.0074
136	2.3049	0.0074
137	2.3122	0.0073
138	2.3195	0.0073
139	2.3268	0.0073
140	2.3340	0.0072
141	2.3412	0.0072
142	2.3484	0.0072
143	2.3556	0.0071
144	2.3627	0.0071
145	2.3698	0.0071
146	2.3768	0.0071
147	2.3839	0.0070
148	2.3909	0.0070
149	2.3979	0.0070
150	2.4048	0.0070
151	2.4118	0.0069
152	2.4187	0.0069
153	2.4256	0.0069
154	2.4324	0.0069
155	2.4392	0.0068
156	2.4460	0.0068
157	2.4528	0.0068
158	2.4596	0.0068
159	2.4663	0.0067
160	2.4730	0.0067
161	2.4797	0.0067
162	2.4863	0.0067
163	2.4930	0.0066
164	2.4996	0.0066
165	2.5062	0.0066
166	2.5128	0.0066
167	2.5193	0.0065
168	2.5258	0.0065
169	2.5323	0.0065

170	2.5388	0.0065
171	2.5453	0.0065
172	2.5517	0.0064
173	2.5581	0.0064
174	2.5645	0.0064
175	2.5709	0.0064
176	2.5772	0.0064
177	2.5836	0.0063
178	2.5899	0.0063
179	2.5962	0.0063
180	2.6024	0.0063
181	2.6087	0.0063
182	2.6149	0.0062
183	2.6211	0.0062
184	2.6273	0.0062
185	2.6335	0.0062
186	2.6397	0.0062
187	2.6458	0.0061
188	2.6519	0.0061
189	2.6580	0.0061
190	2.6641	0.0061
191	2.6702	0.0061
192	2.6762	0.0060
193	2.6822	0.0060
194	2.6882	0.0060
195	2.6942	0.0060
196	2.7002	0.0060
197	2.7062	0.0060
198	2.7121	0.0059
199	2.7180	0.0059
200	2.7239	0.0059
201	2.7298	0.0059
202	2.7357	0.0059
203	2.7416	0.0059
204	2.7474	0.0058
205	2.7532	0.0058
206	2.7590	0.0058
207	2.7648	0.0058
208	2.7706	0.0058
209	2.7764	0.0058
210	2.7821	0.0057
211	2.7878	0.0057
212	2.7936	0.0057
213	2.7993	0.0057
214	2.8049	0.0057
215	2.8106	0.0057
216	2.8163	0.0057
217	2.8219	0.0056
218	2.8275	0.0056
219	2.8331	0.0056
220	2.8387	0.0056
221	2.8443	0.0056
222	2.8499	0.0056
223	2.8554	0.0056
224	2.8610	0.0055
225	2.8665	0.0055
226	2.8720	0.0055
227	2.8775	0.0055
228	2.8830	0.0055
229	2.8885	0.0055
230	2.8939	0.0055
231	2.8994	0.0054
232	2.9048	0.0054
233	2.9102	0.0054
234	2.9156	0.0054
235	2.9210	0.0054
236	2.9264	0.0054
237	2.9317	0.0054
238	2.9371	0.0054
239	2.9424	0.0053
240	2.9478	0.0053

241	2.9531	0.0053
242	2.9584	0.0053
243	2.9637	0.0053
244	2.9689	0.0053
245	2.9742	0.0053
246	2.9795	0.0053
247	2.9847	0.0052
248	2.9899	0.0052
249	2.9951	0.0052
250	3.0003	0.0052
251	3.0055	0.0052
252	3.0107	0.0052
253	3.0159	0.0052
254	3.0210	0.0052
255	3.0262	0.0051
256	3.0313	0.0051
257	3.0364	0.0051
258	3.0416	0.0051
259	3.0467	0.0051
260	3.0517	0.0051
261	3.0568	0.0051
262	3.0619	0.0051
263	3.0669	0.0051
264	3.0720	0.0050
265	3.0770	0.0050
266	3.0820	0.0050
267	3.0871	0.0050
268	3.0921	0.0050
269	3.0971	0.0050
270	3.1020	0.0050
271	3.1070	0.0050
272	3.1120	0.0050
273	3.1169	0.0050
274	3.1219	0.0049
275	3.1268	0.0049
276	3.1317	0.0049
277	3.1366	0.0049
278	3.1415	0.0049
279	3.1464	0.0049
280	3.1513	0.0049
281	3.1562	0.0049
282	3.1610	0.0049
283	3.1659	0.0048
284	3.1707	0.0048
285	3.1755	0.0048
286	3.1804	0.0048
287	3.1852	0.0048
288	3.1900	0.0048

Unit Period (number)	Unit Rainfall (In)	Unit Soil-Loss (In)	Effective Rainfall (In)
1	0.0048	0.0008	0.0040
2	0.0048	0.0008	0.0040
3	0.0048	0.0008	0.0041
4	0.0048	0.0008	0.0041
5	0.0049	0.0008	0.0041
6	0.0049	0.0008	0.0041
7	0.0049	0.0008	0.0041
8	0.0049	0.0008	0.0041
9	0.0049	0.0008	0.0041
10	0.0049	0.0008	0.0041
11	0.0050	0.0008	0.0042
12	0.0050	0.0008	0.0042
13	0.0050	0.0008	0.0042
14	0.0050	0.0008	0.0042
15	0.0050	0.0008	0.0042
16	0.0050	0.0008	0.0042
17	0.0050	0.0008	0.0042
18	0.0051	0.0008	0.0042

19	0.0051	0.0008	0.0043
20	0.0051	0.0008	0.0043
21	0.0051	0.0008	0.0043
22	0.0051	0.0008	0.0043
23	0.0051	0.0008	0.0043
24	0.0052	0.0008	0.0043
25	0.0052	0.0008	0.0044
26	0.0052	0.0008	0.0044
27	0.0052	0.0008	0.0044
28	0.0052	0.0008	0.0044
29	0.0053	0.0008	0.0044
30	0.0053	0.0008	0.0044
31	0.0053	0.0008	0.0044
32	0.0053	0.0008	0.0045
33	0.0053	0.0009	0.0045
34	0.0053	0.0009	0.0045
35	0.0054	0.0009	0.0045
36	0.0054	0.0009	0.0045
37	0.0054	0.0009	0.0045
38	0.0054	0.0009	0.0045
39	0.0054	0.0009	0.0046
40	0.0055	0.0009	0.0046
41	0.0055	0.0009	0.0046
42	0.0055	0.0009	0.0046
43	0.0055	0.0009	0.0046
44	0.0055	0.0009	0.0047
45	0.0056	0.0009	0.0047
46	0.0056	0.0009	0.0047
47	0.0056	0.0009	0.0047
48	0.0056	0.0009	0.0047
49	0.0057	0.0009	0.0047
50	0.0057	0.0009	0.0048
51	0.0057	0.0009	0.0048
52	0.0057	0.0009	0.0048
53	0.0057	0.0009	0.0048
54	0.0058	0.0009	0.0048
55	0.0058	0.0009	0.0049
56	0.0058	0.0009	0.0049
57	0.0058	0.0009	0.0049
58	0.0059	0.0009	0.0049
59	0.0059	0.0009	0.0049
60	0.0059	0.0009	0.0050
61	0.0059	0.0010	0.0050
62	0.0060	0.0010	0.0050
63	0.0060	0.0010	0.0050
64	0.0060	0.0010	0.0050
65	0.0060	0.0010	0.0051
66	0.0061	0.0010	0.0051
67	0.0061	0.0010	0.0051
68	0.0061	0.0010	0.0051
69	0.0062	0.0010	0.0052
70	0.0062	0.0010	0.0052
71	0.0062	0.0010	0.0052
72	0.0062	0.0010	0.0052
73	0.0063	0.0010	0.0053
74	0.0063	0.0010	0.0053
75	0.0063	0.0010	0.0053
76	0.0064	0.0010	0.0053
77	0.0064	0.0010	0.0054
78	0.0064	0.0010	0.0054
79	0.0065	0.0010	0.0054
80	0.0065	0.0010	0.0054
81	0.0065	0.0010	0.0055
82	0.0065	0.0010	0.0055
83	0.0066	0.0011	0.0055
84	0.0066	0.0011	0.0056
85	0.0067	0.0011	0.0056
86	0.0067	0.0011	0.0056
87	0.0067	0.0011	0.0057
88	0.0068	0.0011	0.0057
89	0.0068	0.0011	0.0057

90	0.0068	0.0011	0.0057
91	0.0069	0.0011	0.0058
92	0.0069	0.0011	0.0058
93	0.0070	0.0011	0.0058
94	0.0070	0.0011	0.0059
95	0.0070	0.0011	0.0059
96	0.0071	0.0011	0.0059
97	0.0071	0.0011	0.0060
98	0.0071	0.0011	0.0060
99	0.0072	0.0012	0.0061
100	0.0072	0.0012	0.0061
101	0.0073	0.0012	0.0061
102	0.0073	0.0012	0.0062
103	0.0074	0.0012	0.0062
104	0.0074	0.0012	0.0062
105	0.0075	0.0012	0.0063
106	0.0075	0.0012	0.0063
107	0.0076	0.0012	0.0064
108	0.0076	0.0012	0.0064
109	0.0077	0.0012	0.0065
110	0.0077	0.0012	0.0065
111	0.0078	0.0012	0.0065
112	0.0078	0.0013	0.0066
113	0.0079	0.0013	0.0066
114	0.0079	0.0013	0.0067
115	0.0080	0.0013	0.0067
116	0.0081	0.0013	0.0068
117	0.0081	0.0013	0.0068
118	0.0082	0.0013	0.0069
119	0.0083	0.0013	0.0069
120	0.0083	0.0013	0.0070
121	0.0084	0.0013	0.0070
122	0.0084	0.0014	0.0071
123	0.0085	0.0014	0.0072
124	0.0086	0.0014	0.0072
125	0.0087	0.0014	0.0073
126	0.0087	0.0014	0.0073
127	0.0088	0.0014	0.0074
128	0.0089	0.0014	0.0074
129	0.0090	0.0014	0.0075
130	0.0090	0.0014	0.0076
131	0.0091	0.0015	0.0077
132	0.0092	0.0015	0.0077
133	0.0093	0.0015	0.0078
134	0.0094	0.0015	0.0079
135	0.0095	0.0015	0.0080
136	0.0095	0.0015	0.0080
137	0.0097	0.0016	0.0081
138	0.0097	0.0016	0.0082
139	0.0099	0.0016	0.0083
140	0.0100	0.0016	0.0084
141	0.0101	0.0016	0.0085
142	0.0102	0.0016	0.0085
143	0.0103	0.0017	0.0087
144	0.0104	0.0017	0.0087
145	0.0128	0.0021	0.0108
146	0.0129	0.0021	0.0109
147	0.0131	0.0021	0.0110
148	0.0132	0.0021	0.0111
149	0.0134	0.0021	0.0112
150	0.0135	0.0022	0.0113
151	0.0137	0.0022	0.0115
152	0.0138	0.0022	0.0116
153	0.0140	0.0022	0.0118
154	0.0141	0.0023	0.0119
155	0.0144	0.0023	0.0121
156	0.0145	0.0023	0.0122
157	0.0147	0.0024	0.0124
158	0.0149	0.0024	0.0125
159	0.0151	0.0024	0.0127
160	0.0153	0.0024	0.0128

161	0.0156	0.0025	0.0131
162	0.0157	0.0025	0.0132
163	0.0161	0.0026	0.0135
164	0.0163	0.0026	0.0136
165	0.0166	0.0027	0.0140
166	0.0168	0.0027	0.0141
167	0.0172	0.0028	0.0145
168	0.0174	0.0028	0.0146
169	0.0179	0.0029	0.0150
170	0.0181	0.0029	0.0152
171	0.0187	0.0030	0.0157
172	0.0189	0.0030	0.0159
173	0.0195	0.0031	0.0164
174	0.0199	0.0032	0.0167
175	0.0206	0.0033	0.0173
176	0.0209	0.0034	0.0176
177	0.0218	0.0035	0.0183
178	0.0222	0.0036	0.0187
179	0.0232	0.0037	0.0195
180	0.0238	0.0038	0.0200
181	0.0250	0.0040	0.0210
182	0.0257	0.0041	0.0216
183	0.0273	0.0044	0.0230
184	0.0283	0.0045	0.0238
185	0.0233	0.0037	0.0196
186	0.0246	0.0039	0.0207
187	0.0279	0.0045	0.0234
188	0.0301	0.0048	0.0253
189	0.0363	0.0058	0.0305
190	0.0410	0.0065	0.0344
191	0.0585	0.0065	0.0520
192	0.0805	0.0065	0.0740
193	0.2520	0.0065	0.2454
194	0.0477	0.0065	0.0411
195	0.0328	0.0053	0.0276
196	0.0261	0.0042	0.0219
197	0.0293	0.0047	0.0246
198	0.0265	0.0042	0.0222
199	0.0244	0.0039	0.0205
200	0.0227	0.0036	0.0191
201	0.0213	0.0034	0.0179
202	0.0202	0.0032	0.0170
203	0.0192	0.0031	0.0162
204	0.0184	0.0029	0.0155
205	0.0177	0.0028	0.0148
206	0.0170	0.0027	0.0143
207	0.0164	0.0026	0.0138
208	0.0159	0.0025	0.0134
209	0.0154	0.0025	0.0130
210	0.0150	0.0024	0.0126
211	0.0146	0.0023	0.0123
212	0.0142	0.0023	0.0120
213	0.0139	0.0022	0.0117
214	0.0136	0.0022	0.0114
215	0.0133	0.0021	0.0112
216	0.0130	0.0021	0.0109
217	0.0105	0.0017	0.0088
218	0.0102	0.0016	0.0086
219	0.0100	0.0016	0.0084
220	0.0098	0.0016	0.0082
221	0.0096	0.0015	0.0081
222	0.0094	0.0015	0.0079
223	0.0092	0.0015	0.0078
224	0.0091	0.0015	0.0076
225	0.0089	0.0014	0.0075
226	0.0088	0.0014	0.0074
227	0.0086	0.0014	0.0072
228	0.0085	0.0014	0.0071
229	0.0083	0.0013	0.0070
230	0.0082	0.0013	0.0069
231	0.0081	0.0013	0.0068

232	0.0080	0.0013	0.0067
233	0.0079	0.0013	0.0066
234	0.0078	0.0012	0.0065
235	0.0076	0.0012	0.0064
236	0.0075	0.0012	0.0063
237	0.0074	0.0012	0.0063
238	0.0074	0.0012	0.0062
239	0.0073	0.0012	0.0061
240	0.0072	0.0012	0.0060
241	0.0071	0.0011	0.0060
242	0.0070	0.0011	0.0059
243	0.0069	0.0011	0.0058
244	0.0069	0.0011	0.0058
245	0.0068	0.0011	0.0057
246	0.0067	0.0011	0.0056
247	0.0066	0.0011	0.0056
248	0.0066	0.0011	0.0055
249	0.0065	0.0010	0.0055
250	0.0064	0.0010	0.0054
251	0.0064	0.0010	0.0054
252	0.0063	0.0010	0.0053
253	0.0063	0.0010	0.0053
254	0.0062	0.0010	0.0052
255	0.0061	0.0010	0.0052
256	0.0061	0.0010	0.0051
257	0.0060	0.0010	0.0051
258	0.0060	0.0010	0.0050
259	0.0059	0.0009	0.0050
260	0.0059	0.0009	0.0049
261	0.0058	0.0009	0.0049
262	0.0058	0.0009	0.0049
263	0.0057	0.0009	0.0048
264	0.0057	0.0009	0.0048
265	0.0056	0.0009	0.0047
266	0.0056	0.0009	0.0047
267	0.0056	0.0009	0.0047
268	0.0055	0.0009	0.0046
269	0.0055	0.0009	0.0046
270	0.0054	0.0009	0.0046
271	0.0054	0.0009	0.0045
272	0.0054	0.0009	0.0045
273	0.0053	0.0009	0.0045
274	0.0053	0.0008	0.0044
275	0.0052	0.0008	0.0044
276	0.0052	0.0008	0.0044
277	0.0052	0.0008	0.0043
278	0.0051	0.0008	0.0043
279	0.0051	0.0008	0.0043
280	0.0051	0.0008	0.0043
281	0.0050	0.0008	0.0042
282	0.0050	0.0008	0.0042
283	0.0050	0.0008	0.0042
284	0.0049	0.0008	0.0041
285	0.0049	0.0008	0.0041
286	0.0049	0.0008	0.0041
287	0.0048	0.0008	0.0041
288	0.0048	0.0008	0.0040

Total soil rain loss = 0.47(In)
Total effective rainfall = 2.72(In)
Peak flow rate in flood hydrograph = 12.09(CFS)

++


24 - H O U R S T O R M
R u n o f f H y d r o g r a p h

Hydrograph in 5 Minute intervals ((CFS))

Time(h+m) Volume Ac.Ft Q(CFS) 0 5.0 10.0 15.0 20.0

0+ 5	0.0001	0.02	Q				
0+10	0.0009	0.12	Q				
0+15	0.0028	0.27	Q				
0+20	0.0052	0.35	Q				
0+25	0.0077	0.37	Q				
0+30	0.0103	0.38	Q				
0+35	0.0130	0.38	Q				
0+40	0.0157	0.39	Q				
0+45	0.0183	0.39	Q				
0+50	0.0210	0.39	Q				
0+55	0.0237	0.39	Q				
1+ 0	0.0264	0.39	Q				
1+ 5	0.0291	0.39	Q				
1+10	0.0318	0.39	Q				
1+15	0.0345	0.39	Q				
1+20	0.0372	0.40	Q				
1+25	0.0399	0.40	Q				
1+30	0.0427	0.40	Q				
1+35	0.0454	0.40	QV				
1+40	0.0482	0.40	QV				
1+45	0.0510	0.40	QV				
1+50	0.0537	0.40	QV				
1+55	0.0565	0.40	QV				
2+ 0	0.0593	0.41	QV				
2+ 5	0.0621	0.41	QV				
2+10	0.0649	0.41	QV				
2+15	0.0678	0.41	QV				
2+20	0.0706	0.41	QV				
2+25	0.0734	0.41	QV				
2+30	0.0763	0.41	QV				
2+35	0.0792	0.42	QV				
2+40	0.0820	0.42	QV				
2+45	0.0849	0.42	QV				
2+50	0.0878	0.42	QV				
2+55	0.0907	0.42	Q V				
3+ 0	0.0936	0.42	Q V				
3+ 5	0.0965	0.42	Q V				
3+10	0.0995	0.43	Q V				
3+15	0.1024	0.43	Q V				
3+20	0.1054	0.43	Q V				
3+25	0.1084	0.43	Q V				
3+30	0.1113	0.43	Q V				
3+35	0.1143	0.43	Q V				
3+40	0.1173	0.44	Q V				
3+45	0.1203	0.44	Q V				
3+50	0.1234	0.44	Q V				
3+55	0.1264	0.44	Q V				
4+ 0	0.1294	0.44	Q V				
4+ 5	0.1325	0.44	Q V				
4+10	0.1356	0.45	Q V				
4+15	0.1386	0.45	Q V				
4+20	0.1417	0.45	Q V				
4+25	0.1448	0.45	Q V				
4+30	0.1480	0.45	Q V				
4+35	0.1511	0.45	Q V				
4+40	0.1542	0.46	Q V				
4+45	0.1574	0.46	Q V				
4+50	0.1606	0.46	Q V				
4+55	0.1638	0.46	Q V				
5+ 0	0.1669	0.46	Q V				
5+ 5	0.1702	0.47	Q V				
5+10	0.1734	0.47	Q V				
5+15	0.1766	0.47	Q V				
5+20	0.1799	0.47	Q V				
5+25	0.1831	0.47	Q V				
5+30	0.1864	0.48	Q V				
5+35	0.1897	0.48	Q V				
5+40	0.1930	0.48	Q V				
5+45	0.1964	0.48	Q V				
5+50	0.1997	0.48	Q V				

5+55	0.2030	0.49	Q V	|	|	|	|
6+ 0	0.2064	0.49	Q V	|	|	|	|
6+ 5	0.2098	0.49	Q V	|	|	|	|
6+10	0.2132	0.49	Q V	|	|	|	|
6+15	0.2166	0.50	Q V	|	|	|	|
6+20	0.2201	0.50	Q V	|	|	|	|
6+25	0.2235	0.50	|Q V	|	|	|	|
6+30	0.2270	0.50	|Q V	|	|	|	|
6+35	0.2305	0.51	|Q V	|	|	|	|
6+40	0.2340	0.51	|Q V	|	|	|	|
6+45	0.2375	0.51	|Q V	|	|	|	|
6+50	0.2410	0.51	|Q V	|	|	|	|
6+55	0.2446	0.52	|Q V	|	|	|	|
7+ 0	0.2481	0.52	|Q V	|	|	|	|
7+ 5	0.2517	0.52	|Q V	|	|	|	|
7+10	0.2553	0.52	|Q V	|	|	|	|
7+15	0.2590	0.53	|Q V	|	|	|	|
7+20	0.2626	0.53	|Q V	|	|	|	|
7+25	0.2663	0.53	|Q V	|	|	|	|
7+30	0.2700	0.54	|Q V	|	|	|	|
7+35	0.2737	0.54	|Q V	|	|	|	|
7+40	0.2774	0.54	|Q V	|	|	|	|
7+45	0.2812	0.54	|Q V	|	|	|	|
7+50	0.2849	0.55	|Q V	|	|	|	|
7+55	0.2887	0.55	|Q V	|	|	|	|
8+ 0	0.2925	0.55	|Q V	|	|	|	|
8+ 5	0.2964	0.56	|Q V	|	|	|	|
8+10	0.3002	0.56	|Q V	|	|	|	|
8+15	0.3041	0.56	|Q V	|	|	|	|
8+20	0.3080	0.57	|Q V	|	|	|	|
8+25	0.3119	0.57	|Q V	|	|	|	|
8+30	0.3159	0.57	|Q V	|	|	|	|
8+35	0.3199	0.58	|Q V	|	|	|	|
8+40	0.3239	0.58	|Q V	|	|	|	|
8+45	0.3279	0.58	|Q V	|	|	|	|
8+50	0.3319	0.59	|Q V	|	|	|	|
8+55	0.3360	0.59	|Q V	|	|	|	|
9+ 0	0.3401	0.60	|Q V	|	|	|	|
9+ 5	0.3442	0.60	|Q V	|	|	|	|
9+10	0.3484	0.60	|Q V	|	|	|	|
9+15	0.3526	0.61	|Q V	|	|	|	|
9+20	0.3568	0.61	|Q V	|	|	|	|
9+25	0.3610	0.62	|Q V	|	|	|	|
9+30	0.3653	0.62	|Q V	|	|	|	|
9+35	0.3696	0.62	|Q V	|	|	|	|
9+40	0.3739	0.63	|Q V	|	|	|	|
9+45	0.3783	0.63	|Q V	|	|	|	|
9+50	0.3827	0.64	|Q V	|	|	|	|
9+55	0.3871	0.64	|Q V	|	|	|	|
10+ 0	0.3916	0.65	|Q V	|	|	|	|
10+ 5	0.3961	0.65	|Q V	|	|	|	|
10+10	0.4006	0.66	|Q V|	|	|	|	|
10+15	0.4052	0.66	|Q V|	|	|	|	|
10+20	0.4098	0.67	|Q V|	|	|	|	|
10+25	0.4144	0.67	|Q V|	|	|	|	|
10+30	0.4191	0.68	|Q V|	|	|	|	|
10+35	0.4238	0.69	|Q V|	|	|	|	|
10+40	0.4286	0.69	|Q V|	|	|	|	|
10+45	0.4334	0.70	|Q V|	|	|	|	|
10+50	0.4382	0.70	|Q V|	|	|	|	|
10+55	0.4431	0.71	|Q V	|	|	|	|
11+ 0	0.4480	0.72	|Q V	|	|	|	|
11+ 5	0.4530	0.72	|Q V	|	|	|	|
11+10	0.4580	0.73	|Q V	|	|	|	|
11+15	0.4631	0.74	|Q V	|	|	|	|
11+20	0.4682	0.74	|Q V	|	|	|	|
11+25	0.4734	0.75	|Q V	|	|	|	|
11+30	0.4786	0.76	|Q V	|	|	|	|
11+35	0.4839	0.77	|Q V	|	|	|	|
11+40	0.4892	0.77	|Q |V	|	|	|	|
11+45	0.4946	0.78	|Q |V	|	|	|	|



17+45	1.4683	1.16	| Q	|	|	| V	|
17+50	1.4761	1.13	| Q	|	|	| V	|
17+55	1.4837	1.10	| Q	|	|	| V	|
18+ 0	1.4911	1.08	| Q	|	|	| V	|
18+ 5	1.4983	1.05	| Q	|	|	| V	|
18+10	1.5051	0.98	|Q	|	|	| V	|
18+15	1.5112	0.89	|Q	|	|	| V	|
18+20	1.5169	0.83	|Q	|	|	| V	|
18+25	1.5224	0.80	|Q	|	|	| V	|
18+30	1.5278	0.78	|Q	|	|	| V	|
18+35	1.5331	0.76	|Q	|	|	| V	|
18+40	1.5382	0.75	|Q	|	|	| V	|
18+45	1.5433	0.73	|Q	|	|	| V	|
18+50	1.5482	0.72	|Q	|	|	| V	|
18+55	1.5531	0.71	|Q	|	|	| V	|
19+ 0	1.5579	0.70	|Q	|	|	| V	|
19+ 5	1.5626	0.68	|Q	|	|	| V	|
19+10	1.5672	0.67	|Q	|	|	| V	|
19+15	1.5718	0.66	|Q	|	|	| V	|
19+20	1.5763	0.65	|Q	|	|	| V	|
19+25	1.5807	0.64	|Q	|	|	| V	|
19+30	1.5850	0.63	|Q	|	|	| V	|
19+35	1.5893	0.62	|Q	|	|	| V	|
19+40	1.5936	0.61	|Q	|	|	| V	|
19+45	1.5978	0.61	|Q	|	|	| V	|
19+50	1.6019	0.60	|Q	|	|	| V	|
19+55	1.6059	0.59	|Q	|	|	| V	|
20+ 0	1.6100	0.58	|Q	|	|	| V	|
20+ 5	1.6139	0.58	|Q	|	|	| V	|
20+10	1.6179	0.57	|Q	|	|	| V	|
20+15	1.6217	0.56	|Q	|	|	| V	|
20+20	1.6256	0.56	|Q	|	|	| V	|
20+25	1.6293	0.55	|Q	|	|	| V	|
20+30	1.6331	0.54	|Q	|	|	| V	|
20+35	1.6368	0.54	|Q	|	|	| V	|
20+40	1.6404	0.53	|Q	|	|	| V	|
20+45	1.6441	0.53	|Q	|	|	| V	|
20+50	1.6477	0.52	|Q	|	|	| V	|
20+55	1.6512	0.52	|Q	|	|	| V	|
21+ 0	1.6547	0.51	|Q	|	|	| V	|
21+ 5	1.6582	0.51	|Q	|	|	| V	|
21+10	1.6616	0.50	|Q	|	|	| V	|
21+15	1.6651	0.50	Q	|	|	| V	|
21+20	1.6684	0.49	Q	|	|	| V	|
21+25	1.6718	0.49	Q	|	|	| V	|
21+30	1.6751	0.48	Q	|	|	| V	|
21+35	1.6784	0.48	Q	|	|	| V	|
21+40	1.6817	0.47	Q	|	|	| V	|
21+45	1.6849	0.47	Q	|	|	| V	|
21+50	1.6881	0.47	Q	|	|	| V	|
21+55	1.6913	0.46	Q	|	|	| V	|
22+ 0	1.6944	0.46	Q	|	|	| V	|
22+ 5	1.6976	0.45	Q	|	|	| V	|
22+10	1.7007	0.45	Q	|	|	| V	|
22+15	1.7037	0.45	Q	|	|	| V	|
22+20	1.7068	0.44	Q	|	|	| V	|
22+25	1.7098	0.44	Q	|	|	| V	|
22+30	1.7128	0.44	Q	|	|	| V	|
22+35	1.7158	0.43	Q	|	|	| V	|
22+40	1.7188	0.43	Q	|	|	| V	|
22+45	1.7217	0.43	Q	|	|	| V	|
22+50	1.7247	0.42	Q	|	|	| V	|
22+55	1.7276	0.42	Q	|	|	| V	|
23+ 0	1.7304	0.42	Q	|	|	| V	|
23+ 5	1.7333	0.42	Q	|	|	| V	|
23+10	1.7361	0.41	Q	|	|	| V	|
23+15	1.7390	0.41	Q	|	|	| V	|
23+20	1.7418	0.41	Q	|	|	| V	|
23+25	1.7445	0.40	Q	|	|	| V	|
23+30	1.7473	0.40	Q	|	|	| V	|
23+35	1.7501	0.40	Q	|	|	| V	|

```
   23+40       1.7528      0.40  Q         |         |         |        V|
   23+45       1.7555      0.39  Q         |         |         |        V|
   23+50       1.7582      0.39  Q         |         |         |        V|
   23+55       1.7609      0.39  Q         |         |         |        V|
   24+ 0       1.7635      0.39  Q         |         |         |        V|
   24+ 5       1.7661      0.37  Q         |         |         |        V|
   24+10       1.7679      0.26  Q         |         |         |        V|
   24+15       1.7687      0.11  Q         |         |         |        V|
   24+20       1.7689      0.04  Q         |         |         |        V|
   24+25       1.7690      0.01  Q         |         |         |        V|
   24+30       1.7690      0.00  Q         |         |         |         V
-------------------------------------------------------------------------
```

Flood Routing Analysis
Detention Chamber Routing
(Contech CMP-2)

Detention Chamber Volume Table (348'-pipe Length, Total 4 Pipes, 5'Dia. Each)

(Refer to the Incremental Volume Spreadsheet)

Total Depth	Elevation	Volume (cf)	Volume (ac-ft):4 Pipes	Det Vol.	Outflow (cfs)-100yr Storm
0.0	930.0	0	0.00		0.00
0.5	930.5	2,065	0.05		0.00
Detention			Inf. Vol. 0.10 ac-ft		
1.5	931.5	7,502	0.17	0.12	0.50
3.0	933.0	19,239	0.44	0.39	1.50
4.5	934.5	31,543	0.72	0.68	4.30
6.0	936.0	41,268	0.95	0.90	8.00
6.7	936.7	44,021	1.01	0.96	8.70

Det Vol (Total) 0.96 AC-FT

DETENTION VOLUME IN CHAMBER SYSTEM CMP-2: 0.96 AC-FT = 41,818 CF

MAX. MITIGATED OUTFLOW FROM DETENTION CHAMBER: 8.3 CFS = 29,880 CF/HR (8.3*3600)

TIME TO EMPTY THE DETNTION WATER FROM DETENTION CHAMBER: 1.40 HRS (41,818 / 29,880)

Date: 6/21/2023
Project Name: Detention Chamber System-1 - 32851 (6-21-2023 21-23-50)

City / County:
State:

Designed By:
Company:
Telephone:

CMP: Underground Detention System Storage Volume Estimation

=Adjustable Input Cells

Contech Engineered Solutions, LLC is pleased to offer the following estimate of storage volume for the above named project. The results are submitted as an estimate only, without liability on the part of Contech Engineered Solutions, LLC for accuracy or suitability to any particular applicaton and are subject to verification of the Engineer of Record. This tool is only applicable for rectangular shaped systems.

Summary of Inputs

System Information		Backfill Information		Pipe & Analysis Information	
Out-to-out length (ft):	348.0	Backfill Porosity (%):	40%	System Diameter (in):	60
Out-to-out width (ft):	27.5	Depth Above Pipe (in):	12.0	Pipe Spacing (in):	30
Number of Manifolds (ea):	1.0	Depth Below Pipe (in):	9.0	Incremental Analysis (in):	2
Number of Barrels (ea):	4.0	Width At Ends (ft):	1.0	System Invert (Elevation):	0
		Width At Sides (ft):	1.0		

Storage Volume Estimation

System		Pipe		Stone		Total System		Miscellaneous	
Depth (ft)	Elevation (ft)	Incremental Storage (cf)	Cumulative Storage (cf)	Incremental Storage (cf)	Cumulative Storage (cf)	Incremental Storage (cf)	Cumulative Storage (cf)	Percent Open Storage (%)	Ave. Surface Area (sf)
0.00	0.00	0.0	0.0	0.0	0.0	0.0	0.0	0.0%	4,130.0
0.17	0.16	0.0	0.0	688.3	688.3	688.3	688.3	0.0%	4,130.0
0.33	0.33	0.0	0.0	688.3	1,376.7	688.3	1,376.7	0.0%	4,130.0
0.50	0.50	0.0	0.0	688.3	2,065.0	688.3	2,065.0	0.0%	4,130.0
0.67	0.66	0.0	0.0	688.3	2,753.3	688.3	2,753.3	0.0%	4,130.0
0.83	0.83	0.0	0.0	688.3	3,441.7	688.3	3,441.7	0.0%	4,130.0
1.00	1.00	281.0	281.0	575.9	4,017.6	857.0	4,298.6	6.5%	5,637.3
1.17	1.16	505.7	786.7	486.1	4,503.6	991.8	5,290.4	14.9%	6,224.6
1.33	1.33	643.4	1,430.1	431.0	4,934.6	1,074.4	6,364.7	22.5%	6,649.1
1.50	1.50	748.0	2,178.1	389.1	5,323.8	1,137.1	7,501.9	29.0%	6,984.4
1.67	1.66	832.3	3,010.4	355.4	5,679.2	1,187.7	8,689.6	34.6%	7,259.4
1.83	1.83	902.1	3,912.4	327.5	6,006.7	1,229.6	9,919.1	39.4%	7,488.8
2.00	2.00	960.5	4,873.0	304.1	6,310.8	1,264.7	11,183.8	43.6%	7,681.5
2.17	2.16	1,009.7	5,882.6	284.5	6,595.3	1,294.1	12,477.9	47.1%	7,843.3
2.33	2.33	1,050.8	6,933.4	268.0	6,863.3	1,318.8	13,796.7	50.3%	7,978.0
2.50	2.50	1,084.8	8,018.2	254.4	7,117.7	1,339.2	15,135.9	53.0%	8,088.4
2.67	2.66	1,112.3	9,130.5	243.4	7,361.2	1,355.7	16,491.6	55.4%	8,176.5
2.83	2.83	1,133.8	10,264.3	234.8	7,596.0	1,368.6	17,860.2	57.5%	8,243.7
3.00	3.00	1,149.7	11,414.0	228.4	7,824.4	1,378.2	19,238.4	59.3%	8,291.0

These results are submitted to you as a guideline only, without liability on the part of CONTECH Engineered Solutions, LLC for accuracy or suitability to any particular application, and are subject to your verification.

3.17	3.16	1,160.2	12,574.2	224.3	8,048.7	1,384.4	20,622.8	61.0%	8,319.2
3.33	3.33	1,165.4	13,739.6	222.2	8,270.8	1,387.6	22,010.4	62.4%	8,328.5
3.50	3.50	1,165.4	14,904.9	222.2	8,493.0	1,387.6	23,398.0	63.7%	8,319.2
3.67	3.66	1,160.2	16,065.1	224.3	8,717.3	1,384.4	24,782.4	64.8%	8,291.0
3.83	3.83	1,149.7	17,214.8	228.4	8,945.7	1,378.2	26,160.6	65.8%	8,243.7
4.00	4.00	1,133.8	18,348.7	234.8	9,180.5	1,368.6	27,529.2	66.7%	8,176.5
4.17	4.16	1,112.3	19,460.9	243.4	9,424.0	1,355.7	28,884.9	67.4%	8,088.4
4.33	4.33	1,084.8	20,545.7	254.4	9,678.4	1,339.2	30,224.1	68.0%	7,978.0
4.50	4.50	1,050.8	21,596.5	268.0	9,946.4	1,318.8	31,542.9	68.5%	7,843.3
4.67	4.66	1,009.7	22,606.1	284.5	10,230.9	1,294.1	32,837.0	68.8%	7,681.5
4.83	4.83	960.5	23,566.7	304.1	10,535.0	1,264.7	34,101.7	69.1%	7,488.8
5.00	5.00	902.1	24,468.8	327.5	10,862.5	1,229.6	35,331.3	69.3%	7,259.4
5.17	5.16	832.3	25,301.0	355.4	11,217.9	1,187.7	36,519.0	69.3%	6,984.4
5.33	5.33	748.0	26,049.0	389.1	11,607.1	1,137.1	37,656.1	69.2%	6,649.1
5.50	5.50	643.4	26,692.4	431.0	12,038.0	1,074.4	38,730.4	68.9%	6,224.6
5.67	5.66	505.7	27,198.1	486.1	12,524.1	991.8	39,722.2	68.5%	5,637.3
5.83	5.83	281.0	27,479.1	575.9	13,100.0	857.0	40,579.1	67.7%	4,130.0
6.00	6.00	0.0	27,479.1	688.3	13,788.4	688.3	41,267.5	66.6%	4,130.0
6.17	6.16	0.0	27,479.1	688.3	14,476.7	688.3	41,955.8	65.5%	4,130.0
6.33	6.33	0.0	27,479.1	688.3	15,165.0	688.3	42,644.1	64.4%	4,130.0
6.50	6.50	0.0	27,479.1	688.3	15,853.4	688.3	43,332.5	63.4%	4,130.0
6.67	6.66	0.0	27,479.1	688.3	16,541.7	688.3	44,020.8	62.4%	4,130.0

These results are submitted to you as a guideline only, without liability on the part of CONTECH Engineered Solutions, LLC for accuracy or suitability to any particular application, and are subject to your verification.


PROJECT SUMMARY

CALCULATION DETAILS
- LOADING = HS20/HS25
- APPROX. LINEAR FOOTAGE = 1,400 LF

STORAGE SUMMARY
- STORAGE VOLUME REQUIRED = N/A
- PIPE STORAGE VOLUME = 27,479 CF
- BACKFILL STORAGE VOLUME = 16,886 CF
- TOTAL STORAGE PROVIDED = 44,365 CF

PIPE DETAILS
- DIAMETER = 60"
- CORRUGATION = 5x1
- GAGE = 16
- COATING = ALT2
- WALL TYPE = PERFORATED
- BARREL SPACING = 30"

BACKFILL DETAILS
- WIDTH AT ENDS = 12"
- ABOVE PIPE = 12"
- WIDTH AT SIDES = 12"
- BELOW PIPE = 9"



NOTES

- ALL RISER AND STUB DIMENSIONS ARE TO CENTERLINE. ALL ELEVATIONS, DIMENSIONS, AND LOCATIONS OF RISERS AND INLETS, SHALL BE VERIFIED BY THE ENGINEER OF RECORD PRIOR TO RELEASING FOR FABRICATION.
- ALL FITTINGS AND REINFORCEMENT COMPLY WITH ASTM A998.
- ALL RISERS AND STUBS ARE $2\frac{2}{3}$" x $\frac{1}{2}$" CORRUGATION AND 16 GAGE UNLESS OTHERWISE NOTED.
- RISERS TO BE FIELD TRIMMED TO GRADE.
- QUANTITY OF PIPE SHOWN DOES NOT PROVIDE EXTRA PIPE FOR CONNECTING THE SYSTEM TO EXISTING PIPE OR DRAINAGE STRUCTURES. OUR SYSTEM AS DETAILED PROVIDES NOMINAL INLET AND/OR OUTLET PIPE STUB FOR CONNECTION TO EXISTING DRAINAGE FACILITIES. IF ADDITIONAL PIPE IS NEEDED IT IS THE RESPONSIBILITY OF THE CONTRACTOR.
- BAND TYPE TO BE DETERMINED UPON FINAL DESIGN.
- THE PROJECT SUMMARY IS REFLECTIVE OF THE DYODS DESIGN, QUANTITIES ARE APPROX. AND SHOULD BE VERIFIED UPON FINAL DESIGN AND APPROVAL. FOR EXAMPLE, TOTAL EXCAVATION DOES NOT CONSIDER ALL VARIABLES SUCH AS SHORING AND ONLY ACCOUNTS FOR MATERIAL WITHIN THE ESTIMATED EXCAVATION FOOTPRINT.
- THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES AND DO NOT REFLECT ANY LOCAL PREFERENCES OR REGULATIONS. PLEASE CONTACT YOUR LOCAL CONTECH REP FOR MODIFICATIONS.

ASSEMBLY
SCALE: 1" = 40'

The design and information shown on this drawing is provided as a service to the project owner, engineer and contractor by Contech Engineered Solutions LLC ("Contech"). Neither this drawing, nor any part thereof, may be used, reproduced or modified in any manner without the prior written consent of Contech. Failure to comply is done at the user's own risk and Contech expressly disclaims any liability or responsibility for such use.

If discrepancies between the supplied information upon which the drawing is based and actual field conditions are encountered as site work progresses, these discrepancies must be reported to Contech immediately for re-evaluation of the design. Contech accepts no liability for designs based on missing, incomplete or inaccurate information supplied by others.

DATE	REVISION DESCRIPTION	BY

CONTECH ENGINEERED SOLUTIONS LLC
www.ContechES.com
9025 Centre Pointe Dr., Suite 400, West Chester, OH 45069
800-338-1122 513-645-7000 513-645-7993 FAX

CONTECH CMP DETENTION SYSTEMS
CONTECH DYODS DRAWING


DYO32851 Conco, Fontana
Detention Chamber System-1
Fontana, CA
DETENTION SYSTEM

PROJECT No.:	SEQ. No.:	DATE:
22258	32851	6/21/2023
DESIGNED: DYO	DRAWN: DYO	
CHECKED: DYO	APPROVED: DYO	
SHEET NO.: 1		

C:\EXPORTS\TEMPLATES\CMP_V8.DWG 10/18/2019 10:02 AM

18" RCP

Q (cfs)	Elev (ft)
1	934.1
3	934.3
5	934.8
9	936.6
12	938.6



WSPG-18" Outflow Pipe from Detention Chamber

Input Data:

```
T1 18" OUTLET WSPG                                                          0
T2 CONCO
T3
SO       .000 927.000  1                          934.000
R     352.000 930.500  1      .013                                .000    .000 0
SH    352.000 930.500  1                          935.500
CD   1  4   1    .000   1.500     .000  .000  .000   .00
Q             1.000   .0
Q             3.000   .0
Q             5.000   .0
Q             9.000   .0
Q            12.000   .0
```

WSPG Output: 18" Outlet Pipe

FILE: CONC.WSW W S P G W - CIVILDESIGN Version 14.11 PAGE 1

Program Package Serial Number: 7323

WATER SURFACE PROFILE LISTING Date: 6-19-2023 Time: 5:12:11

18" OUTLET WSPG
CONCO

Station	Invert Elev	Depth (FT)	Water Elev	Q (CFS)	Vel (FPS)	Vel Head	Energy Grd.El.	Super Elev	Critical Depth	Flow Top Width	Height/ Dia.-FT	Base Wt or I.D.	ZL	No Wth Prs/Pip
L/Elem	Ch Slope					SF Ave	HF	SE Dpth	Froude N	Norm Dp	"N"	X-Fall	ZR	Type Ch
.000	927.000	7.000	934.000	1.00	.57	.00	934.00	.00	.37	.00	1.500	.000	.00	1 .0
352.000	.0099					.0001	.03	7.00	.00	.31	.013	.00	.00	PIPE
352.000	930.500	3.532	934.032	1.00	.57	.00	934.04	.00	.37	.00	1.500	.000	.00	1 .0

Program Package Serial Number: 7323

WATER SURFACE PROFILE LISTING Date: 6-19-2023 Time: 5:12:11

18" OUTLET WSPG
CONCO

Station / L/Elem	Invert Elev / Ch Slope	Depth (FT)	Water Elev	Q (CFS)	Vel (FPS) / Vel Head / SF Ave	Energy Grd.El. / HF	Super Elev / SE Dpth	Critical Depth / Froude N	Flow Top Width / Norm Dp	Height/ Dia.-FT / "N"	Base Wt or I.D. / X-Fall	ZL / ZR	No Wth Prs/Pip / Type Ch
.000	927.000	7.000	934.000	3.00	1.70 / .04 /	934.04 /	.00 /	.66 /	.00 /	1.500 /	.000 /	.00 /	1 / .0
352.000	.0099				/ .0008 /	.29 /	7.00 /	.00 /	.55 /	.013 /	.00 /	.00 /	PIPE
352.000	930.500	3.787	934.287	3.00	1.70 / .04 /	934.33 /	.00 /	.66 /	.00 /	1.500 /	.000 /	.00 /	1 / .0

Program Package Serial Number: 7323

WATER SURFACE PROFILE LISTING Date: 6-19-2023 Time: 5:12:11

18" OUTLET WSPG
CONCO

Station / L/Elem	Invert Elev / Ch Slope	Depth (FT)	Water Elev	Q (CFS)	Vel (FPS) / Vel Head / SF Ave	Energy Grd.El. / HF	Super Elev / SE Dpth	Critical Depth / Froude N	Flow Top Width / Norm Dp	Height/ Dia.-FT / "N"	Base Wt or I.D. / X-Fall	ZL / ZR	No Wth Prs/Pip / Type Ch
.000	927.000	7.000	934.000	5.00	2.83 / .12 /	934.12 /	.00 /	.86 /	.00 /	1.500 /	.000 /	.00 /	1 / .0
352.000	.0099				/ .0023	.80	7.00	.00	.73	.013	.00	.00	PIPE
352.000	930.500	4.298	934.798	5.00	2.83 / .12 /	934.92 /	.00 /	.86 /	.00 /	1.500 /	.000 /	.00 /	1 / .0

Program Package Serial Number: 7323

WATER SURFACE PROFILE LISTING Date: 6-19-2023 Time: 5:12:11

18" OUTLET WSPG
CONCO

Station	Invert Elev	Depth (FT)	Water Elev	Q (CFS)	Vel (FPS)	Vel Head	Energy Grd.El.	Super Elev	Critical Depth	Flow Top Width	Height/ Dia.-FT	Base Wt or I.D.	ZL	No Wth Prs/Pip
L/Elem	Ch Slope					SF Ave	HF	SE Dpth	Froude N	Norm Dp	"N"	X-Fall	ZR	Type Ch
.000	927.000	7.000	934.000	9.00	5.09	.40	934.40	.00	1.16	.00	1.500	.000	.00	1 .0
352.000	.0099					.0073	2.58	7.00	.00	1.07	.013	.00	.00	PIPE
352.000	930.500	6.084	936.584	9.00	5.09	.40	936.99	.00	1.16	.00	1.500	.000	.00	1 .0

Program Package Serial Number: 7323

WATER SURFACE PROFILE LISTING Date: 6-19-2023 Time: 5:12:11

18" OUTLET WSPG
CONCO

Station	Invert Elev	Depth (FT)	Water Elev	Q (CFS)	Vel (FPS)	Vel Head	Energy Grd.El.	Super Elev	Critical Depth	Flow Top Width	Height/ Dia.-FT	Base Wt or I.D.	ZL	No Wth Prs/Pip
L/Elem	Ch Slope					SF Ave	HF	SE Dpth	Froude N	Norm Dp	"N"	X-Fall	ZR	Type Ch
.000	927.000	7.000	934.000	12.00	6.79	.72	934.72	.00	1.31	.00	1.500	.000	.00	1 .0
352.000	.0099					.0131	4.59	7.00	.00	1.50	.013	.00	.00	PIPE
352.000	930.500	8.094	938.594	12.00	6.79	.72	939.31	.00	1.31	.00	1.500	.000	.00	1 .0

Flood Routing Analysis: Developed Condition (100 yr Storm Event)

```
                FLOOD HYDROGRAPH ROUTING PROGRAM
          Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018
                     Study date: 06/21/23

 ---------------------------------------------------------------------


 CHAMBER ROUTING
 CONCO INDUSTRIAL
 100-YR STORM EVENT

 ---------------------------------------------------------------------


 Program License Serial Number 6484

 ---------------------------------------------------------------------
 ********************* HYDROGRAPH INFORMATION **********************

                From study/file name: CON1.rte
 ****************************HYDROGRAPH DATA****************************
                Number of intervals =   294
                Time interval =    5.0 (Min.)
                Maximum/Peak flow rate =       23.239 (CFS)
                Total volume =       3.256 (Ac.Ft)
        Status of hydrographs being held in storage
                     Stream 1  Stream 2  Stream 3  Stream 4  Stream 5
        Peak (CFS)      0.000     0.000     0.000     0.000     0.000
        Vol (Ac.Ft)      0.000     0.000     0.000     0.000     0.000
 **********************************************************************



 ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
 Process from Point/Station        0.000 to Point/Station        1.000
 **** RETARDING BASIN ROUTING ****
 _____________________________________________________________________

 User entry of depth-outflow-storage data
 ---------------------------------------------------------------------
 Total number of inflow hydrograph intervals = 294
 Hydrograph time unit =  5.000 (Min.)
 Initial depth in storage basin =   0.00(Ft.)
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
 Initial basin depth =   0.00 (Ft.)
 Initial basin storage =      0.00 (Ac.Ft)
 Initial basin outflow =   0.00 (CFS)
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
 Depth vs. Storage and Depth vs. Discharge data:
  Basin Depth  Storage    Outflow   (S-O*dt/2)   (S+O*dt/2)
      (Ft.)    (Ac.Ft)    (CFS)     (Ac.Ft)    (Ac.Ft)
 ---------------------------------------------------------------------
    0.000      0.000      0.000      0.000        0.000
    1.500      0.170      0.500      0.168        0.172
    3.000      0.390      1.500      0.385        0.395
    4.500      0.680      4.300      0.665        0.695
    6.000      0.900      8.000      0.872        0.928
    6.700      0.960      8.700      0.930        0.990
 ---------------------------------------------------------------------
                Hydrograph Detention Basin Routing
 ---------------------------------------------------------------------

 Graph values: 'I'= unit inflow; 'O'=outflow at time shown
 ---------------------------------------------------------------------
  Time   Inflow  Outflow    Storage                                    Depth
 (Hours)  (CFS)   (CFS)     (Ac.Ft) .0       5.8   11.62   17.43   23.24 (Ft.)
  0.083    0.03    0.00      0.000  O       |       |       |       |     0.00
```

0.167	0.21	0.00	0.001	O				0.01
0.250	0.49	0.01	0.003	O				0.03
0.333	0.63	0.02	0.007	O				0.06
0.417	0.68	0.03	0.011	O				0.10
0.500	0.70	0.05	0.016	O				0.14
0.583	0.71	0.06	0.020	O				0.18
0.667	0.71	0.07	0.025	O				0.22
0.750	0.71	0.09	0.029	O				0.26
0.833	0.71	0.10	0.033	O				0.29
0.917	0.71	0.11	0.038	O				0.33
1.000	0.72	0.12	0.042	O				0.37
1.083	0.72	0.13	0.046	O				0.40
1.167	0.72	0.15	0.050	O				0.44
1.250	0.72	0.16	0.054	O				0.47
1.333	0.73	0.17	0.058	O				0.51
1.417	0.73	0.18	0.061	OI				0.54
1.500	0.73	0.19	0.065	OI				0.57
1.583	0.73	0.20	0.069	OI				0.61
1.667	0.73	0.21	0.072	OI				0.64
1.750	0.74	0.22	0.076	OI				0.67
1.833	0.74	0.23	0.079	OI				0.70
1.917	0.74	0.24	0.083	OI				0.73
2.000	0.74	0.25	0.086	OI				0.76
2.083	0.75	0.26	0.090	OI				0.79
2.167	0.75	0.27	0.093	OI				0.82
2.250	0.75	0.28	0.096	OI				0.85
2.333	0.75	0.29	0.099	OI				0.88
2.417	0.76	0.30	0.103	OI				0.91
2.500	0.76	0.31	0.106	OI				0.93
2.583	0.76	0.32	0.109	OI				0.96
2.667	0.77	0.33	0.112	OI				0.99
2.750	0.77	0.34	0.115	OI				1.01
2.833	0.77	0.35	0.118	OI				1.04
2.917	0.77	0.35	0.121	OI				1.06
3.000	0.78	0.36	0.124	OI				1.09
3.083	0.78	0.37	0.126	OI				1.11
3.167	0.78	0.38	0.129	OI				1.14
3.250	0.78	0.39	0.132	OI				1.16
3.333	0.79	0.40	0.135	OI				1.19
3.417	0.79	0.40	0.137	OI				1.21
3.500	0.79	0.41	0.140	OI				1.23
3.583	0.80	0.42	0.143	OI				1.26
3.667	0.80	0.43	0.145	OI				1.28
3.750	0.80	0.43	0.148	OI				1.30
3.833	0.81	0.44	0.150	OI				1.33
3.917	0.81	0.45	0.153	OI				1.35
4.000	0.81	0.46	0.155	OI				1.37
4.083	0.81	0.46	0.158	OI				1.39
4.167	0.82	0.47	0.160	OI				1.41
4.250	0.82	0.48	0.162	OI				1.43
4.333	0.82	0.48	0.165	OI				1.45
4.417	0.83	0.49	0.167	OI				1.47
4.500	0.83	0.50	0.169	OI				1.49
4.583	0.83	0.51	0.172	OI				1.51
4.667	0.84	0.52	0.174	OI				1.53
4.750	0.84	0.53	0.176	OI				1.54
4.833	0.84	0.54	0.178	OI				1.56
4.917	0.85	0.55	0.180	OI				1.57
5.000	0.85	0.56	0.182	OI				1.58
5.083	0.86	0.57	0.184	OI				1.60
5.167	0.86	0.57	0.186	OI				1.61
5.250	0.86	0.58	0.188	OI				1.62
5.333	0.87	0.59	0.190	OI				1.64
5.417	0.87	0.60	0.192	OI				1.65
5.500	0.87	0.61	0.194	OI				1.66
5.583	0.88	0.62	0.196	OI				1.68
5.667	0.88	0.63	0.198	OI				1.69
5.750	0.89	0.63	0.199	OI				1.70
5.833	0.89	0.64	0.201	OI				1.71
5.917	0.89	0.65	0.203	OI				1.72
6.000	0.90	0.66	0.204	OI				1.73

6.083	0.90	0.66	0.206	OI					1.75
6.167	0.91	0.67	0.208	OI					1.76
6.250	0.91	0.68	0.209	OI					1.77
6.333	0.92	0.69	0.211	OI					1.78
6.417	0.92	0.69	0.212	OI					1.79
6.500	0.92	0.70	0.214	OI					1.80
6.583	0.93	0.71	0.216	OI					1.81
6.667	0.93	0.71	0.217	OI					1.82
6.750	0.94	0.72	0.219	OI					1.83
6.833	0.94	0.73	0.220	|O					1.84
6.917	0.95	0.73	0.222	|O					1.85
7.000	0.95	0.74	0.223	|O					1.86
7.083	0.96	0.75	0.224	|O					1.87
7.167	0.96	0.75	0.226	|O					1.88
7.250	0.97	0.76	0.227	|O					1.89
7.333	0.97	0.77	0.229	|O					1.90
7.417	0.98	0.77	0.230	|O					1.91
7.500	0.98	0.78	0.232	|O					1.92
7.583	0.99	0.79	0.233	|O					1.93
7.667	0.99	0.79	0.234	|O					1.94
7.750	1.00	0.80	0.236	|O					1.95
7.833	1.00	0.80	0.237	|O					1.96
7.917	1.01	0.81	0.238	|O					1.97
8.000	1.02	0.82	0.240	|O					1.98
8.083	1.02	0.82	0.241	|O					1.99
8.167	1.03	0.83	0.243	|O					1.99
8.250	1.03	0.84	0.244	|O					2.00
8.333	1.04	0.84	0.245	|O					2.01
8.417	1.05	0.85	0.247	|O					2.02
8.500	1.05	0.85	0.248	|O					2.03
8.583	1.06	0.86	0.249	|O					2.04
8.667	1.07	0.87	0.251	|O					2.05
8.750	1.07	0.87	0.252	|O					2.06
8.833	1.08	0.88	0.254	|O					2.07
8.917	1.09	0.89	0.255	|O					2.08
9.000	1.09	0.89	0.256	|O					2.09
9.083	1.10	0.90	0.258	|O					2.10
9.167	1.11	0.90	0.259	|O					2.11
9.250	1.12	0.91	0.261	|O					2.12
9.333	1.12	0.92	0.262	|O					2.13
9.417	1.13	0.92	0.263	|O					2.14
9.500	1.14	0.93	0.265	|O					2.15
9.583	1.15	0.94	0.266	|O					2.16
9.667	1.16	0.94	0.268	|O					2.17
9.750	1.16	0.95	0.269	|O					2.18
9.833	1.17	0.96	0.271	|O					2.19
9.917	1.18	0.96	0.272	|O					2.20
10.000	1.19	0.97	0.274	|O					2.21
10.083	1.20	0.98	0.275	|O					2.22
10.167	1.21	0.98	0.277	|O					2.23
10.250	1.22	0.99	0.278	|O					2.24
10.333	1.23	1.00	0.280	|O					2.25
10.417	1.24	1.01	0.281	|O					2.26
10.500	1.25	1.01	0.283	|O					2.27
10.583	1.26	1.02	0.285	|O					2.28
10.667	1.27	1.03	0.286	|O					2.29
10.750	1.28	1.04	0.288	|O					2.30
10.833	1.29	1.04	0.290	|O					2.32
10.917	1.30	1.05	0.291	|O					2.33
11.000	1.31	1.06	0.293	|O					2.34
11.083	1.33	1.07	0.295	|O					2.35
11.167	1.34	1.08	0.297	|O					2.36
11.250	1.35	1.08	0.299	|O					2.38
11.333	1.36	1.09	0.300	|O					2.39
11.417	1.38	1.10	0.302	|O					2.40
11.500	1.39	1.11	0.304	|O					2.41
11.583	1.41	1.12	0.306	|O					2.43
11.667	1.42	1.13	0.308	|O					2.44
11.750	1.44	1.14	0.310	|O					2.46
11.833	1.45	1.15	0.312	|O					2.47
11.917	1.47	1.16	0.314	|OI					2.48

12.000	1.48	1.17	0.317	OI					2.50
12.083	1.51	1.18	0.319	OI					2.51
12.167	1.58	1.19	0.321	OI					2.53
12.250	1.68	1.20	0.324	OI					2.55
12.333	1.74	1.22	0.328	OI					2.58
12.417	1.78	1.23	0.331	OI					2.60
12.500	1.80	1.25	0.335	OI					2.63
12.583	1.82	1.27	0.339	OI					2.65
12.667	1.85	1.29	0.343	OI					2.68
12.750	1.87	1.30	0.347	OI					2.71
12.833	1.89	1.32	0.351	OI					2.73
12.917	1.92	1.34	0.355	OI					2.76
13.000	1.94	1.36	0.359	OI					2.79
13.083	1.97	1.38	0.363	OI					2.81
13.167	1.99	1.39	0.367	OI					2.84
13.250	2.02	1.41	0.371	OI					2.87
13.333	2.05	1.43	0.375	OI					2.90
13.417	2.08	1.45	0.379	OI					2.93
13.500	2.11	1.47	0.384	O					2.96
13.583	2.15	1.49	0.388	O					2.99
13.667	2.18	1.53	0.393	OI					3.01
13.750	2.22	1.57	0.397	OI					3.04
13.833	2.26	1.61	0.402	OI					3.06
13.917	2.30	1.66	0.406	OI					3.08
14.000	2.34	1.70	0.411	OI					3.11
14.083	2.39	1.74	0.415	OI					3.13
14.167	2.44	1.78	0.419	OI					3.15
14.250	2.49	1.83	0.424	OI					3.18
14.333	2.54	1.87	0.429	OI					3.20
14.417	2.60	1.92	0.433	OI					3.22
14.500	2.67	1.96	0.438	OI					3.25
14.583	2.73	2.01	0.443	OI					3.27
14.667	2.81	2.06	0.448	OI					3.30
14.750	2.89	2.11	0.453	OI					3.33
14.833	2.97	2.16	0.459	O I					3.36
14.917	3.07	2.22	0.464	OI					3.38
15.000	3.17	2.28	0.470	OI					3.42
15.083	3.29	2.34	0.477	OI					3.45
15.167	3.41	2.40	0.484	OI					3.48
15.250	3.56	2.47	0.491	OI					3.52
15.333	3.72	2.55	0.499	O I					3.56
15.417	3.88	2.63	0.507	O I					3.60
15.500	3.89	2.71	0.515	O I					3.65
15.583	3.84	2.78	0.523	O I					3.69
15.667	3.99	2.86	0.531	O I					3.73
15.750	4.36	2.94	0.539	O I					3.77
15.833	4.94	3.05	0.551	O I					3.83
15.917	5.84	3.20	0.566	O I					3.91
16.000	7.42	3.42	0.589	O I					4.03
16.083	11.35	3.81	0.629	O	I				4.24
16.167	19.79	4.75	0.707	O			I		4.68
16.250	23.24	6.58	0.816	O				I	5.43
16.333	14.81	7.95	0.897	O	I				5.98
16.417	8.18	8.24	0.920	O					6.24
16.500	5.34	8.12	0.910	I	O				6.12
16.583	4.65	7.83	0.890	I	O				5.93
16.667	3.88	7.44	0.867	I	O				5.77
16.750	3.55	7.03	0.842	I	O				5.61
16.833	3.27	6.64	0.819	I	O				5.45
16.917	3.06	6.26	0.796	I	O				5.29
17.000	2.88	5.90	0.775	I	O				5.15
17.083	2.73	5.56	0.755	I	O				5.01
17.167	2.60	5.24	0.736	I	O				4.88
17.250	2.48	4.94	0.718	I	O				4.76
17.333	2.38	4.67	0.702	I	O				4.65
17.417	2.29	4.41	0.687	I	O				4.55
17.500	2.21	4.23	0.673	I	O				4.46
17.583	2.14	4.10	0.659	I	O				4.39
17.667	2.08	3.97	0.646	I	O				4.32
17.750	2.02	3.84	0.633	I	O				4.26
17.833	1.96	3.72	0.620	I	O				4.19

17.917	1.91	3.61	0.609	| I O	|	|	|	4.13
18.000	1.86	3.50	0.597	| I O	|	|	|	4.07
18.083	1.81	3.39	0.586	| I O	|	|	|	4.01
18.167	1.71	3.29	0.575	| I O	|	|	|	3.96
18.250	1.59	3.18	0.564	| I O	|	|	|	3.90
18.333	1.52	3.08	0.553	| I O	|	|	|	3.85
18.417	1.47	2.98	0.543	| I O	|	|	|	3.79
18.500	1.43	2.88	0.533	|I O	|	|	|	3.74
18.583	1.40	2.78	0.523	|I O	|	|	|	3.69
18.667	1.38	2.69	0.514	|I O	|	|	|	3.64
18.750	1.35	2.61	0.505	|I O	|	|	|	3.59
18.833	1.32	2.53	0.496	|I O	|	|	|	3.55
18.917	1.30	2.45	0.488	|I O	|	|	|	3.51
19.000	1.28	2.37	0.480	|I O	|	|	|	3.47
19.083	1.26	2.30	0.473	|I O	|	|	|	3.43
19.167	1.24	2.23	0.466	|I O	|	|	|	3.39
19.250	1.22	2.17	0.459	|IO	|	|	|	3.36
19.333	1.20	2.11	0.453	|IO	|	|	|	3.33
19.417	1.18	2.05	0.447	|IO	|	|	|	3.29
19.500	1.16	1.99	0.441	|IO	|	|	|	3.26
19.583	1.15	1.94	0.435	|IO	|	|	|	3.23
19.667	1.13	1.89	0.430	|IO	|	|	|	3.21
19.750	1.11	1.84	0.425	|IO	|	|	|	3.18
19.833	1.10	1.79	0.420	|IO	|	|	|	3.16
19.917	1.09	1.75	0.415	|IO	|	|	|	3.13
20.000	1.07	1.70	0.411	|IO	|	|	|	3.11
20.083	1.06	1.66	0.407	|IO	|	|	|	3.09
20.167	1.05	1.62	0.403	|IO	|	|	|	3.07
20.250	1.03	1.58	0.399	|IO	|	|	|	3.05
20.333	1.02	1.55	0.395	|IO	|	|	|	3.03
20.417	1.01	1.51	0.392	|IO	|	|	|	3.01
20.500	1.00	1.49	0.388	|IO	|	|	|	2.99
20.583	0.99	1.48	0.385	|IO	|	|	|	2.96
20.667	0.98	1.46	0.381	|IO	|	|	|	2.94
20.750	0.97	1.45	0.378	|O	|	|	|	2.92
20.833	0.96	1.43	0.375	|O	|	|	|	2.90
20.917	0.95	1.42	0.371	|O	|	|	|	2.87
21.000	0.94	1.40	0.368	|O	|	|	|	2.85
21.083	0.93	1.39	0.365	|O	|	|	|	2.83
21.167	0.92	1.37	0.362	|O	|	|	|	2.81
21.250	0.91	1.36	0.359	|O	|	|	|	2.79
21.333	0.90	1.34	0.356	|O	|	|	|	2.77
21.417	0.89	1.33	0.353	|O	|	|	|	2.75
21.500	0.89	1.32	0.350	|O	|	|	|	2.73
21.583	0.88	1.30	0.347	|O	|	|	|	2.71
21.667	0.87	1.29	0.344	|O	|	|	|	2.69
21.750	0.86	1.28	0.341	|O	|	|	|	2.67
21.833	0.85	1.26	0.338	|O	|	|	|	2.65
21.917	0.85	1.25	0.335	|O	|	|	|	2.63
22.000	0.84	1.24	0.333	|O	|	|	|	2.61
22.083	0.83	1.23	0.330	|O	|	|	|	2.59
22.167	0.83	1.21	0.327	|O	|	|	|	2.57
22.250	0.82	1.20	0.325	|O	|	|	|	2.55
22.333	0.81	1.19	0.322	|O	|	|	|	2.54
22.417	0.81	1.18	0.319	|O	|	|	|	2.52
22.500	0.80	1.17	0.317	|O	|	|	|	2.50
22.583	0.80	1.16	0.314	|O	|	|	|	2.48
22.667	0.79	1.14	0.312	|O	|	|	|	2.47
22.750	0.78	1.13	0.309	|O	|	|	|	2.45
22.833	0.78	1.12	0.307	|O	|	|	|	2.43
22.917	0.77	1.11	0.305	|O	|	|	|	2.42
23.000	0.77	1.10	0.302	|O	|	|	|	2.40
23.083	0.76	1.09	0.300	|O	|	|	|	2.39
23.167	0.76	1.08	0.298	|O	|	|	|	2.37
23.250	0.75	1.07	0.296	|O	|	|	|	2.36
23.333	0.75	1.06	0.293	|O	|	|	|	2.34
23.417	0.74	1.05	0.291	|O	|	|	|	2.33
23.500	0.74	1.04	0.289	|O	|	|	|	2.31
23.583	0.73	1.03	0.287	|O	|	|	|	2.30
23.667	0.73	1.02	0.285	|O	|	|	|	2.28
23.750	0.72	1.01	0.283	IO	|	|	|	2.27

23.833	0.72	1.00	0.281	IO				2.26
23.917	0.71	1.00	0.279	IO				2.24
24.000	0.71	0.99	0.277	IO				2.23
24.083	0.67	0.98	0.275	IO				2.22
24.167	0.49	0.97	0.272	IO				2.20
24.250	0.21	0.95	0.268	IO				2.17
24.333	0.07	0.92	0.263	IO				2.13
24.417	0.02	0.89	0.257	IO				2.09
24.500	0.01	0.87	0.251	IO				2.05
24.583	0.00	0.84	0.245	IO				2.01
24.667	0.00	0.81	0.239	IO				1.97
24.750	0.00	0.79	0.234	IO				1.93
24.833	0.00	0.77	0.228	IO				1.90
24.917	0.00	0.74	0.223	IO				1.86
25.000	0.00	0.72	0.218	O				1.83
25.083	0.00	0.70	0.213	O				1.80
25.167	0.00	0.68	0.209	O				1.76
25.250	0.00	0.65	0.204	O				1.73
25.333	0.00	0.63	0.200	O				1.70
25.417	0.00	0.61	0.195	O				1.67
25.500	0.00	0.60	0.191	O				1.64
25.583	0.00	0.58	0.187	O				1.62
25.667	0.00	0.56	0.183	O				1.59
25.750	0.00	0.54	0.179	O				1.56
25.833	0.00	0.53	0.176	O				1.54
25.917	0.00	0.51	0.172	O				1.51
26.000	0.00	0.50	0.169	O				1.49
26.083	0.00	0.49	0.165	O				1.46
26.167	0.00	0.48	0.162	O				1.43
26.250	0.00	0.47	0.159	O				1.40
26.333	0.00	0.46	0.155	O				1.37
26.417	0.00	0.45	0.152	O				1.34
26.500	0.00	0.44	0.149	O				1.32
26.583	0.00	0.43	0.146	O				1.29
26.667	0.00	0.42	0.143	O				1.27
26.750	0.00	0.41	0.141	O				1.24
26.833	0.00	0.41	0.138	O				1.22
26.917	0.00	0.40	0.135	O				1.19
27.000	0.00	0.39	0.132	O				1.17
27.083	0.00	0.38	0.130	O				1.14
27.167	0.00	0.37	0.127	O				1.12
27.250	0.00	0.37	0.124	O				1.10
27.333	0.00	0.36	0.122	O				1.08
27.417	0.00	0.35	0.119	O				1.05
27.500	0.00	0.34	0.117	O				1.03
27.583	0.00	0.34	0.115	O				1.01
27.667	0.00	0.33	0.112	O				0.99
27.750	0.00	0.32	0.110	O				0.97
27.833	0.00	0.32	0.108	O				0.95
27.917	0.00	0.31	0.106	O				0.93
28.000	0.00	0.31	0.104	O				0.92
28.083	0.00	0.30	0.102	O				0.90
28.167	0.00	0.29	0.100	O				0.88
28.250	0.00	0.29	0.098	O				0.86
28.333	0.00	0.28	0.096	O				0.84
28.417	0.00	0.28	0.094	O				0.83
28.500	0.00	0.27	0.092	O				0.81
28.583	0.00	0.26	0.090	O				0.79
28.667	0.00	0.26	0.088	O				0.78
28.750	0.00	0.25	0.086	O				0.76
28.833	0.00	0.25	0.085	O				0.75
28.917	0.00	0.24	0.083	O				0.73
29.000	0.00	0.24	0.081	O				0.72
29.083	0.00	0.23	0.080	O				0.70
29.167	0.00	0.23	0.078	O				0.69
29.250	0.00	0.23	0.077	O				0.68
29.333	0.00	0.22	0.075	O				0.66
29.417	0.00	0.22	0.073	O				0.65
29.500	0.00	0.21	0.072	O				0.64
29.583	0.00	0.21	0.071	O				0.62
29.667	0.00	0.20	0.069	O				0.61

29.750	0.00	0.20	0.068	O	|	|	|	|	0.60
29.833	0.00	0.20	0.066	O	|	|	|	|	0.59
29.917	0.00	0.19	0.065	O	|	|	|	|	0.57
30.000	0.00	0.19	0.064	O	|	|	|	|	0.56
30.083	0.00	0.18	0.062	O	|	|	|	|	0.55
30.167	0.00	0.18	0.061	O	|	|	|	|	0.54
30.250	0.00	0.18	0.060	O	|	|	|	|	0.53
30.333	0.00	0.17	0.059	O	|	|	|	|	0.52
30.417	0.00	0.17	0.058	O	|	|	|	|	0.51
30.500	0.00	0.17	0.056	O	|	|	|	|	0.50
30.583	0.00	0.16	0.055	O	|	|	|	|	0.49
30.667	0.00	0.16	0.054	O	|	|	|	|	0.48
30.750	0.00	0.16	0.053	O	|	|	|	|	0.47
30.833	0.00	0.15	0.052	O	|	|	|	|	0.46
30.917	0.00	0.15	0.051	O	|	|	|	|	0.45
31.000	0.00	0.15	0.050	O	|	|	|	|	0.44
31.083	0.00	0.14	0.049	O	|	|	|	|	0.43
31.167	0.00	0.14	0.048	O	|	|	|	|	0.42
31.250	0.00	0.14	0.047	O	|	|	|	|	0.42
31.333	0.00	0.14	0.046	O	|	|	|	|	0.41
31.417	0.00	0.13	0.045	O	|	|	|	|	0.40
31.500	0.00	0.13	0.044	O	|	|	|	|	0.39
31.583	0.00	0.13	0.043	O	|	|	|	|	0.38
31.667	0.00	0.13	0.043	O	|	|	|	|	0.38
31.750	0.00	0.12	0.042	O	|	|	|	|	0.37
31.833	0.00	0.12	0.041	O	|	|	|	|	0.36
31.917	0.00	0.12	0.040	O	|	|	|	|	0.35
32.000	0.00	0.12	0.039	O	|	|	|	|	0.35
32.083	0.00	0.11	0.038	O	|	|	|	|	0.34
32.167	0.00	0.11	0.038	O	|	|	|	|	0.33
32.250	0.00	0.11	0.037	O	|	|	|	|	0.33
32.333	0.00	0.11	0.036	O	|	|	|	|	0.32
32.417	0.00	0.10	0.035	O	|	|	|	|	0.31
32.500	0.00	0.10	0.035	O	|	|	|	|	0.31
32.583	0.00	0.10	0.034	O	|	|	|	|	0.30
32.667	0.00	0.10	0.033	O	|	|	|	|	0.29
32.750	0.00	0.10	0.033	O	|	|	|	|	0.29
32.833	0.00	0.09	0.032	O	|	|	|	|	0.28
32.917	0.00	0.09	0.031	O	|	|	|	|	0.28
33.000	0.00	0.09	0.031	O	|	|	|	|	0.27
33.083	0.00	0.09	0.030	O	|	|	|	|	0.27
33.167	0.00	0.09	0.030	O	|	|	|	|	0.26
33.250	0.00	0.09	0.029	O	|	|	|	|	0.26
33.333	0.00	0.08	0.028	O	|	|	|	|	0.25
33.417	0.00	0.08	0.028	O	|	|	|	|	0.25
33.500	0.00	0.08	0.027	O	|	|	|	|	0.24
33.583	0.00	0.08	0.027	O	|	|	|	|	0.24
33.667	0.00	0.08	0.026	O	|	|	|	|	0.23
33.750	0.00	0.08	0.026	O	|	|	|	|	0.23
33.833	0.00	0.07	0.025	O	|	|	|	|	0.22
33.917	0.00	0.07	0.025	O	|	|	|	|	0.22
34.000	0.00	0.07	0.024	O	|	|	|	|	0.21
34.083	0.00	0.07	0.024	O	|	|	|	|	0.21
34.167	0.00	0.07	0.023	O	|	|	|	|	0.20
34.250	0.00	0.07	0.023	O	|	|	|	|	0.20
34.333	0.00	0.07	0.022	O	|	|	|	|	0.20
34.417	0.00	0.06	0.022	O	|	|	|	|	0.19
34.500	0.00	0.06	0.021	O	|	|	|	|	0.19
34.583	0.00	0.06	0.021	O	|	|	|	|	0.18
34.667	0.00	0.06	0.021	O	|	|	|	|	0.18
34.750	0.00	0.06	0.020	O	|	|	|	|	0.18
34.833	0.00	0.06	0.020	O	|	|	|	|	0.17
34.917	0.00	0.06	0.019	O	|	|	|	|	0.17
35.000	0.00	0.06	0.019	O	|	|	|	|	0.17
35.083	0.00	0.05	0.019	O	|	|	|	|	0.16
35.167	0.00	0.05	0.018	O	|	|	|	|	0.16
35.250	0.00	0.05	0.018	O	|	|	|	|	0.16
35.333	0.00	0.05	0.017	O	|	|	|	|	0.15
35.417	0.00	0.05	0.017	O	|	|	|	|	0.15
35.500	0.00	0.05	0.017	O	|	|	|	|	0.15
35.583	0.00	0.05	0.016	O	|	|	|	|	0.14

35.667	0.00	0.05	0.016	O	|	|	|	0.14
35.750	0.00	0.05	0.016	O	|	|	|	0.14
35.833	0.00	0.05	0.015	O	|	|	|	0.14
35.917	0.00	0.04	0.015	O	|	|	|	0.13
36.000	0.00	0.04	0.015	O	|	|	|	0.13
36.083	0.00	0.04	0.015	O	|	|	|	0.13
36.167	0.00	0.04	0.014	O	|	|	|	0.13
36.250	0.00	0.04	0.014	O	|	|	|	0.12
36.333	0.00	0.04	0.014	O	|	|	|	0.12
36.417	0.00	0.04	0.013	O	|	|	|	0.12
36.500	0.00	0.04	0.013	O	|	|	|	0.12
36.583	0.00	0.04	0.013	O	|	|	|	0.11
36.667	0.00	0.04	0.013	O	|	|	|	0.11
36.750	0.00	0.04	0.012	O	|	|	|	0.11
36.833	0.00	0.04	0.012	O	|	|	|	0.11
36.917	0.00	0.03	0.012	O	|	|	|	0.10
37.000	0.00	0.03	0.012	O	|	|	|	0.10
37.083	0.00	0.03	0.011	O	|	|	|	0.10
37.167	0.00	0.03	0.011	O	|	|	|	0.10
37.250	0.00	0.03	0.011	O	|	|	|	0.10
37.333	0.00	0.03	0.011	O	|	|	|	0.09
37.417	0.00	0.03	0.011	O	|	|	|	0.09
37.500	0.00	0.03	0.010	O	|	|	|	0.09
37.583	0.00	0.03	0.010	O	|	|	|	0.09
37.667	0.00	0.03	0.010	O	|	|	|	0.09
37.750	0.00	0.03	0.010	O	|	|	|	0.09
37.833	0.00	0.03	0.009	O	|	|	|	0.08
37.917	0.00	0.03	0.009	O	|	|	|	0.08
38.000	0.00	0.03	0.009	O	|	|	|	0.08
38.083	0.00	0.03	0.009	O	|	|	|	0.08
38.167	0.00	0.03	0.009	O	|	|	|	0.08
38.250	0.00	0.03	0.009	O	|	|	|	0.08
38.333	0.00	0.02	0.008	O	|	|	|	0.07
38.417	0.00	0.02	0.008	O	|	|	|	0.07
38.500	0.00	0.02	0.008	O	|	|	|	0.07
38.583	0.00	0.02	0.008	O	|	|	|	0.07
38.667	0.00	0.02	0.008	O	|	|	|	0.07
38.750	0.00	0.02	0.008	O	|	|	|	0.07
38.833	0.00	0.02	0.007	O	|	|	|	0.07
38.917	0.00	0.02	0.007	O	|	|	|	0.06
39.000	0.00	0.02	0.007	O	|	|	|	0.06
39.083	0.00	0.02	0.007	O	|	|	|	0.06
39.167	0.00	0.02	0.007	O	|	|	|	0.06
39.250	0.00	0.02	0.007	O	|	|	|	0.06
39.333	0.00	0.02	0.007	O	|	|	|	0.06
39.417	0.00	0.02	0.006	O	|	|	|	0.06
39.500	0.00	0.02	0.006	O	|	|	|	0.06
39.583	0.00	0.02	0.006	O	|	|	|	0.05
39.667	0.00	0.02	0.006	O	|	|	|	0.05
39.750	0.00	0.02	0.006	O	|	|	|	0.05
39.833	0.00	0.02	0.006	O	|	|	|	0.05
39.917	0.00	0.02	0.006	O	|	|	|	0.05
40.000	0.00	0.02	0.006	O	|	|	|	0.05
40.083	0.00	0.02	0.005	O	|	|	|	0.05
40.167	0.00	0.02	0.005	O	|	|	|	0.05
40.250	0.00	0.02	0.005	O	|	|	|	0.05
40.333	0.00	0.02	0.005	O	|	|	|	0.05
40.417	0.00	0.01	0.005	O	|	|	|	0.04
40.500	0.00	0.01	0.005	O	|	|	|	0.04
40.583	0.00	0.01	0.005	O	|	|	|	0.04
40.667	0.00	0.01	0.005	O	|	|	|	0.04
40.750	0.00	0.01	0.005	O	|	|	|	0.04
40.833	0.00	0.01	0.005	O	|	|	|	0.04
40.917	0.00	0.01	0.004	O	|	|	|	0.04
41.000	0.00	0.01	0.004	O	|	|	|	0.04
41.083	0.00	0.01	0.004	O	|	|	|	0.04
41.167	0.00	0.01	0.004	O	|	|	|	0.04
41.250	0.00	0.01	0.004	O	|	|	|	0.04
41.333	0.00	0.01	0.004	O	|	|	|	0.04
41.417	0.00	0.01	0.004	O	|	|	|	0.04
41.500	0.00	0.01	0.004	O	|	|	|	0.03

41.583	0.00	0.01	0.004	O	|	|	|	|	0.03
41.667	0.00	0.01	0.004	O	|	|	|	|	0.03
41.750	0.00	0.01	0.004	O	|	|	|	|	0.03
41.833	0.00	0.01	0.004	O	|	|	|	|	0.03
41.917	0.00	0.01	0.004	O	|	|	|	|	0.03
42.000	0.00	0.01	0.003	O	|	|	|	|	0.03
42.083	0.00	0.01	0.003	O	|	|	|	|	0.03
42.167	0.00	0.01	0.003	O	|	|	|	|	0.03
42.250	0.00	0.01	0.003	O	|	|	|	|	0.03
42.333	0.00	0.01	0.003	O	|	|	|	|	0.03
42.417	0.00	0.01	0.003	O	|	|	|	|	0.03
42.500	0.00	0.01	0.003	O	|	|	|	|	0.03
42.583	0.00	0.01	0.003	O	|	|	|	|	0.03
42.667	0.00	0.01	0.003	O	|	|	|	|	0.03
42.750	0.00	0.01	0.003	O	|	|	|	|	0.03
42.833	0.00	0.01	0.003	O	|	|	|	|	0.02
42.917	0.00	0.01	0.003	O	|	|	|	|	0.02
43.000	0.00	0.01	0.003	O	|	|	|	|	0.02
43.083	0.00	0.01	0.003	O	|	|	|	|	0.02
43.167	0.00	0.01	0.003	O	|	|	|	|	0.02
43.250	0.00	0.01	0.003	O	|	|	|	|	0.02
43.333	0.00	0.01	0.002	O	|	|	|	|	0.02
43.417	0.00	0.01	0.002	O	|	|	|	|	0.02
43.500	0.00	0.01	0.002	O	|	|	|	|	0.02
43.583	0.00	0.01	0.002	O	|	|	|	|	0.02
43.667	0.00	0.01	0.002	O	|	|	|	|	0.02
43.750	0.00	0.01	0.002	O	|	|	|	|	0.02
43.833	0.00	0.01	0.002	O	|	|	|	|	0.02
43.917	0.00	0.01	0.002	O	|	|	|	|	0.02
44.000	0.00	0.01	0.002	O	|	|	|	|	0.02
44.083	0.00	0.01	0.002	O	|	|	|	|	0.02
44.167	0.00	0.01	0.002	O	|	|	|	|	0.02
44.250	0.00	0.01	0.002	O	|	|	|	|	0.02
44.333	0.00	0.01	0.002	O	|	|	|	|	0.02
44.417	0.00	0.01	0.002	O	|	|	|	|	0.02
44.500	0.00	0.01	0.002	O	|	|	|	|	0.02
44.583	0.00	0.01	0.002	O	|	|	|	|	0.02
44.667	0.00	0.01	0.002	O	|	|	|	|	0.02
44.750	0.00	0.01	0.002	O	|	|	|	|	0.02
44.833	0.00	0.01	0.002	O	|	|	|	|	0.02
44.917	0.00	0.00	0.002	O	|	|	|	|	0.01
45.000	0.00	0.00	0.002	O	|	|	|	|	0.01
45.083	0.00	0.00	0.002	O	|	|	|	|	0.01
45.167	0.00	0.00	0.002	O	|	|	|	|	0.01
45.250	0.00	0.00	0.002	O	|	|	|	|	0.01
45.333	0.00	0.00	0.002	O	|	|	|	|	0.01
45.417	0.00	0.00	0.002	O	|	|	|	|	0.01
45.500	0.00	0.00	0.001	O	|	|	|	|	0.01
45.583	0.00	0.00	0.001	O	|	|	|	|	0.01
45.667	0.00	0.00	0.001	O	|	|	|	|	0.01
45.750	0.00	0.00	0.001	O	|	|	|	|	0.01
45.833	0.00	0.00	0.001	O	|	|	|	|	0.01
45.917	0.00	0.00	0.001	O	|	|	|	|	0.01
46.000	0.00	0.00	0.001	O	|	|	|	|	0.01
46.083	0.00	0.00	0.001	O	|	|	|	|	0.01
46.167	0.00	0.00	0.001	O	|	|	|	|	0.01
46.250	0.00	0.00	0.001	O	|	|	|	|	0.01
46.333	0.00	0.00	0.001	O	|	|	|	|	0.01
46.417	0.00	0.00	0.001	O	|	|	|	|	0.01
46.500	0.00	0.00	0.001	O	|	|	|	|	0.01
46.583	0.00	0.00	0.001	O	|	|	|	|	0.01
46.667	0.00	0.00	0.001	O	|	|	|	|	0.01
46.750	0.00	0.00	0.001	O	|	|	|	|	0.01
46.833	0.00	0.00	0.001	O	|	|	|	|	0.01
46.917	0.00	0.00	0.001	O	|	|	|	|	0.01
47.000	0.00	0.00	0.001	O	|	|	|	|	0.01
47.083	0.00	0.00	0.001	O	|	|	|	|	0.01
47.167	0.00	0.00	0.001	O	|	|	|	|	0.01
47.250	0.00	0.00	0.001	O	|	|	|	|	0.01
47.333	0.00	0.00	0.001	O	|	|	|	|	0.01
47.417	0.00	0.00	0.001	O	|	|	|	|	0.01

47.500	0.00	0.00	0.001	O	|	|	|	|	0.01
47.583	0.00	0.00	0.001	O	|	|	|	|	0.01
47.667	0.00	0.00	0.001	O	|	|	|	|	0.01
47.750	0.00	0.00	0.001	O	|	|	|	|	0.01
47.833	0.00	0.00	0.001	O	|	|	|	|	0.01
47.917	0.00	0.00	0.001	O	|	|	|	|	0.01
48.000	0.00	0.00	0.001	O	|	|	|	|	0.01
48.083	0.00	0.00	0.001	O	|	|	|	|	0.01
48.167	0.00	0.00	0.001	O	|	|	|	|	0.01
48.250	0.00	0.00	0.001	O	|	|	|	|	0.01
48.333	0.00	0.00	0.001	O	|	|	|	|	0.01
48.417	0.00	0.00	0.001	O	|	|	|	|	0.01
48.500	0.00	0.00	0.001	O	|	|	|	|	0.01
48.583	0.00	0.00	0.001	O	|	|	|	|	0.01
48.667	0.00	0.00	0.001	O	|	|	|	|	0.01
48.750	0.00	0.00	0.001	O	|	|	|	|	0.01
48.833	0.00	0.00	0.001	O	|	|	|	|	0.01
48.917	0.00	0.00	0.001	O	|	|	|	|	0.01
49.000	0.00	0.00	0.001	O	|	|	|	|	0.01
49.083	0.00	0.00	0.001	O	|	|	|	|	0.01
49.167	0.00	0.00	0.001	O	|	|	|	|	0.01
49.250	0.00	0.00	0.001	O	|	|	|	|	0.01
49.333	0.00	0.00	0.001	O	|	|	|	|	0.01
49.417	0.00	0.00	0.001	O	|	|	|	|	0.01
49.500	0.00	0.00	0.001	O	|	|	|	|	0.00
49.583	0.00	0.00	0.001	O	|	|	|	|	0.00
49.667	0.00	0.00	0.001	O	|	|	|	|	0.00
49.750	0.00	0.00	0.001	O	|	|	|	|	0.00
49.833	0.00	0.00	0.001	O	|	|	|	|	0.00
49.917	0.00	0.00	0.001	O	|	|	|	|	0.00
50.000	0.00	0.00	0.000	O	|	|	|	|	0.00
50.083	0.00	0.00	0.000	O	|	|	|	|	0.00
50.167	0.00	0.00	0.000	O	|	|	|	|	0.00
50.250	0.00	0.00	0.000	O	|	|	|	|	0.00
50.333	0.00	0.00	0.000	O	|	|	|	|	0.00
50.417	0.00	0.00	0.000	O	|	|	|	|	0.00
50.500	0.00	0.00	0.000	O	|	|	|	|	0.00
50.583	0.00	0.00	0.000	O	|	|	|	|	0.00
50.667	0.00	0.00	0.000	O	|	|	|	|	0.00
50.750	0.00	0.00	0.000	O	|	|	|	|	0.00
50.833	0.00	0.00	0.000	O	|	|	|	|	0.00
50.917	0.00	0.00	0.000	O	|	|	|	|	0.00
51.000	0.00	0.00	0.000	O	|	|	|	|	0.00
51.083	0.00	0.00	0.000	O	|	|	|	|	0.00
51.167	0.00	0.00	0.000	O	|	|	|	|	0.00
51.250	0.00	0.00	0.000	O	|	|	|	|	0.00
51.333	0.00	0.00	0.000	O	|	|	|	|	0.00
51.417	0.00	0.00	0.000	O	|	|	|	|	0.00
51.500	0.00	0.00	0.000	O	|	|	|	|	0.00
51.583	0.00	0.00	0.000	O	|	|	|	|	0.00

**********HYDROGRAPH DATA**********

Number of intervals = 619
Time interval = 5.0 (Min.)
Maximum/Peak flow rate = 8.236 (CFS)
Total volume = 3.255 (Ac.Ft)

Status of hydrographs being held in storage

	Stream 1	Stream 2	Stream 3	Stream 4	Stream 5
Peak (CFS)	0.000	0.000	0.000	0.000	0.000
Vol (Ac.Ft)	0.000	0.000	0.000	0.000	0.000

****

Flood Routing Analysis: Developed Condition (25 yr Storm Event)

```
                    FLOOD HYDROGRAPH ROUTING PROGRAM
              Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018
                          Study date: 07/01/23

      ----------------------------------------------------------------------


      CHAMBER ROUTING
      CONCO INDUSTRIAL
      25-YR STORM EVENT

      ----------------------------------------------------------------------


      Program License Serial Number 6484

      ----------------------------------------------------------------------
      ********************* HYDROGRAPH INFORMATION **********************

                    From study/file name: CON1.rte
      ****************************HYDROGRAPH DATA****************************
                    Number of intervals =   294
                    Time interval =    5.0 (Min.)
                    Maximum/Peak flow rate =       18.007 (CFS)
                    Total volume =       2.584 (Ac.Ft)
             Status of hydrographs being held in storage
                         Stream 1  Stream 2  Stream 3  Stream 4  Stream 5
             Peak (CFS)      0.000     0.000     0.000     0.000     0.000
             Vol (Ac.Ft)      0.000     0.000     0.000     0.000     0.000
      **********************************************************************



      ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
      Process from Point/Station        0.000 to Point/Station        1.000
      **** RETARDING BASIN ROUTING ****
      ______________________________________________________________________

      User entry of depth-outflow-storage data
      ----------------------------------------------------------------------
      Total number of inflow hydrograph intervals = 294
      Hydrograph time unit =  5.000 (Min.)
      Initial depth in storage basin =   0.00(Ft.)
      ----------------------------------------------------------------------
      ----------------------------------------------------------------------
      Initial basin depth =   0.00 (Ft.)
      Initial basin storage =      0.00 (Ac.Ft)
      Initial basin outflow =   0.00 (CFS)
      ----------------------------------------------------------------------
      ----------------------------------------------------------------------
      Depth vs. Storage and Depth vs. Discharge data:
       Basin Depth  Storage    Outflow   (S-O*dt/2)   (S+O*dt/2)
           (Ft.)    (Ac.Ft)    (CFS)     (Ac.Ft)    (Ac.Ft)
      ----------------------------------------------------------------------
        0.000      0.000      0.000      0.000        0.000
        1.500      0.170      0.500      0.168        0.172
        3.000      0.390      1.500      0.385        0.395
        4.500      0.680      4.300      0.665        0.695
        6.000      0.900      8.000      0.872        0.928
        6.700      0.960      8.700      0.930        0.990
      ----------------------------------------------------------------------
                     Hydrograph Detention Basin Routing
      ----------------------------------------------------------------------

      Graph values: 'I'= unit inflow; 'O'=outflow at time shown
      ----------------------------------------------------------------------
       Time   Inflow  Outflow    Storage                                 Depth
      (Hours)  (CFS)   (CFS)     (Ac.Ft) .0       4.5    9.00   13.51   18.01 (Ft.)
       0.083    0.03    0.00      0.000  O       |       |       |       |     0.00
```

0.167	0.18	0.00	0.001	O				0.01
0.250	0.40	0.01	0.003	O				0.02
0.333	0.51	0.02	0.006	O				0.05
0.417	0.55	0.03	0.009	O				0.08
0.500	0.56	0.04	0.013	O				0.11
0.583	0.57	0.05	0.016	OI				0.14
0.667	0.57	0.06	0.020	OI				0.18
0.750	0.57	0.07	0.023	OI				0.21
0.833	0.57	0.08	0.027	OI				0.24
0.917	0.57	0.09	0.030	OI				0.27
1.000	0.57	0.10	0.034	OI				0.30
1.083	0.58	0.11	0.037	OI				0.32
1.167	0.58	0.12	0.040	OI				0.35
1.250	0.58	0.13	0.043	OI				0.38
1.333	0.58	0.14	0.046	OI				0.41
1.417	0.58	0.14	0.049	OI				0.43
1.500	0.59	0.15	0.052	OI				0.46
1.583	0.59	0.16	0.055	OI				0.49
1.667	0.59	0.17	0.058	OI				0.51
1.750	0.59	0.18	0.061	OI				0.54
1.833	0.59	0.19	0.064	OI				0.56
1.917	0.60	0.20	0.067	OI				0.59
2.000	0.60	0.20	0.069	OI				0.61
2.083	0.60	0.21	0.072	OI				0.64
2.167	0.60	0.22	0.075	OI				0.66
2.250	0.60	0.23	0.077	OI				0.68
2.333	0.61	0.23	0.080	OI				0.70
2.417	0.61	0.24	0.082	OI				0.73
2.500	0.61	0.25	0.085	OI				0.75
2.583	0.61	0.26	0.087	OI				0.77
2.667	0.61	0.26	0.090	OI				0.79
2.750	0.62	0.27	0.092	OI				0.81
2.833	0.62	0.28	0.094	OI				0.83
2.917	0.62	0.28	0.097	OI				0.85
3.000	0.62	0.29	0.099	OI				0.87
3.083	0.62	0.30	0.101	OI				0.89
3.167	0.63	0.30	0.104	OI				0.91
3.250	0.63	0.31	0.106	OI				0.93
3.333	0.63	0.32	0.108	OI				0.95
3.417	0.63	0.32	0.110	OI				0.97
3.500	0.64	0.33	0.112	OI				0.99
3.583	0.64	0.34	0.114	OI				1.01
3.667	0.64	0.34	0.116	OI				1.03
3.750	0.64	0.35	0.118	OI				1.04
3.833	0.65	0.35	0.120	OI				1.06
3.917	0.65	0.36	0.122	OI				1.08
4.000	0.65	0.37	0.124	OI				1.10
4.083	0.65	0.37	0.126	OI				1.11
4.167	0.66	0.38	0.128	OI				1.13
4.250	0.66	0.38	0.130	OI				1.15
4.333	0.66	0.39	0.132	OI				1.17
4.417	0.66	0.39	0.134	OI				1.18
4.500	0.67	0.40	0.136	OI				1.20
4.583	0.67	0.40	0.138	OI				1.21
4.667	0.67	0.41	0.139	OI				1.23
4.750	0.67	0.42	0.141	OI				1.25
4.833	0.68	0.42	0.143	OI				1.26
4.917	0.68	0.43	0.145	OI				1.28
5.000	0.68	0.43	0.146	OI				1.29
5.083	0.69	0.44	0.148	OI				1.31
5.167	0.69	0.44	0.150	OI				1.32
5.250	0.69	0.45	0.152	OI				1.34
5.333	0.69	0.45	0.153	OI				1.35
5.417	0.70	0.46	0.155	OI				1.37
5.500	0.70	0.46	0.157	OI				1.38
5.583	0.70	0.47	0.158	OI				1.40
5.667	0.71	0.47	0.160	OI				1.41
5.750	0.71	0.47	0.161	OI				1.42
5.833	0.71	0.48	0.163	OI				1.44
5.917	0.72	0.48	0.165	OI				1.45
6.000	0.72	0.49	0.166	OI				1.47

6.083	0.72	0.49	0.168	OI					1.48
6.167	0.73	0.50	0.169	OI					1.50
6.250	0.73	0.50	0.171	OI					1.51
6.333	0.73	0.51	0.173	OI					1.52
6.417	0.74	0.52	0.174	OI					1.53
6.500	0.74	0.53	0.176	OI					1.54
6.583	0.74	0.53	0.177	OI					1.55
6.667	0.75	0.54	0.178	OI					1.56
6.750	0.75	0.54	0.180	OI					1.57
6.833	0.75	0.55	0.181	OI					1.58
6.917	0.76	0.56	0.183	OI					1.59
7.000	0.76	0.56	0.184	O					1.60
7.083	0.77	0.57	0.185	O					1.60
7.167	0.77	0.58	0.187	O					1.61
7.250	0.77	0.58	0.188	O					1.62
7.333	0.78	0.59	0.189	O					1.63
7.417	0.78	0.59	0.191	O					1.64
7.500	0.79	0.60	0.192	O					1.65
7.583	0.79	0.61	0.193	O					1.66
7.667	0.79	0.61	0.195	O					1.67
7.750	0.80	0.62	0.196	O					1.68
7.833	0.80	0.62	0.197	O					1.68
7.917	0.81	0.63	0.198	O					1.69
8.000	0.81	0.63	0.200	O					1.70
8.083	0.82	0.64	0.201	O					1.71
8.167	0.82	0.65	0.202	O					1.72
8.250	0.83	0.65	0.203	O					1.73
8.333	0.83	0.66	0.204	O					1.73
8.417	0.84	0.66	0.206	O					1.74
8.500	0.84	0.67	0.207	O					1.75
8.583	0.85	0.67	0.208	O					1.76
8.667	0.85	0.68	0.209	O					1.77
8.750	0.86	0.68	0.210	O					1.78
8.833	0.86	0.69	0.212	O					1.78
8.917	0.87	0.69	0.213	O					1.79
9.000	0.87	0.70	0.214	O					1.80
9.083	0.88	0.71	0.215	O					1.81
9.167	0.89	0.71	0.216	O					1.82
9.250	0.89	0.72	0.218	O					1.82
9.333	0.90	0.72	0.219	O					1.83
9.417	0.90	0.73	0.220	O					1.84
9.500	0.91	0.73	0.221	O					1.85
9.583	0.92	0.74	0.222	O					1.86
9.667	0.92	0.74	0.224	O					1.87
9.750	0.93	0.75	0.225	O					1.87
9.833	0.94	0.76	0.226	O					1.88
9.917	0.94	0.76	0.227	O					1.89
10.000	0.95	0.77	0.229	O					1.90
10.083	0.96	0.77	0.230	O					1.91
10.167	0.97	0.78	0.231	O					1.92
10.250	0.97	0.78	0.233	O					1.93
10.333	0.98	0.79	0.234	O					1.94
10.417	0.99	0.80	0.235	O					1.94
10.500	1.00	0.80	0.237	O					1.95
10.583	1.01	0.81	0.238	O					1.96
10.667	1.01	0.81	0.239	O					1.97
10.750	1.02	0.82	0.241	O					1.98
10.833	1.03	0.83	0.242	O					1.99
10.917	1.04	0.83	0.243	O					2.00
11.000	1.05	0.84	0.245	O					2.01
11.083	1.06	0.85	0.246	O					2.02
11.167	1.07	0.85	0.248	O					2.03
11.250	1.08	0.86	0.249	O					2.04
11.333	1.09	0.87	0.251	O					2.05
11.417	1.10	0.87	0.252	O					2.06
11.500	1.11	0.88	0.254	O					2.07
11.583	1.12	0.89	0.255	O					2.08
11.667	1.13	0.90	0.257	OI					2.09
11.750	1.15	0.90	0.259	OI					2.11
11.833	1.16	0.91	0.260	OI					2.12
11.917	1.17	0.92	0.262	OI					2.13

12.000	1.18	0.93	0.264	OI					2.14
12.083	1.21	0.94	0.266	OI					2.15
12.167	1.27	0.94	0.268	OI					2.17
12.250	1.36	0.96	0.270	OI					2.18
12.333	1.42	0.97	0.273	OI					2.20
12.417	1.45	0.98	0.276	OI					2.23
12.500	1.47	1.00	0.280	OI					2.25
12.583	1.48	1.01	0.283	OI					2.27
12.667	1.50	1.03	0.286	OI					2.29
12.750	1.52	1.04	0.289	OI					2.31
12.833	1.54	1.06	0.293	OI					2.34
12.917	1.56	1.07	0.296	OI					2.36
13.000	1.58	1.09	0.299	OI					2.38
13.083	1.60	1.10	0.303	OI					2.40
13.167	1.62	1.12	0.306	OI					2.43
13.250	1.64	1.13	0.310	O					2.45
13.333	1.66	1.15	0.313	O					2.48
13.417	1.69	1.17	0.317	O					2.50
13.500	1.71	1.18	0.320	OI					2.52
13.583	1.74	1.20	0.324	OI					2.55
13.667	1.77	1.22	0.328	OI					2.57
13.750	1.79	1.23	0.331	OI					2.60
13.833	1.82	1.25	0.335	OI					2.63
13.917	1.86	1.27	0.339	OI					2.65
14.000	1.89	1.29	0.343	OI					2.68
14.083	1.93	1.31	0.348	OI					2.71
14.167	1.96	1.33	0.352	OI					2.74
14.250	2.01	1.35	0.356	OI					2.77
14.333	2.05	1.37	0.361	OI					2.80
14.417	2.09	1.39	0.366	OI					2.84
14.500	2.14	1.41	0.371	OI					2.87
14.583	2.20	1.44	0.376	OI					2.90
14.667	2.25	1.46	0.381	O I					2.94
14.750	2.32	1.49	0.387	O I					2.98
14.833	2.38	1.53	0.393	O I					3.01
14.917	2.46	1.58	0.399	O I					3.04
15.000	2.54	1.64	0.405	O I					3.08
15.083	2.63	1.70	0.411	OI					3.11
15.167	2.72	1.76	0.417	OI					3.14
15.250	2.84	1.83	0.424	O I					3.18
15.333	2.96	1.90	0.431	O I					3.21
15.417	3.08	1.97	0.439	O I					3.25
15.500	3.05	2.04	0.446	O I					3.29
15.583	2.97	2.10	0.453	O I					3.32
15.667	3.07	2.16	0.459	O I					3.36
15.750	3.34	2.23	0.466	O I					3.39
15.833	3.77	2.32	0.474	O I					3.44
15.917	4.45	2.43	0.486	O I					3.50
16.000	5.68	2.60	0.504	O	I				3.59
16.083	8.78	2.90	0.535	O	I				3.75
16.167	15.46	3.49	0.596	O			I		4.07
16.250	18.01	4.38	0.684	O				I	4.53
16.333	11.24	5.50	0.751	O	I				4.99
16.417	6.15	5.85	0.772	O					5.13
16.500	4.07	5.77	0.767	O					5.09
16.583	3.62	5.56	0.755	O					5.01
16.667	3.06	5.31	0.740	O					4.91
16.750	2.81	5.05	0.725	O					4.81
16.833	2.61	4.80	0.710	O					4.70
16.917	2.45	4.55	0.695	O					4.60
17.000	2.30	4.31	0.681	O					4.50
17.083	2.19	4.17	0.667	O					4.43
17.167	2.08	4.04	0.653	O					4.36
17.250	2.00	3.91	0.640	O					4.29
17.333	1.92	3.79	0.627	O					4.23
17.417	1.85	3.66	0.614	O					4.16
17.500	1.79	3.55	0.602	O					4.10
17.583	1.73	3.43	0.590	O					4.03
17.667	1.68	3.32	0.579	O					3.98
17.750	1.63	3.21	0.567	O					3.92
17.833	1.59	3.11	0.557	O					3.86

17.917	1.55	3.01	0.546	| I O |	|	|	|	3.81
18.000	1.51	2.92	0.537	| I O |	|	|	|	3.76
18.083	1.47	2.82	0.527	| I O |	|	|	|	3.71
18.167	1.39	2.73	0.518	| I O |	|	|	|	3.66
18.250	1.28	2.64	0.508	| I O |	|	|	|	3.61
18.333	1.21	2.55	0.499	| I O |	|	|	|	3.56
18.417	1.17	2.47	0.490	| I O |	|	|	|	3.52
18.500	1.14	2.38	0.481	| I O |	|	|	|	3.47
18.583	1.12	2.30	0.473	|I O |	|	|	|	3.43
18.667	1.10	2.22	0.465	|I O |	|	|	|	3.39
18.750	1.08	2.15	0.457	|I O |	|	|	|	3.35
18.833	1.06	2.08	0.450	|I O |	|	|	|	3.31
18.917	1.04	2.01	0.443	|I O |	|	|	|	3.28
19.000	1.02	1.95	0.437	|I O |	|	|	|	3.24
19.083	1.00	1.89	0.430	|I O |	|	|	|	3.21
19.167	0.99	1.83	0.425	|I O |	|	|	|	3.18
19.250	0.97	1.78	0.419	|I O |	|	|	|	3.15
19.333	0.96	1.73	0.413	|I O |	|	|	|	3.12
19.417	0.94	1.68	0.408	|IO |	|	|	|	3.09
19.500	0.93	1.63	0.403	|IO |	|	|	|	3.07
19.583	0.91	1.58	0.399	|IO |	|	|	|	3.04
19.667	0.90	1.54	0.394	|IO |	|	|	|	3.02
19.750	0.89	1.50	0.390	|IO |	|	|	|	3.00
19.833	0.88	1.48	0.386	|IO |	|	|	|	2.97
19.917	0.87	1.46	0.381	|IO |	|	|	|	2.94
20.000	0.86	1.44	0.377	|IO |	|	|	|	2.91
20.083	0.85	1.42	0.373	|IO |	|	|	|	2.89
20.167	0.84	1.41	0.369	|IO |	|	|	|	2.86
20.250	0.83	1.39	0.366	|IO |	|	|	|	2.83
20.333	0.82	1.37	0.362	|IO |	|	|	|	2.81
20.417	0.81	1.35	0.358	|IO |	|	|	|	2.78
20.500	0.80	1.34	0.354	|IO |	|	|	|	2.76
20.583	0.79	1.32	0.350	|IO |	|	|	|	2.73
20.667	0.78	1.30	0.347	|IO |	|	|	|	2.71
20.750	0.77	1.29	0.343	|IO |	|	|	|	2.68
20.833	0.76	1.27	0.340	|IO |	|	|	|	2.66
20.917	0.76	1.26	0.336	|IO |	|	|	|	2.63
21.000	0.75	1.24	0.333	|IO |	|	|	|	2.61
21.083	0.74	1.23	0.330	|IO |	|	|	|	2.59
21.167	0.74	1.21	0.326	|IO |	|	|	|	2.57
21.250	0.73	1.20	0.323	|IO |	|	|	|	2.54
21.333	0.72	1.18	0.320	|IO |	|	|	|	2.52
21.417	0.71	1.17	0.317	|IO |	|	|	|	2.50
21.500	0.71	1.15	0.314	|IO |	|	|	|	2.48
21.583	0.70	1.14	0.311	|IO |	|	|	|	2.46
21.667	0.70	1.13	0.308	|O |	|	|	|	2.44
21.750	0.69	1.11	0.305	|O |	|	|	|	2.42
21.833	0.68	1.10	0.302	|O |	|	|	|	2.40
21.917	0.68	1.09	0.299	|O |	|	|	|	2.38
22.000	0.67	1.07	0.296	|O |	|	|	|	2.36
22.083	0.67	1.06	0.293	|O |	|	|	|	2.34
22.167	0.66	1.05	0.291	|O |	|	|	|	2.32
22.250	0.66	1.04	0.288	|O |	|	|	|	2.31
22.333	0.65	1.02	0.285	|O |	|	|	|	2.29
22.417	0.65	1.01	0.283	|O |	|	|	|	2.27
22.500	0.64	1.00	0.280	|O |	|	|	|	2.25
22.583	0.64	0.99	0.278	|O |	|	|	|	2.24
22.667	0.63	0.98	0.276	|O |	|	|	|	2.22
22.750	0.63	0.97	0.273	|O |	|	|	|	2.20
22.833	0.62	0.96	0.271	|O |	|	|	|	2.19
22.917	0.62	0.95	0.269	|O |	|	|	|	2.17
23.000	0.61	0.94	0.266	|O |	|	|	|	2.16
23.083	0.61	0.93	0.264	|O |	|	|	|	2.14
23.167	0.61	0.92	0.262	|O |	|	|	|	2.13
23.250	0.60	0.91	0.260	|O |	|	|	|	2.11
23.333	0.60	0.90	0.258	|O |	|	|	|	2.10
23.417	0.59	0.89	0.256	|O |	|	|	|	2.08
23.500	0.59	0.88	0.254	|O |	|	|	|	2.07
23.583	0.59	0.87	0.252	|O |	|	|	|	2.06
23.667	0.58	0.86	0.250	|O |	|	|	|	2.04
23.750	0.58	0.85	0.248	|O |	|	|	|	2.03

23.833	0.58	0.85	0.246	|O	|	|	|	|	2.02
23.917	0.57	0.84	0.244	|O	|	|	|	|	2.01
24.000	0.57	0.83	0.242	|O	|	|	|	|	1.99
24.083	0.54	0.82	0.240	IO	|	|	|	|	1.98
24.167	0.39	0.81	0.238	IO	|	|	|	|	1.96
24.250	0.16	0.79	0.234	IO	|	|	|	|	1.94
24.333	0.05	0.77	0.230	IO	|	|	|	|	1.91
24.417	0.01	0.75	0.225	IO	|	|	|	|	1.87
24.500	0.01	0.73	0.220	IO	|	|	|	|	1.84
24.583	0.00	0.70	0.215	IO	|	|	|	|	1.81
24.667	0.00	0.68	0.210	IO	|	|	|	|	1.77
24.750	0.00	0.66	0.205	IO	|	|	|	|	1.74
24.833	0.00	0.64	0.201	IO	|	|	|	|	1.71
24.917	0.00	0.62	0.197	IO	|	|	|	|	1.68
25.000	0.00	0.60	0.192	IO	|	|	|	|	1.65
25.083	0.00	0.58	0.188	IO	|	|	|	|	1.62
25.167	0.00	0.57	0.184	IO	|	|	|	|	1.60
25.250	0.00	0.55	0.181	O	|	|	|	|	1.57
25.333	0.00	0.53	0.177	O	|	|	|	|	1.55
25.417	0.00	0.51	0.173	O	|	|	|	|	1.52
25.500	0.00	0.50	0.170	O	|	|	|	|	1.50
25.583	0.00	0.49	0.166	O	|	|	|	|	1.47
25.667	0.00	0.48	0.163	O	|	|	|	|	1.44
25.750	0.00	0.47	0.160	O	|	|	|	|	1.41
25.833	0.00	0.46	0.157	O	|	|	|	|	1.38
25.917	0.00	0.45	0.153	O	|	|	|	|	1.35
26.000	0.00	0.44	0.150	O	|	|	|	|	1.33
26.083	0.00	0.43	0.147	O	|	|	|	|	1.30
26.167	0.00	0.42	0.144	O	|	|	|	|	1.27
26.250	0.00	0.42	0.141	O	|	|	|	|	1.25
26.333	0.00	0.41	0.139	O	|	|	|	|	1.22
26.417	0.00	0.40	0.136	O	|	|	|	|	1.20
26.500	0.00	0.39	0.133	O	|	|	|	|	1.17
26.583	0.00	0.38	0.130	O	|	|	|	|	1.15
26.667	0.00	0.38	0.128	O	|	|	|	|	1.13
26.750	0.00	0.37	0.125	O	|	|	|	|	1.11
26.833	0.00	0.36	0.123	O	|	|	|	|	1.08
26.917	0.00	0.35	0.120	O	|	|	|	|	1.06
27.000	0.00	0.35	0.118	O	|	|	|	|	1.04
27.083	0.00	0.34	0.116	O	|	|	|	|	1.02
27.167	0.00	0.33	0.113	O	|	|	|	|	1.00
27.250	0.00	0.33	0.111	O	|	|	|	|	0.98
27.333	0.00	0.32	0.109	O	|	|	|	|	0.96
27.417	0.00	0.31	0.107	O	|	|	|	|	0.94
27.500	0.00	0.31	0.104	O	|	|	|	|	0.92
27.583	0.00	0.30	0.102	O	|	|	|	|	0.90
27.667	0.00	0.29	0.100	O	|	|	|	|	0.88
27.750	0.00	0.29	0.098	O	|	|	|	|	0.87
27.833	0.00	0.28	0.096	O	|	|	|	|	0.85
27.917	0.00	0.28	0.094	O	|	|	|	|	0.83
28.000	0.00	0.27	0.092	O	|	|	|	|	0.82
28.083	0.00	0.27	0.091	O	|	|	|	|	0.80
28.167	0.00	0.26	0.089	O	|	|	|	|	0.78
28.250	0.00	0.26	0.087	O	|	|	|	|	0.77
28.333	0.00	0.25	0.085	O	|	|	|	|	0.75
28.417	0.00	0.25	0.084	O	|	|	|	|	0.74
28.500	0.00	0.24	0.082	O	|	|	|	|	0.72
28.583	0.00	0.24	0.080	O	|	|	|	|	0.71
28.667	0.00	0.23	0.079	O	|	|	|	|	0.69
28.750	0.00	0.23	0.077	O	|	|	|	|	0.68
28.833	0.00	0.22	0.075	O	|	|	|	|	0.67
28.917	0.00	0.22	0.074	O	|	|	|	|	0.65
29.000	0.00	0.21	0.072	O	|	|	|	|	0.64
29.083	0.00	0.21	0.071	O	|	|	|	|	0.63
29.167	0.00	0.20	0.070	O	|	|	|	|	0.61
29.250	0.00	0.20	0.068	O	|	|	|	|	0.60
29.333	0.00	0.20	0.067	O	|	|	|	|	0.59
29.417	0.00	0.19	0.066	O	|	|	|	|	0.58
29.500	0.00	0.19	0.064	O	|	|	|	|	0.57
29.583	0.00	0.19	0.063	O	|	|	|	|	0.56
29.667	0.00	0.18	0.062	O	|	|	|	|	0.54

29.750	0.00	0.18	0.060	O	|	|	|	|	0.53
29.833	0.00	0.17	0.059	O	|	|	|	|	0.52
29.917	0.00	0.17	0.058	O	|	|	|	|	0.51
30.000	0.00	0.17	0.057	O	|	|	|	|	0.50
30.083	0.00	0.16	0.056	O	|	|	|	|	0.49
30.167	0.00	0.16	0.055	O	|	|	|	|	0.48
30.250	0.00	0.16	0.053	O	|	|	|	|	0.47
30.333	0.00	0.15	0.052	O	|	|	|	|	0.46
30.417	0.00	0.15	0.051	O	|	|	|	|	0.45
30.500	0.00	0.15	0.050	O	|	|	|	|	0.44
30.583	0.00	0.15	0.049	O	|	|	|	|	0.44
30.667	0.00	0.14	0.048	O	|	|	|	|	0.43
30.750	0.00	0.14	0.047	O	|	|	|	|	0.42
30.833	0.00	0.14	0.046	O	|	|	|	|	0.41
30.917	0.00	0.13	0.045	O	|	|	|	|	0.40
31.000	0.00	0.13	0.045	O	|	|	|	|	0.39
31.083	0.00	0.13	0.044	O	|	|	|	|	0.39
31.167	0.00	0.13	0.043	O	|	|	|	|	0.38
31.250	0.00	0.12	0.042	O	|	|	|	|	0.37
31.333	0.00	0.12	0.041	O	|	|	|	|	0.36
31.417	0.00	0.12	0.040	O	|	|	|	|	0.36
31.500	0.00	0.12	0.039	O	|	|	|	|	0.35
31.583	0.00	0.11	0.039	O	|	|	|	|	0.34
31.667	0.00	0.11	0.038	O	|	|	|	|	0.33
31.750	0.00	0.11	0.037	O	|	|	|	|	0.33
31.833	0.00	0.11	0.036	O	|	|	|	|	0.32
31.917	0.00	0.10	0.036	O	|	|	|	|	0.31
32.000	0.00	0.10	0.035	O	|	|	|	|	0.31
32.083	0.00	0.10	0.034	O	|	|	|	|	0.30
32.167	0.00	0.10	0.034	O	|	|	|	|	0.30
32.250	0.00	0.10	0.033	O	|	|	|	|	0.29
32.333	0.00	0.09	0.032	O	|	|	|	|	0.28
32.417	0.00	0.09	0.032	O	|	|	|	|	0.28
32.500	0.00	0.09	0.031	O	|	|	|	|	0.27
32.583	0.00	0.09	0.030	O	|	|	|	|	0.27
32.667	0.00	0.09	0.030	O	|	|	|	|	0.26
32.750	0.00	0.09	0.029	O	|	|	|	|	0.26
32.833	0.00	0.08	0.029	O	|	|	|	|	0.25
32.917	0.00	0.08	0.028	O	|	|	|	|	0.25
33.000	0.00	0.08	0.027	O	|	|	|	|	0.24
33.083	0.00	0.08	0.027	O	|	|	|	|	0.24
33.167	0.00	0.08	0.026	O	|	|	|	|	0.23
33.250	0.00	0.08	0.026	O	|	|	|	|	0.23
33.333	0.00	0.07	0.025	O	|	|	|	|	0.22
33.417	0.00	0.07	0.025	O	|	|	|	|	0.22
33.500	0.00	0.07	0.024	O	|	|	|	|	0.21
33.583	0.00	0.07	0.024	O	|	|	|	|	0.21
33.667	0.00	0.07	0.023	O	|	|	|	|	0.21
33.750	0.00	0.07	0.023	O	|	|	|	|	0.20
33.833	0.00	0.07	0.022	O	|	|	|	|	0.20
33.917	0.00	0.06	0.022	O	|	|	|	|	0.19
34.000	0.00	0.06	0.021	O	|	|	|	|	0.19
34.083	0.00	0.06	0.021	O	|	|	|	|	0.19
34.167	0.00	0.06	0.021	O	|	|	|	|	0.18
34.250	0.00	0.06	0.020	O	|	|	|	|	0.18
34.333	0.00	0.06	0.020	O	|	|	|	|	0.17
34.417	0.00	0.06	0.019	O	|	|	|	|	0.17
34.500	0.00	0.06	0.019	O	|	|	|	|	0.17
34.583	0.00	0.05	0.019	O	|	|	|	|	0.16
34.667	0.00	0.05	0.018	O	|	|	|	|	0.16
34.750	0.00	0.05	0.018	O	|	|	|	|	0.16
34.833	0.00	0.05	0.018	O	|	|	|	|	0.15
34.917	0.00	0.05	0.017	O	|	|	|	|	0.15
35.000	0.00	0.05	0.017	O	|	|	|	|	0.15
35.083	0.00	0.05	0.017	O	|	|	|	|	0.15
35.167	0.00	0.05	0.016	O	|	|	|	|	0.14
35.250	0.00	0.05	0.016	O	|	|	|	|	0.14
35.333	0.00	0.05	0.016	O	|	|	|	|	0.14
35.417	0.00	0.04	0.015	O	|	|	|	|	0.13
35.500	0.00	0.04	0.015	O	|	|	|	|	0.13
35.583	0.00	0.04	0.015	O	|	|	|	|	0.13

35.667	0.00	0.04	0.014	O	|	|	|	0.13
35.750	0.00	0.04	0.014	O	|	|	|	0.12
35.833	0.00	0.04	0.014	O	|	|	|	0.12
35.917	0.00	0.04	0.013	O	|	|	|	0.12
36.000	0.00	0.04	0.013	O	|	|	|	0.12
36.083	0.00	0.04	0.013	O	|	|	|	0.11
36.167	0.00	0.04	0.013	O	|	|	|	0.11
36.250	0.00	0.04	0.012	O	|	|	|	0.11
36.333	0.00	0.04	0.012	O	|	|	|	0.11
36.417	0.00	0.04	0.012	O	|	|	|	0.11
36.500	0.00	0.03	0.012	O	|	|	|	0.10
36.583	0.00	0.03	0.011	O	|	|	|	0.10
36.667	0.00	0.03	0.011	O	|	|	|	0.10
36.750	0.00	0.03	0.011	O	|	|	|	0.10
36.833	0.00	0.03	0.011	O	|	|	|	0.10
36.917	0.00	0.03	0.011	O	|	|	|	0.09
37.000	0.00	0.03	0.010	O	|	|	|	0.09
37.083	0.00	0.03	0.010	O	|	|	|	0.09
37.167	0.00	0.03	0.010	O	|	|	|	0.09
37.250	0.00	0.03	0.010	O	|	|	|	0.09
37.333	0.00	0.03	0.010	O	|	|	|	0.08
37.417	0.00	0.03	0.009	O	|	|	|	0.08
37.500	0.00	0.03	0.009	O	|	|	|	0.08
37.583	0.00	0.03	0.009	O	|	|	|	0.08
37.667	0.00	0.03	0.009	O	|	|	|	0.08
37.750	0.00	0.03	0.009	O	|	|	|	0.08
37.833	0.00	0.02	0.008	O	|	|	|	0.07
37.917	0.00	0.02	0.008	O	|	|	|	0.07
38.000	0.00	0.02	0.008	O	|	|	|	0.07
38.083	0.00	0.02	0.008	O	|	|	|	0.07
38.167	0.00	0.02	0.008	O	|	|	|	0.07
38.250	0.00	0.02	0.008	O	|	|	|	0.07
38.333	0.00	0.02	0.007	O	|	|	|	0.07
38.417	0.00	0.02	0.007	O	|	|	|	0.06
38.500	0.00	0.02	0.007	O	|	|	|	0.06
38.583	0.00	0.02	0.007	O	|	|	|	0.06
38.667	0.00	0.02	0.007	O	|	|	|	0.06
38.750	0.00	0.02	0.007	O	|	|	|	0.06
38.833	0.00	0.02	0.007	O	|	|	|	0.06
38.917	0.00	0.02	0.007	O	|	|	|	0.06
39.000	0.00	0.02	0.006	O	|	|	|	0.06
39.083	0.00	0.02	0.006	O	|	|	|	0.06
39.167	0.00	0.02	0.006	O	|	|	|	0.05
39.250	0.00	0.02	0.006	O	|	|	|	0.05
39.333	0.00	0.02	0.006	O	|	|	|	0.05
39.417	0.00	0.02	0.006	O	|	|	|	0.05
39.500	0.00	0.02	0.006	O	|	|	|	0.05
39.583	0.00	0.02	0.006	O	|	|	|	0.05
39.667	0.00	0.02	0.005	O	|	|	|	0.05
39.750	0.00	0.02	0.005	O	|	|	|	0.05
39.833	0.00	0.02	0.005	O	|	|	|	0.05
39.917	0.00	0.02	0.005	O	|	|	|	0.05
40.000	0.00	0.01	0.005	O	|	|	|	0.04
40.083	0.00	0.01	0.005	O	|	|	|	0.04
40.167	0.00	0.01	0.005	O	|	|	|	0.04
40.250	0.00	0.01	0.005	O	|	|	|	0.04
40.333	0.00	0.01	0.005	O	|	|	|	0.04
40.417	0.00	0.01	0.005	O	|	|	|	0.04
40.500	0.00	0.01	0.004	O	|	|	|	0.04
40.583	0.00	0.01	0.004	O	|	|	|	0.04
40.667	0.00	0.01	0.004	O	|	|	|	0.04
40.750	0.00	0.01	0.004	O	|	|	|	0.04
40.833	0.00	0.01	0.004	O	|	|	|	0.04
40.917	0.00	0.01	0.004	O	|	|	|	0.04
41.000	0.00	0.01	0.004	O	|	|	|	0.03
41.083	0.00	0.01	0.004	O	|	|	|	0.03
41.167	0.00	0.01	0.004	O	|	|	|	0.03
41.250	0.00	0.01	0.004	O	|	|	|	0.03
41.333	0.00	0.01	0.004	O	|	|	|	0.03
41.417	0.00	0.01	0.004	O	|	|	|	0.03
41.500	0.00	0.01	0.003	O	|	|	|	0.03

41.583	0.00	0.01	0.003	O	|	|	|	|	0.03
41.667	0.00	0.01	0.003	O	|	|	|	|	0.03
41.750	0.00	0.01	0.003	O	|	|	|	|	0.03
41.833	0.00	0.01	0.003	O	|	|	|	|	0.03
41.917	0.00	0.01	0.003	O	|	|	|	|	0.03
42.000	0.00	0.01	0.003	O	|	|	|	|	0.03
42.083	0.00	0.01	0.003	O	|	|	|	|	0.03
42.167	0.00	0.01	0.003	O	|	|	|	|	0.03
42.250	0.00	0.01	0.003	O	|	|	|	|	0.03
42.333	0.00	0.01	0.003	O	|	|	|	|	0.03
42.417	0.00	0.01	0.003	O	|	|	|	|	0.02
42.500	0.00	0.01	0.003	O	|	|	|	|	0.02
42.583	0.00	0.01	0.003	O	|	|	|	|	0.02
42.667	0.00	0.01	0.003	O	|	|	|	|	0.02
42.750	0.00	0.01	0.003	O	|	|	|	|	0.02
42.833	0.00	0.01	0.003	O	|	|	|	|	0.02
42.917	0.00	0.01	0.002	O	|	|	|	|	0.02
43.000	0.00	0.01	0.002	O	|	|	|	|	0.02
43.083	0.00	0.01	0.002	O	|	|	|	|	0.02
43.167	0.00	0.01	0.002	O	|	|	|	|	0.02
43.250	0.00	0.01	0.002	O	|	|	|	|	0.02
43.333	0.00	0.01	0.002	O	|	|	|	|	0.02
43.417	0.00	0.01	0.002	O	|	|	|	|	0.02
43.500	0.00	0.01	0.002	O	|	|	|	|	0.02
43.583	0.00	0.01	0.002	O	|	|	|	|	0.02
43.667	0.00	0.01	0.002	O	|	|	|	|	0.02
43.750	0.00	0.01	0.002	O	|	|	|	|	0.02
43.833	0.00	0.01	0.002	O	|	|	|	|	0.02
43.917	0.00	0.01	0.002	O	|	|	|	|	0.02
44.000	0.00	0.01	0.002	O	|	|	|	|	0.02
44.083	0.00	0.01	0.002	O	|	|	|	|	0.02
44.167	0.00	0.01	0.002	O	|	|	|	|	0.02
44.250	0.00	0.01	0.002	O	|	|	|	|	0.02
44.333	0.00	0.01	0.002	O	|	|	|	|	0.02
44.417	0.00	0.01	0.002	O	|	|	|	|	0.02
44.500	0.00	0.00	0.002	O	|	|	|	|	0.01
44.583	0.00	0.00	0.002	O	|	|	|	|	0.01
44.667	0.00	0.00	0.002	O	|	|	|	|	0.01
44.750	0.00	0.00	0.002	O	|	|	|	|	0.01
44.833	0.00	0.00	0.002	O	|	|	|	|	0.01
44.917	0.00	0.00	0.002	O	|	|	|	|	0.01
45.000	0.00	0.00	0.001	O	|	|	|	|	0.01
45.083	0.00	0.00	0.001	O	|	|	|	|	0.01
45.167	0.00	0.00	0.001	O	|	|	|	|	0.01
45.250	0.00	0.00	0.001	O	|	|	|	|	0.01
45.333	0.00	0.00	0.001	O	|	|	|	|	0.01
45.417	0.00	0.00	0.001	O	|	|	|	|	0.01
45.500	0.00	0.00	0.001	O	|	|	|	|	0.01
45.583	0.00	0.00	0.001	O	|	|	|	|	0.01
45.667	0.00	0.00	0.001	O	|	|	|	|	0.01
45.750	0.00	0.00	0.001	O	|	|	|	|	0.01
45.833	0.00	0.00	0.001	O	|	|	|	|	0.01
45.917	0.00	0.00	0.001	O	|	|	|	|	0.01
46.000	0.00	0.00	0.001	O	|	|	|	|	0.01
46.083	0.00	0.00	0.001	O	|	|	|	|	0.01
46.167	0.00	0.00	0.001	O	|	|	|	|	0.01
46.250	0.00	0.00	0.001	O	|	|	|	|	0.01
46.333	0.00	0.00	0.001	O	|	|	|	|	0.01
46.417	0.00	0.00	0.001	O	|	|	|	|	0.01
46.500	0.00	0.00	0.001	O	|	|	|	|	0.01
46.583	0.00	0.00	0.001	O	|	|	|	|	0.01
46.667	0.00	0.00	0.001	O	|	|	|	|	0.01
46.750	0.00	0.00	0.001	O	|	|	|	|	0.01
46.833	0.00	0.00	0.001	O	|	|	|	|	0.01
46.917	0.00	0.00	0.001	O	|	|	|	|	0.01
47.000	0.00	0.00	0.001	O	|	|	|	|	0.01
47.083	0.00	0.00	0.001	O	|	|	|	|	0.01
47.167	0.00	0.00	0.001	O	|	|	|	|	0.01
47.250	0.00	0.00	0.001	O	|	|	|	|	0.01
47.333	0.00	0.00	0.001	O	|	|	|	|	0.01
47.417	0.00	0.00	0.001	O	|	|	|	|	0.01

47.500	0.00	0.00	0.001	O	|	|	|	|	0.01
47.583	0.00	0.00	0.001	O	|	|	|	|	0.01
47.667	0.00	0.00	0.001	O	|	|	|	|	0.01
47.750	0.00	0.00	0.001	O	|	|	|	|	0.01
47.833	0.00	0.00	0.001	O	|	|	|	|	0.01
47.917	0.00	0.00	0.001	O	|	|	|	|	0.01
48.000	0.00	0.00	0.001	O	|	|	|	|	0.01
48.083	0.00	0.00	0.001	O	|	|	|	|	0.01
48.167	0.00	0.00	0.001	O	|	|	|	|	0.01
48.250	0.00	0.00	0.001	O	|	|	|	|	0.01
48.333	0.00	0.00	0.001	O	|	|	|	|	0.01
48.417	0.00	0.00	0.001	O	|	|	|	|	0.01
48.500	0.00	0.00	0.001	O	|	|	|	|	0.01
48.583	0.00	0.00	0.001	O	|	|	|	|	0.01
48.667	0.00	0.00	0.001	O	|	|	|	|	0.01
48.750	0.00	0.00	0.001	O	|	|	|	|	0.01
48.833	0.00	0.00	0.001	O	|	|	|	|	0.01
48.917	0.00	0.00	0.001	O	|	|	|	|	0.01
49.000	0.00	0.00	0.001	O	|	|	|	|	0.00
49.083	0.00	0.00	0.001	O	|	|	|	|	0.00
49.167	0.00	0.00	0.001	O	|	|	|	|	0.00
49.250	0.00	0.00	0.001	O	|	|	|	|	0.00
49.333	0.00	0.00	0.001	O	|	|	|	|	0.00
49.417	0.00	0.00	0.001	O	|	|	|	|	0.00
49.500	0.00	0.00	0.000	O	|	|	|	|	0.00
49.583	0.00	0.00	0.000	O	|	|	|	|	0.00
49.667	0.00	0.00	0.000	O	|	|	|	|	0.00
49.750	0.00	0.00	0.000	O	|	|	|	|	0.00
49.833	0.00	0.00	0.000	O	|	|	|	|	0.00
49.917	0.00	0.00	0.000	O	|	|	|	|	0.00
50.000	0.00	0.00	0.000	O	|	|	|	|	0.00
50.083	0.00	0.00	0.000	O	|	|	|	|	0.00
50.167	0.00	0.00	0.000	O	|	|	|	|	0.00
50.250	0.00	0.00	0.000	O	|	|	|	|	0.00
50.333	0.00	0.00	0.000	O	|	|	|	|	0.00
50.417	0.00	0.00	0.000	O	|	|	|	|	0.00
50.500	0.00	0.00	0.000	O	|	|	|	|	0.00
50.583	0.00	0.00	0.000	O	|	|	|	|	0.00
50.667	0.00	0.00	0.000	O	|	|	|	|	0.00
50.750	0.00	0.00	0.000	O	|	|	|	|	0.00
50.833	0.00	0.00	0.000	O	|	|	|	|	0.00
50.917	0.00	0.00	0.000	O	|	|	|	|	0.00
51.000	0.00	0.00	0.000	O	|	|	|	|	0.00
51.083	0.00	0.00	0.000	O	|	|	|	|	0.00

**********HYDROGRAPH DATA**********

Number of intervals = 613
Time interval = 5.0 (Min.)
Maximum/Peak flow rate = 5.848 (CFS)
Total volume = 2.584 (Ac.Ft)

Status of hydrographs being held in storage

	Stream 1	Stream 2	Stream 3	Stream 4	Stream 5
Peak (CFS)	0.000	0.000	0.000	0.000	0.000
Vol (Ac.Ft)	0.000	0.000	0.000	0.000	0.000

****

Flood Routing Analysis: Developed Condition
(10 yr Storm Event)

```
                FLOOD HYDROGRAPH ROUTING PROGRAM
          Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018
                      Study date: 07/01/23


------------------------------------------------------------------------


CHAMBER ROUTING
CONCO INDUSTRIAL
10-YR STORM EVENT

------------------------------------------------------------------------


Program License Serial Number 6484

------------------------------------------------------------------------
******************** HYDROGRAPH INFORMATION **********************

               From study/file name: CON1.rte
*****************************HYDROGRAPH DATA****************************
               Number of intervals =   294
               Time interval =    5.0 (Min.)
               Maximum/Peak flow rate =       14.597 (CFS)
               Total volume =       2.122 (Ac.Ft)
       Status of hydrographs being held in storage
                  Stream 1  Stream 2  Stream 3  Stream 4  Stream 5
       Peak (CFS)      0.000     0.000     0.000     0.000     0.000
       Vol (Ac.Ft)      0.000     0.000     0.000     0.000     0.000
************************************************************************



++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
Process from Point/Station        0.000 to Point/Station        1.000
**** RETARDING BASIN ROUTING ****
________________________________________________________________________

User entry of depth-outflow-storage data
------------------------------------------------------------------------
Total number of inflow hydrograph intervals = 294
Hydrograph time unit =  5.000 (Min.)
Initial depth in storage basin =   0.00(Ft.)
------------------------------------------------------------------------
------------------------------------------------------------------------
Initial basin depth =   0.00 (Ft.)
Initial basin storage =      0.00 (Ac.Ft)
Initial basin outflow =   0.00 (CFS)
------------------------------------------------------------------------
------------------------------------------------------------------------
Depth vs. Storage and Depth vs. Discharge data:
 Basin Depth  Storage    Outflow   (S-O*dt/2)   (S+O*dt/2)
     (Ft.)    (Ac.Ft)    (CFS)     (Ac.Ft)    (Ac.Ft)
------------------------------------------------------------------------
   0.000      0.000      0.000      0.000        0.000
   1.500      0.170      0.500      0.168        0.172
   3.000      0.390      1.500      0.385        0.395
   4.500      0.680      4.300      0.665        0.695
   6.000      0.900      8.000      0.872        0.928
   6.700      0.960      8.700      0.930        0.990
------------------------------------------------------------------------
               Hydrograph Detention Basin Routing
------------------------------------------------------------------------

Graph values: 'I'= unit inflow; 'O'=outflow at time shown
------------------------------------------------------------------------
 Time   Inflow  Outflow    Storage                                    Depth
(Hours)  (CFS)   (CFS)     (Ac.Ft) .0       3.6    7.30   10.95   14.60 (Ft.)
 0.083    0.02    0.00      0.000  O       |       |       |       |     0.00
```

0.167	0.14	0.00	0.001	O				0.01
0.250	0.33	0.01	0.002	O				0.02
0.333	0.42	0.01	0.005	O				0.04
0.417	0.45	0.02	0.008	O				0.07
0.500	0.46	0.03	0.011	OI				0.09
0.583	0.46	0.04	0.013	OI				0.12
0.667	0.47	0.05	0.016	OI				0.14
0.750	0.47	0.06	0.019	OI				0.17
0.833	0.47	0.06	0.022	OI				0.19
0.917	0.47	0.07	0.025	OI				0.22
1.000	0.47	0.08	0.028	OI				0.24
1.083	0.47	0.09	0.030	OI				0.27
1.167	0.47	0.10	0.033	OI				0.29
1.250	0.48	0.10	0.035	OI				0.31
1.333	0.48	0.11	0.038	OI				0.33
1.417	0.48	0.12	0.040	OI				0.36
1.500	0.48	0.13	0.043	OI				0.38
1.583	0.48	0.13	0.045	OI				0.40
1.667	0.48	0.14	0.048	OI				0.42
1.750	0.49	0.15	0.050	OI				0.44
1.833	0.49	0.15	0.052	OI				0.46
1.917	0.49	0.16	0.055	OI				0.48
2.000	0.49	0.17	0.057	OI				0.50
2.083	0.49	0.17	0.059	OI				0.52
2.167	0.49	0.18	0.061	OI				0.54
2.250	0.50	0.19	0.063	OI				0.56
2.333	0.50	0.19	0.066	OI				0.58
2.417	0.50	0.20	0.068	OI				0.60
2.500	0.50	0.20	0.070	OI				0.61
2.583	0.50	0.21	0.072	OI				0.63
2.667	0.50	0.22	0.074	OI				0.65
2.750	0.51	0.22	0.076	OI				0.67
2.833	0.51	0.23	0.078	OI				0.68
2.917	0.51	0.23	0.079	OI				0.70
3.000	0.51	0.24	0.081	OI				0.72
3.083	0.51	0.24	0.083	OI				0.73
3.167	0.51	0.25	0.085	OI				0.75
3.250	0.52	0.26	0.087	OI				0.77
3.333	0.52	0.26	0.089	OI				0.78
3.417	0.52	0.27	0.090	OI				0.80
3.500	0.52	0.27	0.092	OI				0.81
3.583	0.52	0.28	0.094	OI				0.83
3.667	0.53	0.28	0.096	OI				0.84
3.750	0.53	0.29	0.097	OI				0.86
3.833	0.53	0.29	0.099	OI				0.87
3.917	0.53	0.30	0.101	OI				0.89
4.000	0.53	0.30	0.102	OI				0.90
4.083	0.54	0.31	0.104	OI				0.92
4.167	0.54	0.31	0.105	OI				0.93
4.250	0.54	0.31	0.107	OI				0.94
4.333	0.54	0.32	0.108	OI				0.96
4.417	0.54	0.32	0.110	OI				0.97
4.500	0.55	0.33	0.111	OI				0.98
4.583	0.55	0.33	0.113	OI				1.00
4.667	0.55	0.34	0.114	OI				1.01
4.750	0.55	0.34	0.116	OI				1.02
4.833	0.56	0.35	0.117	OI				1.04
4.917	0.56	0.35	0.119	OI				1.05
5.000	0.56	0.35	0.120	OI				1.06
5.083	0.56	0.36	0.122	OI				1.07
5.167	0.57	0.36	0.123	OI				1.09
5.250	0.57	0.37	0.124	OI				1.10
5.333	0.57	0.37	0.126	OI				1.11
5.417	0.57	0.37	0.127	OI				1.12
5.500	0.57	0.38	0.129	OI				1.13
5.583	0.58	0.38	0.130	OI				1.15
5.667	0.58	0.39	0.131	OI				1.16
5.750	0.58	0.39	0.133	OI				1.17
5.833	0.59	0.39	0.134	OI				1.18
5.917	0.59	0.40	0.135	OI				1.19
6.000	0.59	0.40	0.137	OI				1.20

6.083	0.59	0.41	0.138	OI					1.22
6.167	0.60	0.41	0.139	OI					1.23
6.250	0.60	0.41	0.140	OI					1.24
6.333	0.60	0.42	0.142	OI					1.25
6.417	0.60	0.42	0.143	OI					1.26
6.500	0.61	0.42	0.144	OI					1.27
6.583	0.61	0.43	0.145	OI					1.28
6.667	0.61	0.43	0.147	OI					1.29
6.750	0.62	0.44	0.148	OI					1.31
6.833	0.62	0.44	0.149	OI					1.32
6.917	0.62	0.44	0.150	OI					1.33
7.000	0.63	0.45	0.152	OI					1.34
7.083	0.63	0.45	0.153	OI					1.35
7.167	0.63	0.45	0.154	OI					1.36
7.250	0.64	0.46	0.155	|O					1.37
7.333	0.64	0.46	0.157	|O					1.38
7.417	0.64	0.46	0.158	|O					1.39
7.500	0.65	0.47	0.159	|O					1.40
7.583	0.65	0.47	0.160	|O					1.41
7.667	0.65	0.48	0.162	|O					1.43
7.750	0.66	0.48	0.163	|O					1.44
7.833	0.66	0.48	0.164	|O					1.45
7.917	0.66	0.49	0.165	|O					1.46
8.000	0.67	0.49	0.166	|O					1.47
8.083	0.67	0.49	0.168	|O					1.48
8.167	0.68	0.50	0.169	|O					1.49
8.250	0.68	0.50	0.170	|O					1.50
8.333	0.68	0.51	0.171	|O					1.51
8.417	0.69	0.51	0.173	|O					1.52
8.500	0.69	0.52	0.174	|O					1.53
8.583	0.70	0.52	0.175	|O					1.53
8.667	0.70	0.53	0.176	|O					1.54
8.750	0.70	0.53	0.177	|O					1.55
8.833	0.71	0.54	0.179	|O					1.56
8.917	0.71	0.54	0.180	|O					1.57
9.000	0.72	0.55	0.181	|O					1.57
9.083	0.72	0.55	0.182	|O					1.58
9.167	0.73	0.56	0.183	|O					1.59
9.250	0.73	0.57	0.184	|O					1.60
9.333	0.74	0.57	0.185	|O					1.61
9.417	0.74	0.58	0.187	|O					1.61
9.500	0.75	0.58	0.188	|O					1.62
9.583	0.75	0.59	0.189	|O					1.63
9.667	0.76	0.59	0.190	|O					1.64
9.750	0.76	0.60	0.191	|O					1.64
9.833	0.77	0.60	0.192	|O					1.65
9.917	0.78	0.61	0.194	|O					1.66
10.000	0.78	0.61	0.195	|O					1.67
10.083	0.79	0.62	0.196	|O					1.68
10.167	0.79	0.62	0.197	|O					1.68
10.250	0.80	0.63	0.198	|O					1.69
10.333	0.81	0.63	0.199	|O					1.70
10.417	0.81	0.64	0.201	|O					1.71
10.500	0.82	0.64	0.202	|O					1.72
10.583	0.83	0.65	0.203	|O					1.72
10.667	0.83	0.66	0.204	|O					1.73
10.750	0.84	0.66	0.205	|O					1.74
10.833	0.85	0.67	0.207	|O					1.75
10.917	0.85	0.67	0.208	|O					1.76
11.000	0.86	0.68	0.209	|O					1.77
11.083	0.87	0.68	0.210	|O					1.78
11.167	0.88	0.69	0.212	|O					1.78
11.250	0.89	0.70	0.213	|O					1.79
11.333	0.89	0.70	0.214	|O					1.80
11.417	0.90	0.71	0.216	|O					1.81
11.500	0.91	0.71	0.217	|O					1.82
11.583	0.92	0.72	0.218	|OI					1.83
11.667	0.93	0.73	0.220	|OI					1.84
11.750	0.94	0.73	0.221	|OI					1.85
11.833	0.95	0.74	0.223	|OI					1.86
11.917	0.96	0.75	0.224	|OI					1.87

12.000	0.97	0.75	0.226	OI				1.88
12.083	0.99	0.76	0.227	OI				1.89
12.167	1.05	0.77	0.229	OI				1.90
12.250	1.14	0.78	0.231	OI				1.92
12.333	1.19	0.79	0.234	OI				1.93
12.417	1.21	0.80	0.237	OI				1.95
12.500	1.23	0.82	0.239	OI				1.97
12.583	1.24	0.83	0.242	OI				1.99
12.667	1.26	0.84	0.245	OI				2.01
12.750	1.27	0.85	0.248	OI				2.03
12.833	1.29	0.87	0.251	OI				2.05
12.917	1.30	0.88	0.254	OI				2.07
13.000	1.32	0.89	0.257	OI				2.09
13.083	1.34	0.91	0.260	OI				2.11
13.167	1.35	0.92	0.263	O				2.13
13.250	1.37	0.93	0.266	OI				2.15
13.333	1.39	0.95	0.269	OI				2.17
13.417	1.41	0.96	0.272	OI				2.19
13.500	1.43	0.98	0.275	OI				2.21
13.583	1.45	0.99	0.278	OI				2.24
13.667	1.47	1.01	0.281	OI				2.26
13.750	1.50	1.02	0.284	OI				2.28
13.833	1.52	1.03	0.288	OI				2.30
13.917	1.55	1.05	0.291	OI				2.33
14.000	1.58	1.07	0.295	OI				2.35
14.083	1.61	1.08	0.298	OI				2.37
14.167	1.64	1.10	0.302	OI				2.40
14.250	1.67	1.12	0.306	OI				2.42
14.333	1.70	1.13	0.309	OI				2.45
14.417	1.74	1.15	0.313	OI				2.48
14.500	1.78	1.17	0.318	OI				2.51
14.583	1.83	1.19	0.322	O I				2.54
14.667	1.87	1.21	0.326	O I				2.57
14.750	1.92	1.23	0.331	O I				2.60
14.833	1.98	1.25	0.336	O I				2.63
14.917	2.04	1.28	0.341	O I				2.67
15.000	2.10	1.30	0.346	O I				2.70
15.083	2.17	1.33	0.352	O I				2.74
15.167	2.25	1.35	0.358	O I				2.78
15.250	2.34	1.38	0.364	O I				2.82
15.333	2.45	1.41	0.371	O I				2.87
15.417	2.53	1.45	0.378	O I				2.92
15.500	2.50	1.48	0.386	O I				2.97
15.583	2.41	1.52	0.392	O I				3.01
15.667	2.48	1.58	0.398	O I				3.04
15.750	2.69	1.65	0.405	O I				3.08
15.833	3.02	1.72	0.413	O I				3.12
15.917	3.54	1.82	0.424	O I				3.17
16.000	4.53	1.97	0.438	O I				3.25
16.083	7.04	2.21	0.464	O I				3.38
16.167	12.47	2.70	0.514	O			I	3.64
16.250	14.60	3.39	0.586	O			I	4.02
16.333	9.15	3.94	0.643	O	I			4.31
16.417	5.01	4.14	0.664	OI				4.42
16.500	3.31	4.14	0.664	I O				4.42
16.583	2.97	4.08	0.657	I O				4.38
16.667	2.52	3.99	0.648	I O				4.34
16.750	2.32	3.89	0.638	I O				4.28
16.833	2.16	3.79	0.627	I O				4.22
16.917	2.03	3.68	0.615	I O				4.17
17.000	1.91	3.57	0.604	I O				4.11
17.083	1.82	3.46	0.593	I O				4.05
17.167	1.74	3.35	0.582	I O				3.99
17.250	1.66	3.24	0.571	I O				3.93
17.333	1.60	3.14	0.560	I O				3.88
17.417	1.54	3.04	0.549	I O				3.82
17.500	1.49	2.94	0.539	I O				3.77
17.583	1.45	2.85	0.529	I O				3.72
17.667	1.41	2.75	0.520	I O				3.67
17.750	1.37	2.67	0.511	I O				3.62
17.833	1.33	2.58	0.502	I O				3.58

17.917	1.30	2.50	0.494	| I O |	|	|	|	3.54
18.000	1.27	2.42	0.485	| I O |	|	|	|	3.49
18.083	1.23	2.35	0.478	| I O |	|	|	|	3.45
18.167	1.16	2.27	0.470	| I O |	|	|	|	3.41
18.250	1.06	2.20	0.462	| I O |	|	|	|	3.37
18.333	1.00	2.12	0.454	| I O |	|	|	|	3.33
18.417	0.96	2.05	0.447	| I O |	|	|	|	3.29
18.500	0.94	1.98	0.439	| I O |	|	|	|	3.26
18.583	0.92	1.91	0.433	| I O |	|	|	|	3.22
18.667	0.90	1.85	0.426	|I O |	|	|	|	3.19
18.750	0.88	1.78	0.419	|I O |	|	|	|	3.15
18.833	0.87	1.73	0.413	|I O |	|	|	|	3.12
18.917	0.85	1.67	0.408	|I O |	|	|	|	3.09
19.000	0.84	1.62	0.402	|I O |	|	|	|	3.06
19.083	0.82	1.57	0.397	|I O |	|	|	|	3.04
19.167	0.81	1.52	0.392	|I O |	|	|	|	3.01
19.250	0.80	1.49	0.387	|I O |	|	|	|	2.98
19.333	0.79	1.47	0.382	|I O |	|	|	|	2.95
19.417	0.77	1.44	0.378	|I O |	|	|	|	2.92
19.500	0.76	1.42	0.373	|I O |	|	|	|	2.88
19.583	0.75	1.40	0.369	|I O |	|	|	|	2.85
19.667	0.74	1.38	0.364	|I O |	|	|	|	2.82
19.750	0.73	1.36	0.360	|IO |	|	|	|	2.79
19.833	0.72	1.34	0.355	|IO |	|	|	|	2.76
19.917	0.71	1.32	0.351	|IO |	|	|	|	2.74
20.000	0.70	1.30	0.347	|IO |	|	|	|	2.71
20.083	0.69	1.29	0.343	|IO |	|	|	|	2.68
20.167	0.69	1.27	0.339	|IO |	|	|	|	2.65
20.250	0.68	1.25	0.335	|IO |	|	|	|	2.62
20.333	0.67	1.23	0.331	|IO |	|	|	|	2.60
20.417	0.66	1.21	0.327	|IO |	|	|	|	2.57
20.500	0.66	1.20	0.323	|IO |	|	|	|	2.55
20.583	0.65	1.18	0.320	|IO |	|	|	|	2.52
20.667	0.64	1.16	0.316	|IO |	|	|	|	2.50
20.750	0.63	1.15	0.313	|IO |	|	|	|	2.47
20.833	0.63	1.13	0.309	|IO |	|	|	|	2.45
20.917	0.62	1.12	0.306	|IO |	|	|	|	2.42
21.000	0.62	1.10	0.302	|IO |	|	|	|	2.40
21.083	0.61	1.09	0.299	|IO |	|	|	|	2.38
21.167	0.60	1.07	0.296	|IO |	|	|	|	2.36
21.250	0.60	1.06	0.292	|IO |	|	|	|	2.33
21.333	0.59	1.04	0.289	|IO |	|	|	|	2.31
21.417	0.59	1.03	0.286	|IO |	|	|	|	2.29
21.500	0.58	1.01	0.283	|IO |	|	|	|	2.27
21.583	0.58	1.00	0.280	|IO |	|	|	|	2.25
21.667	0.57	0.99	0.277	|IO |	|	|	|	2.23
21.750	0.57	0.98	0.275	|IO |	|	|	|	2.21
21.833	0.56	0.96	0.272	|IO |	|	|	|	2.19
21.917	0.56	0.95	0.269	|IO |	|	|	|	2.18
22.000	0.55	0.94	0.266	|IO |	|	|	|	2.16
22.083	0.55	0.93	0.264	|IO |	|	|	|	2.14
22.167	0.54	0.91	0.261	|IO |	|	|	|	2.12
22.250	0.54	0.90	0.259	|O |	|	|	|	2.10
22.333	0.54	0.89	0.256	|O |	|	|	|	2.09
22.417	0.53	0.88	0.254	|O |	|	|	|	2.07
22.500	0.53	0.87	0.251	|O |	|	|	|	2.05
22.583	0.52	0.86	0.249	|O |	|	|	|	2.04
22.667	0.52	0.85	0.247	|O |	|	|	|	2.02
22.750	0.52	0.84	0.244	|O |	|	|	|	2.01
22.833	0.51	0.83	0.242	|O |	|	|	|	1.99
22.917	0.51	0.82	0.240	|O |	|	|	|	1.98
23.000	0.50	0.81	0.238	|O |	|	|	|	1.96
23.083	0.50	0.80	0.236	|O |	|	|	|	1.95
23.167	0.50	0.79	0.234	|O |	|	|	|	1.94
23.250	0.49	0.78	0.232	|O |	|	|	|	1.92
23.333	0.49	0.77	0.230	|O |	|	|	|	1.91
23.417	0.49	0.76	0.228	|O |	|	|	|	1.90
23.500	0.49	0.76	0.226	|O |	|	|	|	1.88
23.583	0.48	0.75	0.224	|O |	|	|	|	1.87
23.667	0.48	0.74	0.222	|O |	|	|	|	1.86
23.750	0.48	0.73	0.221	|O |	|	|	|	1.85

23.833	0.47	0.72	0.219	|O	|	|	|	|	1.83
23.917	0.47	0.71	0.217	|O	|	|	|	|	1.82
24.000	0.47	0.71	0.216	|O	|	|	|	|	1.81
24.083	0.44	0.70	0.214	IO	|	|	|	|	1.80
24.167	0.32	0.69	0.212	IO	|	|	|	|	1.78
24.250	0.14	0.68	0.209	IO	|	|	|	|	1.76
24.333	0.04	0.66	0.205	IO	|	|	|	|	1.74
24.417	0.01	0.64	0.200	IO	|	|	|	|	1.71
24.500	0.01	0.62	0.196	IO	|	|	|	|	1.68
24.583	0.00	0.60	0.192	IO	|	|	|	|	1.65
24.667	0.00	0.58	0.188	IO	|	|	|	|	1.62
24.750	0.00	0.56	0.184	IO	|	|	|	|	1.59
24.833	0.00	0.55	0.180	IO	|	|	|	|	1.57
24.917	0.00	0.53	0.176	IO	|	|	|	|	1.54
25.000	0.00	0.51	0.173	IO	|	|	|	|	1.52
25.083	0.00	0.50	0.169	IO	|	|	|	|	1.49
25.167	0.00	0.49	0.166	IO	|	|	|	|	1.46
25.250	0.00	0.48	0.163	IO	|	|	|	|	1.43
25.333	0.00	0.47	0.159	IO	|	|	|	|	1.41
25.417	0.00	0.46	0.156	IO	|	|	|	|	1.38
25.500	0.00	0.45	0.153	O	|	|	|	|	1.35
25.583	0.00	0.44	0.150	O	|	|	|	|	1.32
25.667	0.00	0.43	0.147	O	|	|	|	|	1.30
25.750	0.00	0.42	0.144	O	|	|	|	|	1.27
25.833	0.00	0.41	0.141	O	|	|	|	|	1.24
25.917	0.00	0.41	0.138	O	|	|	|	|	1.22
26.000	0.00	0.40	0.135	O	|	|	|	|	1.20
26.083	0.00	0.39	0.133	O	|	|	|	|	1.17
26.167	0.00	0.38	0.130	O	|	|	|	|	1.15
26.250	0.00	0.38	0.128	O	|	|	|	|	1.13
26.333	0.00	0.37	0.125	O	|	|	|	|	1.10
26.417	0.00	0.36	0.122	O	|	|	|	|	1.08
26.500	0.00	0.35	0.120	O	|	|	|	|	1.06
26.583	0.00	0.35	0.118	O	|	|	|	|	1.04
26.667	0.00	0.34	0.115	O	|	|	|	|	1.02
26.750	0.00	0.33	0.113	O	|	|	|	|	1.00
26.833	0.00	0.33	0.111	O	|	|	|	|	0.98
26.917	0.00	0.32	0.108	O	|	|	|	|	0.96
27.000	0.00	0.31	0.106	O	|	|	|	|	0.94
27.083	0.00	0.31	0.104	O	|	|	|	|	0.92
27.167	0.00	0.30	0.102	O	|	|	|	|	0.90
27.250	0.00	0.29	0.100	O	|	|	|	|	0.88
27.333	0.00	0.29	0.098	O	|	|	|	|	0.86
27.417	0.00	0.28	0.096	O	|	|	|	|	0.85
27.500	0.00	0.28	0.094	O	|	|	|	|	0.83
27.583	0.00	0.27	0.092	O	|	|	|	|	0.81
27.667	0.00	0.27	0.090	O	|	|	|	|	0.80
27.750	0.00	0.26	0.089	O	|	|	|	|	0.78
27.833	0.00	0.26	0.087	O	|	|	|	|	0.77
27.917	0.00	0.25	0.085	O	|	|	|	|	0.75
28.000	0.00	0.25	0.083	O	|	|	|	|	0.74
28.083	0.00	0.24	0.082	O	|	|	|	|	0.72
28.167	0.00	0.24	0.080	O	|	|	|	|	0.71
28.250	0.00	0.23	0.078	O	|	|	|	|	0.69
28.333	0.00	0.23	0.077	O	|	|	|	|	0.68
28.417	0.00	0.22	0.075	O	|	|	|	|	0.66
28.500	0.00	0.22	0.074	O	|	|	|	|	0.65
28.583	0.00	0.21	0.072	O	|	|	|	|	0.64
28.667	0.00	0.21	0.071	O	|	|	|	|	0.63
28.750	0.00	0.20	0.069	O	|	|	|	|	0.61
28.833	0.00	0.20	0.068	O	|	|	|	|	0.60
28.917	0.00	0.20	0.067	O	|	|	|	|	0.59
29.000	0.00	0.19	0.065	O	|	|	|	|	0.58
29.083	0.00	0.19	0.064	O	|	|	|	|	0.57
29.167	0.00	0.18	0.063	O	|	|	|	|	0.55
29.250	0.00	0.18	0.061	O	|	|	|	|	0.54
29.333	0.00	0.18	0.060	O	|	|	|	|	0.53
29.417	0.00	0.17	0.059	O	|	|	|	|	0.52
29.500	0.00	0.17	0.058	O	|	|	|	|	0.51
29.583	0.00	0.17	0.057	O	|	|	|	|	0.50
29.667	0.00	0.16	0.056	O	|	|	|	|	0.49

29.750	0.00	0.16	0.054	O	|	|	|	|	0.48
29.833	0.00	0.16	0.053	O	|	|	|	|	0.47
29.917	0.00	0.15	0.052	O	|	|	|	|	0.46
30.000	0.00	0.15	0.051	O	|	|	|	|	0.45
30.083	0.00	0.15	0.050	O	|	|	|	|	0.44
30.167	0.00	0.14	0.049	O	|	|	|	|	0.43
30.250	0.00	0.14	0.048	O	|	|	|	|	0.43
30.333	0.00	0.14	0.047	O	|	|	|	|	0.42
30.417	0.00	0.14	0.046	O	|	|	|	|	0.41
30.500	0.00	0.13	0.045	O	|	|	|	|	0.40
30.583	0.00	0.13	0.044	O	|	|	|	|	0.39
30.667	0.00	0.13	0.044	O	|	|	|	|	0.38
30.750	0.00	0.13	0.043	O	|	|	|	|	0.38
30.833	0.00	0.12	0.042	O	|	|	|	|	0.37
30.917	0.00	0.12	0.041	O	|	|	|	|	0.36
31.000	0.00	0.12	0.040	O	|	|	|	|	0.35
31.083	0.00	0.12	0.039	O	|	|	|	|	0.35
31.167	0.00	0.11	0.039	O	|	|	|	|	0.34
31.250	0.00	0.11	0.038	O	|	|	|	|	0.33
31.333	0.00	0.11	0.037	O	|	|	|	|	0.33
31.417	0.00	0.11	0.036	O	|	|	|	|	0.32
31.500	0.00	0.10	0.036	O	|	|	|	|	0.31
31.583	0.00	0.10	0.035	O	|	|	|	|	0.31
31.667	0.00	0.10	0.034	O	|	|	|	|	0.30
31.750	0.00	0.10	0.033	O	|	|	|	|	0.30
31.833	0.00	0.10	0.033	O	|	|	|	|	0.29
31.917	0.00	0.09	0.032	O	|	|	|	|	0.28
32.000	0.00	0.09	0.032	O	|	|	|	|	0.28
32.083	0.00	0.09	0.031	O	|	|	|	|	0.27
32.167	0.00	0.09	0.030	O	|	|	|	|	0.27
32.250	0.00	0.09	0.030	O	|	|	|	|	0.26
32.333	0.00	0.09	0.029	O	|	|	|	|	0.26
32.417	0.00	0.08	0.028	O	|	|	|	|	0.25
32.500	0.00	0.08	0.028	O	|	|	|	|	0.25
32.583	0.00	0.08	0.027	O	|	|	|	|	0.24
32.667	0.00	0.08	0.027	O	|	|	|	|	0.24
32.750	0.00	0.08	0.026	O	|	|	|	|	0.23
32.833	0.00	0.08	0.026	O	|	|	|	|	0.23
32.917	0.00	0.07	0.025	O	|	|	|	|	0.22
33.000	0.00	0.07	0.025	O	|	|	|	|	0.22
33.083	0.00	0.07	0.024	O	|	|	|	|	0.21
33.167	0.00	0.07	0.024	O	|	|	|	|	0.21
33.250	0.00	0.07	0.023	O	|	|	|	|	0.21
33.333	0.00	0.07	0.023	O	|	|	|	|	0.20
33.417	0.00	0.07	0.022	O	|	|	|	|	0.20
33.500	0.00	0.06	0.022	O	|	|	|	|	0.19
33.583	0.00	0.06	0.021	O	|	|	|	|	0.19
33.667	0.00	0.06	0.021	O	|	|	|	|	0.19
33.750	0.00	0.06	0.021	O	|	|	|	|	0.18
33.833	0.00	0.06	0.020	O	|	|	|	|	0.18
33.917	0.00	0.06	0.020	O	|	|	|	|	0.17
34.000	0.00	0.06	0.019	O	|	|	|	|	0.17
34.083	0.00	0.06	0.019	O	|	|	|	|	0.17
34.167	0.00	0.05	0.019	O	|	|	|	|	0.16
34.250	0.00	0.05	0.018	O	|	|	|	|	0.16
34.333	0.00	0.05	0.018	O	|	|	|	|	0.16
34.417	0.00	0.05	0.018	O	|	|	|	|	0.15
34.500	0.00	0.05	0.017	O	|	|	|	|	0.15
34.583	0.00	0.05	0.017	O	|	|	|	|	0.15
34.667	0.00	0.05	0.016	O	|	|	|	|	0.15
34.750	0.00	0.05	0.016	O	|	|	|	|	0.14
34.833	0.00	0.05	0.016	O	|	|	|	|	0.14
34.917	0.00	0.05	0.016	O	|	|	|	|	0.14
35.000	0.00	0.04	0.015	O	|	|	|	|	0.13
35.083	0.00	0.04	0.015	O	|	|	|	|	0.13
35.167	0.00	0.04	0.015	O	|	|	|	|	0.13
35.250	0.00	0.04	0.014	O	|	|	|	|	0.13
35.333	0.00	0.04	0.014	O	|	|	|	|	0.12
35.417	0.00	0.04	0.014	O	|	|	|	|	0.12
35.500	0.00	0.04	0.013	O	|	|	|	|	0.12
35.583	0.00	0.04	0.013	O	|	|	|	|	0.12

35.667	0.00	0.04	0.013	O	|	|	|	0.11
35.750	0.00	0.04	0.013	O	|	|	|	0.11
35.833	0.00	0.04	0.012	O	|	|	|	0.11
35.917	0.00	0.04	0.012	O	|	|	|	0.11
36.000	0.00	0.04	0.012	O	|	|	|	0.11
36.083	0.00	0.03	0.012	O	|	|	|	0.10
36.167	0.00	0.03	0.011	O	|	|	|	0.10
36.250	0.00	0.03	0.011	O	|	|	|	0.10
36.333	0.00	0.03	0.011	O	|	|	|	0.10
36.417	0.00	0.03	0.011	O	|	|	|	0.10
36.500	0.00	0.03	0.011	O	|	|	|	0.09
36.583	0.00	0.03	0.010	O	|	|	|	0.09
36.667	0.00	0.03	0.010	O	|	|	|	0.09
36.750	0.00	0.03	0.010	O	|	|	|	0.09
36.833	0.00	0.03	0.010	O	|	|	|	0.09
36.917	0.00	0.03	0.010	O	|	|	|	0.08
37.000	0.00	0.03	0.009	O	|	|	|	0.08
37.083	0.00	0.03	0.009	O	|	|	|	0.08
37.167	0.00	0.03	0.009	O	|	|	|	0.08
37.250	0.00	0.03	0.009	O	|	|	|	0.08
37.333	0.00	0.03	0.009	O	|	|	|	0.08
37.417	0.00	0.02	0.008	O	|	|	|	0.07
37.500	0.00	0.02	0.008	O	|	|	|	0.07
37.583	0.00	0.02	0.008	O	|	|	|	0.07
37.667	0.00	0.02	0.008	O	|	|	|	0.07
37.750	0.00	0.02	0.008	O	|	|	|	0.07
37.833	0.00	0.02	0.008	O	|	|	|	0.07
37.917	0.00	0.02	0.007	O	|	|	|	0.07
38.000	0.00	0.02	0.007	O	|	|	|	0.06
38.083	0.00	0.02	0.007	O	|	|	|	0.06
38.167	0.00	0.02	0.007	O	|	|	|	0.06
38.250	0.00	0.02	0.007	O	|	|	|	0.06
38.333	0.00	0.02	0.007	O	|	|	|	0.06
38.417	0.00	0.02	0.007	O	|	|	|	0.06
38.500	0.00	0.02	0.006	O	|	|	|	0.06
38.583	0.00	0.02	0.006	O	|	|	|	0.06
38.667	0.00	0.02	0.006	O	|	|	|	0.06
38.750	0.00	0.02	0.006	O	|	|	|	0.05
38.833	0.00	0.02	0.006	O	|	|	|	0.05
38.917	0.00	0.02	0.006	O	|	|	|	0.05
39.000	0.00	0.02	0.006	O	|	|	|	0.05
39.083	0.00	0.02	0.006	O	|	|	|	0.05
39.167	0.00	0.02	0.006	O	|	|	|	0.05
39.250	0.00	0.02	0.005	O	|	|	|	0.05
39.333	0.00	0.02	0.005	O	|	|	|	0.05
39.417	0.00	0.02	0.005	O	|	|	|	0.05
39.500	0.00	0.01	0.005	O	|	|	|	0.04
39.583	0.00	0.01	0.005	O	|	|	|	0.04
39.667	0.00	0.01	0.005	O	|	|	|	0.04
39.750	0.00	0.01	0.005	O	|	|	|	0.04
39.833	0.00	0.01	0.005	O	|	|	|	0.04
39.917	0.00	0.01	0.005	O	|	|	|	0.04
40.000	0.00	0.01	0.005	O	|	|	|	0.04
40.083	0.00	0.01	0.004	O	|	|	|	0.04
40.167	0.00	0.01	0.004	O	|	|	|	0.04
40.250	0.00	0.01	0.004	O	|	|	|	0.04
40.333	0.00	0.01	0.004	O	|	|	|	0.04
40.417	0.00	0.01	0.004	O	|	|	|	0.04
40.500	0.00	0.01	0.004	O	|	|	|	0.04
40.583	0.00	0.01	0.004	O	|	|	|	0.03
40.667	0.00	0.01	0.004	O	|	|	|	0.03
40.750	0.00	0.01	0.004	O	|	|	|	0.03
40.833	0.00	0.01	0.004	O	|	|	|	0.03
40.917	0.00	0.01	0.004	O	|	|	|	0.03
41.000	0.00	0.01	0.004	O	|	|	|	0.03
41.083	0.00	0.01	0.003	O	|	|	|	0.03
41.167	0.00	0.01	0.003	O	|	|	|	0.03
41.250	0.00	0.01	0.003	O	|	|	|	0.03
41.333	0.00	0.01	0.003	O	|	|	|	0.03
41.417	0.00	0.01	0.003	O	|	|	|	0.03
41.500	0.00	0.01	0.003	O	|	|	|	0.03

41.583	0.00	0.01	0.003	O	|	|	|	|	0.03
41.667	0.00	0.01	0.003	O	|	|	|	|	0.03
41.750	0.00	0.01	0.003	O	|	|	|	|	0.03
41.833	0.00	0.01	0.003	O	|	|	|	|	0.03
41.917	0.00	0.01	0.003	O	|	|	|	|	0.02
42.000	0.00	0.01	0.003	O	|	|	|	|	0.02
42.083	0.00	0.01	0.003	O	|	|	|	|	0.02
42.167	0.00	0.01	0.003	O	|	|	|	|	0.02
42.250	0.00	0.01	0.003	O	|	|	|	|	0.02
42.333	0.00	0.01	0.003	O	|	|	|	|	0.02
42.417	0.00	0.01	0.003	O	|	|	|	|	0.02
42.500	0.00	0.01	0.002	O	|	|	|	|	0.02
42.583	0.00	0.01	0.002	O	|	|	|	|	0.02
42.667	0.00	0.01	0.002	O	|	|	|	|	0.02
42.750	0.00	0.01	0.002	O	|	|	|	|	0.02
42.833	0.00	0.01	0.002	O	|	|	|	|	0.02
42.917	0.00	0.01	0.002	O	|	|	|	|	0.02
43.000	0.00	0.01	0.002	O	|	|	|	|	0.02
43.083	0.00	0.01	0.002	O	|	|	|	|	0.02
43.167	0.00	0.01	0.002	O	|	|	|	|	0.02
43.250	0.00	0.01	0.002	O	|	|	|	|	0.02
43.333	0.00	0.01	0.002	O	|	|	|	|	0.02
43.417	0.00	0.01	0.002	O	|	|	|	|	0.02
43.500	0.00	0.01	0.002	O	|	|	|	|	0.02
43.583	0.00	0.01	0.002	O	|	|	|	|	0.02
43.667	0.00	0.01	0.002	O	|	|	|	|	0.02
43.750	0.00	0.01	0.002	O	|	|	|	|	0.02
43.833	0.00	0.01	0.002	O	|	|	|	|	0.02
43.917	0.00	0.01	0.002	O	|	|	|	|	0.02
44.000	0.00	0.01	0.002	O	|	|	|	|	0.02
44.083	0.00	0.00	0.002	O	|	|	|	|	0.01
44.167	0.00	0.00	0.002	O	|	|	|	|	0.01
44.250	0.00	0.00	0.002	O	|	|	|	|	0.01
44.333	0.00	0.00	0.002	O	|	|	|	|	0.01
44.417	0.00	0.00	0.002	O	|	|	|	|	0.01
44.500	0.00	0.00	0.002	O	|	|	|	|	0.01
44.583	0.00	0.00	0.001	O	|	|	|	|	0.01
44.667	0.00	0.00	0.001	O	|	|	|	|	0.01
44.750	0.00	0.00	0.001	O	|	|	|	|	0.01
44.833	0.00	0.00	0.001	O	|	|	|	|	0.01
44.917	0.00	0.00	0.001	O	|	|	|	|	0.01
45.000	0.00	0.00	0.001	O	|	|	|	|	0.01
45.083	0.00	0.00	0.001	O	|	|	|	|	0.01
45.167	0.00	0.00	0.001	O	|	|	|	|	0.01
45.250	0.00	0.00	0.001	O	|	|	|	|	0.01
45.333	0.00	0.00	0.001	O	|	|	|	|	0.01
45.417	0.00	0.00	0.001	O	|	|	|	|	0.01
45.500	0.00	0.00	0.001	O	|	|	|	|	0.01
45.583	0.00	0.00	0.001	O	|	|	|	|	0.01
45.667	0.00	0.00	0.001	O	|	|	|	|	0.01
45.750	0.00	0.00	0.001	O	|	|	|	|	0.01
45.833	0.00	0.00	0.001	O	|	|	|	|	0.01
45.917	0.00	0.00	0.001	O	|	|	|	|	0.01
46.000	0.00	0.00	0.001	O	|	|	|	|	0.01
46.083	0.00	0.00	0.001	O	|	|	|	|	0.01
46.167	0.00	0.00	0.001	O	|	|	|	|	0.01
46.250	0.00	0.00	0.001	O	|	|	|	|	0.01
46.333	0.00	0.00	0.001	O	|	|	|	|	0.01
46.417	0.00	0.00	0.001	O	|	|	|	|	0.01
46.500	0.00	0.00	0.001	O	|	|	|	|	0.01
46.583	0.00	0.00	0.001	O	|	|	|	|	0.01
46.667	0.00	0.00	0.001	O	|	|	|	|	0.01
46.750	0.00	0.00	0.001	O	|	|	|	|	0.01
46.833	0.00	0.00	0.001	O	|	|	|	|	0.01
46.917	0.00	0.00	0.001	O	|	|	|	|	0.01
47.000	0.00	0.00	0.001	O	|	|	|	|	0.01
47.083	0.00	0.00	0.001	O	|	|	|	|	0.01
47.167	0.00	0.00	0.001	O	|	|	|	|	0.01
47.250	0.00	0.00	0.001	O	|	|	|	|	0.01
47.333	0.00	0.00	0.001	O	|	|	|	|	0.01
47.417	0.00	0.00	0.001	O	|	|	|	|	0.01

47.500	0.00	0.00	0.001	O	|	|	|	|	0.01
47.583	0.00	0.00	0.001	O	|	|	|	|	0.01
47.667	0.00	0.00	0.001	O	|	|	|	|	0.01
47.750	0.00	0.00	0.001	O	|	|	|	|	0.01
47.833	0.00	0.00	0.001	O	|	|	|	|	0.01
47.917	0.00	0.00	0.001	O	|	|	|	|	0.01
48.000	0.00	0.00	0.001	O	|	|	|	|	0.01
48.083	0.00	0.00	0.001	O	|	|	|	|	0.01
48.167	0.00	0.00	0.001	O	|	|	|	|	0.01
48.250	0.00	0.00	0.001	O	|	|	|	|	0.01
48.333	0.00	0.00	0.001	O	|	|	|	|	0.01
48.417	0.00	0.00	0.001	O	|	|	|	|	0.01
48.500	0.00	0.00	0.001	O	|	|	|	|	0.01
48.583	0.00	0.00	0.001	O	|	|	|	|	0.00
48.667	0.00	0.00	0.001	O	|	|	|	|	0.00
48.750	0.00	0.00	0.001	O	|	|	|	|	0.00
48.833	0.00	0.00	0.001	O	|	|	|	|	0.00
48.917	0.00	0.00	0.001	O	|	|	|	|	0.00
49.000	0.00	0.00	0.001	O	|	|	|	|	0.00
49.083	0.00	0.00	0.000	O	|	|	|	|	0.00
49.167	0.00	0.00	0.000	O	|	|	|	|	0.00
49.250	0.00	0.00	0.000	O	|	|	|	|	0.00
49.333	0.00	0.00	0.000	O	|	|	|	|	0.00
49.417	0.00	0.00	0.000	O	|	|	|	|	0.00
49.500	0.00	0.00	0.000	O	|	|	|	|	0.00
49.583	0.00	0.00	0.000	O	|	|	|	|	0.00
49.667	0.00	0.00	0.000	O	|	|	|	|	0.00
49.750	0.00	0.00	0.000	O	|	|	|	|	0.00
49.833	0.00	0.00	0.000	O	|	|	|	|	0.00
49.917	0.00	0.00	0.000	O	|	|	|	|	0.00
50.000	0.00	0.00	0.000	O	|	|	|	|	0.00
50.083	0.00	0.00	0.000	O	|	|	|	|	0.00
50.167	0.00	0.00	0.000	O	|	|	|	|	0.00
50.250	0.00	0.00	0.000	O	|	|	|	|	0.00
50.333	0.00	0.00	0.000	O	|	|	|	|	0.00
50.417	0.00	0.00	0.000	O	|	|	|	|	0.00
50.500	0.00	0.00	0.000	O	|	|	|	|	0.00
50.583	0.00	0.00	0.000	O	|	|	|	|	0.00
50.667	0.00	0.00	0.000	O	|	|	|	|	0.00

**********HYDROGRAPH DATA**********

Number of intervals = 608
Time interval = 5.0 (Min.)
Maximum/Peak flow rate = 4.143 (CFS)
Total volume = 2.122 (Ac.Ft)

Status of hydrographs being held in storage

	Stream 1	Stream 2	Stream 3	Stream 4	Stream 5
Peak (CFS)	0.000	0.000	0.000	0.000	0.000
Vol (Ac.Ft)	0.000	0.000	0.000	0.000	0.000

****

Flood Routing Analysis: Developed Condition (5 yr Storm Event)

```
                FLOOD HYDROGRAPH ROUTING PROGRAM
          Copyright (c) CIVILCADD/CIVILDESIGN, 1989 - 2018
                      Study date: 07/01/23


 ---------------------------------------------------------------------


 CHAMBER ROUTING
 CONCO INDUSTRIAL
 5-YR STORM EVENT

 ---------------------------------------------------------------------


 Program License Serial Number 6484

 ---------------------------------------------------------------------
 ********************* HYDROGRAPH INFORMATION **********************

                From study/file name: CON1.rte
 ****************************HYDROGRAPH DATA****************************
                Number of intervals =   294
                Time interval =    5.0 (Min.)
                Maximum/Peak flow rate =       12.093 (CFS)
                Total volume =       1.769 (Ac.Ft)
        Status of hydrographs being held in storage
                     Stream 1  Stream 2  Stream 3  Stream 4  Stream 5
        Peak (CFS)      0.000     0.000     0.000     0.000     0.000
        Vol (Ac.Ft)      0.000     0.000     0.000     0.000     0.000
 **********************************************************************



 ++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++++
 Process from Point/Station        0.000 to Point/Station        1.000
 **** RETARDING BASIN ROUTING ****
 ________________________________________________________________________

 User entry of depth-outflow-storage data
 ---------------------------------------------------------------------
 Total number of inflow hydrograph intervals = 294
 Hydrograph time unit =  5.000 (Min.)
 Initial depth in storage basin =   0.00(Ft.)
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
 Initial basin depth =   0.00 (Ft.)
 Initial basin storage =      0.00 (Ac.Ft)
 Initial basin outflow =   0.00 (CFS)
 ---------------------------------------------------------------------
 ---------------------------------------------------------------------
 Depth vs. Storage and Depth vs. Discharge data:
  Basin Depth  Storage    Outflow   (S-O*dt/2)   (S+O*dt/2)
      (Ft.)    (Ac.Ft)    (CFS)     (Ac.Ft)    (Ac.Ft)
 ---------------------------------------------------------------------
    0.000      0.000      0.000      0.000        0.000
    1.500      0.170      0.500      0.168        0.172
    3.000      0.390      1.500      0.385        0.395
    4.500      0.680      4.300      0.665        0.695
    6.000      0.900      8.000      0.872        0.928
    6.700      0.960      8.700      0.930        0.990
 ---------------------------------------------------------------------
                Hydrograph Detention Basin Routing
 ---------------------------------------------------------------------

 Graph values: 'I'= unit inflow; 'O'=outflow at time shown
 ---------------------------------------------------------------------
  Time   Inflow  Outflow    Storage                                  Depth
 (Hours)  (CFS)   (CFS)     (Ac.Ft) .0       3.0    6.05    9.07   12.09 (Ft.)
  0.083    0.02    0.00      0.000  O       |       |       |       |     0.00
```

0.167	0.12	0.00	0.001	O				0.00
0.250	0.27	0.01	0.002	O				0.02
0.333	0.35	0.01	0.004	O				0.03
0.417	0.37	0.02	0.006	O				0.06
0.500	0.38	0.03	0.009	OI				0.08
0.583	0.38	0.03	0.011	OI				0.10
0.667	0.39	0.04	0.014	OI				0.12
0.750	0.39	0.05	0.016	OI				0.14
0.833	0.39	0.05	0.018	OI				0.16
0.917	0.39	0.06	0.021	OI				0.18
1.000	0.39	0.07	0.023	OI				0.20
1.083	0.39	0.07	0.025	OI				0.22
1.167	0.39	0.08	0.027	OI				0.24
1.250	0.39	0.09	0.029	OI				0.26
1.333	0.40	0.09	0.031	OI				0.28
1.417	0.40	0.10	0.033	OI				0.30
1.500	0.40	0.10	0.035	OI				0.31
1.583	0.40	0.11	0.038	OI				0.33
1.667	0.40	0.12	0.039	OI				0.35
1.750	0.40	0.12	0.041	OI				0.37
1.833	0.40	0.13	0.043	OI				0.38
1.917	0.40	0.13	0.045	OI				0.40
2.000	0.41	0.14	0.047	OI				0.42
2.083	0.41	0.14	0.049	OI				0.43
2.167	0.41	0.15	0.051	OI				0.45
2.250	0.41	0.15	0.052	OI				0.46
2.333	0.41	0.16	0.054	OI				0.48
2.417	0.41	0.16	0.056	OI				0.49
2.500	0.41	0.17	0.058	OI				0.51
2.583	0.42	0.17	0.059	OI				0.52
2.667	0.42	0.18	0.061	OI				0.54
2.750	0.42	0.18	0.063	OI				0.55
2.833	0.42	0.19	0.064	OI				0.57
2.917	0.42	0.19	0.066	OI				0.58
3.000	0.42	0.20	0.067	OI				0.59
3.083	0.42	0.20	0.069	OI				0.61
3.167	0.43	0.21	0.070	OI				0.62
3.250	0.43	0.21	0.072	OI				0.63
3.333	0.43	0.22	0.073	OI				0.65
3.417	0.43	0.22	0.075	OI				0.66
3.500	0.43	0.22	0.076	OI				0.67
3.583	0.43	0.23	0.078	OI				0.69
3.667	0.44	0.23	0.079	OI				0.70
3.750	0.44	0.24	0.081	OI				0.71
3.833	0.44	0.24	0.082	OI				0.72
3.917	0.44	0.24	0.083	OI				0.73
4.000	0.44	0.25	0.085	OI				0.75
4.083	0.44	0.25	0.086	OI				0.76
4.167	0.45	0.26	0.087	OI				0.77
4.250	0.45	0.26	0.089	OI				0.78
4.333	0.45	0.26	0.090	OI				0.79
4.417	0.45	0.27	0.091	OI				0.80
4.500	0.45	0.27	0.092	OI				0.81
4.583	0.45	0.28	0.094	OI				0.83
4.667	0.46	0.28	0.095	OI				0.84
4.750	0.46	0.28	0.096	OI				0.85
4.833	0.46	0.29	0.097	OI				0.86
4.917	0.46	0.29	0.098	OI				0.87
5.000	0.46	0.29	0.100	OI				0.88
5.083	0.47	0.30	0.101	OI				0.89
5.167	0.47	0.30	0.102	OI				0.90
5.250	0.47	0.30	0.103	OI				0.91
5.333	0.47	0.31	0.104	OI				0.92
5.417	0.47	0.31	0.105	OI				0.93
5.500	0.48	0.31	0.106	OI				0.94
5.583	0.48	0.32	0.108	OI				0.95
5.667	0.48	0.32	0.109	OI				0.96
5.750	0.48	0.32	0.110	OI				0.97
5.833	0.48	0.33	0.111	OI				0.98
5.917	0.49	0.33	0.112	OI				0.99
6.000	0.49	0.33	0.113	OI				1.00

6.083	0.49	0.34	0.114	OI					1.01
6.167	0.49	0.34	0.115	OI					1.02
6.250	0.50	0.34	0.116	OI					1.03
6.333	0.50	0.35	0.117	OI					1.04
6.417	0.50	0.35	0.118	OI					1.04
6.500	0.50	0.35	0.119	OI					1.05
6.583	0.51	0.35	0.121	OI					1.06
6.667	0.51	0.36	0.122	OI					1.07
6.750	0.51	0.36	0.123	OI					1.08
6.833	0.51	0.36	0.124	OI					1.09
6.917	0.52	0.37	0.125	OI					1.10
7.000	0.52	0.37	0.126	OI					1.11
7.083	0.52	0.37	0.127	OI					1.12
7.167	0.52	0.38	0.128	OI					1.13
7.250	0.53	0.38	0.129	O					1.14
7.333	0.53	0.38	0.130	O					1.15
7.417	0.53	0.38	0.131	O					1.15
7.500	0.54	0.39	0.132	O					1.16
7.583	0.54	0.39	0.133	O					1.17
7.667	0.54	0.39	0.134	O					1.18
7.750	0.54	0.40	0.135	O					1.19
7.833	0.55	0.40	0.136	O					1.20
7.917	0.55	0.40	0.137	O					1.21
8.000	0.55	0.41	0.138	O					1.22
8.083	0.56	0.41	0.139	O					1.23
8.167	0.56	0.41	0.140	O					1.23
8.250	0.56	0.41	0.141	O					1.24
8.333	0.57	0.42	0.142	O					1.25
8.417	0.57	0.42	0.143	O					1.26
8.500	0.57	0.42	0.144	O					1.27
8.583	0.58	0.43	0.145	O					1.28
8.667	0.58	0.43	0.146	O					1.29
8.750	0.58	0.43	0.147	O					1.30
8.833	0.59	0.44	0.148	O					1.31
8.917	0.59	0.44	0.149	O					1.32
9.000	0.60	0.44	0.150	O					1.33
9.083	0.60	0.45	0.151	O					1.34
9.167	0.60	0.45	0.152	O					1.35
9.250	0.61	0.45	0.154	O					1.35
9.333	0.61	0.45	0.155	O					1.36
9.417	0.62	0.46	0.156	O					1.37
9.500	0.62	0.46	0.157	O					1.38
9.583	0.62	0.46	0.158	O					1.39
9.667	0.63	0.47	0.159	O					1.40
9.750	0.63	0.47	0.160	O					1.41
9.833	0.64	0.47	0.161	O					1.42
9.917	0.64	0.48	0.162	O					1.43
10.000	0.65	0.48	0.164	O					1.44
10.083	0.65	0.48	0.165	O					1.45
10.167	0.66	0.49	0.166	O					1.46
10.250	0.66	0.49	0.167	O					1.47
10.333	0.67	0.49	0.168	O					1.48
10.417	0.67	0.50	0.169	O					1.49
10.500	0.68	0.50	0.171	O					1.50
10.583	0.69	0.51	0.172	O					1.51
10.667	0.69	0.51	0.173	O					1.52
10.750	0.70	0.52	0.174	O					1.53
10.833	0.70	0.53	0.176	O					1.54
10.917	0.71	0.53	0.177	O					1.55
11.000	0.72	0.54	0.178	O					1.55
11.083	0.72	0.54	0.179	O					1.56
11.167	0.73	0.55	0.180	O					1.57
11.250	0.74	0.55	0.182	O					1.58
11.333	0.74	0.56	0.183	O					1.59
11.417	0.75	0.56	0.184	O					1.60
11.500	0.76	0.57	0.186	OI					1.61
11.583	0.77	0.58	0.187	OI					1.61
11.667	0.77	0.58	0.188	OI					1.62
11.750	0.78	0.59	0.189	OI					1.63
11.833	0.79	0.59	0.191	OI					1.64
11.917	0.80	0.60	0.192	OI					1.65

12.000	0.81	0.61	0.193	OI				1.66
12.083	0.82	0.61	0.195	OI				1.67
12.167	0.88	0.62	0.197	OI				1.68
12.250	0.96	0.63	0.199	OI				1.69
12.333	1.01	0.64	0.201	OI				1.71
12.417	1.03	0.65	0.204	OI				1.73
12.500	1.04	0.66	0.206	OI				1.75
12.583	1.06	0.68	0.209	OI				1.76
12.667	1.07	0.69	0.211	OI				1.78
12.750	1.08	0.70	0.214	OI				1.80
12.833	1.09	0.71	0.217	OI				1.82
12.917	1.11	0.72	0.219	OI				1.84
13.000	1.12	0.74	0.222	OI				1.85
13.083	1.13	0.75	0.225	O I				1.87
13.167	1.15	0.76	0.227	OI				1.89
13.250	1.16	0.77	0.230	OI				1.91
13.333	1.18	0.78	0.233	OI				1.93
13.417	1.20	0.80	0.235	OI				1.95
13.500	1.21	0.81	0.238	OI				1.96
13.583	1.23	0.82	0.241	OI				1.98
13.667	1.25	0.84	0.244	OI				2.00
13.750	1.27	0.85	0.247	OI				2.02
13.833	1.29	0.86	0.250	OI				2.04
13.917	1.31	0.88	0.253	OI				2.06
14.000	1.33	0.89	0.256	OI				2.08
14.083	1.36	0.90	0.259	OI				2.10
14.167	1.38	0.92	0.262	OI				2.13
14.250	1.41	0.93	0.265	OI				2.15
14.333	1.44	0.95	0.269	OI				2.17
14.417	1.47	0.96	0.272	OI				2.20
14.500	1.51	0.98	0.276	OI				2.22
14.583	1.54	1.00	0.279	O I				2.24
14.667	1.58	1.01	0.283	O I				2.27
14.750	1.62	1.03	0.287	O I				2.30
14.833	1.67	1.05	0.291	O I				2.33
14.917	1.71	1.07	0.295	O I				2.36
15.000	1.77	1.09	0.300	O I				2.39
15.083	1.83	1.11	0.305	O I				2.42
15.167	1.89	1.14	0.310	O I				2.45
15.250	1.97	1.16	0.315	O I				2.49
15.333	2.05	1.19	0.321	O I				2.53
15.417	2.12	1.21	0.327	O I				2.57
15.500	2.09	1.24	0.333	O I				2.61
15.583	2.00	1.27	0.339	O I				2.65
15.667	2.04	1.29	0.344	O I				2.68
15.750	2.21	1.32	0.349	O I				2.72
15.833	2.48	1.35	0.356	O I				2.77
15.917	2.90	1.39	0.365	O I				2.83
16.000	3.70	1.45	0.378	O I				2.92
16.083	5.78	1.60	0.401	O	I			3.05
16.167	10.29	2.02	0.443	O			I	3.28
16.250	12.09	2.61	0.505	O			I	3.59
16.333	7.59	3.07	0.553	O	I			3.84
16.417	4.14	3.25	0.571	O I				3.94
16.500	2.74	3.26	0.573	IO				3.95
16.583	2.47	3.22	0.568	I O				3.92
16.667	2.11	3.16	0.562	I O				3.89
16.750	1.95	3.09	0.555	I O				3.85
16.833	1.82	3.01	0.547	I O				3.81
16.917	1.71	2.93	0.538	I O				3.77
17.000	1.62	2.85	0.530	I O				3.72
17.083	1.54	2.77	0.521	I O				3.68
17.167	1.47	2.69	0.513	I O				3.64
17.250	1.41	2.61	0.505	I O				3.59
17.333	1.35	2.53	0.496	I O				3.55
17.417	1.31	2.45	0.488	I O				3.51
17.500	1.27	2.38	0.481	I O				3.47
17.583	1.23	2.30	0.473	I O				3.43
17.667	1.19	2.23	0.466	I O				3.39
17.750	1.16	2.16	0.459	I O				3.36
17.833	1.13	2.10	0.452	I O				3.32

17.917	1.10	2.04	0.445	| I O |	|	|	|	3.29
18.000	1.08	1.98	0.439	| I O |	|	|	|	3.25
18.083	1.05	1.92	0.433	| I O |	|	|	|	3.22
18.167	0.98	1.86	0.427	| I O |	|	|	|	3.19
18.250	0.89	1.80	0.421	| I O |	|	|	|	3.16
18.333	0.83	1.74	0.415	| I O |	|	|	|	3.13
18.417	0.80	1.68	0.409	| I O |	|	|	|	3.10
18.500	0.78	1.62	0.403	| I O |	|	|	|	3.07
18.583	0.76	1.57	0.397	| I O |	|	|	|	3.04
18.667	0.75	1.51	0.392	|I O |	|	|	|	3.01
18.750	0.73	1.48	0.386	|I O |	|	|	|	2.97
18.833	0.72	1.46	0.381	|I O |	|	|	|	2.94
18.917	0.71	1.44	0.376	|I O |	|	|	|	2.91
19.000	0.70	1.41	0.371	|I O |	|	|	|	2.87
19.083	0.68	1.39	0.366	|I O |	|	|	|	2.84
19.167	0.67	1.37	0.361	|I O |	|	|	|	2.80
19.250	0.66	1.35	0.357	|I O |	|	|	|	2.77
19.333	0.65	1.33	0.352	|I O |	|	|	|	2.74
19.417	0.64	1.31	0.347	|I O |	|	|	|	2.71
19.500	0.63	1.29	0.343	|I O |	|	|	|	2.68
19.583	0.62	1.27	0.338	|I O |	|	|	|	2.65
19.667	0.61	1.25	0.334	|I O |	|	|	|	2.62
19.750	0.61	1.23	0.330	|I O |	|	|	|	2.59
19.833	0.60	1.21	0.325	|I O |	|	|	|	2.56
19.917	0.59	1.19	0.321	|I O |	|	|	|	2.53
20.000	0.58	1.17	0.317	|I O |	|	|	|	2.50
20.083	0.58	1.15	0.313	|I O |	|	|	|	2.48
20.167	0.57	1.13	0.309	|IO |	|	|	|	2.45
20.250	0.56	1.12	0.305	|IO |	|	|	|	2.42
20.333	0.56	1.10	0.302	|IO |	|	|	|	2.40
20.417	0.55	1.08	0.298	|IO |	|	|	|	2.37
20.500	0.54	1.07	0.294	|IO |	|	|	|	2.35
20.583	0.54	1.05	0.291	|IO |	|	|	|	2.32
20.667	0.53	1.03	0.287	|IO |	|	|	|	2.30
20.750	0.53	1.02	0.284	|IO |	|	|	|	2.28
20.833	0.52	1.00	0.281	|IO |	|	|	|	2.25
20.917	0.52	0.99	0.277	|IO |	|	|	|	2.23
21.000	0.51	0.97	0.274	|IO |	|	|	|	2.21
21.083	0.51	0.96	0.271	|IO |	|	|	|	2.19
21.167	0.50	0.94	0.268	|IO |	|	|	|	2.17
21.250	0.50	0.93	0.265	|IO |	|	|	|	2.15
21.333	0.49	0.92	0.262	|IO |	|	|	|	2.13
21.417	0.49	0.90	0.259	|IO |	|	|	|	2.11
21.500	0.48	0.89	0.256	|IO |	|	|	|	2.09
21.583	0.48	0.88	0.253	|IO |	|	|	|	2.07
21.667	0.47	0.87	0.251	|IO |	|	|	|	2.05
21.750	0.47	0.85	0.248	|IO |	|	|	|	2.03
21.833	0.47	0.84	0.245	|IO |	|	|	|	2.01
21.917	0.46	0.83	0.243	|IO |	|	|	|	2.00
22.000	0.46	0.82	0.240	|IO |	|	|	|	1.98
22.083	0.45	0.81	0.238	|IO |	|	|	|	1.96
22.167	0.45	0.80	0.235	|IO |	|	|	|	1.95
22.250	0.45	0.79	0.233	|IO |	|	|	|	1.93
22.333	0.44	0.78	0.231	|IO |	|	|	|	1.91
22.417	0.44	0.77	0.228	|IO |	|	|	|	1.90
22.500	0.44	0.76	0.226	|O |	|	|	|	1.88
22.583	0.43	0.75	0.224	|O |	|	|	|	1.87
22.667	0.43	0.74	0.222	|O |	|	|	|	1.85
22.750	0.43	0.73	0.220	|O |	|	|	|	1.84
22.833	0.42	0.72	0.218	|O |	|	|	|	1.83
22.917	0.42	0.71	0.216	|O |	|	|	|	1.81
23.000	0.42	0.70	0.214	|O |	|	|	|	1.80
23.083	0.42	0.69	0.212	|O |	|	|	|	1.79
23.167	0.41	0.68	0.210	|O |	|	|	|	1.77
23.250	0.41	0.67	0.208	|O |	|	|	|	1.76
23.333	0.41	0.67	0.206	|O |	|	|	|	1.75
23.417	0.40	0.66	0.205	|O |	|	|	|	1.74
23.500	0.40	0.65	0.203	|O |	|	|	|	1.72
23.583	0.40	0.64	0.201	|O |	|	|	|	1.71
23.667	0.40	0.63	0.200	|O |	|	|	|	1.70
23.750	0.39	0.63	0.198	|O |	|	|	|	1.69

23.833	0.39	0.62	0.196	|O	|	|	|	|	1.68
23.917	0.39	0.61	0.195	|O	|	|	|	|	1.67
24.000	0.39	0.61	0.193	|O	|	|	|	|	1.66
24.083	0.37	0.60	0.192	IO	|	|	|	|	1.65
24.167	0.26	0.59	0.190	IO	|	|	|	|	1.63
24.250	0.11	0.58	0.187	IO	|	|	|	|	1.62
24.333	0.04	0.56	0.184	IO	|	|	|	|	1.59
24.417	0.01	0.55	0.180	IO	|	|	|	|	1.57
24.500	0.00	0.53	0.176	IO	|	|	|	|	1.54
24.583	0.00	0.51	0.173	IO	|	|	|	|	1.52
24.667	0.00	0.50	0.169	IO	|	|	|	|	1.49
24.750	0.00	0.49	0.166	IO	|	|	|	|	1.46
24.833	0.00	0.48	0.163	IO	|	|	|	|	1.43
24.917	0.00	0.47	0.159	IO	|	|	|	|	1.41
25.000	0.00	0.46	0.156	IO	|	|	|	|	1.38
25.083	0.00	0.45	0.153	IO	|	|	|	|	1.35
25.167	0.00	0.44	0.150	IO	|	|	|	|	1.32
25.250	0.00	0.43	0.147	IO	|	|	|	|	1.30
25.333	0.00	0.42	0.144	IO	|	|	|	|	1.27
25.417	0.00	0.41	0.141	IO	|	|	|	|	1.24
25.500	0.00	0.41	0.138	IO	|	|	|	|	1.22
25.583	0.00	0.40	0.135	IO	|	|	|	|	1.20
25.667	0.00	0.39	0.133	IO	|	|	|	|	1.17
25.750	0.00	0.38	0.130	IO	|	|	|	|	1.15
25.833	0.00	0.37	0.127	O	|	|	|	|	1.12
25.917	0.00	0.37	0.125	O	|	|	|	|	1.10
26.000	0.00	0.36	0.122	O	|	|	|	|	1.08
26.083	0.00	0.35	0.120	O	|	|	|	|	1.06
26.167	0.00	0.35	0.118	O	|	|	|	|	1.04
26.250	0.00	0.34	0.115	O	|	|	|	|	1.02
26.333	0.00	0.33	0.113	O	|	|	|	|	1.00
26.417	0.00	0.33	0.111	O	|	|	|	|	0.98
26.500	0.00	0.32	0.108	O	|	|	|	|	0.96
26.583	0.00	0.31	0.106	O	|	|	|	|	0.94
26.667	0.00	0.31	0.104	O	|	|	|	|	0.92
26.750	0.00	0.30	0.102	O	|	|	|	|	0.90
26.833	0.00	0.29	0.100	O	|	|	|	|	0.88
26.917	0.00	0.29	0.098	O	|	|	|	|	0.86
27.000	0.00	0.28	0.096	O	|	|	|	|	0.85
27.083	0.00	0.28	0.094	O	|	|	|	|	0.83
27.167	0.00	0.27	0.092	O	|	|	|	|	0.81
27.250	0.00	0.27	0.090	O	|	|	|	|	0.80
27.333	0.00	0.26	0.089	O	|	|	|	|	0.78
27.417	0.00	0.26	0.087	O	|	|	|	|	0.77
27.500	0.00	0.25	0.085	O	|	|	|	|	0.75
27.583	0.00	0.25	0.083	O	|	|	|	|	0.74
27.667	0.00	0.24	0.082	O	|	|	|	|	0.72
27.750	0.00	0.24	0.080	O	|	|	|	|	0.71
27.833	0.00	0.23	0.078	O	|	|	|	|	0.69
27.917	0.00	0.23	0.077	O	|	|	|	|	0.68
28.000	0.00	0.22	0.075	O	|	|	|	|	0.66
28.083	0.00	0.22	0.074	O	|	|	|	|	0.65
28.167	0.00	0.21	0.072	O	|	|	|	|	0.64
28.250	0.00	0.21	0.071	O	|	|	|	|	0.63
28.333	0.00	0.20	0.069	O	|	|	|	|	0.61
28.417	0.00	0.20	0.068	O	|	|	|	|	0.60
28.500	0.00	0.20	0.067	O	|	|	|	|	0.59
28.583	0.00	0.19	0.065	O	|	|	|	|	0.58
28.667	0.00	0.19	0.064	O	|	|	|	|	0.56
28.750	0.00	0.18	0.063	O	|	|	|	|	0.55
28.833	0.00	0.18	0.061	O	|	|	|	|	0.54
28.917	0.00	0.18	0.060	O	|	|	|	|	0.53
29.000	0.00	0.17	0.059	O	|	|	|	|	0.52
29.083	0.00	0.17	0.058	O	|	|	|	|	0.51
29.167	0.00	0.17	0.057	O	|	|	|	|	0.50
29.250	0.00	0.16	0.056	O	|	|	|	|	0.49
29.333	0.00	0.16	0.054	O	|	|	|	|	0.48
29.417	0.00	0.16	0.053	O	|	|	|	|	0.47
29.500	0.00	0.15	0.052	O	|	|	|	|	0.46
29.583	0.00	0.15	0.051	O	|	|	|	|	0.45
29.667	0.00	0.15	0.050	O	|	|	|	|	0.44

29.750	0.00	0.14	0.049	O	|	|	|	|	0.43
29.833	0.00	0.14	0.048	O	|	|	|	|	0.43
29.917	0.00	0.14	0.047	O	|	|	|	|	0.42
30.000	0.00	0.14	0.046	O	|	|	|	|	0.41
30.083	0.00	0.13	0.045	O	|	|	|	|	0.40
30.167	0.00	0.13	0.044	O	|	|	|	|	0.39
30.250	0.00	0.13	0.044	O	|	|	|	|	0.38
30.333	0.00	0.13	0.043	O	|	|	|	|	0.38
30.417	0.00	0.12	0.042	O	|	|	|	|	0.37
30.500	0.00	0.12	0.041	O	|	|	|	|	0.36
30.583	0.00	0.12	0.040	O	|	|	|	|	0.35
30.667	0.00	0.12	0.039	O	|	|	|	|	0.35
30.750	0.00	0.11	0.039	O	|	|	|	|	0.34
30.833	0.00	0.11	0.038	O	|	|	|	|	0.33
30.917	0.00	0.11	0.037	O	|	|	|	|	0.33
31.000	0.00	0.11	0.036	O	|	|	|	|	0.32
31.083	0.00	0.10	0.036	O	|	|	|	|	0.31
31.167	0.00	0.10	0.035	O	|	|	|	|	0.31
31.250	0.00	0.10	0.034	O	|	|	|	|	0.30
31.333	0.00	0.10	0.033	O	|	|	|	|	0.30
31.417	0.00	0.10	0.033	O	|	|	|	|	0.29
31.500	0.00	0.09	0.032	O	|	|	|	|	0.28
31.583	0.00	0.09	0.032	O	|	|	|	|	0.28
31.667	0.00	0.09	0.031	O	|	|	|	|	0.27
31.750	0.00	0.09	0.030	O	|	|	|	|	0.27
31.833	0.00	0.09	0.030	O	|	|	|	|	0.26
31.917	0.00	0.09	0.029	O	|	|	|	|	0.26
32.000	0.00	0.08	0.028	O	|	|	|	|	0.25
32.083	0.00	0.08	0.028	O	|	|	|	|	0.25
32.167	0.00	0.08	0.027	O	|	|	|	|	0.24
32.250	0.00	0.08	0.027	O	|	|	|	|	0.24
32.333	0.00	0.08	0.026	O	|	|	|	|	0.23
32.417	0.00	0.08	0.026	O	|	|	|	|	0.23
32.500	0.00	0.07	0.025	O	|	|	|	|	0.22
32.583	0.00	0.07	0.025	O	|	|	|	|	0.22
32.667	0.00	0.07	0.024	O	|	|	|	|	0.21
32.750	0.00	0.07	0.024	O	|	|	|	|	0.21
32.833	0.00	0.07	0.023	O	|	|	|	|	0.21
32.917	0.00	0.07	0.023	O	|	|	|	|	0.20
33.000	0.00	0.07	0.022	O	|	|	|	|	0.20
33.083	0.00	0.06	0.022	O	|	|	|	|	0.19
33.167	0.00	0.06	0.021	O	|	|	|	|	0.19
33.250	0.00	0.06	0.021	O	|	|	|	|	0.19
33.333	0.00	0.06	0.021	O	|	|	|	|	0.18
33.417	0.00	0.06	0.020	O	|	|	|	|	0.18
33.500	0.00	0.06	0.020	O	|	|	|	|	0.17
33.583	0.00	0.06	0.019	O	|	|	|	|	0.17
33.667	0.00	0.06	0.019	O	|	|	|	|	0.17
33.750	0.00	0.05	0.019	O	|	|	|	|	0.16
33.833	0.00	0.05	0.018	O	|	|	|	|	0.16
33.917	0.00	0.05	0.018	O	|	|	|	|	0.16
34.000	0.00	0.05	0.018	O	|	|	|	|	0.15
34.083	0.00	0.05	0.017	O	|	|	|	|	0.15
34.167	0.00	0.05	0.017	O	|	|	|	|	0.15
34.250	0.00	0.05	0.016	O	|	|	|	|	0.15
34.333	0.00	0.05	0.016	O	|	|	|	|	0.14
34.417	0.00	0.05	0.016	O	|	|	|	|	0.14
34.500	0.00	0.05	0.016	O	|	|	|	|	0.14
34.583	0.00	0.04	0.015	O	|	|	|	|	0.13
34.667	0.00	0.04	0.015	O	|	|	|	|	0.13
34.750	0.00	0.04	0.015	O	|	|	|	|	0.13
34.833	0.00	0.04	0.014	O	|	|	|	|	0.13
34.917	0.00	0.04	0.014	O	|	|	|	|	0.12
35.000	0.00	0.04	0.014	O	|	|	|	|	0.12
35.083	0.00	0.04	0.013	O	|	|	|	|	0.12
35.167	0.00	0.04	0.013	O	|	|	|	|	0.12
35.250	0.00	0.04	0.013	O	|	|	|	|	0.11
35.333	0.00	0.04	0.013	O	|	|	|	|	0.11
35.417	0.00	0.04	0.012	O	|	|	|	|	0.11
35.500	0.00	0.04	0.012	O	|	|	|	|	0.11
35.583	0.00	0.04	0.012	O	|	|	|	|	0.11

35.667	0.00	0.03	0.012	O	|	|	|	0.10
35.750	0.00	0.03	0.011	O	|	|	|	0.10
35.833	0.00	0.03	0.011	O	|	|	|	0.10
35.917	0.00	0.03	0.011	O	|	|	|	0.10
36.000	0.00	0.03	0.011	O	|	|	|	0.10
36.083	0.00	0.03	0.011	O	|	|	|	0.09
36.167	0.00	0.03	0.010	O	|	|	|	0.09
36.250	0.00	0.03	0.010	O	|	|	|	0.09
36.333	0.00	0.03	0.010	O	|	|	|	0.09
36.417	0.00	0.03	0.010	O	|	|	|	0.09
36.500	0.00	0.03	0.010	O	|	|	|	0.08
36.583	0.00	0.03	0.009	O	|	|	|	0.08
36.667	0.00	0.03	0.009	O	|	|	|	0.08
36.750	0.00	0.03	0.009	O	|	|	|	0.08
36.833	0.00	0.03	0.009	O	|	|	|	0.08
36.917	0.00	0.03	0.009	O	|	|	|	0.08
37.000	0.00	0.02	0.008	O	|	|	|	0.07
37.083	0.00	0.02	0.008	O	|	|	|	0.07
37.167	0.00	0.02	0.008	O	|	|	|	0.07
37.250	0.00	0.02	0.008	O	|	|	|	0.07
37.333	0.00	0.02	0.008	O	|	|	|	0.07
37.417	0.00	0.02	0.008	O	|	|	|	0.07
37.500	0.00	0.02	0.007	O	|	|	|	0.07
37.583	0.00	0.02	0.007	O	|	|	|	0.06
37.667	0.00	0.02	0.007	O	|	|	|	0.06
37.750	0.00	0.02	0.007	O	|	|	|	0.06
37.833	0.00	0.02	0.007	O	|	|	|	0.06
37.917	0.00	0.02	0.007	O	|	|	|	0.06
38.000	0.00	0.02	0.007	O	|	|	|	0.06
38.083	0.00	0.02	0.006	O	|	|	|	0.06
38.167	0.00	0.02	0.006	O	|	|	|	0.06
38.250	0.00	0.02	0.006	O	|	|	|	0.05
38.333	0.00	0.02	0.006	O	|	|	|	0.05
38.417	0.00	0.02	0.006	O	|	|	|	0.05
38.500	0.00	0.02	0.006	O	|	|	|	0.05
38.583	0.00	0.02	0.006	O	|	|	|	0.05
38.667	0.00	0.02	0.006	O	|	|	|	0.05
38.750	0.00	0.02	0.006	O	|	|	|	0.05
38.833	0.00	0.02	0.005	O	|	|	|	0.05
38.917	0.00	0.02	0.005	O	|	|	|	0.05
39.000	0.00	0.02	0.005	O	|	|	|	0.05
39.083	0.00	0.01	0.005	O	|	|	|	0.04
39.167	0.00	0.01	0.005	O	|	|	|	0.04
39.250	0.00	0.01	0.005	O	|	|	|	0.04
39.333	0.00	0.01	0.005	O	|	|	|	0.04
39.417	0.00	0.01	0.005	O	|	|	|	0.04
39.500	0.00	0.01	0.005	O	|	|	|	0.04
39.583	0.00	0.01	0.005	O	|	|	|	0.04
39.667	0.00	0.01	0.004	O	|	|	|	0.04
39.750	0.00	0.01	0.004	O	|	|	|	0.04
39.833	0.00	0.01	0.004	O	|	|	|	0.04
39.917	0.00	0.01	0.004	O	|	|	|	0.04
40.000	0.00	0.01	0.004	O	|	|	|	0.04
40.083	0.00	0.01	0.004	O	|	|	|	0.04
40.167	0.00	0.01	0.004	O	|	|	|	0.03
40.250	0.00	0.01	0.004	O	|	|	|	0.03
40.333	0.00	0.01	0.004	O	|	|	|	0.03
40.417	0.00	0.01	0.004	O	|	|	|	0.03
40.500	0.00	0.01	0.004	O	|	|	|	0.03
40.583	0.00	0.01	0.004	O	|	|	|	0.03
40.667	0.00	0.01	0.003	O	|	|	|	0.03
40.750	0.00	0.01	0.003	O	|	|	|	0.03
40.833	0.00	0.01	0.003	O	|	|	|	0.03
40.917	0.00	0.01	0.003	O	|	|	|	0.03
41.000	0.00	0.01	0.003	O	|	|	|	0.03
41.083	0.00	0.01	0.003	O	|	|	|	0.03
41.167	0.00	0.01	0.003	O	|	|	|	0.03
41.250	0.00	0.01	0.003	O	|	|	|	0.03
41.333	0.00	0.01	0.003	O	|	|	|	0.03
41.417	0.00	0.01	0.003	O	|	|	|	0.03
41.500	0.00	0.01	0.003	O	|	|	|	0.02

41.583	0.00	0.01	0.003	O	|	|	|	|	0.02
41.667	0.00	0.01	0.003	O	|	|	|	|	0.02
41.750	0.00	0.01	0.003	O	|	|	|	|	0.02
41.833	0.00	0.01	0.003	O	|	|	|	|	0.02
41.917	0.00	0.01	0.003	O	|	|	|	|	0.02
42.000	0.00	0.01	0.003	O	|	|	|	|	0.02
42.083	0.00	0.01	0.002	O	|	|	|	|	0.02
42.167	0.00	0.01	0.002	O	|	|	|	|	0.02
42.250	0.00	0.01	0.002	O	|	|	|	|	0.02
42.333	0.00	0.01	0.002	O	|	|	|	|	0.02
42.417	0.00	0.01	0.002	O	|	|	|	|	0.02
42.500	0.00	0.01	0.002	O	|	|	|	|	0.02
42.583	0.00	0.01	0.002	O	|	|	|	|	0.02
42.667	0.00	0.01	0.002	O	|	|	|	|	0.02
42.750	0.00	0.01	0.002	O	|	|	|	|	0.02
42.833	0.00	0.01	0.002	O	|	|	|	|	0.02
42.917	0.00	0.01	0.002	O	|	|	|	|	0.02
43.000	0.00	0.01	0.002	O	|	|	|	|	0.02
43.083	0.00	0.01	0.002	O	|	|	|	|	0.02
43.167	0.00	0.01	0.002	O	|	|	|	|	0.02
43.250	0.00	0.01	0.002	O	|	|	|	|	0.02
43.333	0.00	0.01	0.002	O	|	|	|	|	0.02
43.417	0.00	0.01	0.002	O	|	|	|	|	0.02
43.500	0.00	0.01	0.002	O	|	|	|	|	0.02
43.583	0.00	0.01	0.002	O	|	|	|	|	0.02
43.667	0.00	0.00	0.002	O	|	|	|	|	0.01
43.750	0.00	0.00	0.002	O	|	|	|	|	0.01
43.833	0.00	0.00	0.002	O	|	|	|	|	0.01
43.917	0.00	0.00	0.002	O	|	|	|	|	0.01
44.000	0.00	0.00	0.002	O	|	|	|	|	0.01
44.083	0.00	0.00	0.002	O	|	|	|	|	0.01
44.167	0.00	0.00	0.001	O	|	|	|	|	0.01
44.250	0.00	0.00	0.001	O	|	|	|	|	0.01
44.333	0.00	0.00	0.001	O	|	|	|	|	0.01
44.417	0.00	0.00	0.001	O	|	|	|	|	0.01
44.500	0.00	0.00	0.001	O	|	|	|	|	0.01
44.583	0.00	0.00	0.001	O	|	|	|	|	0.01
44.667	0.00	0.00	0.001	O	|	|	|	|	0.01
44.750	0.00	0.00	0.001	O	|	|	|	|	0.01
44.833	0.00	0.00	0.001	O	|	|	|	|	0.01
44.917	0.00	0.00	0.001	O	|	|	|	|	0.01
45.000	0.00	0.00	0.001	O	|	|	|	|	0.01
45.083	0.00	0.00	0.001	O	|	|	|	|	0.01
45.167	0.00	0.00	0.001	O	|	|	|	|	0.01
45.250	0.00	0.00	0.001	O	|	|	|	|	0.01
45.333	0.00	0.00	0.001	O	|	|	|	|	0.01
45.417	0.00	0.00	0.001	O	|	|	|	|	0.01
45.500	0.00	0.00	0.001	O	|	|	|	|	0.01
45.583	0.00	0.00	0.001	O	|	|	|	|	0.01
45.667	0.00	0.00	0.001	O	|	|	|	|	0.01
45.750	0.00	0.00	0.001	O	|	|	|	|	0.01
45.833	0.00	0.00	0.001	O	|	|	|	|	0.01
45.917	0.00	0.00	0.001	O	|	|	|	|	0.01
46.000	0.00	0.00	0.001	O	|	|	|	|	0.01
46.083	0.00	0.00	0.001	O	|	|	|	|	0.01
46.167	0.00	0.00	0.001	O	|	|	|	|	0.01
46.250	0.00	0.00	0.001	O	|	|	|	|	0.01
46.333	0.00	0.00	0.001	O	|	|	|	|	0.01
46.417	0.00	0.00	0.001	O	|	|	|	|	0.01
46.500	0.00	0.00	0.001	O	|	|	|	|	0.01
46.583	0.00	0.00	0.001	O	|	|	|	|	0.01
46.667	0.00	0.00	0.001	O	|	|	|	|	0.01
46.750	0.00	0.00	0.001	O	|	|	|	|	0.01
46.833	0.00	0.00	0.001	O	|	|	|	|	0.01
46.917	0.00	0.00	0.001	O	|	|	|	|	0.01
47.000	0.00	0.00	0.001	O	|	|	|	|	0.01
47.083	0.00	0.00	0.001	O	|	|	|	|	0.01
47.167	0.00	0.00	0.001	O	|	|	|	|	0.01
47.250	0.00	0.00	0.001	O	|	|	|	|	0.01
47.333	0.00	0.00	0.001	O	|	|	|	|	0.01
47.417	0.00	0.00	0.001	O	|	|	|	|	0.01

47.500	0.00	0.00	0.001	O	|	|	|	|	0.01
47.583	0.00	0.00	0.001	O	|	|	|	|	0.01
47.667	0.00	0.00	0.001	O	|	|	|	|	0.01
47.750	0.00	0.00	0.001	O	|	|	|	|	0.01
47.833	0.00	0.00	0.001	O	|	|	|	|	0.01
47.917	0.00	0.00	0.001	O	|	|	|	|	0.01
48.000	0.00	0.00	0.001	O	|	|	|	|	0.01
48.083	0.00	0.00	0.001	O	|	|	|	|	0.01
48.167	0.00	0.00	0.001	O	|	|	|	|	0.00
48.250	0.00	0.00	0.001	O	|	|	|	|	0.00
48.333	0.00	0.00	0.001	O	|	|	|	|	0.00
48.417	0.00	0.00	0.001	O	|	|	|	|	0.00
48.500	0.00	0.00	0.001	O	|	|	|	|	0.00
48.583	0.00	0.00	0.001	O	|	|	|	|	0.00
48.667	0.00	0.00	0.000	O	|	|	|	|	0.00
48.750	0.00	0.00	0.000	O	|	|	|	|	0.00
48.833	0.00	0.00	0.000	O	|	|	|	|	0.00
48.917	0.00	0.00	0.000	O	|	|	|	|	0.00
49.000	0.00	0.00	0.000	O	|	|	|	|	0.00
49.083	0.00	0.00	0.000	O	|	|	|	|	0.00
49.167	0.00	0.00	0.000	O	|	|	|	|	0.00
49.250	0.00	0.00	0.000	O	|	|	|	|	0.00
49.333	0.00	0.00	0.000	O	|	|	|	|	0.00
49.417	0.00	0.00	0.000	O	|	|	|	|	0.00
49.500	0.00	0.00	0.000	O	|	|	|	|	0.00
49.583	0.00	0.00	0.000	O	|	|	|	|	0.00
49.667	0.00	0.00	0.000	O	|	|	|	|	0.00
49.750	0.00	0.00	0.000	O	|	|	|	|	0.00
49.833	0.00	0.00	0.000	O	|	|	|	|	0.00
49.917	0.00	0.00	0.000	O	|	|	|	|	0.00
50.000	0.00	0.00	0.000	O	|	|	|	|	0.00
50.083	0.00	0.00	0.000	O	|	|	|	|	0.00
50.167	0.00	0.00	0.000	O	|	|	|	|	0.00
50.250	0.00	0.00	0.000	O	|	|	|	|	0.00

**********HYDROGRAPH DATA**********

Number of intervals = 603
Time interval = 5.0 (Min.)
Maximum/Peak flow rate = 3.264 (CFS)
Total volume = 1.769 (Ac.Ft)

Status of hydrographs being held in storage

	Stream 1	Stream 2	Stream 3	Stream 4	Stream 5
Peak (CFS)	0.000	0.000	0.000	0.000	0.000
Vol (Ac.Ft)	0.000	0.000	0.000	0.000	0.000

****

HYDRAULIC CALCULATION

```
************************************************************************
                HYDRAULIC ELEMENTS - I  PROGRAM PACKAGE
        (C) Copyright 1982-2016 Advanced Engineering Software (aes)
            Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                          Analysis prepared by:



------------------------------------------------------------------------
  TIME/DATE OF STUDY: 14:22 06/19/2023
========================================================================
 Problem Descriptions:
  18" PIPE CAPACITY CALC


************************************************************************
>>>>PIPEFLOW HYDRAULIC INPUT INFORMATION<<<<
------------------------------------------------------------------------
    PIPE DIAMETER(FEET) =   1.500
    FLOWDEPTH(FEET) =   1.420
    PIPE SLOPE(FEET/FEET) =  0.0100
    MANNINGS FRICTION FACTOR = 0.013000
    >>>>> NORMAL DEPTH FLOW(CFS) =     11.29
========================================================================
    NORMAL-DEPTH FLOW INFORMATION:
------------------------------------------------------------------------
    NORMAL DEPTH(FEET) =      1.42
    FLOW AREA(SQUARE FEET) =      1.73
    FLOW TOP-WIDTH(FEET) =     0.674
    FLOW PRESSURE + MOMENTUM(POUNDS) =          216.90
    FLOW VELOCITY(FEET/SEC.) =           6.525
    FLOW VELOCITY HEAD(FEET) =           0.661
    HYDRAULIC DEPTH(FEET) =      2.57
    FROUDE NUMBER =     0.718
    SPECIFIC ENERGY(FEET) =            2.08
========================================================================
```

```
**************************************************************************
                HYDRAULIC ELEMENTS - I  PROGRAM PACKAGE
        (C) Copyright 1982-2016 Advanced Engineering Software (aes)
            Ver. 23.0  Release Date: 07/01/2016  License ID 1400

                        Analysis prepared by:



--------------------------------------------------------------------------
  TIME/DATE OF STUDY: 15:27 06/05/2023
==========================================================================
 Problem Descriptions:
  PARKWAY DRAIN SIZING CALC
  Q100 (Mitigated): 8.9 CFS

**************************************************************************
>>>>CHANNEL INPUT INFORMATION<<<<
--------------------------------------------------------------------------
    CHANNEL Z1(HORIZONTAL/VERTICAL) =    0.00
            Z2(HORIZONTAL/VERTICAL) =    0.00
    BASEWIDTH(FEET) =     4.00
    CONSTANT CHANNEL SLOPE(FEET/FEET) = 0.020000
    UNIFORM FLOW(CFS) =       8.3   )
    MANNINGS FRICTION FACTOR = 0.0130
==========================================================================
    NORMAL-DEPTH FLOW INFORMATION:
--------------------------------------------------------------------------
    >>>>> NORMAL DEPTH(FEET) =   0.32
    FLOW TOP-WIDTH(FEET) =         4.00
    FLOW AREA(SQUARE FEET) =           1.29
    HYDRAULIC DEPTH(FEET) =     0.32
    FLOW AVERAGE VELOCITY(FEET/SEC.) =     6.90
    UNIFORM FROUDE NUMBER =    2.143
    PRESSURE + MOMENTUM(POUNDS) =          132.02
    AVERAGED VELOCITY HEAD(FEET) =      0.740
    SPECIFIC ENERGY(FEET) =      1.062
==========================================================================
    CRITICAL-DEPTH FLOW INFORMATION:
--------------------------------------------------------------------------
    CRITICAL FLOW TOP-WIDTH(FEET) =         4.00
    CRITICAL FLOW AREA(SQUARE FEET) =           2.14
    CRITICAL FLOW HYDRAULIC DEPTH(FEET) =     0.54
    CRITICAL FLOW AVERAGE VELOCITY(FEET/SEC.) =     4.16
    CRITICAL DEPTH(FEET) =     0.54
    CRITICAL FLOW PRESSURE + MOMENTUM(POUNDS) =          107.45
    AVERAGED CRITICAL FLOW VELOCITY HEAD(FEET) =      0.268
    CRITICAL FLOW SPECIFIC ENERGY(FEET) =      0.804
==========================================================================
```

Q100(Mitigated)

USE 4' W x 0.33' H
PARKWAY DRAIN

Grate Inlet Capacity (4'x4')

The capacity of grate inlet operating under oriface flow is computed with Equation (4-10). Equation (4-10) is from Handbook of Hydraulics Brater and King Sixth Edition.

$$Q_o = C_o A \sqrt{2gh} \qquad \text{(Eq. 4-10)}$$

- Q_o = orifice capacity of grate (cfs)
- Co = orifice flow coefficient = 0.67
- A = clear opening area (sq. ft.) of the grate (the total area available for flow). A multiplier of about 0.5 is recommended to be applied to the measured area as a safety factor
- g = acceleration due to gravity (32.2 ft/s^2)
- h = allowable head on grate (ft.)

Note:
Use 48"x48" CPC TR. ADA Grate BD (Clear Opening Aera, A= 11.52 sf)
Assume 50% reduction in open area for clogging
Q100: 30.8 CFS (From Site Developed Condition)


Inlet #	Water Depth (ft.)	Flow Rate (Q100 cfs)	Grate Capacity (cfs)	Remarks:
1	0.36	15.4	18.6	100% Pick up
2	0.36	15.4	18.6	100% Pick up

FOR Q100 MITIGATED FLOW OUT (8.3 CFS) ONE 4'x4' BASIN OK FOR UNMITIGATED FLOW PICKUP NEED TWO BASIN's

HEAD: 0.36' ~ 4.3"

Drainage Exhibit

Developed Condition



COMM
5.5 960

COMMERCIAL (10% PRV)

ACREAGE (AC.)

TRAVEL LENGTH (FT)

INDICATES DRAINAGE BOUNDARY

INDICATES FLOW DIRECTION

GRAPHIC SCALE
80 40 0 40 80
(in feet)
1 inch = 80 ft

FG 948 (HP)
Q_{100} = 0.0 CFS
0

SURFACE ELEV

NODES

FLOW RATE
100-YR STORMEVENT

VICINITY MAP



DRAINAGE EXHIBIT-DEVELOPED CONDITION

Prepared By:

ALLARD ENGINEERING

Civil Engineering - Land Surveying - Land Planning

16866 Seville Avenue
Fontana, California 92335
PHONE (909) 356-1815 Fax (909) 356-1795

PREPARED FOR:

THE CONCO COMPANIES

13052 DAHLIA STREET
FONTANA, CA 92337
PH: (925) 685-6799

Drainage Exhibit

Existing Condition

FS 934.0
Q_{100} = 11.5 CFS
2

FS 937.0
Q_{100} = 7.4 CFS
1

DAHLIA STREET

SANTA ANA AVENUE

COMM
(10% PERV)
2.3 | 296

GRV
(80% PERV)
5.5 | 752

FS 949.0 (HP)
Q_{100} = 0.0 CFS
0


GRV
5.5 | 960
GRAVEL PAVED(80% PRV)
ACREAGE (AC.)
TRAVEL LENGTH (FT)

INDICATES DRAINAGE BOUNDARY

INDICATES FLOW DIRECTION

SURFACE ELEV
NODES
FG 948 (HP)
0
Q_{100} = 0.0 CFS
FLOW RATE
100-YR STORMEVENT

GRAPHIC SCALE
80 40 0 40 80
(IN FEET)
1 SCALE: 1"=80'



VICINITY MAP
NTS

DRAINAGE EXHIBIT-EXISTING CONDITION

Prepared By:
ALLARD ENGINEERING
Civil Engineering - Land Surveying - Land Planning
16866 Seville Avenue
Fontana, California 92335
PHONE (909) 356-1815 Fax (909) 356-1795

PREPARED FOR:
THE CONCO COMPANIES
13052 DAHLIA STREET
FONTANA, CA 92337
PH: (925) 685-6799

Filename: I:\Conco Companies\DWG\ENTITLEMENT\EXHIBITS\DRAINAGE EXHIBIT.dwg